Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	09-2591-7	**Version number:**	7.01
Revision date:	29/05/2026	**Supersedes date:**	15/12/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M(TM) Structural Bonding Tape #9259 #9260

Product Identification Numbers

JR-1521-2951-6	JR-1527-0923-4	JR-1527-1931-6	UU-0150-0599-2
7100420626	7000007875	7000090655	7000090653

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Thermosetting semi-structural tape.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredient	Identifier(s)	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	10 - 30

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

Contains 62% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Acrylic copolymer	Trade Secret	45 - 60	Substance not classified as hazardous
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	(CAS-No.) 25068-38-6	10 - 20	Substance not classified as hazardous
Dicyandiamide	(CAS-No.) 461-58-5 (EC-No.) 207-312-8	1 - 5	Substance not classified as hazardous
Fumed Silica	Trade Secret	1 - 5	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the GB CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering,

and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Hydrogen cyanide.	During combustion.
Irritant vapours or gases.	During combustion.
Ammonia	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray.

Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
Fumed Silica	Trade Secret	UK HSE	TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable dust):6 mg/m3	

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls
Provide ventilated enclosure for heat curing. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 16321

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136: filter type A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Roll of Tape.
Colour	Milky White
Odor	Slight Acrylic
Odour threshold	*No data available.*
Melting point/freezing point	*Not applicable.*
Boiling point/boiling range	*Not applicable.*
Flammability	Not applicable.
Flammable Limits(LEL)	*Not applicable.*
Flammable Limits(UEL)	*Not applicable.*
Flash point	No flash point
Autoignition temperature	*Not applicable.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	*Not applicable.*
Water solubility	*Not applicable.*
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*Not applicable.*
Density	1.15 - 1.3 g/cm3
Relative density	1.15 - 1.3 [*Ref Std:*WATER=1]
Relative Vapour Density	*Not applicable.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*Not applicable.*
Molecular weight	*No data available.*
Percent volatile	*No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.
Heat.
Temperatures above +25°C

10.5 Incompatible materials
Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Vapours released during curing may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact
Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Dermal	Rat	LD50 > 1,600 mg/kg
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Ingestion	Rat	LD50 > 1,000 mg/kg
Fumed Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Rabbit	No significant irritation
Fumed Silica	Rabbit	No significant irritation
Dicyandiamide	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Rabbit	Mild irritant
Fumed Silica	Rabbit	No significant irritation
Dicyandiamide	Professional judgement	Mild irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Guinea pig	Not classified
Fumed Silica	Human and animal	Not classified
Dicyandiamide	Guinea	Not classified

	pig	

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	In vivo	Not mutagenic
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Fumed Silica	In Vitro	Not mutagenic
Dicyandiamide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Fumed Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Fumed Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000	44 days

				mg/kg/day	
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Fumed Silica	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	25068-38-6	Water flea	Estimated	21 days	NOEC	>1.48 mg/l
Dicyandiamide	461-58-5	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
Dicyandiamide	461-58-5	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Dicyandiamide	461-58-5	Water flea	Experimental	48 hours	EC50	3,177 mg/l
Dicyandiamide	461-58-5	Green algae	Experimental	72 hours	NOEC	310 mg/l
Dicyandiamide	461-58-5	Water flea	Experimental	21 days	NOEC	25 mg/l
Dicyandiamide	461-58-5	Redworm	Experimental	14 days	LC50	>3,200 mg/kg (Dry Weight)
Fumed Silica	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	25068-38-6	Estimated Biodegradation	28 days	BOD	7 %BOD/ThOD	OECD 301C - MITI test (I)
Dicyandiamide	461-58-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 301E - Modif. OECD Screen
Dicyandiamide	461-58-5	Experimental Aquatic Inherent Biodegrad.	14 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 302B Zahn-Wellens/EVPA

Dicyandiamide	461-58-5	Experimental Biodegradation	61 days	CO2 evolution	1.1 %CO2 evolution/THCO2 evolution	OECD 309 Aero Sim Biod Water
Fumed Silica	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
reaction product: bisphenol-A-(epichlorhydrin) (MW>1200)	25068-38-6	Estimated Bioconcentration		Bioaccumulation factor	7.4	
Dicyandiamide	461-58-5	Experimental BCF - Fish	42 days	Bioaccumulation factor	<=3.1	OECD305-Bioconcentration
Dicyandiamide	461-58-5	Experimental Bioconcentration		Log Kow	-0.52	OECD 107 log Kow shke flsk mtd
Fumed Silica	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
Dicyandiamide	461-58-5	Modeled Mobility in Soil	Koc	9 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

170203	Plastic
20 01 39	Plastics

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	Identifier(s)	Classification	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:
The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient	Identifier(s)
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3

Restriction status: listed in UK REACH Annex XVII
Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Global inventory status
Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

COMAH Regulation, SI 2015/483
Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Revision information:
Section 14 - Not Hazardous for Transportation information was added.
EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.
GBSDS Section 14 Transport in bulk - Main Heading information was deleted.
GBSDS Section 14 UN Number information was deleted.
Section 1: Product identification numbers information was modified.
Section 01: SAP Material Numbers information was modified.
Label: Graphic information was modified.
Section 9: Vapour pressure value information was added.
Section 9: Vapour pressure value information was deleted.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 UN Number Column data information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk
For Northern Ireland documents, please contact your 3M representative to obtain a copy.