

# **Safety Data Sheet**

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 45-6479-5 **Version number:** 1.00 **Issue Date:** 24/09/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **IDENTIFICATION:**

### 1.1. Product identifier

DP810NS KIT

#### **Product Identification Numbers**

UU-0140-2195-8 UU-0140-4059-4

7100387125 7100387555

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

#### 1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

45-6292-2, 45-5052-1

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

# TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



# Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 45-5052-1 **Version number:** 1.00 **Issue Date:** 24/09/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

#### 1.1. Product identifier

DP810NS Part B

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

# **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 1. Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

#### Signal word

Danger

#### **Symbols**

Corrosion | Exclamation mark | Health Hazard |

**Pictograms** 



#### **Hazard statements**

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

### **Precautionary statements**

**Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash exposed skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280B Wear protective gloves and eye/face protection.

**Response:** 

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
2-Hydroxypropyl Methacrylate	868-77-9	20 - 30
Phenoxyethyl Methacrylate	10595-06-9	20 - 30
Hydroxypropyl Methacrylate	27813-02-1	10 - 20
Methyl Methacrylate- Butadiene-Styrene	25101-28-4	10 - 20
Acrylonitrile-Butadiene Polymer	9010-81-5	<= 10
Bisphenol A Polyethylene Glycol Diether	41637-38-1	<= 10
Dimethacrylate (polymer)		
Modified Silica	68611-44-9	<= 5
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	<= 3
Phenothiazine	92-84-2	< 1

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxide.During combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.

#### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

\_\_\_\_\_\_

Hazchem Code: •3Z

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (eg. gloves, respirators...) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

TOT LITE COMPONENT.				
Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Phenothiazine	92-84-2	ACGIH	mg/m3	A4: Not class. as human carcin, SKIN; Dermal sensitizer
Phenothiazine	92-84-2	Australia OELs	TWA(8 hours):5 mg/m3	SKIN

#### DP810NS Part B

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.		
Specific Physical Form:	Paste		
Colour	Green		
Odour	Methacrylate		
Odour threshold	No data available.		
рН	No data available.		
Melting point/Freezing point	No data available.		
Boiling point/Initial boiling point/Boiling range	87 °C		
Flash point	>=93.3 °C [Details: POLYMERS Slight Slight]		
Evaporation rate	No data available.		
Flammability	Not applicable.		
Flammable Limits(LEL)	No data available.		
Flammable Limits(UEL)	No data available.		
Vapour pressure	<=13.3 Pa		
Relative Vapor Density	No data available.		
Density	No data available.		
Relative density	1.07		
Water solubility	No data available.		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Autoignition temperature	No data available.		
Decomposition temperature	No data available.		
Kinematic Viscosity	No data available.		
Volatile organic compounds (VOC)	No data available.		
Percent volatile	No data available.		
VOC less H2O & exempt solvents	No data available.		
Molecular weight	No data available.		

Particle Characteristics	Not applicable.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

# 10.3. Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke. Sparks and/or flames.

# 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

# 10.5 Incompatible materials

Amines.

Reactive metals

Reducing agents.

\_\_\_\_\_

### 10.6 Hazardous decomposition products **Substance**

None known.

#### **Condition**

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. Photosensitisation: Signs/symptoms may include a sunburn-like reaction such as blistering, redness, swelling, and itching from minor exposure to sunlight.

#### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000
_			mg/kg
2-Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Phenoxyethyl Methacrylate	Dermal	similar compounds	LD50 > 2,000 mg/kg
Phenoxyethyl Methacrylate	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Methyl Methacrylate- Butadiene-	Dermal		LD50 estimated to be > 5,000 mg/kg
Styrene			

Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Methyl Methacrylate- Butadiene-	Ingestion	Rat	LD50 > 5,000 mg/kg
Styrene			
Acrylonitrile-Butadiene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Bisphenol A Polyethylene Glycol	Dermal	Rat	LD50 > 2,000 mg/kg
Diether Dimethacrylate (polymer)			
Bisphenol A Polyethylene Glycol	Ingestion	Rat	LD50 > 35,000 mg/kg
Diether Dimethacrylate (polymer)			
Modified Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Modified Silica	Inhalation-Dust/Mist	Rat	LC50 > 0.691 mg/l
	(4 hours)		
Modified Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Phosphate			
Phenothiazine	Dermal	Rat	LD50 > 2,000 mg/kg
Phenothiazine	Ingestion	Rat	LD50 1,370 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
2-Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Phenoxyethyl Methacrylate	similar compounds	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether	Rabbit	Minimal irritation
Dimethacrylate (polymer)		
Modified Silica	Rabbit	No significant irritation
2-Hydroxypropyl Methacrylate Phosphate	Rabbit	Corrosive
Phenothiazine	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
2-Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Phenoxyethyl Methacrylate	similar compounds	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether	Rabbit	No significant irritation
Dimethacrylate (polymer)		
Modified Silica	Rabbit	No significant irritation
2-Hydroxypropyl Methacrylate Phosphate	similar health hazards	Corrosive
Phenothiazine	Rabbit	Mild irritant

### **Skin Sensitisation**

Skin Schsitisation		
Name	Species	Value
2-Hydroxypropyl Methacrylate	Human and animal	Sensitising
Phenoxyethyl Methacrylate	similar compounds	Sensitising
Hydroxypropyl Methacrylate	Human and animal	Sensitising
Bisphenol A Polyethylene Glycol Diether	Guinea pig	Not classified
Dimethacrylate (polymer)		
Modified Silica	Human and animal	Not classified
2-Hydroxypropyl Methacrylate Phosphate	Mouse	Sensitising
Phenothiazine	Guinea pig	Sensitising

### **Photosensitisation**

Name	Species	Value
Phenothiazine	Human	Sensitising

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
2-Hydroxypropyl Methacrylate	In vivo	Not mutagenic
2-Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenoxyethyl Methacrylate	In Vitro	Not mutagenic
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	In Vitro	Not mutagenic
Modified Silica	In Vitro	Not mutagenic
2-Hydroxypropyl Methacrylate Phosphate	In Vitro	Not mutagenic
Phenothiazine	In Vitro	Not mutagenic
Phenothiazine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Modified Silica	Not specified.	Mouse	Some positive data exist, but the data
	-		are not sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
2-Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000	premating & during gestation
2-Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	mg/kg/day NOAEL 1,000 mg/kg/day	49 days
2-Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Phenoxyethyl Methacrylate	Ingestion	Toxic to female reproduction	similar compounds	NOAEL 300 mg/kg/day	premating into lactation
Phenoxyethyl Methacrylate	Ingestion	Toxic to development	similar compounds	NOAEL 300 mg/kg/day	premating into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Modified Silica	Ingestion	Not classified for	Rat	NOAEL 509	1 generation

		female reproduction		mg/kg/day	
Modified Silica	Ingestion	Not classified for	Rat	NOAEL 497	1 generation
		male reproduction		mg/kg/day	
Modified Silica	Ingestion	Not classified for	Rat	NOAEL	during
		development		1,350	organogenesis
				mg/kg/day	
2-Hydroxypropyl	Ingestion	Not classified for	Rat	NOAEL	during gestation
Methacrylate		development		1,000	
Phosphate				mg/kg/day	
Phenothiazine	Ingestion	Not classified for	Rat	NOAEL 150	during
	_	development		mg/kg/day	organogenesis

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydroxyprop yl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2- Hydroxyprop yl Methacrylate Phosphate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydroxyprop yl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxyprop yl Methacrylate	Ingestion	hematopoietic system   heart   endocrine system   liver   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Modified Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2- Hydroxyprop yl Methacrylate Phosphate	Ingestion	hematopoietic system   kidney and/or bladder   heart   liver   immune system   eyes	Not classified	Rat	NOAEL 300 mg/kg/day	90 days
Phenothiazine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Dog	NOAEL 18 mg/kg/day	13 weeks
Phenothiazine	Ingestion	heart   endocrine system   liver   kidney and/or bladder   respiratory	Not classified	Dog	NOAEL 67 mg/kg/day	13 weeks

DP810NS Part B

,		
system		
System		

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

#### **Interactive Effects**

Not Determined

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
2-Hydroxypropyl Methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-Hydroxypropyl Methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Phenoxyethyl Methacrylate	10595-06-9	Activated sludge	Analogous Compound	3 hours	EC50	177 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Golden Orfe	Analogous Compound	96 hours	LC50	10 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC50	4.4 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Water flea	Analogous Compound	48 hours	EC50	1.21 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC10	0.74 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Bacteria	Experimental	N/A	EC10	1,140 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l

Hydroxypropyl	27813-02-1	Green algae	Experimental	72 hours	ErC50	>97.2 mg/l
Methacrylate	27813-02-1	Green argae	Experimental	72 Hours	EIC30	
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
Methyl Methacrylate- Butadiene-Styrene	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Acrylonitrile- Butadiene Polymer	9010-81-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Green algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Modified Silica	68611-44-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Green algae	Experimental	72 hours	EC50	>120 mg/l
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Rainbow trout	Experimental	96 hours	LC50	>112 mg/l
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Water flea	Experimental	48 hours	EC50	68 mg/l
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Green algae	Experimental	72 hours	NOEC	30 mg/l
Phenothiazine	92-84-2	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
Phenothiazine	92-84-2	Ciliated protozoa	Experimental	48 hours	IC50	8 mg/l
Phenothiazine	92-84-2	Green algae	Experimental	72 hours	ErC50	>100 mg/l
Phenothiazine	92-84-2	Rainbow trout	Experimental	96 hours	LC50	0.597 mg/l
Phenothiazine	92-84-2	Water flea	Experimental	48 hours	EC50	0.154 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Hydroxypropyl	868-77-9	Experimental	28 days	BOD	84 %BOD/COD	OECD 301D - Closed bottle
Methacrylate		Biodegradation				test
2-Hydroxypropyl	868-77-9	Experimental		Hydrolytic half-life	10.9 days (t 1/2)	OECD 111 Hydrolysis func
Methacrylate		Hydrolysis		basic pH		of pH
Phenoxyethyl	10595-06-9	Analogous	28 days	BOD	22.3 %BOD/ThOD	OECD 301D - Closed bottle

\_\_\_\_\_

Methacrylate		Compound Biodegradation				test
Phenoxyethyl Methacrylate	10595-06-9	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	1 years (t 1/2)	OECD 111 Hydrolysis func of pH
Hydroxypropyl Methacrylate	27813-02-1	Experimental Biodegradation	28 days	BOD	81 %BOD/ThOD	OECD 301C - MITI test (I)
Methyl Methacrylate- Butadiene-Styrene	25101-28-4	Data not available- insufficient	N/A	N/A	N/A	N/A
Acrylonitrile- Butadiene Polymer	9010-81-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 % degraded	
Modified Silica	68611-44-9	Data not available- insufficient	N/A	N/A	N/A	N/A
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Experimental Biodegradation	28 days	BOD	93.1 %BOD/ThOD	OECD 301F - Manometric respirometry
Phenothiazine	92-84-2	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301D - Closed bottle test

# 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-Hydroxypropyl Methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
Phenoxyethyl Methacrylate	10595-06-9	Modeled Bioconcentration		Bioaccumulation factor	5.8	Catalogic <sup>TM</sup>
Phenoxyethyl Methacrylate	10595-06-9	Experimental Bioconcentration		Log Kow	3.137	OECD 117 log Kow HPLC method
Hydroxypropyl Methacrylate	27813-02-1	Experimental Bioconcentration		Log Kow	0.97	EC A.8 Partition Coefficient
Methyl Methacrylate- Butadiene-Styrene	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylonitrile- Butadiene Polymer	9010-81-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Estimated Bioconcentration		Bioaccumulation factor	6.6	
Modified Silica	68611-44-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Hydroxypropyl Methacrylate Phosphate	52628-03-2	Experimental Bioconcentration		Log Kow	1 - 2.72	OECD 117 log Kow HPLC method
Phenothiazine	92-84-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	660	
Phenothiazine	92-84-2	Experimental Bioconcentration		Log Kow	3.78	OECD 117 log Kow HPLC method

**12.4. Mobility in soil** Please contact manufacturer for more details

# 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

# **SECTION 14: Transport Information**

#### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Acrylate oligomer)

Class/Division: 9

Sub Risk: Not applicable. Packing Group: III

**Special Instructions:** Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

Hazchem Code: •3Z

**IERG: 47** 

### International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Acrylate oligomer)

Class/Division: 9

**Sub Risk:** Not applicable. **Packing Group:** III

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Acrylate oligomer)

Class/Division: 9
Sub Risk: Not applicable.
Packing Group: III

Marine Pollutant: Not applicable.

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

# **SECTION 16: Other information**

#### **Revision information:**

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of

# **DP810NS Part B**

the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State

regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au

Page: 15 of 15



# Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 45-6292-2 **Version number:** 1.00 **Issue Date:** 24/09/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

#### 1.1. Product identifier

DP810NS KIT

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

# **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4.
Acute Toxicity (dermal): Category 4.
Acute Toxicity (inhalation): Category 4.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1A.

Carcinogenicity: Category 1B.
Reproductive Toxicity: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

#### Signal word

Danger

### **Symbols**

Corrosion | Exclamation mark | Health Hazard |

### **Pictograms**







#### Hazard statements

H302 Harmful if swallowed. H312 Harmful in contact with skin. H332 Harmful if inhaled. Causes skin irritation. H315 Causes serious eve damage. H318 May cause an allergic skin reaction. H317 H350 May cause cancer. May damage fertility or the unborn child. H360

H373 May cause damage to organs through prolonged or repeated exposure: nervous

system | respiratory system.

#### **Precautionary statements**

**Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

P330 Rinse mouth.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

### Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other assigned/identified product hazards

None known.

#### 2.4. Other hazards which do not result in classification

Harmful to aquatic life.

Toxic to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
METHACRYLIC ACID ESTER	Trade Secret	30 - 50
POLYMERS	Trade Secret	20 - 40
2-hydroxyethyl methacrylate	868-77-9	10 - 30
α,α-Dimethylbenzyl hydroperoxide	80-15-9	<= 3
Cumene	98-82-8	< 0.5
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	< 0.5
Styrenated phenol	61788-44-1	< 0.3
TRIETHYLENE GLYCOL BIS[3-(3-	36443-68-2	< 0.3
TERT-BUTYL-4-HYDROXY-5-		
METHYLPHENYL)PROPIONATE]		
2,5-Di-tert-pentylhydroquinone	79-74-3	< 0.1

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

# If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxide.During combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.

#### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** •3Z

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (eg. gloves, respirators...) as

required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient		CAS Nbr	Agency	Limit type	Additional comments
α,α-Dimeth	ylbenzyl	80-15-9	AIHA	TWA:6 mg/m3(1 ppm)	SKIN
hydroperox	ide				
Cumene		98-82-8	ACGIH	TWA:5 ppm	A3: Confirmed animal
					carcinogen.
Cumene		98-82-8	Australia OELs	TWA(8 hours): 125 mg/m3	SKIN
				(25 ppm); STEL(15	
				minutes): 375 mg/m3 (75 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

# 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odour	Acrylic
Odour threshold	No data available.
рН	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	87 °C
Flash point	102.2 °C [Details: POLYMERS Slight Slight]
Evaporation rate	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	<=13.3 Pa
Relative Vapor Density	No data available.
Density	1.07 g/ml
Relative density	1.07 [ <i>Ref Std</i> :WATER=1]
Water solubility	No data available.
Solubility- non-water	<=10 % [Details:Slight ]
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	>=84,112 mm <sup>2</sup> /sec
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

Particle Characteristics Not applicable.	
--	--

\_\_\_\_\_

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

#### 10.3. Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Sparks and/or flames.

#### 10.4. Possibility of hazardous reactions

Hazardous polymerisation may occur.

#### 10.5 Incompatible materials

Amines.

Reactive metals

Reducing agents.

#### 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >1,000 - =2,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >10 - =20 mg/l
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
α,α-Dimethylbenzyl hydroperoxide	Dermal	Rat	LD50 500 mg/kg
α,α-Dimethylbenzyl hydroperoxide	Inhalation-Vapour (4 hours)	Rat	LC50 1.4 mg/l
α,α-Dimethylbenzyl hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
Cumene	Dermal	Rabbit	LD50 > 3,160 mg/kg
Cumene	Inhalation-Vapour (4 hours)	Rat	LC50 39.4 mg/l
Cumene	Ingestion	Rat	LD50 2,260 mg/kg
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Dermal	Rabbit	LD50 > 10,000 mg/kg
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Ingestion	Rat	LD50 > 5,000 mg/kg
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL-4-HYDROXY-5- METHYLPHENYL)PROPIONATE]	Dermal	Rat	LD50 > 2,000 mg/kg
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL-4-HYDROXY-5- METHYLPHENYL)PROPIONATE]	Ingestion	Rat	LD50 > 7,000 mg/kg
Styrenated phenol	Dermal	Rat	LD50 > 2,000 mg/kg
Styrenated phenol	Ingestion	Rat	LD50 > 2,000 mg/kg
2,5-Di-tert-pentylhydroquinone	Dermal	Rabbit	LD50 > 3,160 mg/kg
2,5-Di-tert-pentylhydroquinone	Ingestion	Rat	LD50 1,900 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value

2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
α,α-Dimethylbenzyl hydroperoxide	official classification	Corrosive
Cumene	Rabbit	Minimal irritation
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Rabbit	No significant irritation
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Rabbit	No significant irritation
Styrenated phenol	Rabbit	No significant irritation
2,5-Di-tert-pentylhydroquinone	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
α,α-Dimethylbenzyl hydroperoxide	official classification	Corrosive
Cumene	Rabbit	Mild irritant
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Rabbit	Mild irritant
TRIETHYLENE GLYCOL BIS[3-(3-TERT-	Rabbit	No significant irritation
BUTYL-4-HYDROXY-5-		
METHYLPHENYL)PROPIONATE]		
Styrenated phenol	Rabbit	Mild irritant
2,5-Di-tert-pentylhydroquinone	Rabbit	Mild irritant

# **Skin Sensitisation**

Name	Species	Value
2-hydroxyethyl methacrylate	Human and animal	Sensitising
Cumene	Guinea pig	Not classified
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Mouse	Not classified
TRIETHYLENE GLYCOL BIS[3-(3-TERT-	Guinea pig	Not classified
BUTYL-4-HYDROXY-5-		
METHYLPHENYL)PROPIONATE]		
Styrenated phenol	Mouse	Sensitising
2,5-Di-tert-pentylhydroquinone	Mouse	Sensitising

# **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
α,α-Dimethylbenzyl hydroperoxide	In vivo	Not mutagenic
α,α-Dimethylbenzyl hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cumene	In Vitro	Not mutagenic
Cumene	In vivo	Not mutagenic
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	In Vitro	Not mutagenic
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	In Vitro	Not mutagenic
2,5-Di-tert-pentylhydroquinone	In vivo	Not mutagenic
2,5-Di-tert-pentylhydroquinone	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Cumene	Inhalation	Multiple animal	Carcinogenic.
		species	
TRIETHYLENE GLYCOL BIS[3-	Ingestion	Rat	Some positive data exist, but the data
(3-TERT-BUTYL-4-HYDROXY-5-			are not sufficient for classification
METHYLPHENYL)PROPIONATE]			

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Cumene	Inhalation	Not classified for development	Rabbit	NOAEL 11.3 mg/l	during organogenesis
6,6'-Di-tert-butyl- 2,2'-methylenedi-p- cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	premating into lactation
6,6'-Di-tert-butyl- 2,2'-methylenedi-p- cresol	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	premating into lactation
6,6'-Di-tert-butyl- 2,2'-methylenedi-p- cresol	Ingestion	Toxic to male reproduction	Rat	NOAEL 12.5 mg/kg/day	50 days
TRIETHYLENE GLYCOL BIS[3-(3- TERT-BUTYL-4- HYDROXY-5- METHYLPHENYL) PROPIONATE]	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2,5-Di-tert- pentylhydroquinone	Ingestion	Not classified for development	Rat	NOAEL 70 mg/kg/day	during organogenesis

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
α,α- Dimethylbenz yl hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
α,α- Dimethylbenz yl hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
α,α- Dimethylbenz yl hydroperoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

D. . . . 10 . C . 10

Cumene	Inhalation	central nervous	May cause	Multiple	NOAEL Not	not available
		system	drowsiness or	animal species	available	
		depression	dizziness			
Cumene	Inhalation	respiratory	May cause	Human	LOAEL 0.2 mg/l	occupational
		irritation	respiratory			exposure
			irritation			
Cumene	Ingestion	central nervous	May cause	Multiple	NOAEL Not	not available
		system	drowsiness or	animal species	available	
		depression	dizziness			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
α,α- Dimethylbenz yl hydroperoxide	Inhalation	nervous system   respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
α,α- Dimethylbenz yl hydroperoxide	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
Cumene	Inhalation	auditory system   endocrine system   hematopoietic system   liver   nervous system   eyes	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4.9 mg/l	13 weeks
Cumene	Inhalation	respiratory system	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Ingestion	kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   respiratory system	Not classified	Rat	NOAEL 769 mg/kg/day	6 months
6,6'-Di-tert- butyl-2,2'- methylenedi- p-cresol	Ingestion	liver   heart   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 42 mg/kg/day	18 months
TRIETHYLE NE GLYCOL BIS[3-(3- TERT- BUTYL-4- HYDROXY- 5-	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 110 mg/kg/day	90 days

D 11 C 1

METHYLPH		1				
ENYL)PROP IONATE]						
TRIETHYLE NE GLYCOL BIS[3-(3- TERT- BUTYL-4- HYDROXY- 5- METHYLPH	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
ENYL)PROP IONATE]						
TRIETHYLE NE GLYCOL BIS[3-(3- TERT- BUTYL-4- HYDROXY- 5- METHYLPH ENYL)PROP IONATE]	Ingestion	liver	Not classified	Rat	NOAEL 100 mg/kg/day	24 months
TRIETHYLE NE GLYCOL BIS[3-(3- TERT- BUTYL-4- HYDROXY- 5- METHYLPH ENYL)PROP IONATE]	Ingestion	hematopoietic system	Not classified	Monkey	NOAEL 1,000 mg/kg/day	28 days
2,5-Di-tert- pentylhydroqu inone	Ingestion	endocrine system   gastrointestinal tract   liver   kidney and/or bladder   heart   skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   eyes   respiratory system   vascular system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

**Aspiration Hazard** 

113pii ation 11azai u	
Name	Value
Cumene	Aspiration hazard

# **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

# **Interactive Effects**

Not Determined

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
J J J	868-77-9	Turbot	Analogous	96 hours	LC50	833 mg/l
methacrylate			Compound			
3 3 3	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
methacrylate						
	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
methacrylate						
3 3 3	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
methacrylate						
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
methacrylate						
J J J	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
methacrylate						
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
	80-15-9	Bacteria	Experimental	18 hours	EC10	0.103 mg/l
Dimethylbenzyl						
hydroperoxide						
,	80-15-9	Green algae	Experimental	72 hours	EC50	3.1 mg/l
Dimethylbenzyl						
hydroperoxide						
	80-15-9	Rainbow trout	Experimental	96 hours	LC50	3.9 mg/l
Dimethylbenzyl						
hydroperoxide						
	80-15-9	Water flea	Experimental	48 hours	EC50	18.84 mg/l
Dimethylbenzyl						
hydroperoxide	00.15.0	C 1	P : (1	72.1	NOEC	1 /1
α,α- Dimethylbenzyl	80-15-9	Green algae	Experimental	72 hours	NOEC	1 mg/l
hydroperoxide						
	119-47-1	Green algae	Endpoint not	72 hours	EC50	>100 mg/l
2,2'-methylenedi-p-	117-4/-1	Green argae	reached	72 Hours	ECSO	100 mg/1
cresol			reactica			
	119-47-1	Water flea	Endpoint not	48 hours	EC50	>100 mg/l
2,2'-methylenedi-p-	, .		reached			
cresol						
6,6'-Di-tert-butyl-	119-47-1	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,2'-methylenedi-p-						
cresol						
	119-47-1	Medaka	Experimental	96 hours	No tox obs at lmt	>100 mg/l
2,2'-methylenedi-p-			_		of water sol	
cresol						

\_\_\_\_\_

6,6'-Di-tert-butyl-	119-47-1	Green algae	Experimental	72 hours	NOEC	1.3 mg/l
2,2'-methylenedi-p-		Green argue	Experimental	/2 nours	NOLC	1.5 mg/1
cresol						
Cumene	98-82-8	Activated sludge	Experimental	3 hours	EC10	>2,000 mg/l
Cumene	98-82-8	Green algae	Experimental	72 hours	EC50	2.6 mg/l
Cumene	98-82-8	Mysid Shrimp	Experimental	96 hours	EC50	1.2 mg/l
Cumene	98-82-8	Rainbow trout	Experimental	96 hours	LC50	2.7 mg/l
Cumene	98-82-8	Water flea	Experimental	48 hours	EC50	2.14 mg/l
Cumene	98-82-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
Cumene	98-82-8	Water flea	Experimental	21 days	NOEC	0.35 mg/l
Styrenated phenol	61788-44-1	Green algae	Experimental	72 hours	ErC50	1.35 mg/l
Styrenated phenol	61788-44-1	Medaka	Experimental	96 hours	LC50	5.6 mg/l
Styrenated phenol	61788-44-1	Water flea	Experimental	48 hours	EC50	4.6 mg/l
Styrenated phenol	61788-44-1	Zebra Fish	Analogous	63 days	NOEC	0.0618 mg/l
			Compound	_		
Styrenated phenol	61788-44-1	Green algae	Experimental	72 hours	NOEC	0.42 mg/l
Styrenated phenol	61788-44-1	Water flea	Experimental	21 days	NOEC	0.2 mg/l
Styrenated phenol	61788-44-1	Activated sludge	Experimental	3 hours	EC50	362 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Bluegill	Endpoint not reached	96 hours	LC50	>100 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5-	36443-68-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
METHYLPHENY L)PROPIONATE] TRIETHYLENE	36443-68-2	Water flea	Experimental	48 hours	No tox obs at lmt	>100 mg/l
GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]					of water sol	·
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Fathead minnow	Experimental	32 days	NOEC	0.0088 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE	36443-68-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Water flea	Experimental	21 days	NOEC	0.0055 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Redworm	Experimental	56 days	NOEC	1,000 mg/kg (Dry Weight)
2,5-Di-tert-	79-74-3	Bluegill	Experimental	96 hours	LC50	0.013 mg/l
pentylhydroquinon		<u> </u>				

e						
2,5-Di-tert- pentylhydroquinon e	79-74-3	Green algae	Experimental	72 hours	ErC50	0.246 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Water flea	Experimental	48 hours	LC50	0.91 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Fathead minnow	Experimental	28 days	NOEC	0.0032 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Green algae	Experimental	72 hours	NOEC	0.049 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Water flea	Experimental	21 days	NOEC	0.011 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
2,5-Di-tert- pentylhydroquinon e	79-74-3	Closed cup POLY MERS Slight	Experimental	21 days	EC50	7.95 mg/kg (Dry Weight)
2,5-Di-tert- pentylhydroquinon e	79-74-3	Redworm	Experimental	56 days	NOEC	1.7 mg/kg (Dry Weight)
2,5-Di-tert- pentylhydroquinon e	79-74-3	Soil microbes	Experimental	28 days	EC50	>1,000 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/COD	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
α,α- Dimethylbenzyl hydroperoxide	80-15-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
6,6'-Di-tert-butyl- 2,2'-methylenedi-p- cresol	119-47-1	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
Cumene	98-82-8	Experimental Biodegradation	14 days	BOD	33 %BOD/ThOD	OECD 301C - MITI test (I)
Cumene	98-82-8	Experimental Photolysis		Photolytic half-life (in air)	4.5 days (t 1/2)	
Styrenated phenol	61788-44-1	Experimental Biodegradation	28 days	BOD	7 %BOD/ThOD	OECD 301F - Manometric respirometry
Styrenated phenol	61788-44-1	Analogous Compound Biodegradation		Half-life (t 1/2)	34.9 days (t 1/2)	
Styrenated phenol	61788-44-1	Analogous Compound Soil Metabolism Aerobic		Half-life (t 1/2)	12.5 days (t 1/2)	
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Experimental Biodegradation	28 days	CO2 evolution	8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
TRIETHYLENE GLYCOL BIS[3-	36443-68-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

(3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]						
2,5-Di-tert- pentylhydroquinon e	79-74-3	Experimental Aquatic Inherent Biodegrad.	38 days		1 %CO2 evolution/THCO2 evolution	similar to OECD 301B
2,5-Di-tert- pentylhydroquinon e	79-74-3	Experimental Biodegradation		Half-life (t 1/2)	4 days (t 1/2)	

### 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
α,α- Dimethylbenzyl hydroperoxide	80-15-9	Experimental Bioconcentration		Log Kow	1.82	
6,6'-Di-tert-butyl- 2,2'-methylenedi-p- cresol	119-47-1	Experimental BCF - Fish	60 days	Bioaccumulation factor	840	OECD305-Bioconcentration
Cumene	98-82-8	Modeled Bioconcentration		Bioaccumulation factor	140	Catalogic™
Cumene	98-82-8	Experimental Bioconcentration		Log Kow	3.55	OECD 107 log Kow shke flsk mtd
Styrenated phenol	61788-44-1	Experimental BCF - Fish	10 days	Bioaccumulation factor	10395	
Styrenated phenol	61788-44-1	Experimental Bioconcentration		Log Kow	>4	
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	8.0	OECD305-Bioconcentration
TRIETHYLENE GLYCOL BIS[3- (3-TERT-BUTYL- 4-HYDROXY-5- METHYLPHENY L)PROPIONATE]	36443-68-2	Experimental Bioconcentration		Log Kow	4.7	OECD 117 log Kow HPLC method
2,5-Di-tert- pentylhydroquinon e	79-74-3	Modeled Bioconcentration		Bioaccumulation factor	44	Catalogic™
2,5-Di-tert- pentylhydroquinon e	79-74-3	Experimental Bioconcentration		Log Kow	5.1	Onion Closed cup POLYMERS

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Cumene

hydroperoxide ) **Class/Division:** 9

**Sub Risk:** Not applicable. **Packing Group:** III

**Special Instructions:** Australian Dangerous Goods Code: Not subject to this code as per Special Provision AU01

Hazchem Code: •3Z

**IERG: 47** 

International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Cumene

hydroperoxide ) **Class/Division:** 9

**Sub Risk:** Not applicable. **Packing Group:** III

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (Cumene

hydroperoxide ) **Class/Division:** 9

**Sub Risk:** Not applicable. **Packing Group:** III

Marine Pollutant: Not applicable.

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

# **SECTION 16: Other information**

#### **Revision information:**

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

P810NS KIT				
POTUNS KIT				
I Australia SDSs are av	ailable at www.3m	.com.au		

Page: 18 of 18