

Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-6251-2
 Version number:
 25.00

 Revision date:
 26/05/2025
 Supersedes date:
 23/09/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld AF-3109-2 High Tack Structural Adhesive Film

Product Identification Numbers

62-2625-6009-7 87-2500-0344-6

7000121225 7000058938

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive film.

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2

Telephone: +353 1 280 3555

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

A similar mixture has been tested for skin corrosion/irritation and the test results do not meet the criteria for classification.

A similar mixture has been tested for skin sensitization and the test results do not meet the criteria for classification.

The eye damage/irritation classification is not applied due to the nature of this product (adhesive film).

CLASSIFICATION:

Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms





Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Benzenamine, 4,4'-methylenebis-, polymer with	28390-91-2	500-062-3	15 - 25
(chloromethyl)oxirane Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-	-	946-427-4	5 - 10
yl)methyl]cyclohexyl\}methoxy)propan-2- yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4			
diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-			
[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane			
ary rors (meany renewy meany rene) jorsoxirane			

HAZARD STATEMENTS:

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

P280K Wear protective gloves and respiratory protection.

Response:

P391 Collect spillage.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH208 Contains Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane.

 $A dipohydrazide. \ | \ bis-[4-(2,3-epoxipropoxi)phenyl] propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ | \ Rxn \ mass: \ 2-(\setminus \{[1-chloro-phenyl]propane. \ |$

3-(\\\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\\\}methoxy)propan-2-

yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-

diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane. May produce an allergic reaction.

Contains 52% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation
			(EC) No. 1272/2008 [CLP]
Polymeric Epoxy Reaction Product (MW >1200)	Trade Secret	30 - 60	Substance not classified as hazardous
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	(CAS-No.) 28390-91-2 (EC-No.) 500-062-3	15 - 25	Aquatic Chronic 2, H411 Skin Sens. 1, H317 Muta. 2, H341
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01- 2119456619-26	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Rxn mass: 2-(\{[1-chloro-3-(\\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	(EC-No.) 946-427-4	5 - 10	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 3, H412
Dicyandiamide	(CAS-No.) 461-58-5 (EC-No.) 207-312-8	3 - 7	Substance not classified as hazardous
Adipohydrazide	(CAS-No.) 1071-93-8 (EC-No.) 213-999-5 (REACH-No.) 01- 2119962900-36	1 - 5	Aquatic Chronic 2, H411 Skin Sens. 1B, H317
N,N"'-(4-methyl-m-phenylene)bis[N',N'-dimethylurea]	(CAS-No.) 17526-94-2 (EC-No.) 241-523-6	1 - 5	Substance not classified as hazardous
	•		•

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If you are concerned, get medical advice.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

<u>Substance</u>	Condition
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Hydrogen cyanide.	During combustion.
Hydrogen Fluoride	During combustion.
Ammonia	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation	Population	Human exposure	DNEL
	Product		pattern	
bis-[4-(2,3-		Worker	Dermal, Long-term	8.3 mg/kg bw/d
epoxipropoxi)phenyl]prop			exposure (8 hours),	
ane			Systemic effects	
bis-[4-(2,3-		Worker	Dermal, Short-term	8.3 mg/kg bw/d
epoxipropoxi)phenyl]prop			exposure, Systemic	

ane		effects	
bis-[4-(2,3-	Worker	Inhalation, Long-term	12.3 mg/m ³
epoxipropoxi)phenyl]prop		exposure (8 hours),	_
ane		Systemic effects	
bis-[4-(2,3-	Worker	Inhalation, Short-term	12.3 mg/m ³
epoxipropoxi)phenyl]prop		exposure, Systemic	
ane		effects	

Predicted no effect concentrations (PNEC)

Ingredient	Degradation	Compartment	PNEC
	Product		
bis-[4-(2,3-		Freshwater	0.003 mg/l
epoxipropoxi)phenyl]propa			
ne			
bis-[4-(2,3-		Freshwater sediments	0.5 mg/kg d.w.
epoxipropoxi)phenyl]propa			
ne			
bis-[4-(2,3-		Intermittent releases to water	0.013 mg/l
epoxipropoxi)phenyl]propa			
ne			
bis-[4-(2,3-		Marine water	0.0003 mg/l
epoxipropoxi)phenyl]propa			
ne			
bis-[4-(2,3-		Marine water sediments	0.5 mg/kg d.w.
epoxipropoxi)phenyl]propa			
ne			
bis-[4-(2,3-		Sewage Treatment Plant	10 mg/l
epoxipropoxi)phenyl]propa			
ne			

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing.

Gloves made from the following material(s) are recommended:

Material
Chemical Protective glove of any
material type

Thickness (mm)
No data available

Breakthrough TimeNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Film
Colour	Blue
Odor	Odourless
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	Not applicable.
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	No flash point
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	Not applicable.
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	Not applicable.
Density	No data available.
Relative density	No data available.
Relative Vapour Density	Not applicable.
Particle Characteristics	Not applicable.

3M Scotch	ı-Weld Al	7-3109-2 1	High Tack	Structural A	Adhesive	Film
DIVI DUULUI	1 11 CIG 111	010/21	migh rach	Sti uctui ai i	Luncont	

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Molecular weightNo data available.Percent volatileNo data available.Percent volatileNegligible

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Amines.

10.6 Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Dermal	Rabbit	LD50 > 3,000 mg/kg
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	Rat	LD50 > 5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	Ingestion	Rat	LD50 1,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
N,N"'-(4-methyl-m-phenylene)bis[N',N'-dimethylurea]	Dermal	Rat	LD50 > 2,000 mg/kg
N,N"'-(4-methyl-m-phenylene)bis[N',N'-dimethylurea]	Ingestion	Rat	LD50 > 2,000 mg/kg
Adipohydrazide	Ingestion	Mouse	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Multiple animal species	No significant irritation
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Rabbit	No significant irritation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-	In vitro	Irritant
yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-	data	
cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-		
cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		
Dicyandiamide	Human	Minimal irritation
	and	
	animal	
N,N"'-(4-methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation
Adipohydrazide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value

Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Rabbit	Mild irritant
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Rxn mass: 2-(\{[1-chloro-3-(\\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In vitro data	No significant irritation
Dicyandiamide Dicyandiamide	Professio nal judgemen t	Mild irritant
N,N"'-(4-methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Overall product	Guinea	Not classified
	pig	
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Human	Sensitising
	and	
	animal	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-	similar	Sensitising
yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-	compoun	
cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-	ds	
cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		
Dicyandiamide	Guinea	Not classified
	pig	
Adipohydrazide	Guinea	Sensitising
	pig	

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	In vivo	Mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl]methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In Vitro	Mutagenic; structurally related to germ cell mutagens
Dicyandiamide	In Vitro	Not mutagenic
Adipohydrazide	In vivo	Not mutagenic

Carcinogenicity

eur emegement,			
Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure

					Duration
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	Not classified for development	Rat	NOAEL 90 mg/kg/day	during gestation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}met hoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymeth ylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymeth ylene)]bisoxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	13 weeks
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	gastrointestinal tract liver immune system nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks

Page: 11 of 19

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Bacteria	Experimental	24 hours	IC50	>10,000 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Common Carp	Experimental	96 hours	LC50	7 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Green algae	Experimental	72 hours	EC50	>11 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Water flea	Experimental	48 hours	EC50	4.7 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Green algae	Experimental	72 hours	EC10	2.4 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Rxn mass: 2-(\{[1- chloro-3-(\{4-	946-427-4	Green algae	Experimental	72 hours	EC50	38 mg/l

Page: 12 of 19

[methoxy(oxiran-2-yl)methyl]cyclohexyl\}						
methoxy)propan-2-						
yl]oxy\}methyl)oxirane & 2,2'-[cis-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane &						
2,2'-[trans-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane	0.46.407.4	XXX	D		EG50	
Rxn mass: 2-(\{[1-	946-427-4	Water flea	Experimental	72 hours	EC50	71 mg/l
chloro-3-(\{4-						
[methoxy(oxiran-2-						
yl)methyl]cyclohexyl\}						
methoxy)propan-2-						
yl]oxy\}methyl)oxirane						
& 2,2'-[cis-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane &						
2,2'-[trans-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane						
Rxn mass: 2-(\{[1-	946-427-4	Green algae	Experimental	72 hours	EC10	18 mg/l
chloro-3-(\{4-			1			
[methoxy(oxiran-2-						
yl)methyl]cyclohexyl\}						
methoxy)propan-2-						
yl]oxy\}methyl)oxirane						
& 2,2'-[cis-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane &						
2,2'-[trans-						
cyclohexane-1,4-						
diylbis(methyleneoxym						
ethylene)]bisoxirane						
	461.50.5	D1 '11	F ' 41	061	1.050	> 1 000 //
Dicyandiamide	461-58-5	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
Dicyandiamide	461-58-5	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
.,			r			, , , , ,
Dicyandiamide	461-58-5	Water flea	Experimental	48 hours	EC50	3,177 mg/l
Bicyundiamide	101 30 3	, vater frea	Experimental	TO HOURS	Leso	3,177 mg/1
Di	461-58-5	C1	E	72 1	NOEC	210/1
Dicyandiamide	401-38-3	Green algae	Experimental	72 hours	NOEC	310 mg/l
Dicyandiamide	461-58-5	Water flea	Experimental	21 days	NOEC	25 mg/l
Dicyandiamide	461-58-5	Redworm	Experimental	14 days	LC50	>3,200 mg/kg (Dry
			1			Weight)
Adipohydrazide	1071-93-8	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Turpony araziae	10,1,55	Treat value stange	- permientar	5 Hours		1,000 mg/1
A dim abanduagi da	1071 02 0	Common Carp	Evmorimontal	06 hours	LC50	>100 mg/l
Adipohydrazide	1071-93-8	Common Carp	Experimental	96 hours	LCSU	- 100 mg/1
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	ErC50	8.7 mg/l
			1			
Adipohydrazide	1071-93-8	Water flea	Experimental	48 hours	EC50	>=106 mg/l
						<u> </u>
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
N,N"'-(4-methyl-m-	17526-94-2	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
phenylene)bis[N',N'-	1/320-34-2	Activated studge	Experimental	Jilouis	LCJU	- 1,000 mg/1
dimethylurea]	1,750 (0.4.5	la ~	<u> </u>	0.61	X 050	100 7
N,N"'-(4-methyl-m-	17526-94-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
phenylene)bis[N',N'-						
dimethylurea]		<u> </u>			<u> </u>	<u> </u>

N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	ErC50	>100 mg/l
N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	NOEC	100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Experimental Biodegradation	28 days	CO2 evolution	10 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}meth oxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		Experimental Biodegradation	28 days	CO2 evolution	1.3 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Dicyandiamide	461-58-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 301E - Modif. OECD Screen
Dicyandiamide	461-58-5	Experimental Aquatic Inherent Biodegrad.	14 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 302B Zahn- Wellens/EVPA
Dicyandiamide	461-58-5	Experimental Biodegradation	61 days	CO2 evolution	1.1 %CO2 evolution/THC O2 evolution	OECD 309 Aero Sim Biod Water
Adipohydrazide	1071-93-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	62.1 %removal of DOC	OECD 301E - Modif. OECD Screen
Adipohydrazide	1071-93-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Experimental Aquatic Inherent Biodegrad.	28 days	Dissolv. Organic Carbon Deplet	10 %removal of DOC (does not pass 10-day window)	similar to OECD 302B
N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	33 days (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-	946-427-4	Experimental Bioconcentration		Log Kow	2.05	

Page: 14 of 19

yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymeth ylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-						
diylbis(methyleneoxymeth ylene)]bisoxirane						
Dicyandiamide	461-58-5	Experimental BCF - Fish	42 days	Bioaccumulation factor	<=3.1	OECD305-Bioconcentration
Dicyandiamide	461-58-5	Experimental Bioconcentration		Log Kow		OECD 107 log Kow shke flsk mtd
Adipohydrazide	1071-93-8	Experimental Bioconcentration		Log Kow	-2.7	OECD 107 log Kow shke flsk mtd
N,N"'-(4-methyl-m- phenylene)bis[N',N'- dimethylurea]	17526-94-2	Experimental Bioconcentration		Log Kow	<0.23	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite TM
Dicyandiamide	461-58-5	Modeled Mobility in Soil	Koc	9 l/kg	Episuite TM
Adipohydrazide	1071-93-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite TM

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	SUBSTANCE, SOLID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN; EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN; EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user		Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

IngredientCAS NbrClassificationRegulationbis-[4-(2,3-epoxipropoxi)phenyl]propane1675-54-3Gr. 3: Not classifiableInternational Agency

Page: 16 of 19

for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

IngredientCAS Nbrbis-[4-(2,3-epoxipropoxi)phenyl]propane1675-54-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Address information was modified. Section 1: E-mail address information was modified. CLP: Ingredient table information was modified.

- Label: CLP Precautionary Prevention information was modified.
- Section 3: Composition/Information of ingredients table information was modified.
- Section 6: Accidental release personal information information was modified.
- Section 7: Conditions safe storage information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Annex

1. Title		
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;	
Exposure Scenario Name	Industrial Use of Tapes and Films	
Lifecycle Stage	Use at industrial sites	
Contributing activities	PROC 21 -Low energy manipulation and handling of substances bound in/on materials or articles ERC 05 -Use at industrial site leading to inclusion into/onto article	
Processes, tasks and activities covered	Cutting and laminating of adhesive films and tapes.	
2. Operational conditions and risk mana	<u> </u>	
Operating Conditions	Physical state:Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Indoors with good general ventilation;	
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;	
Waste management measures	Do not apply industrial sludge to natural soils; Sludge should be incinerated, contained or reclaimed;	
3. Prediction of exposure		
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.	

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com