

# Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-9703-9
 Version number:
 13.00

 Issue Date:
 2025/06/05
 Supercedes Date:
 2020/10/20

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M™ SCOTCH-WELD™ CORE SPLICE ADHESIVE EC-3500 B/A PART B

**Product Identification Numbers** 

LA-T100-2875-8 62-3500-6550-4 62-3500-7550-3 87-3300-0592-4

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Base for two-part epoxy adhesive.

### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Automotive and Aerospace Solutions Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

# 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4. Skin Sensitizer: Category 1A. Germ Cell Mutagenicity: Category 2. Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 2.

#### 2.2. Label elements

Signal word

Warning

\_\_\_\_\_

#### **Symbols**

Exclamation mark | Health Hazard |

#### **Pictograms**





#### **Hazard Statements**

Harmful if swallowed. May cause an allergic skin reaction. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure: gastrointestinal tract.

## **Precautionary statements**

#### **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

## **Response:**

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical attention. Rinse mouth. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

### **Storage:**

Store locked up.

#### Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Epoxy Resin	5026-74-4	55 - 70 Trade Secret *	Oxiranemethanamine, N-[4- (oxiranylmethoxy)phenyl]-N- (oxiranylmethyl)-
Glass Bubbles	65997-17-3	20 - 40	Glass, oxide, chemicals
CLAY	68953-58-2	3 - 7	Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	68140-98-7	0.1 - 1 Trade Secret *	No Data Available

<sup>\*</sup>The concentration (exact or range) of this component has been withheld as a trade secret.

Page: 2 of 10

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Unsuitable extinguishing media

None Determined

#### 5.3. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

**Substance** Condition Carbon monoxide **During Combustion** Carbon dioxide **During Combustion During Combustion** Irritant Vapours or Gases

#### 5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be

Page: 3 of 10

#### 3M™ SCOTCH-WELD™ CORE SPLICE ADHESIVE EC-3500 B/A PART B

absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents. Store locked up.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Glass Bubbles	65997-17-3	Manufacturer	TWA(as non-fibrous,	
		determined	respirable)(8 hours):3	
			mg/m3;TWA(as non-fibrous,	
			inhalable fraction)(8 hours):10	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

# 8.2. Exposure controls

#### **8.2.1.** Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Indirect Vented Goggles** 

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Specific Physical Form:	Paste	
Colour	Tan	
Odour	Pungent Amine	
Odour threshold	No Data Available	
pH	Not Applicable	
Melting point/Freezing point	No Data Available	
Boiling point	No boiling point	
Flash Point	100 °C [Test Method:Closed Cup]	
Evaporation rate	Not Applicable	
Flammability	Not Applicable	
Flammable Limits(LEL)	Not Applicable	
Flammable Limits(UEL)	Not Applicable	
Relative Vapour Density	No Data Available	
Density	0.65 g/ml	
Relative density	0.65 [Ref Std:WATER=1]	
Water solubility	Negligible	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	

Page: 5 of 10

<b>Decomposition temperature</b>	No Data Available		
Kinematic Viscosity	No Data Available		
Volatile Organic Compounds	Not Applicable		
Percent volatile as Text	Nil		
VOC Less H2O & Exempt Solvents	Not Applicable		
Molecular weight	No Data Available		

Particle Characteristics	Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Not determined

#### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

# 10.6. Hazardous decomposition products

#### **Substance**

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No health effects are expected.

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

# **Eye Contact:**

# 3MTM SCOTCH-WELDTM CORE SPLICE ADHESIVE EC-3500 B/A PART B

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### **Additional Health Effects:**

# Prolonged or repeated exposure may cause target organ effects:

Gastrointestinal Effects: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 4,000 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 1,037 mg/kg
Glass Bubbles	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass Bubbles	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
CLAY	Dermal		LD50 estimated to be > 5,000 mg/kg
CLAY	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
CLAY	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Dermal	Rat	LD50 > 2,000 mg/kg
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	No significant irritation
Glass Bubbles	Professio	No significant irritation
	nal	
	judgeme	
	nt	
CLAY	Rat	No significant irritation
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	In vitro	No significant irritation
	data	

#### Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant
Glass Bubbles	Professio	No significant irritation
	nal	
	judgeme	
	nt	

D. . . 7 . C . 10

# 3MTM SCOTCH-WELDTM CORE SPLICE ADHESIVE EC-3500 B/A PART B

CLAY	Rabbit	No significant irritation
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	In vitro	No significant irritation
	data	

## **Skin Sensitization**

Name	Species	Value
Epoxy Resin	Mouse	Sensitizing
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Mouse	Sensitizing

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin	In vivo	Mutagenic
Glass Bubbles	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Glass Bubbles	Inhalation	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects						
Name	Route	Value	Species	Test result	Exposure Duration	
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 25 mg/kg/day	2 generation	
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during gestation	
Epoxy Resin	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	28 days	
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation	
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days	
2-Oxazoline-4-methanol, 4-ethyl-2-(8-heptadecenyl)-	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation	

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin	Ingestion	gastrointestinal tract	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 15 mg/kg/day	90 days
Epoxy Resin	Ingestion	endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver	Not classified	Rat	NOAEL 450 mg/kg/day	28 days

Page: 8 of 10

#### 3M™ SCOTCH-WELD™ CORE SPLICE ADHESIVE EC-3500 B/A PART B

		immune system   kidney and/or bladder   nervous system				
Epoxy Resin	Ingestion	eyes	Not classified	Rat	NOAEL 15 mg/kg/day	90 days
Glass Bubbles	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
2-Oxazoline-4-methanol, 4-ethyl-2-(8- heptadecenyl)-	Ingestion	endocrine system   gastrointestinal tract   liver   immune system   heart   hematopoietic system   nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification

Page: 9 of 10

#### 3M™ SCOTCH-WELD™ CORE SPLICE ADHESIVE EC-3500 B/A PART B

requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	10-9703-9	Version number:	13.00
Issue Date:	2025/06/05	Supercedes Date:	2020/10/20

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 10 of 10