



## Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-2460-3	<b>Version number:</b>	9.01
<b>Revision date:</b>	12/05/2026	<b>Supersedes date:</b>	11/05/2026

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Scotch-Weld™ Fuel Resistant Coating EC-776

#### Product Identification Numbers

62-0776-6530-5

7000000791

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Fuel Resistant coating

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

#### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225  
 Acute Toxicity, Category 4 - Acute Tox. 4; H332  
 Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314  
 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318  
 Skin Sensitization, Category 1 - Skin Sens. 1; H317  
 Germ Cell Mutagenicity, Category 2 - Muta. 2; H341  
 Carcinogenicity, Category 1B - Carc. 1B; H350  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

**2.2. Label elements**

**The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain**

**SIGNAL WORD**

DANGER.

**Symbols**

GHS02 (Flame) |GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

**Pictograms**



Ingredient	Identifier(s)	EC No.	% by Wt
4-methylpentan-2-one	108-10-1	203-550-1	50 - 60
phenol	108-95-2	203-632-7	1 - 5
formaldehyde	50-00-0	200-001-8	< 0.5
methanol	67-56-1	200-659-6	< 0.5
2,5-Di-tert-pentylhydroquinone	79-74-3	201-222-2	< 0.1

**HAZARD STATEMENTS:**

H225	Highly flammable liquid and vapour.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention:**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260E	Do not breathe vapour or spray.
P280J	Wear protective gloves, protective clothing, respiratory protection, eye protection, and face protection.

**Response:**

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

**SUPPLEMENTAL INFORMATION:****Supplemental Precautionary Statements:**

Restricted to professional users.

Contains 14% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
4-methylpentan-2-one	(CAS-No.) 108-10-1 (EC-No.) 203-550-1	50 - 60	Flam. Liq. 2, H225 Acute Tox. 4, H332(LC50 = 11 mg/l **ATE values per GB MCL**) Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066
Cresol-formaldehyde-phenol polymer	(CAS-No.) 9039-25-2	10 - 15	Substance not classified as hazardous
Acrylonitrile - butadiene polymer	(CAS-No.) 9003-18-3	10 - 15	Substance not classified as hazardous
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0	5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6	5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319
phenol	(CAS-No.) 108-95-2 (EC-No.) 203-632-7	1 - 5	Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373

			Aquatic Chronic 2, H411
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2	<= 0.99	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	<= 0.99	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	< 0.5	Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT SE 1, H370
mix-cresol	(CAS-No.) 1319-77-3 (EC-No.) 215-293-2	< 0.5	Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1B, H314 Nota C Eye Dam. 1, H318 Aquatic Chronic 3, H412
formaldehyde	(CAS-No.) 50-00-0 (EC-No.) 200-001-8	< 0.5	Acute Tox. 2, H330 EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350 Nota B,D,F Acute Tox. 3, H311
2,5-Di-tert-pentylhydroquinone	(CAS-No.) 79-74-3 (EC-No.) 201-222-2	< 0.1	Acute Tox. 4, H302 Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10

Please see section 16 for the full text of any H statements referred to in this section

**Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6	(C >= 50%) Eye Irrit. 2, H319
formaldehyde	(CAS-No.) 50-00-0 (EC-No.) 200-001-8	(C >= 25%)EUH071 (C >= 25%) Skin Corr. 1B, H314 (5% <= C < 25%) Skin Irrit. 2, H315 (C >= 25%) Eye Dam. 1, H318 (5% <= C < 25%) Eye Irrit. 2, H319 (5% <= C < 25%) STOT SE 3, H335

methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	(C >= 10%) STOT SE 1, H370 (3% =< C < 10%) STOT SE 2, H371
phenol	(CAS-No.) 108-95-2 (EC-No.) 203-632-7	(C >= 3%) Skin Corr. 1B, H314 (1% =< C < 3%) Skin Irrit. 2, H315 (1% =< C < 3%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. Get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Harmful if inhaled. Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Hydrocarbons.  
formaldehyde  
Carbon monoxide  
Carbon dioxide.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and

prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
4-methylpentan-2-one	108-10-1	UK HSE	TWA:208 mg/m <sup>3</sup> (50 ppm);STEL:416 mg/m <sup>3</sup> (100 ppm)	SKIN
toluene	108-88-3	UK HSE	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN
phenol	108-95-2	UK HSE	TWA:7.8 mg/m <sup>3</sup> (2 ppm);STEL:16 mg/m <sup>3</sup> (4 ppm)	SKIN
cyclohexane	110-82-7	UK HSE	TWA:350 mg/m <sup>3</sup> (100 ppm);STEL:1050 mg/m <sup>3</sup> (300 ppm)	
formaldehyde	50-00-0	UK HSE	TWA:2.5 mg/m <sup>3</sup> (2 ppm);STEL:2.5 mg/m <sup>3</sup> (2 ppm)	
ethanol	64-17-5	UK HSE	TWA:1920 mg/m <sup>3</sup> (1000 ppm)	
methanol	67-56-1	UK HSE	TWA:266 mg/m <sup>3</sup> (200 ppm);STEL:333 mg/m <sup>3</sup> (250 ppm)	SKIN
butanone	78-93-3	UK HSE	TWA: 600 mg/m <sup>3</sup> (200 ppm); STEL: 899 mg/m <sup>3</sup> (300 ppm)	SKIN

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

Ingredient	Identifier(s)	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
4-methylpentan-2-one	108-10-1	UK EH40 BMGVs	4-Methylpentan-2-one	Urine	EOS	20 umol/L	
butanone	78-93-3	UK EH40 BMGVs	Butan-2-one	Urine	EOS	70 umol/L	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

*Applicable Norms/Standards*

Use eye/face protection conforming to EN 16321

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for formaldehyde

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter type formaldehyde

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Colour</b>	Yellow
<b>Odor</b>	Mild Solvent
<b>Odour threshold</b>	No data available.
<b>Melting point/freezing point</b>	No data available.
<b>Boiling point/boiling range</b>	79.4 °C [ @ 101,325 Pa ] [ <i>Test Method: Estimated</i> ]
<b>Flammability</b>	Flammable Liquid: Category 2.
<b>Flammable Limits(LEL)</b>	1.8 % volume [ @ 20 °C ] [ <i>Test Method: Estimated</i> ]
<b>Flammable Limits(UEL)</b>	11.5 % volume [ @ 20 °C ] [ <i>Test Method: Estimated</i> ]
<b>Flash point</b>	10 °C [ @ 101,325 Pa ] [ <i>Test Method: Closed Cup</i> ]
<b>Autoignition temperature</b>	448.9 °C [ <i>Test Method: Estimated</i> ]

<b>Decomposition temperature</b>	<i>No data available.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	1,557 mm <sup>2</sup> /sec
<b>Water solubility</b>	Moderate
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	80 mm Hg [ <i>@ 20 °C</i> ] [ <i>Test Method: Estimated</i> ]
<b>Density</b>	0.899 g/ml [ <i>@ 20 °C</i> ]
<b>Relative density</b>	0.899 [ <i>Ref Std: WATER=1</i> ]
<b>Relative Vapour Density</b>	2.5 [ <i>Ref Std: AIR=1</i> ]
<b>Particle Characteristics</b>	<i>Not applicable.</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Evaporation rate</b>	2.7 [ <i>Ref Std: ETHER=1</i> ]
<b>Molecular weight</b>	<i>No data available.</i>
<b>Percent volatile</b>	<=77 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Sparks and/or flames.

### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

## Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Toxic if inhaled.

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction in sensitive people: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

### Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

## Additional Health Effects:

### Single exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

### Prolonged or repeated exposure may cause target organ effects:

Cardiac effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Hematopoietic effects: Signs/symptoms may include generalised weakness, fatigue and alterations in numbers of circulating blood cells. Liver effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Kidney/Bladder effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

**Additional information:**

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >2 - =10 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
4-methylpentan-2-one	Dermal	Rabbit	LD50 > 16,000 mg/kg
4-methylpentan-2-one	Inhalation-Vapour (4 hours)	Rat	LC50 11 mg/l
4-methylpentan-2-one	Ingestion	Rat	LD50 3,038 mg/kg
Cresol-formaldehyde-phenol polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Cresol-formaldehyde-phenol polymer	Inhalation-Dust/Mist		LC50 estimated to be > 12.5 mg/l
Cresol-formaldehyde-phenol polymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
butanone	Inhalation-Vapour (4 hours)	Rat	LC50 34.5 mg/l
butanone	Ingestion	Rat	LD50 2,737 mg/kg
ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
ethanol	Inhalation-Vapour (4 hours)	Rat	LC50 124.7 mg/l
ethanol	Ingestion	Rat	LD50 17,800 mg/kg
phenol	Inhalation-Vapour		LC50 estimated to be 2 - 10 mg/l
phenol	Ingestion	Human	LD50 > 140 mg/kg
phenol	Dermal	Rat	LD50 670 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
mix-cresol	Dermal	Rat	LD50 620 mg/kg
mix-cresol	Ingestion	Rat	LD50 242 mg/kg
methanol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
methanol	Inhalation-Vapour		LC50 estimated to be 10 - 20 mg/l

methanol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
formaldehyde	Dermal	Rabbit	LD50 270 mg/kg
formaldehyde	Inhalation-Gas (4 hours)	Rat	LC50 479 ppm
formaldehyde	Inhalation-Vapour (4 hours)	Rat	LC50 < 0.57 mg/l
formaldehyde	Ingestion	Rat	LD50 640 mg/kg
2,5-Di-tert-pentylhydroquinone	Dermal	Rabbit	LD50 > 3,160 mg/kg
2,5-Di-tert-pentylhydroquinone	Ingestion	Rat	LD50 1,900 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
4-methylpentan-2-one	Rabbit	Mild irritant
Cresol-formaldehyde-phenol polymer	Professional judgement	No significant irritation
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
butanone	Rabbit	Minimal irritation
ethanol	Rabbit	No significant irritation
phenol	Rat	Corrosive
toluene	Rabbit	Irritant
cyclohexane	Rabbit	Mild irritant
mix-cresol	Rabbit	Corrosive
methanol	Rabbit	Mild irritant
formaldehyde	official classification	Corrosive
2,5-Di-tert-pentylhydroquinone	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
4-methylpentan-2-one	Rabbit	Mild irritant
Cresol-formaldehyde-phenol polymer	Professional judgement	Mild irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
butanone	Rabbit	Severe irritant
ethanol	Rabbit	Severe irritant
phenol	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant
cyclohexane	Rabbit	Mild irritant
mix-cresol	similar health hazards	Corrosive
methanol	Rabbit	Moderate irritant
formaldehyde	official classification	Corrosive
2,5-Di-tert-pentylhydroquinone	Rabbit	Mild irritant

### Skin Sensitisation

Name	Species	Value
4-methylpentan-2-one	Guinea pig	Not classified
ethanol	Human	Not classified
phenol	Guinea pig	Not classified
toluene	Guinea pig	Not classified
methanol	Guinea pig	Not classified
formaldehyde	Guinea pig	Sensitising
2,5-Di-tert-pentylhydroquinone	Mouse	Sensitising

### Respiratory Sensitisation

Name	Species	Value
formaldehyde	Human	Some positive data exist, but the data are not sufficient for classification

### Germ Cell Mutagenicity

Name	Route	Value
4-methylpentan-2-one	In Vitro	Not mutagenic
butanone	In Vitro	Not mutagenic
ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
phenol	In Vitro	Some positive data exist, but the data are not sufficient for classification
phenol	In vivo	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
cyclohexane	In Vitro	Not mutagenic
cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
mix-cresol	In vivo	Not mutagenic
mix-cresol	In Vitro	Some positive data exist, but the data are not sufficient for classification
methanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
methanol	In vivo	Some positive data exist, but the data are not sufficient for classification
formaldehyde	In Vitro	Some positive data exist, but the data are not sufficient for classification
formaldehyde	In vivo	Mutagenic
2,5-Di-tert-pentylhydroquinone	In vivo	Not mutagenic
2,5-Di-tert-pentylhydroquinone	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
4-methylpentan-2-one	Inhalation	Multiple animal species	Carcinogenic.
butanone	Inhalation	Human	Not carcinogenic
ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
phenol	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

phenol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
mix-cresol	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
mix-cresol	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
methanol	Inhalation	Multiple animal species	Not carcinogenic
formaldehyde	Not specified.	Human and animal	Carcinogenic.

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4-methylpentan-2-one	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 321 mg/kg/day	2 generation
phenol	Ingestion	Not classified for development	Rat	NOAEL 120 mg/kg/day	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
mix-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	2 generation
mix-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg/day	2 generation

mix-cresol	Ingestion	Not classified for development	Rat	NOAEL 175 mg/kg/day	during organogenesis
methanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
methanol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
methanol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
formaldehyde	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg	not applicable
formaldehyde	Inhalation	Not classified for development	Rat	NOAEL 10 ppm	during gestation
2,5-Di-tert-pentylhydroquinone	Ingestion	Not classified for development	Rat	NOAEL 70 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4-methylpentan-2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
4-methylpentan-2-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
4-methylpentan-2-one	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
4-methylpentan-2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ethanol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
ethanol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
phenol	Dermal	hematopoietic system	Causes damage to organs	Rat	LOAEL 108 mg/kg	not available
phenol	Dermal	heart   nervous system   kidney and/or bladder	Causes damage to organs	Rat	LOAEL 107 mg/kg	24 hours
phenol	Dermal	liver	Not classified	Human	NOAEL Not available	not available
phenol	Inhalation	respiratory irritation	May cause respiratory irritation	Multiple animal species	NOAEL Not available	not available
phenol	Ingestion	kidney and/or	Causes damage to organs	Rat	NOAEL 120	not applicable

		bladder			mg/kg/day	
phenol	Ingestion	respiratory system	Causes damage to organs	Human	NOAEL not available	poisoning and/or abuse
phenol	Ingestion	endocrine system   liver	Not classified	Rat	NOAEL 224 mg/kg	not applicable
phenol	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
mix-cresol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available.	
mix-cresol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 68 mg/kg	
methanol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
methanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
methanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
methanol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
methanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
formaldehyde	Inhalation	respiratory system	Causes damage to organs	Rat	LOAEL 128 ppm	6 hours
formaldehyde	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4-methylpentan-2-one	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
4-methylpentan-2-one	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
4-methylpentan-2-one	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
4-methylpentan-2-one	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
4-methylpentan-2-one	Inhalation	endocrine system   hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
4-methylpentan-2-one	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks

4-methylpentan-2-one	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Ingestion	heart   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days
butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
butanone	Inhalation	liver   kidney and/or bladder   heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ethanol	Inhalation	hematopoietic system   immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
phenol	Dermal	nervous system	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 260 mg/kg/day	18 days
phenol	Inhalation	heart   liver   kidney and/or bladder   respiratory system	Causes damage to organs through prolonged or repeated exposure	Guinea pig	LOAEL 0.1 mg/l	41 days
phenol	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	LOAEL 0.1 mg/l	14 days
phenol	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
phenol	Inhalation	immune system	Not classified	Rat	NOAEL 0.1 mg/l	2 weeks
phenol	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 12 mg/kg/day	14 days
phenol	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Mouse	LOAEL 1.8 mg/kg/day	28 days
phenol	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 308 mg/kg/day	13 weeks
phenol	Ingestion	liver	Not classified	Rat	NOAEL 40 mg/kg/day	14 days
phenol	Ingestion	respiratory system	Not classified	Rat	LOAEL 40 mg/kg/day	14 days
phenol	Ingestion	immune system	Not classified	Mouse	NOAEL 1.8 mg/kg/day	28 days
phenol	Ingestion	endocrine system	Not classified	Rat	NOAEL 120 mg/kg/day	14 days
phenol	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Multiple animal species	NOAEL 1,204 mg/kg/day	103 weeks
toluene	Inhalation	auditory system	Causes damage to organs through	Human	NOAEL Not	poisoning

		nervous system   eyes   olfactory system	prolonged or repeated exposure		available	and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
mix-cresol	Ingestion	nervous system	Not classified	Rat	NOAEL 450 mg/kg/day	90 days
mix-cresol	Ingestion	hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 2,024 mg/kg/day	90 days
methanol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
methanol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
methanol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
formaldehyde	Dermal	respiratory system	Not classified	Mouse	NOAEL 80 mg/kg/day	60 weeks
formaldehyde	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 ppm	28 months
formaldehyde	Inhalation	liver	Not classified	Rat	NOAEL 20 ppm	13 weeks
formaldehyde	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 15 ppm	3 weeks

formaldehyde	Inhalation	nervous system	Not classified	Mouse	NOAEL 10 ppm	13 weeks
formaldehyde	Inhalation	endocrine system   immune system   muscles   kidney and/or bladder	Not classified	Rat	NOAEL 15 ppm	28 months
formaldehyde	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 15 ppm	2 years
formaldehyde	Inhalation	eyes   vascular system	Not classified	Rat	NOAEL 14.3 ppm	2 years
formaldehyde	Inhalation	heart	Not classified	Mouse	NOAEL 14.3 ppm	2 years
formaldehyde	Ingestion	liver	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
formaldehyde	Ingestion	immune system	Not classified	Rat	NOAEL 20 mg/kg/day	4 weeks
formaldehyde	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 15 mg/kg/day	24 months
formaldehyde	Ingestion	nervous system	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
formaldehyde	Ingestion	heart   endocrine system   hematopoietic system   respiratory system   vascular system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
formaldehyde	Ingestion	skin   muscles   eyes	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
2,5-Di-tert-pentylhydroquinone	Ingestion	endocrine system   gastrointestinal tract   liver   kidney and/or bladder   heart   skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   eyes   respiratory system   vascular system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
4-methylpentan-2-one	Some positive data exist, but the data are not sufficient for classification
toluene	Aspiration hazard
cyclohexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
4-methylpentan-2-one	108-10-1	Green algae	Experimental	96 hours	EC50	400 mg/l
4-methylpentan-2-one	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
4-methylpentan-2-one	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
4-methylpentan-2-one	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
4-methylpentan-2-one	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
4-methylpentan-2-one	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000
Acrylonitrile - butadiene polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Cresol-formaldehyde-phenol polymer	9039-25-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ethanol	64-17-5	Fathead minnow	Experimental	96 hours	LC50	14,200 mg/l
ethanol	64-17-5	Fish	Experimental	96 hours	LC50	11,000 mg/l
ethanol	64-17-5	Green algae	Experimental	72 hours	EC50	275 mg/l
ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
ethanol	64-17-5	Green algae	Experimental	72 hours	ErC10	11.5 mg/l
ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
phenol	108-95-2	Bacteria	Experimental	24 hours	IC50	21 mg/l
phenol	108-95-2	Green algae	Experimental	96 hours	EC50	61.1 mg/l
phenol	108-95-2	Rainbow trout	Experimental	96 hours	LC50	8.9 mg/l
phenol	108-95-2	Water flea	Experimental	48 hours	EC50	3.1 mg/l
phenol	108-95-2	Fish	Experimental	60 days	NOEC	0.077 mg/l
phenol	108-95-2	Water flea	Experimental	16 days	NOEC	0.16 mg/l
cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l

**3M™ Scotch-Weld™ Fuel Resistant Coating EC-776**

toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
mix-cresol	1319-77-3	Activated sludge	Estimated	3 hours	EC50	461.4 mg/l
mix-cresol	1319-77-3	Fish	Estimated	96 hours	LC50	3.36 mg/l
mix-cresol	1319-77-3	Fish	Estimated	96 hours	LC50	4.4 mg/l
mix-cresol	1319-77-3	Water flea	Estimated	48 hours	EC50	7.7 mg/l
mix-cresol	1319-77-3	Fathead minnow	Estimated	32 days	NOEC	1.35 mg/l
mix-cresol	1319-77-3	Water flea	Estimated	21 days	NOEC	1 mg/l
formaldehyde	50-00-0	Green algae	Experimental	72 hours	ErC50	4.89 mg/l
formaldehyde	50-00-0	Striped bass	Experimental	96 hours	LC50	6.7 mg/l
formaldehyde	50-00-0	Water flea	Experimental	48 hours	EC50	5.8 mg/l
formaldehyde	50-00-0	Medaka	Experimental	28 days	NOEC	>=48 mg/l
formaldehyde	50-00-0	Water flea	Experimental	21 days	NOEC	>=6.4 mg/l
formaldehyde	50-00-0	Activated sludge	Experimental	3 hours	EC50	19 mg/l
methanol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
methanol	67-56-1	Bay mussel	Experimental	96 hours	LC50	15,900 mg/l
methanol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
methanol	67-56-1	Green algae	Experimental	96 hours	ErC50	22,000 mg/l
methanol	67-56-1	Sediment organism	Experimental	96 hours	LC50	54,890 mg/l
methanol	67-56-1	Water flea	Experimental	48 hours	LC50	3,289 mg/l
methanol	67-56-1	Green algae	Experimental	96 hours	NOEC	9.96 mg/l
methanol	67-56-1	Medaka	Experimental	8.33 days	NOEC	158,000 mg/l

methanol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
methanol	67-56-1	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
methanol	67-56-1	Barley	Experimental	14 days	EC50	15,492 mg/kg (Dry Weight)
methanol	67-56-1	Redworm	Experimental	63 days	EC50	26,646 mg/kg (Dry Weight)
methanol	67-56-1	Springtail	Experimental	28 days	EC50	5,683 mg/kg (Dry Weight)
2,5-Di-tert-pentylhydroquinone	79-74-3	Bluegill	Experimental	96 hours	LC50	0.013 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Green algae	Experimental	72 hours	ErC50	0.246 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Water flea	Experimental	48 hours	LC50	0.91 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Fathead minnow	Experimental	28 days	NOEC	0.0032 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Green algae	Experimental	72 hours	NOEC	0.049 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Water flea	Experimental	21 days	NOEC	0.011 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
2,5-Di-tert-pentylhydroquinone	79-74-3	Onion	Experimental	21 days	EC50	7.95 mg/kg (Dry Weight)
2,5-Di-tert-pentylhydroquinone	79-74-3	Redworm	Experimental	56 days	NOEC	1.7 mg/kg (Dry Weight)
2,5-Di-tert-pentylhydroquinone	79-74-3	Soil microbes	Experimental	28 days	EC50	>1,000 mg/kg (Dry Weight)

## 12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
4-methylpentan-2-one	108-10-1	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301F - Manometric respirometry
4-methylpentan-2-one	108-10-1	Experimental Photolysis		Photolytic half-life (in air)	2.3 days (t 1/2)	
Acrylonitrile - butadiene polymer	9003-18-3	Data not available - insufficient	N/A	N/A	N/A	N/A
Cresol-formaldehyde-phenol polymer	9039-25-2	Data not available - insufficient	N/A	N/A	N/A	N/A
ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 %BOD/ThOD	OECD 301C - MITI test (I)
butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301D - Closed bottle test
phenol	108-95-2	Experimental Biodegradation	100 hours	BOD	62 %BOD/ThOD	OECD 301C - MITI test (I)
cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental		Photolytic half-life	5.2 days (t 1/2)	

		Photolysis		(in air)		
mix-cresol	1319-77-3	Estimated Biodegradation	28 days	BOD	65 %BOD/ThOD	OECD 301D - Closed bottle test
formaldehyde	50-00-0	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	99 %removal of DOC	OECD 301A - DOC Die Away Test
formaldehyde	50-00-0	Experimental Biodegradation	160 days	BOD	99.5 %BOD/COD	OECD 303A - Simulated Aerobic
methanol	67-56-1	Experimental Biodegradation	3 days	Percent degraded	91 %degraded	
methanol	67-56-1	Experimental Biodegradation	14 days	BOD	92 %BOD/ThOD	OECD 301C - MITI test (I)
methanol	67-56-1	Experimental Photolysis		Photolytic half-life (in air)	35 days (t 1/2)	
methanol	67-56-1	Experimental Soil Metabolism Aerobic	5 days	CO2 evolution	53.4 %CO2 evolution/THCO2 evolution	
2,5-Di-tert-pentylhydroquinone	79-74-3	Experimental Aquatic Inherent Biodegrad.	38 days	CO2 evolution	1 %CO2 evolution/THCO2 evolution	similar to OECD 301B
2,5-Di-tert-pentylhydroquinone	79-74-3	Experimental Biodegradation		Half-life (t 1/2)	4 days (t 1/2)	

### 12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
4-methylpentan-2-one	108-10-1	Experimental Bioconcentration		Log Kow	1.9	OECD 117 log Kow HPLC method
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cresol-formaldehyde-phenol polymer	9039-25-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.35	
butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
phenol	108-95-2	Experimental Bioconcentration		Log Kow	1.47	
cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
cyclohexane	110-82-7	Experimental Bioconcentration		Log Kow	3.44	
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
mix-cresol	1319-77-3	Experimental Bioconcentration		Log Kow	1.95	
formaldehyde	50-00-0	Experimental Bioconcentration		Log Kow	0.35	
methanol	67-56-1	Experimental BCF - Fish	3 days	Bioaccumulation factor	<4.5	
methanol	67-56-1	Experimental Bioconcentration		Log Kow	-0.77	
2,5-Di-tert-pentylhydroquinone	79-74-3	Modeled Bioconcentration		Bioaccumulation factor	44	Catalogic™
2,5-Di-tert-pentylhydroquinone	79-74-3	Experimental Bioconcentration		Log Kow	5.1	EC A.23 Part. Coeff Slow-Stir

### 12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
4-methylpentan-2-one	108-10-1	Modeled Mobility in Soil	Koc	150 l/kg	Episuite™
cyclohexane	110-82-7	Modeled Mobility in Soil	Koc	970 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
formaldehyde	50-00-0	Estimated Mobility in Soil	Koc	15.9 l/kg	
methanol	67-56-1	Experimental Mobility in Soil	Koc	0.13 l/kg	
2,5-Di-tert-pentylhydroquinone	79-74-3	Experimental Mobility in Soil	Koc	4,800 l/kg	OECD 121 Estim. of Koc by HPLC

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

**SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
<b>14.1 - UN Number or ID number</b>	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT	PAINT	PAINT
<b>14.3 Transport hazard class(es)</b>	3	3	3

<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable.	Not a Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>Identifier(s)</u>	<u>Classification</u>	<u>Regulation</u>
formaldehyde	50-00-0	Carc. 1B	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain, UK Mandatory Classification and Labelling list
formaldehyde	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
4-methylpentan-2-one	108-10-1	Carc. 2	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain, UK Mandatory Classification and Labelling list
4-methylpentan-2-one	108-10-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

phenol	108-95-2	Gr. 3: Not classifiable	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

**Restrictions on the manufacture, placing on the market and use:**

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>Identifier(s)</u>
cyclohexane	110-82-7
methanol	67-56-1
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

**Regulation UK regulation 2023/63 (marketing and use of explosive precursors and poisons)**

This product contains a reportable substance according to UK legislation 1972/66: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see UK Regulation 2023/63 for further details.

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**COMAH Regulation, SI 2015/483**

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply  
Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
formaldehyde	50-00-0	5	50
methanol	67-56-1	500	5000

#### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

## SECTION 16: Other information

#### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

H412	Harmful to aquatic life with long lasting effects.
------	--

#### List of Relevant Notas

Nota B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
Nota C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Nota D	Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.
Nota F	This substance may contain a stabiliser. If the stabiliser changes the hazardous properties of the substance, as indicated by the classification in Part 3, classification and labelling should be provided in accordance with the rules for classification and labelling of hazardous mixtures.

#### Revision information:

EU Section 14 - Table Data information was added.  
 EU Section 14 - Table Headers information was added.  
 GB Section 02: CLP Ingredient table information was modified.  
 GB Section 15: Carcinogenicity information information was modified.  
 GBSDS Section 14 Transport in bulk - Main Heading information was deleted.  
 GBSDS Section 14 UN Number information was deleted.  
 Label: Graphic information was modified.  
 Section 03: SCL table information was modified.  
 Section 11: Acute Toxicity table information was modified.  
 Section 11: Carcinogenicity Table information was modified.  
 Section 11: Germ Cell Mutagenicity Table information was modified.  
 Section 11: Health Effects - Inhalation information information was modified.  
 Section 11: Reproductive Toxicity Table information was modified.  
 Section 11: Respiratory Sensitization Table information was modified.  
 Section 11: Serious Eye Damage/Irritation Table information was modified.  
 Section 11: Skin Corrosion/Irritation Table information was modified.  
 Section 11: Skin Sensitization Table information was modified.  
 Section 11: Target Organs - Repeated Table information was modified.  
 Section 11: Target Organs - Single Table information was modified.  
 Section 12: Component ecotoxicity information information was modified.  
 Section 12: Mobility in soil information information was modified.  
 Section 12: Persistence and Degradability information information was modified.  
 Section 12: Bioaccumulative potential information information was modified.  
 Section 14 Classification Code – Main Heading information was deleted.  
 Section 14 Classification Code – Regulation Data information was deleted.  
 Section 14 Control Temperature – Main Heading information was deleted.  
 Section 14 Control Temperature – Regulation Data information was deleted.  
 Section 14 Emergency Temperature – Main Heading information was deleted.  
 Section 14 Emergency Temperature – Regulation Data information was deleted.  
 Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.  
 Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.  
 Section 14 Other Dangerous Goods – Main Heading information was deleted.  
 Section 14 Other Dangerous Goods – Regulation Data information was deleted.

Section 14 Packing Group – Main Heading information was deleted.  
Section 14 Packing Group – Regulation Data information was deleted.  
Section 14 Proper Shipping Name information was deleted.  
Section 14 Regulations – Main Headings information was deleted.  
Section 14 Segregation – Regulation Data information was deleted.  
Section 14 Segregation Code – Main Heading information was deleted.  
Section 14 Special Precautions – Main Heading information was deleted.  
Section 14 Special Precautions – Regulation Data information was deleted.  
Section 14 Transport in bulk – Regulation Data information was deleted.  
Section 14 UN Number Column data information was deleted.  
Section 15: Seveso Substance Text information was modified.  
Section 16: Two-column table displaying the unique list of Notas for all components of the given material. information was added.  
Section 3: Composition/ Information of ingredients table information was modified.  
Section 4: First aid for inhalation information information was modified.  
Section 5: Hazardous combustion products table information was modified.  
Section 8: Occupational exposure limit table information was modified.  
Section 9: Vapour pressure value information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M SDSs for Great Britain are available at [www.3M.com/uk](http://www.3M.com/uk)**

For Northern Ireland documents, please contact your 3M representative to obtain a copy.