



Safety Data Sheet

Copyright, 2026, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-7850-5	Version Number:	3.01
Issue Date:	07/15/2026	Supersedes Date:	10/17/2025

This Safety Data Sheet has been prepared in accordance with the DENR Administrative Order No. 2015-09 Rules and Procedures for the Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Preparation of Safety Data Sheet (SDS) and Labelling Requirements of Toxic Chemical Substances.

SECTION 1: Identification

1.1. Product identifier

3M™ Brake and Parts Cleaner PN08896, PN08894

Product Identification Numbers

PN-2830-0009-1

1.2. Recommended use and restrictions on use

Recommended use

Designed to remove oil, grease, and brake fluid contaminants from all types of brake assemblies and brake parts., Sold in industrial markets (automotive industry). To be used in brake linings and shoes, drums, cylinders, caliper units, disc brake pads, and all other related parts. Should be used in a well ventilated area.

1.3. Supplier's details

ADDRESS:	3M Philippines, Inc., 18th Floor, Bonifacio Stopover Corporate Center, 31st Street corner, 2nd Avenue, Bonifacio Global City, Taguig City, 1635 Philippines
Telephone:	+632 827 11680
E Mail:	mcvillalva@mmm.com
Website:	www.3m.com/ph

1.4. Emergency telephone number

+632 827 11680

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 2B.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Aspiration Hazard: Category 1.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H315	Causes skin irritation.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H370	Causes damage to organs: cardiovascular system.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P273	Avoid release to the environment.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor.
P331	Do NOT induce vomiting.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).
-------------	--

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.
------	---

2.3. Other hazards

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	60 - 80
LIQUEFIED PETROLEUM GAS	68476-85-7	10 - 30
2-METHYLHEXANE	591-76-4	10 - 30*
2-METHYLPENTANE	107-83-5	1 - 10*

*These components are contained as a part of SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC(64742-89-8)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Branched Hexane Isomers	107-83-5	ACGIH	TWA:200 ppm	A3: Confirmed animal carcin.
Heptane (n-heptane)	591-76-4	Philippines OELs	TWA(8 hours):2000 mg/m3(500 ppm)	
Heptane, straight and branched isomers	591-76-4	ACGIH	TWA:200 ppm;STEL:400 ppm	Ototoxicant

Hexane (Commercial, <54% n-Hexane)	64742-89-8	ACGIH	TWA:100 ppm	A3: Confirmed animal carcin., Danger of cutaneous absorption
Naphtha (coal tar)	64742-89-8	Philippines OELs	TWA(8 hours):400 mg/m3(100 ppm)	
LIQUEFIED PETROLEUM GAS	68476-85-7	ACGIH	Limit value not established:	simple asphyxiant
LIQUEFIED PETROLEUM GAS	68476-85-7	Philippines OELs	TWA(8 hours):1800 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Philippines OELs : Philippines. Threshold Limit Values for Airborne Contaminants

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol

Color	Colorless
Odor	Mild Solvent
Odor threshold	<i>No Data Available</i>
pH	5 - 6
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	<i>No Data Available</i>
Flash Point	-15 °C [Test Method: Closed Cup] [Details: CAS#64742-89-8]
Evaporation rate	<i>No Data Available</i>
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Relative Vapor Density	<i>No Data Available</i>
Density	<i>No Data Available</i>
Relative Density	0.653 - 0.753 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight

Heat

High shear and high temperature conditions

Temperatures above the boiling point

Sparks and/or flames

10.5. Incompatible materials

Combustibles

Drugs, medicines and/or food supplies.

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Dermal	Rabbit	LD50 3,000 mg/kg
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Ingestion	Rat	LD50 > 5,000 mg/kg
LIQUEFIED PETROLEUM GAS	Inhalation-Gas (4 hours)	Rat	LC50 227,000 ppm
2-METHYLHEXANE	Dermal	similar compounds	LD50 > 2,000 mg/kg
2-METHYLHEXANE	Inhalation-Vapor (4 hours)	similar compounds	LC50 > 33.5 mg/l
2-METHYLHEXANE	Ingestion	similar compounds	LD50 > 5,000 mg/kg
2-METHYLPENTANE	Dermal		LD50 estimated to be > 5,000 mg/kg
2-METHYLPENTANE	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
2-METHYLPENTANE	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Rabbit	Irritant
LIQUEFIED PETROLEUM GAS	Professional judgement	No significant irritation
2-METHYLHEXANE	Professional judgement	Mild irritant
2-METHYLPENTANE	Professional judgement	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Rabbit	No significant irritation
LIQUEFIED PETROLEUM GAS	Professional judgement	No significant irritation
2-METHYLHEXANE	similar compounds	Mild irritant
2-METHYLPENTANE	Professional judgement	Moderate irritant

Sensitization:

Skin Sensitization

Name	Species	Value
2-METHYLHEXANE	similar compounds	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	In Vitro	Not mutagenic
LIQUEFIED PETROLEUM GAS	In Vitro	Not mutagenic
2-METHYLHEXANE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
LIQUEFIED PETROLEUM GAS	Inhalation	cardiac sensitization	Causes damage to organs	similar compounds	NOAEL Not available	
LIQUEFIED PETROLEUM GAS	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
LIQUEFIED PETROLEUM GAS	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
2-METHYLHEXANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-METHYLHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-METHYLHEXANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-METHYLPENTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-METHYLPENTANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-METHYLPENTANE	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
2-METHYLPENTANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
LIQUEFIED PETROLEUM GAS	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
2-METHYLHEXANE	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
2-METHYLHEXANE	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
2-METHYLHEXANE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
2-METHYLHEXANE	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
2-METHYLPENTANE	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-METHYLPENTANE	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-METHYLPENTANE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	Aspiration hazard
2-METHYLHEXANE	Aspiration hazard
2-METHYLPENTANE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Fathead Minnow	Analogous Compound	96 hours	LL50	4.1 mg/l
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Water flea	Analogous Compound	48 hours	EL50	4.5 mg/l
SOLVENT	64742-89-8	Green algae	Experimental	72 hours	EL50	4.1 mg/l

NAPHTHA (PETROLEUM), LIGHT ALIPHATIC						
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Water flea	Analogous Compound	21 days	NOEL	2.6 mg/l
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Green algae	Experimental	72 hours	NOEL	0.1 mg/l
2-METHYLHEXANE	591-76-4	Mysid Shrimp	Analogous Compound	96 hours	LC50	0.4 mg/l
2-METHYLHEXANE	591-76-4	Water flea	Analogous Compound	48 hours	EC50	0.4 mg/l
LIQUEFIED PETROLEUM GAS	68476-85-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2-METHYLPENTANE	107-83-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Analogous Compound Soil Inherent Biodegradability	28 days	Carbon dioxide evolution	74.3 %CO ₂ evolution/THCO ₂ evolution	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	77.05 %BOD/ThOD	OECD 301F - Manometric Respiro
2-METHYLHEXANE	591-76-4	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	93 %BOD/ThOD	OECD 301C - MITI (I)
LIQUEFIED PETROLEUM GAS	68476-85-7	Estimated Photolysis		Photolytic half-life (in air)	21.4 days (t 1/2)	
2-METHYLPENTANE	107-83-5	Experimental Biodegradation	28 days	Biological Oxygen Demand	93 %BOD/ThOD	OECD 301C - MITI (I)
2-METHYLPENTANE	107-83-5	Experimental Photolysis		Photolytic half-life (in air)	6.1 days (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Estimated Bioconcentration		Log of Octanol/H ₂ O part. coeff	2.72	
2-	591-76-4	Modeled		Bioaccumulation	98	Catalogic™

METHYLHEXANE		Bioconcentration		Factor		
2-METHYLHEXANE	591-76-4	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	3.71	Episuite™
LIQUEFIED PETROLEUM GAS	68476-85-7	Estimated Bioconcentration		Log of Octanol/H2O part. coeff	2.8	
2-METHYLPENTANE	107-83-5	Modeled Bioconcentration		Bioaccumulation Factor	47	Catalogic™
2-METHYLPENTANE	107-83-5	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	3.21	Episuite™

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information**Marine Transport (IMDG)**

UN Number:UN1950

Proper Shipping Name:AEROSOLS, FLAMMABLE

Technical Name:None assigned.

Hazard Class/Division:2.1

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN1950

Proper Shipping Name:AEROSOLS, FLAMMABLE

Technical Name:None assigned.

Hazard Class/Division:2.1

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

Revision information:

Section 02: PH Pictogram information was modified.

Section 04: First Aid - notes to physician (REACH/GHS) information was modified.

Section 06: Accidental release personal information information was modified.

Section 07: Precautions safe handling information information was modified.

Section 11: Health Effects - Eye information information was modified.

Section 11: Health Effects - Ingestion information information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Health Effects - Skin information information was modified.

Section 11: Single exposure may cause standard phrases information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Philippines SDSs are available at www.3m.com/ph