

# **Safety Data Sheet**

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 34-6374-2
 Version number:
 4.00

 Issue Date:
 2025/06/20
 Supercedes Date:
 2020/11/25

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### **SECTION 1: Identification**

#### 1.1. Product identifier

3M(TM) NOVEC (TM) ELECTRONIC DEGREASER

**Product Identification Numbers** 

98-0212-4890-7 98-0212-4890-5 FF-9200-1183-1 FF-9200-1185-6 H0-0023-2299-0

UU-0037-2139-4

#### 1.2. Recommended use and restrictions on use

### **Intended Use**

Electronic Degreaser

#### Restrictions on use

For Industrial Use only. Not intended for consumer sale or use. Not intended for use as a medical device or drug.

### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Electronics Materials Solutions Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

### **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Aerosol: Category 3.

Serious Eye Damage/Irritation: Category 2B.

Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

Signal word

Warning

### **Symbols**

Exclamation mark

#### **Pictograms**



#### **Hazard Statements**

Pressurized container: may burst if heated.

Causes eye irritation. May cause drowsiness or dizziness.

### **Precautionary statements**

#### **Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Avoid breathing vapours, dust, or spray. Wash exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor if you feel unwell. If eye irritation persists: Get medical advice.

#### Storages

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

### Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
1,2-Trans-Dichloroethylene	156-60-5	65 - 70 Trade Secret *	Ethene, 1,2-dichloro-, (E)-
Methyl nonafluoroisobutyl ether	163702-08-7	16.5 - 27	Propane, 2-(difluoromethoxymethyl)-
			1,1,1,2,3,3,3-heptafluoro -
Methyl nonafluorobutyl ether	163702-07-6	3 - 13.5	Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-
			methoxy-
Carbon Dioxide	124-38-9	<= 5	Carbon dioxide

<sup>\*</sup>The concentration (exact or range) of this component has been withheld as a trade secret.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Inhalation:

Page: 2 of 11

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If you feel unwell, get medical attention.

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Unsuitable extinguishing media

None Determined

#### 5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### 5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air.

### **6.2.** Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety

precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Store work clothes separately from other clothing, food and tobacco products. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C). Store away from heat. Store away from strong bases. Store away from oxidizing agents. Store locked up.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Carbon Dioxide	124-38-9	ACGIH	TWA:5000 ppm;STEL:30000	
			ppm	
1,2-Trans-Dichloroethylene	156-60-5	ACGIH	TWA: 200 ppm	
Methyl nonafluorobutyl ether	163702-07-	AIHA	TWA:750 ppm	
_	6			
Methyl nonafluoroisobutyl ether	163702-08-	AIHA	TWA:750 ppm	
	7			

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

No chemical protective gloves are required.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Colour	Colourless
Odour	Slight Solvent
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	43 °C
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability	Non-flammable Aerosol: Category 3.
Flammable Limits(LEL)	6.7 % volume
Flammable Limits(UEL)	13.7 % volume
Vapour Pressure	43,996.3 Pa
Relative Vapour Density	No Data Available
Density	1.28 g/ml
Relative density	1.28 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	396 ℃
Decomposition temperature	No Data Available
Kinematic Viscosity	0.352 mm2/sec
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

\_\_\_\_\_

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Strong oxidizing agents Strong bases

### 10.6. Hazardous decomposition products

Substance Condition Hydrogen Chloride At Elevated Temperatures - - extreme conditions Hydrogen Fluoride At Elevated Temperatures - - extreme conditions Perfluoroisobutylene (PFIB) At Elevated Temperatures - - extreme conditions

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May cause additional health effects (see below).

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
1,2-Trans-Dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,2-Trans-Dichloroethylene	Inhalation- Vapor (4 hours)	Rat	LC50 95.6 mg/l
1,2-Trans-Dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Methyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be > 5,000 mg/kg
Methyl nonafluoroisobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl nonafluorobutyl ether	Dermal		LD50 estimated to be > 5,000 mg/kg
Methyl nonafluorobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Dioxide	Inhalation- Gas (4 hours)	Rat	LC50 > 53,000 ppm

ATE = acute toxicity estimate

### Skin Corresion/Irritation

Skin Corrosion/Irritation		
Name	Species	Value
1,2-Trans-Dichloroethylene	Rabbit	Minimal irritation
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Name	Species	Value
1,2-Trans-Dichloroethylene	Rabbit	Moderate irritant
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
Methyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Methyl nonafluorobutyl ether	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Ger in Cen Wittagementy		
Name	Route	Value
1,2-Trans-Dichloroethylene	In Vitro	Not mutagenic
1,2-Trans-Dichloroethylene	In vivo	Not mutagenic
Methyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Methyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Methyl nonafluorobutyl ether	In Vitro	Not mutagenic

Methyl nonafluorobut	yl ether	In vivo	Not mutagenic

### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
1,2-Trans-Dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesi s
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Methyl nonafluorobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Carbon Dioxide	Inhalation	Not classified for male reproduction	Mouse	LOAEL 350,000 ppm	not available
Carbon Dioxide	Inhalation	Not classified for development	Rat	LOAEL 60,000 ppm	24 hours

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,2-Trans-Dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2-Trans-Dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1,2-Trans-Dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable
Methyl nonafluoroisobutyl ether	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Methyl nonafluoroisobutyl ether	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913 mg/l	10 minutes
Methyl nonafluorobutyl ether	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Methyl nonafluorobutyl ether	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913 mg/l	10 minutes

Specific Target Organ Toxicity - repeated exposure

specific ranger organ	specific Target Organ Toxicity - Tepeated exposure						
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	
1,2-Trans- Dichloroethylene	Inhalation	endocrine system   liver   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 16 mg/l	90 days	
1,2-Trans- Dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks	
1,2-Trans- Dichloroethylene	Ingestion	blood   liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks	

Page: 8 of 11

1,2-Trans-	Ingestion	heart   immune	Not classified	Rat	NOAEL	14 weeks
Dichloroethylene	8.2.	system   respiratory			2,000	
		system			mg/kg/day	
Methyl nonafluoroisobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluoroisobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methyl nonafluorobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluorobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluorobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluorobutyl ether	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Carbon Dioxide	Inhalation	heart   bone, teeth, nails, and/or hair   liver   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	LOAEL 60,000 ppm	166 days

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

Page: 9 of 11

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

### **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

**Health:** 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	34-6374-2	Version number:	4.00
Issue Date:	2025/06/20	Supercedes Date:	2020/11/25

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES

Page: 10 of 11

NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca