



## Safety Data Sheet

Copyright, 2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	11-2661-4	<b>Version number:</b>	18.02
<b>Issue Date:</b>	2026/01/07	<b>Supersedes Date:</b>	2025/08/28

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP460 Off-White

#### Product Identification Numbers

EC-3593	62-2796-1435-8	62-2796-3530-4	62-2796-3830-8	62-2796-6430-4
62-3593-1430-9	62-3593-1431-7	62-3593-1435-8	62-3593-1436-6	62-3593-1438-2
62-3593-1439-0	62-3593-3530-4	62-3593-3830-8	62-3593-3835-7	H0-0016-1675-6
H0-0016-1679-8	H0-0022-6431-7	HB-0041-2980-3	HB-0045-6083-3	HB-0045-6106-2
HB-0047-6721-4	JS-3000-4923-1	JS-3000-4995-9	JS-3000-5047-8	UU-0121-1741-0
XD-0055-2916-4				

### 1.2. Recommended use and restrictions on use

#### Recommended use

Structural adhesive

### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577  
**E Mail:**

### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

22-0526-8, 22-0535-9

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**



## Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 22-0526-8      **Version number:** 6.04  
**Issue Date:** 2025/09/26      **Supersedes Date:** 2025/07/14

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP-460, Off-White (Part B)

#### Product Identification Numbers

JS-3000-4997-5

### 1.2. Recommended use and restrictions on use

#### Intended Use

Structural adhesive

#### Restrictions on use

Not applicable

### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1  
**Telephone:** (800) 364-3577  
**Website:** www.3M.ca

### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

### 2.2. Label elements

#### Signal word

Warning

#### Symbols

Exclamation mark |

**Pictograms**



**Hazard Statements**

Causes eye irritation. May cause an allergic skin reaction.

**Precautionary statements**

**Prevention:**

Avoid breathing vapours. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

**Response:**

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse.

**Disposal:**

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Other hazards**

None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Epoxy Resin	25068-38-6	80 - 100 Trade Secret *	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Acrylic Polymer	Trade Secret	1 - 20	Not Applicable

Acrylic Polymer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

\*The concentration (exact or range) of this component has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical

attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Unsuitable extinguishing media**

None Determined

**5.3. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Irritant Vapours or Gases	During Combustion

**5.4. Special protection actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### **7.2. Conditions for safe storage including any incompatibilities**

Store away from oxidizing agents.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

#### **Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### **8.2. Exposure controls**

#### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### **8.2.2. Personal protective equipment (PPE)**

##### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

##### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

##### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates  
 Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Colour	White
Odour	Mild Epoxy
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point	>=260 °C
Flash Point	248.9 °C [Test Method:Closed Cup]
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	Not Applicable
Relative Vapour Density	Not Applicable
Density	1.14 g/ml
Relative density	1.14 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	30,702 mm <sup>2</sup> /sec
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H <sub>2</sub> O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part A]
VOC Less H <sub>2</sub> O & Exempt Solvents	5 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:as supplied]
VOC Less H <sub>2</sub> O & Exempt Solvents	0 % [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part A]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Acrylic Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylic Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant
Acrylic Polymer	Professional judgement	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant
Acrylic Polymer	Professional judgement	Mild irritant

**Skin Sensitization**

Name	Species	Value
Epoxy Resin	Human and animal	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
Epoxy Resin	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	22-0526-8	<b>Version number:</b>	6.04
<b>Issue Date:</b>	2025/09/26	<b>Supersedes Date:</b>	2025/07/14

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)



## Safety Data Sheet

Copyright, 2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 22-0535-9      **Version number:** 8.04  
**Issue Date:** 2026/01/07      **Supersedes Date:** 2025/06/25

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP460 Off-White, Part A

#### Product Identification Numbers

JS-3000-4993-4

### 1.2. Recommended use and restrictions on use

#### Intended Use

Structural adhesive

#### Restrictions on use

Not applicable

### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1  
**Telephone:** (800) 364-3577  
**Website:** www.3M.ca

### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 1B.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

Health Hazards Not Otherwise Classified - Category 1

### 2.2. Label elements

#### Signal word

Danger

**Symbols**

Corrosion | Exclamation mark |

**Pictograms****Hazard Statements**

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause chemical gastrointestinal burns.

**Precautionary statements****Prevention:**

Do not breathe vapours. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection, and face protection.

**Response:**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Other hazards**

None known.

### SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Modified Epoxy Resin	Trade Secret	40 - 70	Not Applicable
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	30 - 60 Trade Secret *	1-Propanamine, 3,3'-[oxybis(2,1-ethanediyoxy)]bis-
2,4,6-tris((Dimethylamino)-Methyl)Phenol	90-72-2	1 - 5 Trade Secret *	Phenol, 2,4,6-tris[(dimethylamino)methyl]-
Amorphous Silica	67762-90-7	1 - 5	Siloxanes and Silicones, di-Me, reaction products with silica

Modified Epoxy Resin is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

\*The concentration (exact or range) of this component has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Unsuitable extinguishing media

None Determined

### 5.3. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Nitrogen	During Combustion

### 5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so.

Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

## 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines. Store locked up.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Butyl Rubber, Nitrile Rubber, Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	viscous liquid
Colour	Amber
Odour	Mild Amine, Pungent Odour
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	>=171 °C
Flash Point	171.1 °C [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	<=3.0 mmHg [@ 68 °F]
Relative Vapour Density	3.72 [Ref Std: AIR=1]
Density	1.09 g/ml
Relative density	1.09 [Ref Std: WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	9,862 mm <sup>2</sup> /sec
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H <sub>2</sub> O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part B]

VOC Less H <sub>2</sub> O & Exempt Solvents	0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Amines

Alcohols

Strong bases

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

**Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Dermal	Rabbit	LD50 2,525 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Rat	LD50 2,850 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Overall product	In vitro data	Corrosive
4,7,10-Trioxatridecane-1,13-Diamine	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
4,7,10-Trioxatridecane-1,13-Diamine	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
4,7,10-Trioxatridecane-1,13-Diamine	Professional judgment	Sensitizing
Amorphous Silica	Human and animal	Not classified
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Overall product	In Vitro	Not mutagenic
4,7,10-Trioxatridecane-1,13-Diamine	In Vitro	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
2,4,6-tris((Dimethylamino)-Methyl)Phenol	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	pre mating into lactation
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	pre mating into lactation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,7,10-Trioxatridecane-1,13-Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	heart	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	endocrine system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 600 mg/kg/day	59 days

4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	liver	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	immune system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	muscles	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	eyes	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Amorphous Silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous Silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	liver	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	nervous system	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	auditory system	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	hematopoietic system	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Dermal	eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	heart	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	endocrine system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	liver	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	muscles	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	vascular system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	auditory system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

tris((Dimethylamino)-Methyl)Phenol					mg/kg/day	
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	skin	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	immune system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
2,4,6-tris((Dimethylamino)-Methyl)Phenol	Ingestion	eyes	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

#### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	22-0535-9	<b>Version number:</b>	8.04
<b>Issue Date:</b>	2026/01/07	<b>Supersedes Date:</b>	2025/06/25

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**