



Safety Data Sheet

Copyright,2026, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-1817-1	Version Number:	6.00
Issue Date:	01/02/26	Supersedes Date:	10/05/23

SECTION 1: Identification

1.1. Product identifier

3M™ FireDam™ Spray 200-Gray

Product Identification Numbers

98-0400-5587-7

7100006336

1.2. Recommended use and restrictions on use

Recommended use

Fire retardant spray

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Specialties Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary statements

General:

Keep out of reach of children.

Prevention:

Avoid breathing vapor or spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	15 - 40
Polymer (NJTS Reg. No. 04499600-7181)	Trade Secret*	15 - 40
Calcium Carbonate	471-34-1	10 - 30
Alumina Trihydrate	21645-51-2	7 - 13
Styrene-butadiene Polymer	9003-55-8	5 - 10
Alcohol Ethoxysulfate (Sodium Salt)	68585-34-2	< 1
Alcohols, C12-14-Secondary, Ethoxylated	84133-50-6	< 1
Bentonite (nanoplatelets)	1302-78-9	< 1
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfopropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	68815-56-5	0.1 - 1 Trade Secret *
Aliphatic Ethoxylated Nonionic	Trade Secret*	< 1
Amorphous Silica	Trade Secret*	< 1
Cellulose	Trade Secret*	< 1
Isobutene Trimer	Trade Secret*	< 1
Phenol	Trade Secret*	< 1

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum metal and insoluble compounds, respirable fraction	21645-51-2	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Inert or Nuisance Dust, Respirable fraction	21645-51-2	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Inert or Nuisance Dust, Respirable fraction	471-34-1	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Amorphous Silica	Trade Secret	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Gray
Odor	Faint Rubber
Odor threshold	<i>No Data Available</i>
pH	7
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	≥ 100 °C
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	<i>No Data Available</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Relative Vapor Density	<i>No Data Available</i>
Density	<i>No Data Available</i>
Relative Density	1.29 [Ref Std: WATER=1]
Water solubility	Complete

Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	62,016 mm ² /sec
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	<=3 g/l [<i>Test Method:tested per EPA method 24</i>]
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polymer (NJTS Reg. No. 04499600-7181)	Dermal		LD50 estimated to be > 5,000 mg/kg
Polymer (NJTS Reg. No. 04499600-7181)	Ingestion	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Alumina Trihydrate	Dermal		LD50 estimated to be > 5,000 mg/kg
Alumina Trihydrate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Alumina Trihydrate	Ingestion	Rat	LD50 > 5,000 mg/kg
Styrene-butadiene Polymer	Dermal	Rabbit	LD50 > 2,000 mg/kg
Styrene-butadiene Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Cellulose	Dermal	Rabbit	LD50 > 2,000 mg/kg
Cellulose	Ingestion	Rat	LD50 > 27,000 mg/kg
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	Rat	LD50 > 2,000 mg/kg
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	Rat	LD50 2,870 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfofpropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	Ingestion	Mouse	LD50 > 540 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polymer (NJTS Reg. No. 04499600-7181)	Rabbit	Minimal irritation
Calcium Carbonate	Rabbit	No significant irritation
Alumina Trihydrate	Rabbit	No significant irritation
Styrene-butadiene Polymer	Professional judgement	No significant irritation
Cellulose	Human	No significant irritation
Alcohol Ethoxysulfate (Sodium Salt)	Rabbit	Irritant
Amorphous Silica	Rabbit	No significant irritation
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfofpropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	In vitro data	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Polymer (NJTS Reg. No. 04499600-7181)	Professional judgement	Mild irritant
Calcium Carbonate	Rabbit	No significant irritation
Alumina Trihydrate	Rabbit	No significant irritation
Cellulose	Rabbit	No significant irritation
Alcohol Ethoxysulfate (Sodium Salt)	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfopropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	In vitro data	Corrosive

Skin Sensitization

Name	Species	Value
Alumina Trihydrate	Guinea pig	Not classified
Cellulose	Human	Not classified
Alcohol Ethoxysulfate (Sodium Salt)	Guinea pig	Not classified
Amorphous Silica	Human and animal	Not classified
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfopropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	In vitro data	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Cellulose	In Vitro	Not mutagenic
Alcohol Ethoxysulfate (Sodium Salt)	In Vitro	Not mutagenic
Alcohol Ethoxysulfate (Sodium Salt)	In vivo	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfopropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Alumina Trihydrate	Not Specified	Multiple animal species	Not carcinogenic
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Alumina Trihydrate	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis
Cellulose	Ingestion	Not classified for female reproduction	Rat	NOAEL 1 g/kg in the diet	3 generation
Cellulose	Ingestion	Not classified for male reproduction	Rat	NOAEL 1	3 generation

				g/kg in the diet	
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	2 generation
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	2 generation
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	2 generation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Alcohol Ethoxysulfate (Sodium Salt)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Poly(Oxy-1,2-Ethanediy), .Alpha.-(3-Carboxy-1-Oxosulfopropyl)-.Omega.-Hydroxy-, C10-16-Alkyl Ethers, Disodium Salts	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Cellulose	Ingestion	blood	Not classified	Rat	NOAEL 1 g/kg in the diet	25 months
Cellulose	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1 g/kg in the diet	25 months
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	skin	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	heart	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	endocrine system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	gastrointestinal tract	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	hematopoietic system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	liver	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	immune system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	nervous system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	eyes	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	kidney and/or bladder	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate	Dermal	respiratory system	Not classified	Mouse	NOAEL 6.91	90 days

(Sodium Salt)					mg/day	
Alcohol Ethoxysulfate (Sodium Salt)	Dermal	vascular system	Not classified	Mouse	NOAEL 6.91 mg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	blood	Not classified	Rat	NOAEL 225 mg/kg/day	90 days
Alcohol Ethoxysulfate (Sodium Salt)	Ingestion	eyes	Not classified	Rat	NOAEL 225 mg/kg/day	90 days
Amorphous Silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous Silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not Applicable.

Health Hazards

Respiratory or Skin Sensitization

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 26-1817-1 **Version Number:** 6.00
Issue Date: 01/02/26 **Supersedes Date:** 10/05/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com