

Safety Data Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-4894-7	Version number:	3.01
Issue Date:	2020/10/28	Supercedes Date:	2016/02/12

SECTION 1: Identification

1.1. Product identifier

MOTOR LEAD SPLICING KIT 5318

1.2. Recommended use and restrictions on use

Recommended use

Electrical

1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577

E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

34-7684-3, 11-4628-1, 10-2656-6

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or

-----:

MOTOR LEAD SPLICING KIT 5318	
application.	
3M Canada SDSs are available at www.3M.ca	
SM Canada SDSs are available at www.SM.ca	



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-4628-1
 Version number:
 20.00

 Issue Date:
 2025/04/29
 Supercedes Date:
 2023/05/08

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Cable Preparation Kit CC-3 (Bag)

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

Solvent soaked pads for cleaning cable.

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4. Skin Corrosion/Irritation: Category 2. Skin Sensitizer: Category 1B.

2.2. Label elements

Signal word

Warning

Symbols

3MTM Cable Preparation Kit CC-3 (Bag)

Exclamation mark

Pictograms



Hazard Statements

Combustible Liquid

Causes skin irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	64742-48-9	50 - 70	Naphtha, petroleum, hydrotreated heavy
Cotton Pads	None	25 - 40	Not Applicable
D-LIMONENE	5989-27-5	5 - 20	Cyclohexene, 1-methyl-4-(1-
			methylethenyl)-, (R)-

Cotton Pads is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

3M[™] Cable Preparation Kit CC-3 (Bag)

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces.

- No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
D-LIMONENE	5989-27-5	AIHA	TWA:165.5 mg/m3(30 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Polyvinyl Alcohol (PVA)

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour White Odour Moderate Citrus Odour threshold PH No Data Available Solling point Solling	
Colour White Odour Moderate Citrus Odour threshold No Data Available pH 7 Melting point/Freezing point No Data Available Boiling point 193.3 °C - 248.9 °C Flash Point 62.2 °C [Test Method: Closed Cup] Evaporation rate No Data Available Flammability Flammable Liquid: Category 4. Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
OdourModerate CitrusOdour thresholdNo Data AvailablepH7Melting point/Freezing pointNo Data AvailableBoiling point193.3 °C - 248.9 °CFlash Point62.2 °C [Test Method: Closed Cup]Evaporation rateNo Data AvailableFlammabilityFlammable Liquid: Category 4.Flammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapour Pressure< 133.3 Pa [@ 25 °C]	
Odour thresholdNo Data AvailablepH7Melting point/Freezing pointNo Data AvailableBoiling point193.3 °C - 248.9 °CFlash Point62.2 °C [Test Method: Closed Cup]Evaporation rateNo Data AvailableFlammabilityFlammable Liquid: Category 4.Flammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapour Pressure< 133.3 Pa [@ 25 °C]Relative Vapour Density> 1 [Ref Std: AIR=1]	
pH7Melting point/Freezing pointNo Data AvailableBoiling point193.3 °C - 248.9 °CFlash Point62.2 °C [Test Method: Closed Cup]Evaporation rateNo Data AvailableFlammabilityFlammable Liquid: Category 4.Flammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapour Pressure< 133.3 Pa [@ 25 °C]	
Melting point/Freezing point No Data Available Boiling point 193.3 °C - 248.9 °C Flash Point 62.2 °C [Test Method: Closed Cup] Evaporation rate No Data Available Flammability Flammable Liquid: Category 4. Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Boiling point 193.3 °C - 248.9 °C Flash Point 62.2 °C [Test Method: Closed Cup] Evaporation rate No Data Available Flammability Flammable Liquid: Category 4. Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Flash Point Evaporation rate No Data Available Flammability Flammable Limits(LEL) No Data Available No Data Available No Data Available Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density Ref Std: AIR=1	
Evaporation rate Flammability Flammable Liquid: Category 4. No Data Available Flammable Limits(LEL) No Data Available No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density No Data Available Ref Std: AIR=1	
Flammability Flammable Liquid: Category 4. No Data Available Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density Flammable Liquid: Category 4. No Data Available < 133.3 Pa [@ 25 °C] > 1 [Ref Std: AIR=1]	
Flammable Limits(LEL) Flammable Limits(UEL) No Data Available No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Flammable Limits(UEL) No Data Available Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Vapour Pressure < 133.3 Pa [@ 25 °C] Relative Vapour Density > 1 [Ref Std: AIR=1]	
Relative Vapour Density > 1 [Ref Std: AIR=1]	
Density 0.76 g/ml	
Relative density 0.76 [Ref Std:WATER=1]	
Water solubility Nil	
Solubility- non-water No Data Available	
Partition coefficient: n-octanol/ water No Data Available	
Autoignition temperature No Data Available	
Decomposition temperature No Data Available	
Kinematic Viscosity 2 mm2/sec	
Volatile Organic Compounds Approximately 740 %	
Percent volatile No Data Available	
VOC Less H2O & Exempt Solvents 760 g/l	
Molecular weight No Data Available	

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance Condition Carbon monoxide Not Specified Carbon dioxide Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent regulatory authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	similar compoun ds	LD50 > 2,200 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	similar compoun ds	LD50 > 15,000 mg/kg
D-LIMONENE	Inhalation- Vapor (4 hours)	Mouse	LC50 > 3.14 mg/l
D-LIMONENE	Dermal	Rabbit	LD50 > 5,000 mg/kg

Page: 6 of 9

3MTM Cable Preparation Kit CC-3 (Bag)

D.	-LIMONENE	Ingestion	Rat	LD50 4,400 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compoun ds	Mild irritant
D-LIMONENE	Rabbit	Irritant

Serious Eve Damage/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compoun ds	No significant irritation
D-LIMONENE	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar	Not classified
	compoun	
	ds	
D-LIMONENE	Mouse	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
D-LIMONENE	In Vitro	Not mutagenic
D-LIMONENE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
D-LIMONENE	Ingestion	Rat	Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	premating & during gestation
D-LIMONENE	Ingestion	Not classified for development	Multiple animal species	NOAEL 591 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

3MTM Cable Preparation Kit CC-3 (Bag)

D-LIMONENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
D-LIMONENE	Ingestion	nervous system	Not classified		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 75 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	liver	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	103 weeks

Aspiration Hazard

Name	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard
D-LIMONENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 2 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	11-4628-1	Version number:	20.00
Issue Date:	2025/04/29	Supercedes Date:	2023/05/08

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Article Information Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Article Information Sheet is provided as a courtesy in response to a customer request. A Safety Data Sheet (SDS) has not been prepared for these product(s) because they are articles. Articles are not subject to the Hazardous Products Act or Regulations. As defined in the act: "Article" means any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product.

Document group: 34-7684-3 **Version number:** 2.00

Issue Date: 2025/04/29 **Supercedes Date:** 2023/01/12

SECTION 1: Identification

1.1. Product identifier

Black EPDM Tubing (on plastic core)

Product Identification Numbers

78-8125-9775-1

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

This product is exempt from hazard classification according to the Hazardous Products Act because it meets the manufactured article exemption.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt	Common Name
Black EPDM Tubing Composite	None	100	No Data Available

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

No need for first aid is anticipated.

SECTION 5: Fire-fighting measures

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

-		J	
	DI • 1 4 4		0.111
	Physical state		Solid

Colour	Black
Odour	Mild Rubber
Odour threshold	Not Applicable
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point	Not Applicable
Flash Point	No flash point
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Relative Vapour Density	Not Applicable
Density	No Data Available
Relative density	No Data Available
Water solubility	Not Applicable
Solubility- non-water	Not Applicable
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Kinematic Viscosity	Not Applicable
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Molecular weight	Not Applicable
Kinematic Viscosity Volatile Organic Compounds Percent volatile VOC Less H2O & Exempt Solvents	Not Applicable No Data Available No Data Available No Data Available No Data Available

Particle Characteristics	Not Applicable

SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

SECTION 11: Toxicological information

Inhalation:

No health effects are expected

Skin Contact:

No health effects are expected

Eye Contact:

No health effects are expected

Ingestion:

No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

SECTION 12: Ecological information

Black EPDM Tubing (on plastic core)

No data available.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

This product is an article as defined by CEPA and is exempt from DSL inventory listing.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	34-7684-3	Version number:	2.00
Issue Date:	2025/04/29	Supercedes Date:	2023/01/12

The information in this Article Information Sheet (AIS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-2656-6
 Version number:
 16.08

 Issue Date:
 2025/06/05
 Supercedes Date:
 2023/05/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

SILICONE LUBRICANT

Product Identification Numbers

78-8004-2585-8	78-8007-1728-8	78-8125-9728-0	78-8126-6088-0	80-6108-3463-4
CE-1006-6452-9	CE-1006-7115-1	DE-7110-0302-5	DE-7110-0510-3	DE-7110-0803-2
DE-7110-0809-9	DE-7110-0811-5	DE-7110-0813-1	DE-9999-6748-7	H0-0021-9083-5
H0-0021-9087-6	H0-0021-9089-2	H0-0021-9091-8	KE-2320-9117-0	KE-2320-9118-8
KE-2320-9119-6	KE-2320-9120-4	KE-2320-9123-8	KE-2320-9144-4	KE-2320-9145-1
KE-2320-9156-8	KE-2320-9157-6	KE-2320-9158-4	KE-2320-9160-0	KE-8000-8111-6
KE-8000-8585-1	KE-8000-8586-9	TE-1000-5610-6	TE-1000-5611-4	UU-0009-1463-8
UU-0080-7688-5				

1.2. Recommended use and restrictions on use

Intended Use

SILICONE LUBRICANT GREASE FOR ELECTRICAL SPLICES

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

SILICONE LUBRICANT

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
SILICONE GREASE	63148-62-9	75 - 95	Siloxanes and Silicones, di-Me
Synthetic Amorphous Silica,	112945-52-5	5 - 25	Fumed amorphous silica, crystalline-free
Fumed, Crystalline Free			

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Formaldehyde

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Page: 3 of 8

SILICONE LUBRICANT

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical prop	oei des
Physical state	Solid grease
Specific Physical Form:	GREASE
Colour	Light White
Odour	Odourless
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point	Not Applicable
Flash Point	No flash point
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	Not Applicable
Relative Vapour Density	Not Applicable
Density	No Data Available
Relative density	1.02 - 1.6 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	No Data Available
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Average particle size	No Data Available
Bulk density	No Data Available
Molecular weight	No Data Available
Softening point	No Data Available
	<u> </u>

Particle Characteristics	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong oxidizing agents
Strong acids
Strong bases
Reducing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

11cute 1 officity			
Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
SILICONE GREASE	Dermal	Multiple	LD50 > 2,000 mg/kg

SILICONE LUBRICANT

		animal	
		species	
SILICONE GREASE	Ingestion	Rat	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SILICONE GREASE	Human and animal	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
SILICONE GREASE	Rabbit	No significant irritation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
SILICONE GREASE	Human	Not classified
	and	
	animal	
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human	Not classified
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILICONE GREASE	In Vitro	Not mutagenic
SILICONE GREASE	In vivo	Not mutagenic
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic

Carcinogenicity

<u> </u>			
Name	Route	Species	Value
SILICONE GREASE	Dermal	Mouse	Not carcinogenic
SILICONE GREASE	Ingestion	Mouse	Not carcinogenic
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
SILICONE GREASE	Ingestion	Not classified for development	Rat	NOAEL 3,800 mg/kg/day	during organogenesi s
SILICONE GREASE	Dermal	Not classified for development	Rabbit	NOAEL 1,000 mg/kg/day	during organogenesi s
Synthetic Amorphous Silica, Fumed,	Ingestion	Not classified for female reproduction	Rat	NOAEL 509	1 generation

Page: 6 of 8

SILICONE LUBRICANT

Crystalline Free				mg/kg/day	
Synthetic Amorphous Silica, Fumed,	Ingestion	Not classified for male reproduction	Rat	NOAEL 497	1 generation
Crystalline Free				mg/kg/day	
Synthetic Amorphous Silica, Fumed,	Ingestion	Not classified for development	Rat	NOAEL 1,350	during
Crystalline Free				mg/kg/day	organogenesi
					S

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
SILICONE GREASE	Ingestion	eyes	Not classified	Rat	NOAEL 10%	90 days
SILICONE GREASE	Ingestion	respiratory system	Not classified	Rat	NOAEL 1%	90 days
SILICONE GREASE	Ingestion	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 10%	90 days
SILICONE GREASE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10%	90 days
SILICONE GREASE	Ingestion	heart liver kidney and/or bladder vascular system	Not classified	Rat	NOAEL 1%	90 days
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Page: 7 of 8

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 0 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	10-2656-6	Version number:	16.08
Issue Date:	2025/06/05	Supercedes Date:	2023/05/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 8 of 8