Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	44-7748-5	**Version number:**	1.00
Issue Date:	2026/03/17	**Supersedes Date:**	Initial Issue

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M™ Process Color 888i v2 Green

1.2. Recommended use and restrictions on use

Intended Use
Ink

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Commercial Branding and Transportation Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Flammable Liquid: Category 3.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1A.
Carcinogenicity: Category 2.
Reproductive Toxicity: Category 1B.

2.2. Label elements
Signal word
Danger

Symbols
Flame |Corrosion |Exclamation mark |Health Hazard |

Pictograms



Hazard Statements
Flammable liquid and vapour.
Causes serious eye damage. May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility or the unborn child.

Precautionary statements

Prevention:
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapours. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, face protection, and if needed, respiratory protection (see SDS Section 8).

Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:
Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards
None known.

17% of the mixture consists of ingredients of unknown acute oral toxicity.
17% of the mixture consists of ingredients of unknown acute dermal toxicity.
64% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	88917-22-0	30 - 60	Propanol, 1(or 2)-(2-methoxymethylethoxy)-, acetate (9CI)
2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate	28262-63-7	7 - 13	2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate

Acrylic Polymers	Trade Secret	7 - 13	Not Applicable
1-methoxy-2-propyl acetate	108-65-6	< 10	2-Propanol, 1-methoxy-, acetate
Cyclohexanone	108-94-1	5 - 10 Trade Secret *	Cyclohexanone
Vinyl Polymer	Trade Secret	3 - 7	Not Applicable
Pigment 1	Trade Secret	1 - 5	Not Applicable
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISIL OXANYL]PROPYL ETHER	27306-78-1	0.1 - < 1	Poly(oxy-1,2-ethanediyl), .alpha.-methyl-.omega.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-
Pigment 2	14302-13-7	< 0.7	Copper, [1,3,8,16,18,24-hexabromo-2,4,9,10,11,15,17,22,23,25-decachloro-29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, (SP-4-2)-
2,3-EPOXYPROPYL NEODECANOATE	26761-45-5	< 0.3	Neodecanoic acid, oxiranylmethyl ester
Ethylbenzene	100-41-4	< 0.3	Benzene, ethyl-
DIBUTYLTIN DILAURATE	77-58-7	< 0.2	Stannane, dibutylbis[(1-oxododecyl)oxy]-
N-Butyl Methacrylate	97-88-1	< 0.2	2-Propenoic acid, 2-methyl-, butyl ester

Acrylic Polymers is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.
Vinyl Polymer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.
Pigment 1 is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

5.4. Special protection actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been

read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities
Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
1-methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
Cyclohexanone	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	Danger of cutaneous absorption
Copper, dusts and mists, as Cu	14302-13-7	ACGIH	TWA(as Cu, fume):0.2 mg/m3;TWA(as Cu dust or mist):1 mg/m3	
Tin, organic compounds, as Sn	77-58-7	ACGIH	TWA(as Sn):0.1 mg/m3;STEL(as Sn):0.2 mg/m3	Danger of cutaneous absorption

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Liquid
Colour	Green
Odour	Sweet Ether
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*Not Applicable*
Boiling point	>=140 ºC
Flash Point	42.2 ºC [*Test Method:*Tagliabue Closed Cup]
Evaporation rate	<=0.4 [*Ref Std:*BUOAC=1]
Flammability	Flammable Liquid: Category 3.
Flammable Limits(LEL)	1.1 % volume
Flammable Limits(UEL)	8.6 % volume
Vapour Pressure	<=3.7 mmHg [@ 20 ºC]
Relative Vapour Density	*No Data Available*
Density	0.95 g/ml
Relative density	0.95 [*Ref Std:*WATER=1]
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	1,158 mm2/sec
Volatile Organic Compounds	600 - 800 g/l [*Details:*As Packaged]
Percent volatile	65 - 75 %
VOC Less H2O & Exempt Solvents	*No Data Available*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Sparks and/or flames

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Butyl Methacrylate	97-88-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Dermal	Rat	LD50 > 2,000 mg/kg
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, polymer with butyl 2-methyl-2-propenoate and methyl 2-methyl-2-propenoate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
1-methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-methoxy-2-propyl acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 28.8 mg/l
1-methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 >794, <3160 mg/kg
Cyclohexanone	Inhalation-Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg
Vinyl Polymer	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl Polymer	Ingestion	Rat	LD50 > 8,000 mg/kg
Pigment 2	Dermal		LD50 estimated to be > 5,000 mg/kg
Pigment 2	Ingestion	Rat	LD50 10,000 mg/kg
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Inhalation-Vapor	Professional judgement	LC50 estimated to be 10 - 20 mg/l
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Dermal	Rat	LD50 > 2,000 mg/kg
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2 mg/l
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l

	Vapor (4 hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
2,3-EPOXYPROPYL NEODECANOATE	Dermal	Rat	LD50 > 2,000 mg/kg
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	Rat	LD50 > 2,000 mg/kg
N-Butyl Methacrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
N-Butyl Methacrylate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 27 mg/l
N-Butyl Methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBUTYLTIN DILAURATE	Dermal	Rat	LD50 > 2,000 mg/kg
DIBUTYLTIN DILAURATE	Ingestion	Rat	LD50 1,290 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	No significant irritation
Cyclohexanone	Rabbit	Irritant
Vinyl Polymer	Professional judgement	No significant irritation
Pigment 2	Rabbit	No significant irritation
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
2,3-EPOXYPROPYL NEODECANOATE	Rabbit	No significant irritation
N-Butyl Methacrylate	Rabbit	Irritant
DIBUTYLTIN DILAURATE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	Mild irritant
Cyclohexanone	In vitro data	Corrosive
Vinyl Polymer	Professional judgement	No significant irritation
Pigment 2	Rabbit	No significant irritation
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Rabbit	Severe irritant
Ethylbenzene	Rabbit	Moderate irritant
2,3-EPOXYPROPYL NEODECANOATE	Rabbit	No significant irritation
N-Butyl Methacrylate	Rabbit	Mild irritant
DIBUTYLTIN DILAURATE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Guinea pig	Not classified
1-methoxy-2-propyl acetate	Guinea pig	Not classified
Cyclohexanone	Guinea pig	Not classified
Pigment 2	Human	Not classified
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Guinea pig	Not classified
Ethylbenzene	Human	Not classified
2,3-EPOXYPROPYL NEODECANOATE	Guinea	Sensitizing

	pig	
N-Butyl Methacrylate	Guinea pig	Sensitizing
DIBUTYLTIN DILAURATE	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	In Vitro	Not mutagenic
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	In vivo	Not mutagenic
1-methoxy-2-propyl acetate	In Vitro	Not mutagenic
Cyclohexanone	In Vitro	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
Pigment 2	In Vitro	Not mutagenic
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	In Vitro	Not mutagenic
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,3-EPOXYPROPYL NEODECANOATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,3-EPOXYPROPYL NEODECANOATE	In vivo	Mutagenic
N-Butyl Methacrylate	In Vitro	Not mutagenic
N-Butyl Methacrylate	In vivo	Not mutagenic
DIBUTYLTIN DILAURATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
DIBUTYLTIN DILAURATE	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Cyclohexanone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Pigment 2	Ingestion	Mouse	Not carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
N-Butyl Methacrylate	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
1-methoxy-2-propyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesis

Cyclohexanone	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation
Cyclohexanone	Ingestion	Not classified for development	Rabbit	NOAEL 500 mg/kg/day	during gestation
Cyclohexanone	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Inhalation	Not classified for development	Rat	NOAEL 2.6 mg/l	during gestation
Pigment 2	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Pigment 2	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	42 days
Pigment 2	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	premating into lactation
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg/day	28 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	premating into lactation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	2 generation
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	2 generation
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	2 generation
N-Butyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
N-Butyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating & during gestation
N-Butyl Methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during gestation
N-Butyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 1.8 mg/l	during gestation
DIBUTYLTIN DILAURATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	premating into lactation
DIBUTYLTIN DILAURATE	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1-methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-methoxy-2-propyl acetate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
Cyclohexanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgeme	NOAEL Not available	

				nt		
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
N-Butyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
DIBUTYLTIN DILAURATE	Ingestion	immune system	Causes damage to organs	Rat	LOAEL 5 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
PROPANOL, 1(OR 2)-(2-METHOXYMETHYLETHOXY)-, ACETATE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
1-methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
Cyclohexanone	Inhalation	liver	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	heart	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	skin	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	endocrine system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	immune system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	muscles	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	nervous system	Not classified	Rat	NOAEL 2.5	13 weeks

					mg/l	
Cyclohexanone	Inhalation	eyes	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	respiratory system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	vascular system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
Cyclohexanone	Ingestion	eyes	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
Cyclohexanone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
Pigment 2	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Pigment 2	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Pigment 2	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Pigment 2	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Dermal	skin	Not classified	Rat	NOAEL 1,551 mg/kg/day	9 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.025 mg/l	9 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 110 mg/kg/day	90 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
GLYCOLS,	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL	90 days

POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER					1,000 mg/kg/day	
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
GLYCOLS, POLYETHYLENE, METHYL 3-[1,3,3,3-TETRAMETHYL-1-(TRIMETHYLSILOXY)DISILOXANYL]PROPYL ETHER	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Ethylbenzene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.9 mg/l	13 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Ethylbenzene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL	Ingestion	liver	Not classified	Rat	NOAEL	90 days

NEODECANOATE					1,000 mg/kg/day	
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 100 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	skin	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
2,3-EPOXYPROPYL NEODECANOATE	Ingestion	vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
N-Butyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	olfactory system	Not classified	Rat	NOAEL 1.8 mg/l	28 days
N-Butyl Methacrylate	Inhalation	heart	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	endocrine system	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	liver	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	nervous system	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Inhalation	respiratory system	Not classified	Rat	NOAEL 11 mg/l	28 days
N-Butyl Methacrylate	Ingestion	olfactory system	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	endocrine system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	liver	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	nervous system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	heart	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
N-Butyl Methacrylate	Ingestion	immune system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
DIBUTYLTIN DILAURATE	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	2 weeks
DIBUTYLTIN DILAURATE	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 3 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	44-7748-5	**Version number:**	1.00
Issue Date:	2026/03/17	**Supersedes Date:**	Initial Issue

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca