



## Safety Data Sheet

Copyright,2024, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	07-1664-7	<b>Version number:</b>	9.00
<b>Issue Date:</b>	26/11/2024	<b>Supersedes date:</b>	13/06/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### IDENTIFICATION:

#### 1.1. Product identifier

3M™ Panel Bonding Adhesive PN 08115

#### Product Identification Numbers

60-9800-3093-0

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

**Company Emergency Hotline:**EMERGENCY: 1800 097 146 (Australia only)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

09-3599-9, 32-4327-6

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

### TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	09-3599-9	<b>Version number:</b>	7.00
<b>Issue Date:</b>	28/11/2022	<b>Supersedes date:</b>	13/06/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Use with Part B, MSDS 32-4327-6

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 1.  
Serious Eye Damage/Irritation: Category 1.  
Skin Sensitizer: Category 1B.  
Reproductive Toxicity: Category 1.  
Specific Target Organ Toxicity (single exposure): Category 2.  
Specific Target Organ Toxicity (single exposure): Category 3

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

Danger

**Symbols**

Corrosion | Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs: blood or blood-forming organs.

**Precautionary statements**

**General:**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

**Prevention:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

**Response:**

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.

**Storage:**

P405	Store locked up.
------	------------------

**Disposal:**

P501	Dispose of contents/container in accordance with applicable
------	---

local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. - May cause chemical gastrointestinal burns. All or part of the classification is based on toxicity test data.

### 2.4. Other hazards which do not result in classification

May be harmful if swallowed.

May be harmful in contact with skin.

Very toxic to aquatic life with long lasting effects.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Polymeric Diamide	68911-25-1	30 - 60
Butadiene Acrylonitrile Copolymer	68683-29-4	9 - 30
Silica, vitreous	60676-86-0	10 - 30
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	5 - 15
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	90-72-2	5 - 10
Amine Epoxy Curing Agent	288-32-4	1 - 5
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	1 - 5
Nitric acid, ammonium calcium salt	15245-12-2	1 - 5
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	0.1 - 1.5
Toluene	108-88-3	< 0.5

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methaemoglobinaemia. Methaemoglobinaemia may be clinically suspected by the presence of

clinical "cyanosis" in the presence of a normal PaO<sub>2</sub> (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methaemoglobinaemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methaemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2X

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	108-88-3	Australia OELs	TWA(8 hours):191 mg/m3(50 ppm);STEL(15 minutes):574 mg/m3(150 ppm)	SKIN
Silica, vitreous	60676-86-0	Australia OELs	Limit value not established:	
Silicon dioxide	60676-86-0	Australia OELs	TWA(respirable fraction)(8 hours):2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### **8.2. Exposure controls**

#### **8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### **8.2.2. Personal protective equipment (PPE)**

##### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

##### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous liquid
Colour	Tan
Odour	Slight Amine
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	>=110 °C
Flash point	110 °C [ <i>Test Method</i> :Closed Cup]
Evaporation rate	<=1 [ <i>Ref Std</i> :BUOAC=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<=26,664.4 Pa [@ 20 °C ]
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1.2 g/ml
Density	1.2 kg/l
Relative density	1.2 [ <i>Ref Std</i> :WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	100,000 mPa-s - 225,000 mPa-s [ <i>Test Method</i> :Brookfield]
Volatile organic compounds (VOC)	4 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0.4 % weight [ <i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0.4 % weight
VOC less H2O & exempt solvents	4 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
Molecular weight	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions



## 10.2 Chemical stability

Stable.

## 10.3. Conditions to avoid

None known.

## 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.5 Incompatible materials

Strong oxidising agents.

## 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

# SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

May be harmful in contact with skin.

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

### Additional Health Effects:

#### Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Polymeric Diamide	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Diamide	Ingestion	Rat	LD50 > 2,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Butadiene Acrylonitrile Copolymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
Butadiene Acrylonitrile Copolymer	Ingestion	Rat	LD50 > 15,300 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Dermal	Rabbit	LD50 2,525 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Rat	LD50 2,850 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Amine Epoxy Curing Agent	Ingestion	Rat	LD50 970 mg/kg
Amine Epoxy Curing Agent	Dermal	similar compounds	LD50 400 mg/kg
Nitric acid, ammonium calcium salt	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, ammonium calcium salt	Dermal	similar compounds	LD50 > 2,000 mg/kg
Bis[(Dimethylamino)Methyl]Phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Overall product	Rabbit	Corrosive
Polymeric Diamide	Rat	Irritant
Silica, vitreous	Rabbit	No significant irritation
Butadiene Acrylonitrile Copolymer	Rabbit	Irritant
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive

Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	similar compounds	No significant irritation
Bis[(Dimethylamino)Methyl]Phenol	similar compounds	Corrosive
Toluene	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Overall product	similar health hazards	Corrosive
Polymeric Diamide	In vitro data	Severe irritant
Silica, vitreous	Rabbit	No significant irritation
Butadiene Acrylonitrile Copolymer	Rabbit	Mild irritant
Tris(2,4,6-Dimethylaminomethyl)Phenol	Rabbit	Corrosive
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	Rabbit	Corrosive
Bis[(Dimethylamino)Methyl]Phenol	similar compounds	Corrosive
Toluene	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
Overall product	Guinea pig	Sensitising
Polymeric Diamide	Guinea pig	Sensitising
Silica, vitreous	Human and animal	Not classified
Butadiene Acrylonitrile Copolymer	Guinea pig	Sensitising
Tris(2,4,6-Dimethylaminomethyl)Phenol	Guinea pig	Not classified
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Professional judgement	Sensitising
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not classified
Nitric acid, ammonium calcium salt	Mouse	Not classified
Toluene	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Polymeric Diamide	In Vitro	Not mutagenic
Silica, vitreous	In Vitro	Not mutagenic
Tris(2,4,6-Dimethylaminomethyl)Phenol	In Vitro	Not mutagenic
Bis(3-Aminopropyl) Ether of Diethylene Glycol	In Vitro	Not mutagenic
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In vivo	Not mutagenic
Nitric acid, ammonium calcium salt	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product	Not specified.	Mouse	Some positive data exist, but the data

with Silica			are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Polymeric Diamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Polymeric Diamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Amine Epoxy Curing Agent	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Polymeric Diamide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Butadiene Acrylonitrile Copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Amine Epoxy Curing Agent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Ingestion	methemoglobinemia	Causes damage to organs	similar compounds	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Ingestion	heart   skin   endocrine system   gastrointestinal	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

		tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system				
Silica, vitreous	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	skin   liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Amine Epoxy Curing Agent	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
Amine Epoxy Curing Agent	Ingestion	heart   liver   blood   nervous system   eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver	Not classified	Rat	NOAEL 11.3	15 weeks

		kidney and/or bladder			mg/l	
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

**Aspiration Hazard**

Name	Value
Toluene	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Polymeric Diamide	68911-25-1	Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Polymeric Diamide	68911-25-1	Water flea	Experimental	48 hours	EL50	0.57 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Polymeric Diamide	68911-25-1	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
Butadiene Acrylonitrile Copolymer	68683-29-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	ErC50	133 mg/l
Amine Epoxy Curing Agent	288-32-4	Water flea	Experimental	48 hours	EC50	341.5 mg/l
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
Amine Epoxy Curing Agent	288-32-4	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Fathead minnow	Estimated	32 days	NOEC	157 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	NOEC	100 mg/l



salt						
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polymeric Diamide	68911-25-1	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301F - Manometric respirometry
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available-insufficient	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available-insufficient	N/A	N/A	N/A	N/A
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test
Amine Epoxy Curing Agent	288-32-4	Experimental Biodegradation	18 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 301A - DOC Die Away Test
Amine Epoxy Curing Agent	288-32-4	Experimental Aquatic Inherent Biodegrad.	8 days	CO2 evolution	83 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
Amine Epoxy Curing Agent	288-32-4	Experimental Biodegradation	19 days	Percent degraded	86 %removal of DOC	OECD 303A - Simulated Aerobic
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THCO2 evolution	Catalogic™
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polymeric Diamide	68911-25-1	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic™
Polymeric Diamide	68911-25-1	Modeled Bioconcentration		Log Kow	11.7	Episuite™
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
Amine Epoxy Curing Agent	288-32-4	Experimental Bioconcentration		Log Kow	-0.02	OECD 107 log Kow shke flsk mtd
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Estimated Bioconcentration		Log Kow	-3.1	OECD 107 log Kow shke flsk mtd
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

**SECTION 14: Transport Information****Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN3267

**Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( (BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS ((DIMETHYLAMINO)METHYL)PHENOL) )

**Class/Division:** 8

**Sub Risk:** Not applicable.

**Packing Group:** II

**Special Instructions:** Limited quantity may apply  
**Hazchem Code:** 2X  
**IERG:** 37

**International Air Transport Association (IATA) - Air Transport**

**UN No.:** UN3267

**Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( (BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS ((DIMETHYLAMINO)METHYL)PHENOL) )

**Class/Division:** 8

**Sub Risk:** Not applicable.

**Packing Group:** II

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN3267

**Proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( (BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS ((DIMETHYLAMINO)METHYL)PHENOL) )

**Class/Division:** 8

**Sub Risk:** Not applicable.

**Packing Group:** II

**Marine Pollutant:** Not applicable.

**Special Instructions:** Limited quantity may apply

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Australian Inventory Status:**

An ingredient(s) in this product is being introduced under a Certificate (Standard/Limited/Polymer of Low Concern) granted under Section 39 of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

**Revision information:**

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2021, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	32-4327-6	<b>Version number:</b>	2.00
<b>Issue Date:</b>	13/06/2021	<b>Supersedes date:</b>	10/07/2016

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Structural Panel Bonding Adhesive

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.  
Serious Eye Damage/Irritation: Category 2.  
Skin Sensitizer: Category 1.  
Germ Cell Mutagenicity: Category 2.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

Warning

**Symbols**

Exclamation mark |Health Hazard |

**Pictograms**



**Hazard statements**

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

**Precautionary statements**

**General:**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

**Prevention:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280F	Wear respiratory protection.

**Response:**

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

**Storage:**

P405	Store locked up.
------	------------------

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May be harmful if inhaled.  
Toxic to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Oxide Glass Chemicals	65997-17-3	10 - 30
Silica, vitreous	60676-86-0	7 - 13
Acrylate Polymer	Trade Secret	5 - 10
Silicon dioxide	7631-86-9	1 - 5
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	0.5 - 1.5
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	0.5 - 1.5
Carbon black	1333-86-4	< 0.5

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**5.3. Special protective actions for fire-fighters**

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcinogen.
Carbon black	1333-86-4	Australia OELs	TWA(8 hours): 3 mg/m <sup>3</sup>	
Silica, vitreous	60676-86-0	Australia OELs	Limit value not established:	
Silicon dioxide	60676-86-0	Australia OELs	TWA(respirable fraction)(8 hours):2 mg/m <sup>3</sup>	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
CERAMIC FIBERS	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml	
Glass filaments	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml;TWA(8 hours):0.5 fibers/ml	
Oxide Glass Chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m <sup>3</sup> ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m <sup>3</sup>	
SPECIAL PURPOSE GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.

Silicon dioxide	7631-86-9	Australia OELs	TWA(respirable fraction)(8 hours):2 mg/m3	
-----------------	-----------	----------------	---	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties



<b>Physical state</b>	Liquid.
<b>Colour</b>	Black
<b>Odour</b>	Acrylic
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	>= 35 °C
<b>Flash point</b>	>= 104.4 °C [Test Method:Closed Cup]
<b>Evaporation rate</b>	<= 1 Units not available or not applicable. [Ref Std:BUOAC=1]
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<= 186,158.4 Pa
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1 kg/l
<b>Density</b>	0.96 g/ml
<b>Relative density</b>	0.96 [Ref Std:WATER=1]
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	100,000 mPa-s - 225,000 mPa-s [Test Method:Brookfield]
<b>Volatile organic compounds (VOC)</b>	15 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Volatile organic compounds (VOC)</b>	1.6 % weight [Test Method:calculated per CARB title 2]
<b>Percent volatile</b>	1.6 % weight
<b>VOC less H2O &amp; exempt solvents</b>	15 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Molecular weight</b>	<i>No data available.</i>

**Nanoparticles**

This material contains nanoparticles.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3. Conditions to avoid**

Sparks and/or flames.

**10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

**10.6 Hazardous decomposition products**

**Substance**

Aldehydes.  
Carbon monoxide.  
Carbon dioxide.  
Hydrogen Chloride

**Condition**

Not specified.  
Not specified.  
Not specified.  
Not specified.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Genotoxicity:**

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l

Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Oxide Glass Chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Oxide Glass Chemicals	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professional judgement	Minimal irritation
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Oxide Glass Chemicals	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professional judgement	Mild irritant
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

#### Skin Sensitisation

Name	Species	Value
------	---------	-------

Silica, vitreous	Human and animal	Not classified
Silicon dioxide	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Dimethyl Siloxane, Reaction Product With Silica	Human and animal	Not classified

### Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
Silicon dioxide	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product With Silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Dimethyl Siloxane, Reaction Product With Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350	during organogenesis

				mg/kg/day	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxide Glass Chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dimethyl Siloxane, Reaction Product With Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Acrylate Polymer	Trade Secret		Data not available or insufficient for classification			N/A
Silicon dioxide	7631-86-9		Data not available or insufficient for classification			N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Bacteria	Experimental	5 hours	EC10	1,520 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Crustacea other	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	EC50	350 mg/l

xysilane						
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green Algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	>=100 mg/l
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7		Data not available or insufficient for classification			N/A
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon black	1333-86-4		Data not available or insufficient for classification			N/A

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Oxide Glass Chemicals	65997-17-3	Data not available-insufficient			N/A	
Silica, vitreous	60676-86-0	Data not available-insufficient			N/A	
Acrylate Polymer	Trade Secret	Data not available-insufficient			N/A	
Silicon dioxide	7631-86-9	Data not available-insufficient			N/A	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life	6.5 hours (t 1/2)	Non-standard method
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 % weight	Non-standard method
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not available-insufficient			N/A	
Carbon black	1333-86-4	Data not available-insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Oxide Glass Chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials.

**SECTION 14: Transport Information**

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.



**Hazchem Code:** Not applicable  
**IERG:** Not applicable.

**International Air Transport Association (IATA) - Air Transport**

**UN No.:** Not applicable.  
**Proper shipping name:** Not applicable.  
**Class/Division:** Not applicable.  
**Sub Risk:** Not applicable.  
**Packing Group:** Not applicable.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** Not applicable.  
**Proper shipping name:** Not applicable.  
**Class/Division:** Not applicable.  
**Sub Risk:** Not applicable.  
**Packing Group:** Not applicable.  
**Marine Pollutant:** Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Australian Inventory Status:**

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

**Revision information:**

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**