



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	39-5008-6	Version number:	3.00
Issue Date:	2025/08/14	Supersedes Date:	2023/07/19

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Dyneon™ Fluoroelastomer FE 5660Q

1.2. Recommended use and restrictions on use

Intended Use

Fluoroelastomer

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Advanced Materials Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

Health Hazards Not Otherwise Classified - Category 1

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes serious eye irritation. May cause an allergic skin reaction. May damage fertility or the unborn child. May cause polymer fume fever.

Precautionary statements**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye protection. In case of inadequate ventilation wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

May cause thermal burns. vapours liberated during processing may be hazardous if inhaled. Eye, nose, throat and lung irritation can occur from such vapours.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Vinylidene Fluoride - Hexafluoropropylene Polymer	9011-17-0	90 - 99	1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	1478-61-1	1 - 5 Trade Secret *	Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	921213-47-0	0.5 - 1.5 Trade Secret *	Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)
4,4'-(HEXAFLUOROISOPROPYLDENE)DIPHENOL BENZYLTRIPHENYLPHOSP	75768-65-9	0.1 - 1 Trade Secret *	Phosphonium, triphenyl(phenylmethyl)-, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

HONIUM SALT (1:1)			
4,4'-DICHLORODIPHENYL SULFONE	80-07-9	< 1	Benzene, 1,1'-sulfonylbis[4-chloro-

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

5.4. Special protection actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air

respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid skin contact with hot material. Store work clothes separately from other clothing, food and tobacco products. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Local exhaust required above 400 C.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves - Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Solid Block or Slab
Colour	Straw, White
Odour	Odourless
Odour threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>No Data Available</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapour Pressure	<i>Not Applicable</i>
Relative Vapour Density	<i>Not Applicable</i>
Density	1.8 g/cm ³
Relative density	1.8 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>

VOC Less H2O & Exempt Solvents	No Data Available
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Al or Mg powder and high/shear temperature conditions

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	At Elevated Temperatures
Carbon dioxide	At Elevated Temperatures
Hydrogen Fluoride	At Elevated Temperatures
Perfluoroisobutylene (PFIB)	At Elevated Temperatures
Oxides of Sulfur	At Elevated Temperatures
Toxic Vapor, Gas, Particulate	At Elevated Temperatures

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

During heating:

Polymer Fume Fever: Sign/symptoms may include chest pain or tightness, shortness of breath, cough, malaise, muscle aches, increased heart rate, fever, chills, sweats, nausea and headache.

Skin Contact:

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.
May cause additional health effects (see below).

Additional Health Effects:**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Vinylidene Fluoride - Hexafluoropropylene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Vinylidene Fluoride - Hexafluoropropylene Polymer	Ingestion	Rat	LD50 6,000 mg/kg
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Dermal	Rat	LD50 > 2,000 mg/kg
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Ingestion	Rat	LD50 > 2,000 mg/kg
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2C12)	Dermal	Rat	LD50 > 2,000 mg/kg
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2C12)	Ingestion	Rat	LD50 > 2,000 mg/kg
4,4'-DICHLORODIPHENYL SULFONE	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	Rat	LD50 4,810 mg/kg
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Vinylidene Fluoride - Hexafluoropropylene Polymer	Rabbit	No significant irritation
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Rabbit	No significant irritation
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2C12)	Rabbit	No significant irritation
4,4'-DICHLORODIPHENYL SULFONE	Rabbit	Minimal irritation
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Vinylidene Fluoride - Hexafluoropropylene Polymer	Rabbit	Mild irritant
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Rabbit	Corrosive
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	Rabbit	Severe irritant
4,4'-DICHLORODIPHENYL SULFONE	Rabbit	Severe irritant
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Guinea pig	Not classified
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	Mouse	Sensitizing
4,4'-DICHLORODIPHENYL SULFONE	Mouse	Not classified
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	In vivo	Not mutagenic
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-DICHLORODIPHENYL SULFONE	In Vitro	Not mutagenic
4,4'-DICHLORODIPHENYL SULFONE	In vivo	Some positive data exist, but the data are not sufficient for classification
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Ingestion	Toxic to female reproduction	Rat	LOAEL 338 ppm in the diet	2 generation
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Ingestion	Toxic to male reproduction	Rat	LOAEL 338 ppm in the diet	2 generation
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Ingestion	Toxic to development	Rat	LOAEL 338 ppm in the diet	2 generation
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	Ingestion	Not classified for reproduction and/or development	Rat	NOAEL 150 mg/kg/day	28 days
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 50	42 days

				mg/kg/day	
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 50 mg/kg/day	premating into lactation
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	premating into lactation
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Ingestion	Toxic to female reproduction	similar compounds	LOAEL 338 ppm in the diet	2 generation
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Ingestion	Toxic to male reproduction	similar compounds	LOAEL 338 ppm in the diet	2 generation
4,4'-(HEXAFLUOROISOPROPYLIDENE)DIPHENOL BENZYLTRIPHENYLPHOSPHONIUM SALT (1:1)	Ingestion	Toxic to development	similar compounds	LOAEL 338 ppm in the diet	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
4,4'-DICHLORODIPHENYL SULFONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Vinylidene Fluoride - Hexafluoropropylene Polymer	Ingestion	liver	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 weeks
4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol]	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
Phenol, 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis-, reaction products with benzene, chlorine and sulfur chloride (S2Cl2)	Ingestion	endocrine system liver kidney and/or bladder auditory system heart bone, teeth, nails, and/or hair bone marrow hematopoietic system immune system nervous system respiratory system vascular system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	hematopoietic system liver immune system	Not classified	Rat	NOAEL 200 mg/kg/day	14 weeks
4,4'-DICHLORODIPHENYL SULFONE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 19 mg/kg/day	14 weeks
4,4'-	Ingestion	heart endocrine	Not classified	Rat	NOAEL 200	14 weeks

DICHLORODIPHENYL SULFONE		system gastrointestinal tract bone, teeth, nails, and/or hair muscles nervous system respiratory system vascular system			mg/kg/day	
-----------------------------	--	--	--	--	-----------	--

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *2 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	39-5008-6	Version number:	3.00
Issue Date:	2025/08/14	Supersedes Date:	2023/07/19

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca