

Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 07-1664-7
 Version number:
 10.00

 Revision date:
 24/05/2023
 Supersedes date:
 04/01/2023

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M[™] Panel Bonding Adhesive PN 08115

Product Identification Numbers

UU-0089-1498-6

7100137215

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

09-3599-9, 32-4327-6

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Reproductive Toxicity, Category 1B - Repr. 1B; H360D
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |





Contains:

toluene; Carbon black; 2-piperazin-1-ylethylamine; bis-[4-(2,3-epoxipropoxi)phenyl]propane; Acrylate Polymer; [3-(2,3-epoxypropoxy)propyl]trimethoxysilane; imidazole; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); Silica, vitreous; Oxide glass chemicals; Siloxanes and Silicones, di-Me, reaction products with silica; 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated; Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine ; Silicon dioxide; 2,4,6-tris(dimethylaminomethyl)phenol; Rxn mass: 2-([[1-chloro-3-([4-[methoxy(oxiran-2-yl)methyl]cyclohexyl]methoxy)propan-2-yl]oxy]methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H360D May damage the unborn child.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201 Obtain special instructions before use.

P260A Do not breathe vapours.

P280J Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

GB Kit Information: CLP Percent Unknown information was added. GB Label: CLP Ingredients - kit components information was added.

Label: CLP Percent Unknown - Kit information was deleted.

Kit: Component document group number(s) information was modified. Label: CLP Ingredients - kit components information was deleted.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 09-3599-9 **Version number:** 8.03

Revision date: 08/01/2025 **Supersedes date:** 02/11/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3MTM Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 38515, 58115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for eye damage/irritation and the test results are reflected in the assigned classification.

This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

This material has been tested for skin sensitization and the test results are reflected in the assigned classification.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1B - Skin Sens. 1B; H317

Reproductive Toxicity, Category 1B - Repr. 1B; H360D Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336 Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine		701-270-9	35 - 45
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4		10 - 30
Silica, vitreous	60676-86-0	262-373-8	10 - 30
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	< 10
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	5 - 10
imidazole	288-32-4	206-019-2	1 - 5
Nitric acid, ammonium calcium salt	15245-12-2	239-289-5	1 - 5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		1 - 5
Bis[(dimethylamino)methyl]phenol	71074-89-0	275-162-0	0.1 - 1.5
2-piperazin-1-ylethylamine	140-31-8	205-411-0	0.1 - 1
toluene	108-88-3	203-625-9	< 0.5

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage. May cause an allergic skin reaction. H317 May damage the unborn child. H360D May cause drowsiness or dizziness. H336

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201 Obtain special instructions before use.

P260A Do not breathe vapours.

P280J Wear protective gloves, protective clothing, respiratory protection, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

1% of the mixture consists of components of unknown acute dermal toxicity.

Contains 4% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	(EC-No.) 701-270-9	35 - 45	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	(CAS-No.) 68683-29-4	10 - 30	Skin Irrit. 2, H315 Skin Sens. 1A, H317
Silica, vitreous	(CAS-No.) 60676-86-0 (EC-No.) 262-373-8	10 - 30	Substance with a national occupational exposure limit
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9	5 - 10	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	< 10	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Nitric acid, ammonium calcium salt	(CAS-No.) 15245-12-2 (EC-No.) 239-289-5	1 - 5	Acute Tox. 4, H302 Eye Dam. 1, H318
imidazole	(CAS-No.) 288-32-4	1 - 5	Acute Tox. 4, H302

	(EC-No.) 206-019-2		Skin Corr. 1C, H314 Repr. 1B, H360D Acute Tox. 3, H311
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 5	Substance with a national occupational exposure limit
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	0.1 - 1.5	Acute Tox. 4, H302 Skin Corr. 1C, H314
2-piperazin-1-ylethylamine	(CAS-No.) 140-31-8 (EC-No.) 205-411-0	0.1 - 1	Acute Tox. 3, H311 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 Repr. 2, H361d STOT RE 1, H372
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the

presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide.

Condition

During combustion. During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	UK HSE	TWA: 191 mg/m³ (50 ppm);	SKIN
			STEL: 384 mg/m ³ (100 ppm)	
Silica, vitreous	60676-86-0	UK HSE	TWA(as respirable dust):0.08	
			mg/m³	
Silicon dioxide	67762-90-7	UK HSE	TWA(as respirable dust):2.4	
			mg/m3;TWA(as inhalable	
			dust):6 mg/m3	

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Specific Physical Form:	Viscous liquid	
Colour	Tan	
Odor	Slight Amine	
Odour threshold	No data available.	
Melting point/freezing point	Not applicable.	
Boiling point/boiling range	>=110 °C	
Flammability	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Flash point	110 °C [Test Method:Closed Cup]	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
рН	substance/mixture is non-soluble (in water)	
Kinematic Viscosity	187,500 mm ² /sec	
Water solubility	No data available.	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Vapour pressure	<=26,664.4 Pa [@ 20 °C]	
Density	1.2 g/ml	
Density	1.2 kg/l	
Relative density	1.2 [Ref Std:WATER=1]	
Relative Vapour Density	No data available.	
Particle Characteristics	Not applicable.	

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rate Molecular weight Percent volatile No data available. <=1 [Ref Std:BUOAC=1] No data available. 0.4 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000
			mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000
			mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and	Dermal	Rat	LD50 > 2,000 mg/kg
trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine			
Reaction products of fatty acids, C18-unsaturated, dimers and	Ingestion	Rat	LD50 > 2,000 mg/kg
trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	- ·	D 1111	Y 750 . 5000 . 4
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
Silica, vitreous	(4 hours)	Rat	LD50 > 5 110 /l
/	Ingestion Dermal		LD50 > 5,110 mg/kg
2-Propenentrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Dermai	Rabbit	LD50 > 3,000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-	Ingestion	Rat	LD50 > 15,300 mg/kg
4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	ingestion	Kat	LD30 > 13,300 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
3.3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
imidazole	Ingestion	Rat	LD50 970 mg/kg
imidazole	Dermal	similar	LD50 400 mg/kg
		compoun	
		ds	
Nitric acid, ammonium calcium salt	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, ammonium calcium salt	Dermal	similar	LD50 > 2,000 mg/kg
		compoun	
		ds	

Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
2-piperazin-1-ylethylamine	Dermal	Rabbit	LD50 865 mg/kg
2-piperazin-1-ylethylamine	Ingestion	Rat	LD50 1,470 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapour (4		
	hours)		
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Rat	Irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Rabbit	Irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
imidazole	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	similar	No significant irritation
	compoun	
	ds	
Bis[(dimethylamino)methyl]phenol	similar	Corrosive
	compoun	
	ds	
2-piperazin-1-ylethylamine	Rabbit	Corrosive
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar health hazards	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In vitro data	Severe irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Rabbit	Mild irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
imidazole	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compoun ds	Corrosive
2-piperazin-1-ylethylamine	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant

Skin Sensitisation

Skiii Selisitisatioli		
Name	Species	Value
Overall product	Guinea	Sensitising
	pig	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-	Guinea	Sensitising
[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	pig	
Silica, vitreous	Human	Not classified
	and	

	animal	
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	Guinea	Sensitising
piperazinyl)ethyl]amino]butyl-terminated	pig	
2,4,6-tris(dimethylaminomethyl)phenol	Guinea	Not classified
	pig	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professio	Sensitising
	nal	
	judgemen	
	t	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
Nitric acid, ammonium calcium salt	Mouse	Not classified
2-piperazin-1-ylethylamine	Guinea	Sensitising
	pig	
toluene	Guinea	Not classified
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In Vitro	Not mutagenic
Silica, vitreous	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
imidazole	In Vitro	Not mutagenic
imidazole	In vivo	Not mutagenic
Nitric acid, ammonium calcium salt	In Vitro	Not mutagenic
2-piperazin-1-ylethylamine	In vivo	Not mutagenic
2-piperazin-1-ylethylamine	In Vitro	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1-diyloxy)]dipropan-1- amine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1-diyloxy)]dipropan-1-	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days

amine					
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1-diyloxy)]dipropan-1- amine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
imidazole	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
2-piperazin-1-ylethylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
2-piperazin-1-ylethylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
2-piperazin-1-ylethylamine	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1- diyloxy)]dipropan-1-amine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1- diyloxy)]dipropan-1-amine	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Page: 12 of

[[2-(1- piperazinyl)ethyl]amino]bu tyl-terminated						
2,4,6- tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
imidazole	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Ingestion	methemoglobinemi a	Causes damage to organs	similar compoun ds	NOAEL Not available	
2-piperazin-1-ylethylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Ingestion	heart endocrine system hematopoietic system liver muscles nervous system kidney and/or bladder respiratory system vascular system auditory system	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

	ı	T	T		ı	ı
		skin gastrointestinal tract bone, teeth, nails, and/or hair immune system eyes			NO 151 (00	
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
imidazole	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
imidazole	Ingestion	heart liver blood nervous system eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
2-piperazin-1-ylethylamine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m³	13 weeks
2-piperazin-1-ylethylamine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 53.8 mg/m³	13 weeks
2-piperazin-1-ylethylamine	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the	Rat	NOAEL 625	13 weeks

			data are not sufficient for classification		mg/kg/day	
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine		Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine		Green algae	Experimental	72 hours	EL50	0.43 mg/l
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine		Water flea	Experimental	48 hours	EL50	0.57 mg/l
Reaction products of fatty acids, C18-	701-270-9	Green algae	Experimental	72 hours	NOEL	0.28 mg/l

4 4 1 1	I	1	T	1		T
unsaturated, dimers and trimers with						
3,3'-						
[oxybis(ethane-2,1-						
diyloxy)]dipropan-						
1-amine						
Reaction products	701-270-9	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
of fatty acids, C18-	701 270)	1 icu vaica siaage	Емрегинения	5 Hours	Leso	110.5 mg/1
unsaturated, dimers						
and trimers with						
3,3'-						
[oxybis(ethane-2,1-						
diyloxy)]dipropan-						
1-amine						
2-Propenenitrile,	68683-29-4	N/A	Data not available	N/A	N/A	N/A
polymer with 1,3-	00003-29-4	IN/A	or insufficient for	IN/A	IN/A	IN/A
butadiene, 1-cyano-			classification			
1-methyl-4-oxo-4-			Classification			
[[2-(1-						
piperazinyl)ethyl]a						
mino]butyl-						
terminated	60676.06.0		<u> </u>	72.1	Y 050	10.000 #
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
3,3'-	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Oxybis(ethyleneox			1 1			
y)bis(propylamine)						
3,3'-	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Oxybis(ethyleneox		1		10 110 010		g
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Oxybis(ethyleneox	1210 31 7	Green argue	Емрегинения	72 110415	Leiv	3.1 mg/1
y)bis(propylamine)						
2,4,6-	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
tris(dimethylamino	90-72-2	IN/A	Experimental	90 Hours	LC30	/18 Hig/1
methyl)phenol	00.72.2	0 0	ID : 1	061	1.050	. 100 //
2,4,6-	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
tris(dimethylamino						
methyl)phenol		ļ.,				
2,4,6-	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
tris(dimethylamino						
methyl)phenol						
2,4,6-	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
tris(dimethylamino						
methyl)phenol						
2,4,6-	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
tris(dimethylamino			1			
methyl)phenol						
imidazole	288-32-4	Green algae	Experimental	72 hours	ErC50	133 mg/l
				/		
imidazole	288-32-4	Water flea	Experimental	48 hours	EC50	341.5 mg/l
iduzoio			Z.iporimoniui	.5 110415		mg/1
imidazole	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
minuazoic	200-32-4	Green argae	Laperinicitai	/ 2 HOULS	I TOLK	25 1118/1
imidazole	200 22 4	A ativated aludge	Evmonimontol	20 minutas	EC50	>1,000 mg/l
minuazoie	288-32-4	Activated sludge	Experimental	30 minutes	EC50	71,000 Hig/I
NT:4 : : 1	15245 12.2	C 1	P : 1	72.1	EGG	> 100 //
Nitric acid,	15245-12-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
ammonium calcium		1			1	
salt		1	<u> </u>	1	1222	1 100 #
Nitric acid,	15245-12-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
ammonium calcium		1		1		
salt		l		J		

Nitric acid, ammonium calcium	15245-12-2	Fathead minnow	Estimated	32 days	NOEC	157 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Bis[(dimethylamin o)methyl]phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA
2-piperazin-1- ylethylamine	140-31-8	Bacteria	Experimental	17 hours	EC10	100 mg/l
2-piperazin-1- ylethylamine	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
2-piperazin-1- ylethylamine	140-31-8	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
2-piperazin-1- ylethylamine	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
2-piperazin-1- ylethylamine	140-31-8	Green algae	Experimental	72 hours	NOEC	31 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine		Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301F - Manometric respirometry
2-Propenenitrile, polymer with 1,3- butadiene, 1-cyano- 1-methyl-4-oxo-4-	68683-29-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A

[[2-(1-	l	T				
piperazinyl)ethylla						
11 2/ 21						
mino]butyl-						
terminated			27/1	****	27/1	27/1
Silica, vitreous	60676-86-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A
3,3'-	4246-51-9	Experimental	25 days	CO2 evolution	-8 %CO2	OECD 301B - Modified
Oxybis(ethyleneox		Biodegradation			evolution/THCO2	sturm or CO2
y)bis(propylamine)					evolution	
3,3'-	4246-51-9	Estimated		Photolytic half-life	2.96 hours (t 1/2)	
Oxybis(ethyleneox		Photolysis		(in air)	. ,	
y)bis(propylamine)				,		
2,4,6-	90-72-2	Experimental	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle
tris(dimethylamino		Biodegradation	,-		. , , , , , , , , , , , , , , , , , , ,	test
methyl)phenol		Biodogradation				
imidazole	288-32-4	Experimental	18 days	Dissolv. Organic	98 %removal of	OECD 301A - DOC Die
		Biodegradation	10 44,5	Carbon Deplet	DOC	Away Test
imidazole	288-32-4	Experimental	8 days	CO2 evolution	83 %removal of	OECD 302B Zahn-
mindazoic	200 32 4	Aquatic Inherent	o days	CO2 evolution	DOC	Wellens/EVPA
		Biodegrad.			Doc	W Chens/E/V171
imidazole	288-32-4	Experimental	19 days	Percent degraded	86 %removal of	OECD 303A - Simulated
iiiidazoic	200-32-4	Biodegradation	19 days	i cicciii degiaded	DOC	Aerobic
Nitric acid.	15245-12-2	Data not availbl-	N/A	N/A	N/A	N/A
ammonium calcium		insufficient	IN/A	N/A	IN/A	IN/A
		insufficient				
salt Siloxanes and	67762-90-7	Data not availbl-	N/A	N/A	N/A	N/A
	6//62-90-/		IN/A	N/A	N/A	N/A
Silicones, di-Me,		insufficient				
reaction products						
with silica						
Bis[(dimethylamin	71074-89-0	Modeled	28 days	BOD	41 %CO2	Catalogic™
o)methyl]phenol		Biodegradation			evolution/THCO2	
					evolution	
2-piperazin-1-	140-31-8	Experimental	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
ylethylamine		Biodegradation				
toluene	108-88-3	Experimental	20 days	BOD	80 %BOD/ThOD	APHA Std Meth
		Biodegradation				Water/Wastewater
toluene	108-88-3	Experimental		Photolytic half-life	5.2 days (t 1/2)	
		Photolysis		(in air)	• • • •	
		Photolysis		(ın aır)		

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine	701-270-9	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic™
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'- [oxybis(ethane-2,1- diyloxy)]dipropan- 1-amine		Modeled Bioconcentration		Log Kow	11.7	Episuite™
2-Propenenitrile, polymer with 1,3- butadiene, 1-cyano- 1-methyl-4-oxo-4- [[2-(1- piperazinyl)ethyl]a mino]butyl- terminated	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available	N/A	N/A	N/A	N/A

		or insufficient for classification				
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
imidazole	288-32-4	Experimental Bioconcentration		Log Kow	-0.02	OECD 107 log Kow shke flsk mtd
Nitric acid, ammonium calcium salt	15245-12-2	Estimated Bioconcentration		Log Kow	-3.1	OECD 107 log Kow shke flsk mtd
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis[(dimethylamin o)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™
2-piperazin-1- ylethylamine	140-31-8	Experimental Bioconcentration		Log Kow	0.3	
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Reaction products of fatty acids, C18- unsaturated, dimers and trimers with 3,3'-[oxybis(ethane- 2,1- diyloxy)]dipropan- 1-amine	701-270-9	Modeled Mobility in Soil	Кос	3,780,000,000 l/kg	
3,3'- Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
imidazole	288-32-4	Experimental Mobility in Soil	Koc	23-207 l/kg	OECD 106 Adsp-Desb Batch Equil
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered,

stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3267	UN3267	UN3267
14.2 UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE); TRIS(2,4,6- DIMETHYLAMINOMONO METHYL)PHENOL)	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE); TRIS(2,4,6- DIMETHYLAMINOMONO METHYL)PHENOL)	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY)BIS(PRO PYLAMINE); TRIS(2,4,6- DIMETHYLAMINOMONOMETHY L)PHENOL)
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	<u>CAS Nbr</u>	<u>Classification</u>	Regulation
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

Regulation UK regulation 2023/63 (marketing and use of explosive precursors and poisons)

This product contains a reportable substance according to UK legislation 1972/66: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see UK Regulation 2023/63 for further details.

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonn	es) for the application of
		Lower-tier	Upper-tier requirements
		requirements	

3MTM Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 38515, 58115

toluene	108-88-3	10	50
---------	----------	----	----

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Particle Characteristics N/A information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M [™] Panel Bonding (90 Minu	ites) Adhesive Part A	(Accelerator) PN 081	15, 38315, 38515, 581	15	
3M SDSs for Great Britain a For Northern Ireland documen	are available at www nts, please contact you	.3M.com/uk r 3M representative	to obtain a copy.		

Page: 23 of 23



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 32-4327-6 **Version number:** 5.05

Revision date: 06/03/2024 **Supersedes date:** 25/01/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M[™] Panel Bonding Adhesive Part B PNs 08115, 38315, 38515, 58115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms







Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	30 - 60
Oxide glass chemicals	65997-17-3	266-046-0	10 - 30
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		946-427-4	7 - 13
Acrylate Polymer	Trade Secret		1 - 11
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	219-784-2	0.5 - 1.5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		0.5 - 1.5

HAZARD STATEMENTS:

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P273 Avoid release to the environment.

P280K Wear protective gloves and respiratory protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

Page: 2 of 21

regulations.

Contains 1% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	30 - 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	10 - 30	Substance with a national occupational exposure limit
Silica, vitreous	(CAS-No.) 60676-86-0 (EC-No.) 262-373-8	7 - 13	Substance with a national occupational exposure limit
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane		7 - 13	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 3, H412
Acrylate Polymer	Trade Secret	1 - 11	Substance not classified as hazardous
Silicon dioxide	(CAS-No.) 7631-86-9 (EC-No.) 231-545-4	1 - 5	Substance with a national occupational exposure limit
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2	0.5 - 1.5	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	0.5 - 1.5	Substance with a national occupational exposure limit
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 0.5	Substance with a national occupational exposure limit
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315

Repr. 2, H361d
STOT SE 3, H336
STOT RE 2, H373
Aquatic Chronic 3, H412

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
	,	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective

clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	UK HSC	TWA: 191 mg/m³ (50 ppm); STEL: 384 mg/m³ (100 ppm)	SKIN
Carbon black	1333-86-4	UK HSC	TWA: 3.5 mg/m³; STEL: 7 mg/m³	
Silica, vitreous	60676-86-0	UK HSC	TWA(as respirable dust):0.08 mg/m³	

Glass, oxide, chemicals 65997-17-3 UK HSC TWA(as fiber):5 mg/m3(1

fibers/ml)

Oxide glass chemicals 65997-17-3 Manufacturer TWA(as non-fibrous,

determined respirable)(8 hours):3

mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10

mg/m3

Silicon dioxide 67762-90-7 UK HSC TWA(as respirable dust):2.4

mg/m3;TWA(as inhalable

dust):6 mg/m3

DUST, INERT OR NUISANCE 7631-86-9 UK HSC TWA(as respirable dust):4

mg/m3;TWA(as inhalable

dust):10 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

. Information on basic physical and chemical properties		
Physical state	Liquid.	
Colour	Black	
Odor	Acrylic	
Odour threshold	No data available.	
Melting point/freezing point	No data available.	
Boiling point/boiling range	>= 35 °C	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Flash point	>= 104.4 °C [Test Method:Closed Cup]	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
pH	substance/mixture is non-soluble (in water)	
Kinematic Viscosity	83,333 mm ² /sec	
Water solubility	Negligible	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Vapour pressure	<= 186,158.4 Pa	
Density	1 kg/l	
Density	0.96 g/ml	
Relative density	0.96 [Ref Std:WATER=1]	
Relative Vapour Density	No data available.	
Particle Characteristics	Not applicable.	

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate <= 1 Units not available or not applicable. [*Ref*

Std:BUOAC=1]

Molecular weight
No data available.
Percent volatile
1.6 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance Aldehydes. Carbon monoxide Carbon dioxide. Hydrogen Chloride

Condition

Not specified. Not specified. Not specified. Not specified.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	Ingestion	Rat	LD50 1,000 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation- Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Oxide glass chemicals	Professio nal judgemen t	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In vitro data	Irritant
Acrylate Polymer	Professio nal judgemen t	Minimal irritation
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Oxide glass chemicals	Professio nal judgemen t	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In vitro data	No significant irritation
Acrylate Polymer	Professio nal judgemen t	Mild irritant
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
Silica, vitreous	Human and animal	Not classified
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	similar compoun ds	Sensitising
Silicon dioxide	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and	Not classified

	animal	
toluene	Guinea	Not classified
	pig	

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Silica, vitreous	In Vitro	Not mutagenic		
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}methoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymethylene)]bisoxirane	In Vitro	Mutagenic; structurally related to germ cell mutagens		
Silicon dioxide	In Vitro	Not mutagenic		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic		
Carbon black	In Vitro	Not mutagenic		
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification		
toluene	In Vitro	Not mutagenic		
toluene	In vivo	Not mutagenic		

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects										
Name	Route	Value	Species	Test result	Exposure Duration					
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750	2 generation					

				mg/kg/day	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohexyl\}met hoxy)propan-2-yl]oxy\}methyl)oxirane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneoxymeth ylene)]bisoxirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneoxymeth ylene)]bisoxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous	May cause drowsiness or		NOAEL Not	poisoning
		system depression	dizziness		available	and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3- epoxypropoxy)propyl]trim ethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL	13 weeks

					2,500 mg/kg/day	
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l

Rxn mass: 2-(\{[1-chloro-3-(\\{4-[methoxy(oxiran-2-yl)methyl]cyclohex yl\}methoxy)propa n-2-yl]oxy\}methyl)oxi rane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane Rxn mass: 2-(\\{[1-chloro-3-(\\{4-[methoxy(oxiran-2-yl)methyl]cyclohex]	946-427-4	Green algae Water flea	Experimental	72 hours	EC50	71 mg/l
yl\} methoxy)propa n-2- yl]oxy\} methyl)oxi rane & 2,2'-[cis- cyclohexane-1,4- diylbis(methyleneo xymethylene)]biso xirane & 2,2'- [trans-cyclohexane- 1,4- diylbis(methyleneo xymethylene)]biso xirane						
Rxn mass: 2-(\{[1-chloro-3-(\\{4-[methoxy(oxiran-2-yl)methyl]cyclohex yl\\}methoxy)propa n-2-yl]oxy\\}methyl)oxi rane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane & xymethylene)]biso xirane	946-427-4	Green algae	Experimental	72 hours	EC10	18 mg/l
Acrylate Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silicon dioxide	7631-86-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Green algae	Experimental	96 hours	NOEC	130 mg/l

[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Rxn mass: 2-(\{[1- chloro-3-(\{4- [methoxy(oxiran-2- yl)methyl]cyclohex yl\}methoxy)propa n-2-		Experimental Biodegradation	28 days		1.3 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2

yl]oxy\}methyl)oxi rane & 2,2'-[cis- cyclohexane-1,4- diylbis(methyleneo xymethylene)]biso xirane & 2,2'- [trans-cyclohexane- 1,4- diylbis(methyleneo xymethylene)]biso xirane						
Acrylate Polymer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Rxn mass: 2-(\{[1-chloro-3-(\{4-[methoxy(oxiran-2-yl)methyl]cyclohex yl\}methoxy)propa n-2-yl]oxy\}methyl)oxi rane & 2,2'-[cis-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane & 2,2'-[trans-cyclohexane-1,4-diylbis(methyleneo xymethylene)]biso xirane		Experimental Bioconcentration		Log Kow	2.05	
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

[3-(2,3-	2530-83-8	Experimental		Log Kow	0.5	Episuite TM
epoxypropoxy)prop		Bioconcentration				
yl]trimethoxysilane						
Siloxanes and Silicones, di-Me,	67762-90-7	Data not available or insufficient for	N/A	N/A	N/A	N/A
reaction products with silica		classification				
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental BCF - Other		Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane		Modeled Mobility in Soil	Koc	450 l/kg	Episuite [™]
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite TM
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

aı	Ingredient	CAS Nbr	Classification	Regulation
	bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
	Carbon black	1333-86-4	Grp. 2B: Possible human	C 3
	Q'11 11 11	5 (21 0 0 0	carc.	for Research on Cancer
	Silicon dioxide	7631-86-9	Gr. 3: Not classifiable	International Agency
				for Research on Cancer
	toluene	108-88-3	Gr. 3: Not classifiable	International Agency
				for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

Page: 19 of 21

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier	Upper-tier requirements
		requirements	
toluene	108-88-3	10	50

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.