**Safety Data Sheet**

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 09-1518-1 | **Version number:** | 9.00 |
| **Issue Date:** | 2025/09/05 | **Supersedes Date:** | 2020/10/27 |

# SECTION 1: Identification

**1.1. Product identifier**
7695S/31172/MB-5 QTIII SILICONE TERMINATION KIT

**1.2. Recommended use and restrictions on use**

**Recommended use**
Electrical

**1.3. Supplier's details**

**Company:** 3M Canada Company
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577
**E Mail:**

**1.4. Emergency telephone number**
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

26-2852-7

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**

# Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 26-2852-7 | **Version number:** | 9.00 |
| **Issue Date:** | 2026/10/22 | **Supersedes Date:** | 2025/04/29 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

### 1.1. Product identifier
3M™ Cable Preparation Kit CC-2 (Can)

**Product Identification Numbers**

| | | | | |
|---|---|---|---|---|
| LH-A100-0663-9 | 78-8061-7605-9 | 78-8127-6979-8 | 80-6105-9299-2 | 80-6112-0013-2 |
| 80-6114-2769-3 | CE-1007-3253-2 | CE-1007-4524-5 | JE-1900-3038-5 | UU-0060-7547-5 |
| UU-0060-8786-8 | UU-0109-3614-2 | UU-0112-0459-9 | UU-0114-6788-1 | UU-0115-6093-3 |
| UU-0117-4166-5 | | | | |

### 1.2. Recommended use and restrictions on use

**Intended Use**
Electrical, SOLVENT SOAKED PADS FOR CLEANING CABLE

**Restrictions on use**
Not applicable

### 1.3. Supplier's details

| | |
|---|---|
| **Company:** | 3M Canada Company |
| **Division:** | Electrical Markets Division |
| **Address:** | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| **Telephone:** | (800) 364-3577 |
| **Website:** | www.3M.ca |

### 1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification


### 2.1. Classification of the substance or mixture
Flammable Liquid: Category 4.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1B.

### 2.2. Label elements
**Signal word**

Warning

**Symbols**
Exclamation mark |

**Pictograms**



**Hazard Statements**
Combustible Liquid
Causes skin irritation. May cause an allergic skin reaction.

**Precautionary statements**

**Prevention:**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

**Response:**
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**
Store in a well-ventilated place.

**Disposal:**
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Other hazards**
None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | 64742-48-9 | 50 - 70 Trade Secret * | Naphtha, petroleum, hydrotreated heavy |
| Cotton Pads | None | 25 - 40 | Not Applicable |
| D-LIMONENE | 5989-27-5 | 5 - 10 Trade Secret * | Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)- |

Cotton Pads is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

**If Swallowed:**
Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Unsuitable extinguishing media**
None Determined

**5.3. Special hazards arising from the substance or mixture**
None inherent in this product.

**5.4. Special protection actions for fire-fighters**
Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**
Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| D-LIMONENE | 5989-27-5 | AIHA | TWA:165.5 mg/m3(30 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**
None required.

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber, Polymer laminate, Polyvinyl Alcohol (PVA)

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.),

then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Solid (Lint-free cloths soaked with liquid) |
| **Specific Physical Form:** | Cloth pads soaked in liquid in can or bag |
| **Colour** | White |
| **Odour** | Moderate Citrus |
| **Odour threshold** | *No Data Available* |
| **pH** | 7 |
| **Melting point/Freezing point** | *No Data Available* |
| **Boiling point** | 193.3 ºC - 248.9 ºC |
| **Flash Point** | 62.2 ºC [*Test Method:*Closed Cup] |
| **Evaporation rate** | *No Data Available* |
| **Flammability** | Flammable Liquid: Category 4. |
| **Flammable Limits(LEL)** | *No Data Available* |
| **Flammable Limits(UEL)** | *No Data Available* |
| **Vapour Pressure** | < 1 mmHg [@ 25 ºC] |
| **Relative Vapour Density** | > 1 [*Ref Std:*AIR=1] |
| **Density** | 0.76 g/ml |
| **Relative density** | 0.76 [*Ref Std:*WATER=1] |
| **Water solubility** | Nil |
| **Solubility- non-water** | *No Data Available* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *No Data Available* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | 2 mm2/sec |
| **Volatile Organic Compounds** | Approximately 740 % |
| **Percent volatile** | *No Data Available* |
| **VOC Less H2O & Exempt Solvents** | 760 g/l |
| **Molecular weight** | *No Data Available* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
Sparks and/or flames

**10.5. Incompatible materials**
Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| Carbon monoxide | Not Specified |
| Carbon dioxide | Not Specified |

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**
Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**
Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Dermal | similar compounds | LD50 > 2,200 mg/kg |

| | | | |
|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Ingestion | similar compounds | LD50 > 15,000 mg/kg |
| D-LIMONENE | Inhalation-Vapor (4 hours) | Mouse | LC50 > 3.14 mg/l |
| D-LIMONENE | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| D-LIMONENE | Ingestion | Rat | LD50 4,400 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | Mild irritant |
| D-LIMONENE | Rabbit | Irritant |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | No significant irritation |
| D-LIMONENE | Rabbit | Mild irritant |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | Not classified |
| D-LIMONENE | Mouse | Sensitizing |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | In Vitro | Not mutagenic |
| D-LIMONENE | In Vitro | Not mutagenic |
| D-LIMONENE | In vivo | Not mutagenic |

**Carcinogenicity**

| Name | Route | Species | Value |
|---|---|---|---|
| D-LIMONENE | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|
| D-LIMONENE | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | premating & during gestation |
| D-LIMONENE | Ingestion | Not classified for development | Multiple animal species | NOAEL 591 mg/kg/day | during organogenesis |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| D-LIMONENE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| D-LIMONENE | Ingestion | nervous system | Not classified | | NOAEL Not available | |

**Specific Target Organ Toxicity - repeated exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| D-LIMONENE | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 75 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | liver | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | heart | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | endocrine system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | bone, teeth, nails, and/or hair | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | immune system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | muscles | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | nervous system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | respiratory system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |

**Aspiration Hazard**

| Name | Value |
|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Aspiration hazard |
| D-LIMONENE | Aspiration hazard |

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the

available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**
**Health:** 2 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**
**Health:** 2 **Flammability:** 2 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|---|---|---|---|
| **Document group:** | 26-2852-7 | **Version number:** | 9.00 |
| **Issue Date:** | 2026/10/22 | **Supersedes Date:** | 2025/04/29 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**