



Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	45-9235-8	Version number:	1.00
Issue Date:	2026/02/25	Supersedes Date:	Initial Issue

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Abrasive Products, Cubitron(TM) II 726A Stikit (TM) Discs

1.2. Recommended use and restrictions on use

Intended Use

Abrasive Product

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Abrasive Systems Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

2.3. Other hazards

None known.

76% of the mixture consists of ingredients of unknown acute oral toxicity.

76% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Aluminum Oxide (non-fibrous)	1344-28-1	30 - 85	Aluminum oxide (non-fibrous)
Ceramic materials and wares, chemicals	66402-68-4	15 - 60	Ceramic materials and wares, chemicals
Cloth Backing	Trade Secret	7 - 60	Not Applicable
Cured Resin	Mixture	10 - 30	Not Applicable
PSA STIKIT ADHESIVE	None	5 - 13	Not Applicable
C.I. PIGMENT BLUE 15	147-14-8	< 10	Copper, [29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32]-, (SP-4-1)-
WOLLASTONITE	13983-17-0	3 - 10	Wollastonite (Ca(SiO3))
SODIUM ALUMINUM HEXAFLUORIDE	13775-53-6	1 - 7	No Data Available
Calcium Stearate	1592-23-0	1 - 5	Octadecanoic acid, calcium salt
Titanium Dioxide (aerodynamic diameter >10um)	13463-67-7	0.1 - 1.5	Titanium oxide (TiO2)
Carbon Black	1333-86-4	< 1	Carbon black

Cloth Backing is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

Cured Resin is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

PSA STIKIT ADHESIVE is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Hydrogen Fluoride

Condition

During Combustion

During Combustion

During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Not for consumer sale or use. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m3	

Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	
Titanium Dioxide (aerodynamic diameter >10um)	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	
Fluorides, as F	13775-53-6	ACGIH	TWA(as F):2.5 mg/m3	
WOLLASTONITE	13983-17-0	ACGIH	TWA(inhalable fraction):1 mg/m3	
Stearates (except stearates of toxic metals), inhalable fraction	1592-23-0	ACGIH	TWA(respirable fraction):3 mg/m3;TWA(inhalable fraction):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Solid
Specific Physical Form:	Roll of sandpaper
Colour	Purple
Odour	Odourless
Odour threshold	<i>Not Applicable</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point	<i>Not Applicable</i>
Flash Point	<i>Not Applicable</i>
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapour Pressure	<i>Not Applicable</i>
Relative Vapour Density	<i>Not Applicable</i>
Density	<i>Not Applicable</i>
Relative density	<i>Not Applicable</i>
Water solubility	Insoluble
Solubility- non-water	<i>Not Applicable</i>
Partition coefficient: n-octanol/ water	<i>Not Applicable</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>Not Applicable</i>
Kinematic Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
--------------------------	-----------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May cause additional health effects (see below).

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

This product contains titanium dioxide. Cancer of the lungs has been observed in rats that inhaled high levels of titanium dioxide. No exposure to inhaled titanium dioxide is expected during the normal handling and use of this product. Titanium dioxide was not detected when air sampling was conducted during simulated use of similar products containing titanium dioxide. Therefore, the health effects associated with titanium dioxide are not expected during the normal use of this product.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg

3M(TM) Abrasive Products, Cubitron(TM) II 726A Stikit (TM) Discs

Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Ceramic materials and wares, chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Ceramic materials and wares, chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
C.I. PIGMENT BLUE 15	Dermal		LD50 estimated to be > 5,000 mg/kg
C.I. PIGMENT BLUE 15	Ingestion	Rat	LD50 10,000 mg/kg
WOLLASTONITE	Ingestion	Rat	LD50 > 5,000 mg/kg
WOLLASTONITE	Dermal	similar compounds	LD50 > 5,000 mg/kg
WOLLASTONITE	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 2.08 mg/l
SODIUM ALUMINUM HEXAFLUORIDE	Dermal	Rabbit	LD50 > 2,100 mg/kg
SODIUM ALUMINUM HEXAFLUORIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 4.5 mg/l
SODIUM ALUMINUM HEXAFLUORIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Stearate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Stearate	Ingestion	Rat	LD50 > 2,000 mg/kg
Titanium Dioxide (aerodynamic diameter >10um)	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide (aerodynamic diameter >10um)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide (aerodynamic diameter >10um)	Ingestion	Rat	LD50 > 10,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Ceramic materials and wares, chemicals	Rabbit	No significant irritation
C.I. PIGMENT BLUE 15	Rabbit	No significant irritation
WOLLASTONITE	similar compounds	No significant irritation
SODIUM ALUMINUM HEXAFLUORIDE	Multiple animal species	No significant irritation
Calcium Stearate	In vitro data	No significant irritation
Titanium Dioxide (aerodynamic diameter >10um)	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Ceramic materials and wares, chemicals	Rabbit	Mild irritant
C.I. PIGMENT BLUE 15	Rabbit	No significant irritation
WOLLASTONITE	similar compounds	Mild irritant
SODIUM ALUMINUM HEXAFLUORIDE	Rabbit	Mild irritant
Calcium Stearate	In vitro data	No significant irritation
Titanium Dioxide (aerodynamic diameter >10um)	Rabbit	No significant irritation

3M(TM) Abrasive Products, Cubitron(TM) II 726A Stikit (TM) Discs

Carbon Black	Rabbit	No significant irritation
--------------	--------	---------------------------

Skin Sensitization

Name	Species	Value
C.I. PIGMENT BLUE 15	Human	Not classified
WOLLASTONITE	Human	Not classified
Calcium Stearate	similar compounds	Not classified
Titanium Dioxide (aerodynamic diameter >10um)	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Ceramic materials and wares, chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
C.I. PIGMENT BLUE 15	In Vitro	Not mutagenic
WOLLASTONITE	In Vitro	Not mutagenic
WOLLASTONITE	In vivo	Not mutagenic
Calcium Stearate	In Vitro	Not mutagenic
Titanium Dioxide (aerodynamic diameter >10um)	In Vitro	Not mutagenic
Titanium Dioxide (aerodynamic diameter >10um)	In vivo	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Ceramic materials and wares, chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
C.I. PIGMENT BLUE 15	Ingestion	Mouse	Not carcinogenic
Titanium Dioxide (aerodynamic diameter >10um)	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide (aerodynamic diameter >10um)	Inhalation	Rat	Carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
C.I. PIGMENT BLUE 15	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
C.I. PIGMENT BLUE 15	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	42 days
C.I. PIGMENT BLUE 15	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
WOLLASTONITE	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,600 mg/kg/day	during organogenesis
Calcium Stearate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

3M(TM) Abrasive Products, Cubitron(TM) II 726A Stikit (TM) Discs

Calcium Stearate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Ceramic materials and wares, chemicals	Inhalation	pulmonary fibrosis	Not classified	Multiple animal species	NOAEL not available	
Ceramic materials and wares, chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
C.I. PIGMENT BLUE 15	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
C.I. PIGMENT BLUE 15	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
C.I. PIGMENT BLUE 15	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
C.I. PIGMENT BLUE 15	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
WOLLASTONITE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
WOLLASTONITE	Inhalation	pulmonary fibrosis	Not classified	Human and animal	NOAEL Not available	
WOLLASTONITE	Ingestion	liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	2 years
WOLLASTONITE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	2 years
WOLLASTONITE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,500 mg/kg/day	2 years
SODIUM ALUMINUM HEXAFLUORIDE	Inhalation	bone, teeth, nails, and/or hair	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.0005 mg/l	5 months
SODIUM ALUMINUM HEXAFLUORIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.00021 mg/l	90 days
SODIUM ALUMINUM HEXAFLUORIDE	Ingestion	bone, teeth, nails, and/or hair	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.58 mg/kg/day	14 weeks
Calcium Stearate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	heart	Not classified	Rat	NOAEL 2,000	28 days

3M(TM) Abrasive Products, Cubitron(TM) II 726A Stikit (TM) Discs

					mg/kg/day	
Calcium Stearate	Ingestion	skin	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	endocrine system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	liver	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	immune system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	eyes	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Titanium Dioxide (aerodynamic diameter >10um)	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide (aerodynamic diameter >10um)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	45-9235-8	Version number:	1.00
Issue Date:	2026/02/25	Supersedes Date:	Initial Issue

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca