



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	20-3304-1	Version number:	8.00
Issue Date:	2025/07/10	Supersedes Date:	2025/07/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Marine High Gloss Gelcoat Compound, 06025, 06026

1.2. Recommended use and restrictions on use

Intended Use

Automotive

Specific Use

Marine Finishing Material

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Marine & Specialty Vehicle
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Skin Corrosion/Irritation: Category 2.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Flammable liquid and vapour.

Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness.

Precautionary statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapours. Wash exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, face protection, and respiratory protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Aluminum Oxide (non-fibrous)	1344-28-1	15 - 40	Aluminum oxide (non-fibrous)
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30 Trade Secret *	Distillates, petroleum, hydrotreated light
Water	7732-18-5	10 - 30	Water
Distillates (Petroleum), Acid Treated, Light	64742-14-9	5 - 10 Trade Secret *	Distillates (petroleum), acid-treated light
Hydrosulfurized Kerosine (Petroleum)	64742-81-0	5 - 10 Trade Secret *	No Data Available
Glycerin	56-81-5	< 5	1,2,3-Propanetriol

Poly(Oxyethylene)Sorbitan Monostearate	9005-67-8	1 - 5	Sorbitan, monooctadecanoate, poly(oxy-1,2-ethanediyl) derivs.
Sorbitan Oleate	1338-43-8	1 - 5	Sorbitan, mono-9-octadecenoate, (Z)-
Triethanolamine	102-71-6	1 - 5	Ethanol, 2,2',2"-nitrilotris-
White Mineral Oil (Petroleum)	8042-47-5	1 - 5 Trade Secret *	White mineral oil (petroleum)
Isopropyl Alcohol	67-63-0	0 - 2 Trade Secret *	2-Propanol
Oleic Acid	112-80-1	< 2	9-Octadecenoic acid (Z)-
Ethylbenzene	100-41-4	0.03 - 0.11 Trade Secret *	Benzene, ethyl-
Naphthalene	91-20-3	0.03 - 0.11 Trade Secret *	Naphthalene

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.4. Special protection actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure

demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
Triethanolamine	102-71-6	ACGIH	TWA:5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	
Hydrodesulfurized Kerosine (Petroleum)	64742-81-0	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	SKIN
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	
Naphthalene	91-20-3	ACGIH	TWA:10 ppm	Danger of cutaneous absorption

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates, including oily mists

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	White
Odour	Mild Solvent
Odour threshold	No Data Available

pH	7.8 - 8.1
Melting point/Freezing point	<i>No Data Available</i>
Boiling point	100 °C
Flash Point	39.4 °C [<i>Test Method</i> :Pensky-Martens Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability	Flammable Liquid: Category 3.
Flammable Limits(LEL)	1 %
Flammable Limits(UEL)	7 %
Vapour Pressure	<=133.3 Pa
Relative Vapour Density	<=1 [<i>Ref Std</i> :AIR=1]
Density	1.2 - 1.23 g/ml
Relative density	1.22 [<i>Ref Std</i> :WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	147,541 mm ² /sec
Volatile Organic Compounds	340 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	27.4 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	55.8 % weight
VOC Less H₂O & Exempt Solvents	516 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Vapor	Professional judgment	LC50 estimated to be 20 - 50 mg/l
Hydrotreated Light Petroleum Distillates	Inhalation-	Rat	LC50 > 3 mg/l

	Dust/Mist (4 hours)		
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	similar compound ds	LD50 > 2,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Ingestion	Rat	LD50 > 15,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Dermal	similar compound ds	LD50 > 5,000 mg/kg
Hydrosulfurized Kerosine (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrosulfurized Kerosine (Petroleum)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Hydrosulfurized Kerosine (Petroleum)	Inhalation- Vapor (4 hours)	Rat	LC50 > 5 mg/l
Hydrosulfurized Kerosine (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Dermal	Rat	LD50 > 2,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Rat	LD50 > 60,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation- Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Oleic Acid	Dermal	Guinea pig	LD50 > 3,000 mg/kg
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg
Sorbitan Oleate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan Oleate	Ingestion	Rat	LD50 > 39,800 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation- Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Naphthalene	Dermal	Human	LD50 estimated to be 2,000 - 5,000 mg/kg
Naphthalene	Inhalation- Vapor	Human	LC50 estimated to be 20 - 50 mg/l
Naphthalene	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Irritant
Distillates (Petroleum), Acid Treated, Light	similar compound ds	Mild irritant
Hydrosulfurized Kerosine (Petroleum)	Rabbit	Minimal irritation
Poly(Oxyethylene)Sorbitan Monostearate	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
Isopropyl Alcohol	Multiple animal species	No significant irritation
Oleic Acid	Rabbit	Minimal irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Triethanolamine	Rabbit	Minimal irritation
Ethylbenzene	Rabbit	Mild irritant

Naphthalene	Rabbit	Minimal irritation
-------------	--------	--------------------

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Distillates (Petroleum), Acid Treated, Light	similar compounds	No significant irritation
Hydrosulfurized Kerosine (Petroleum)	Rabbit	No significant irritation
Poly(Oxyethylene)Sorbitan Monostearate	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
Isopropyl Alcohol	Rabbit	Severe irritant
Oleic Acid	Rabbit	Mild irritant
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Triethanolamine	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Naphthalene	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
Distillates (Petroleum), Acid Treated, Light	similar compounds	Not classified
Hydrosulfurized Kerosine (Petroleum)	Guinea pig	Not classified
Poly(Oxyethylene)Sorbitan Monostearate	Human	Not classified
Glycerin	Guinea pig	Not classified
Isopropyl Alcohol	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Triethanolamine	Human	Not classified
Ethylbenzene	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Distillates (Petroleum), Acid Treated, Light	In Vitro	Not mutagenic
Hydrosulfurized Kerosine (Petroleum)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrosulfurized Kerosine (Petroleum)	In vivo	Some positive data exist, but the data are not sufficient for classification
Poly(Oxyethylene)Sorbitan Monostearate	In Vitro	Not mutagenic
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
Oleic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrosulfurized Kerosine (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not Specified	Multiple animal species	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Naphthalene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydrosulfurized Kerosine (Petroleum)	Dermal	Not classified for female reproduction	Rat	NOAEL 494 mg/kg/day	premating & during gestation
Hydrosulfurized Kerosine (Petroleum)	Dermal	Not classified for male reproduction	Rat	NOAEL 494 mg/kg/day	premating & during gestation
Hydrosulfurized Kerosine (Petroleum)	Dermal	Not classified for development	Rat	NOAEL 494 mg/kg/day	premating & during gestation
Hydrosulfurized Kerosine (Petroleum)	Inhalation	Not classified for development	Rat	NOAEL 400 ppm	during organogenesis
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Not classified for male reproduction	Rat	NOAEL 10,000 mg/kg/day	3 generation
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Not classified for female reproduction	Rat	NOAEL 10,000 mg/kg/day	3 generation
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Not classified for development	Rat	NOAEL 7,693 mg/kg/day	during organogenesis
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000	2 generation

				mg/kg/day	
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	during organogenesis
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (Petroleum), Acid Treated, Light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydrosulfurized Kerosine (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	occupational exposure
Hydrosulfurized Kerosine (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	
Hydrosulfurized Kerosine (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	poisoning and/or abuse
Hydrosulfurized Kerosine (Petroleum)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	not applicable
Hydrosulfurized Kerosine (Petroleum)	Ingestion	liver	Not classified	Rat	LOAEL 18,912 mg/kg	not applicable
Hydrosulfurized Kerosine (Petroleum)	Ingestion	heart hematopoietic system	Not classified	Human	NOAEL not available	poisoning and/or abuse
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Naphthalene	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Distillates (Petroleum), Acid Treated, Light	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	hematopoietic system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrosulfurized Kerosine (Petroleum)	Dermal	hematopoietic system	Not classified	Mouse	NOAEL 500 mg/kg/day	13 weeks
Hydrosulfurized Kerosine (Petroleum)	Dermal	liver immune system kidney and/or bladder	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years
Hydrosulfurized Kerosine (Petroleum)	Dermal	nervous system	Not classified	Mouse	NOAEL 2,700 mg/kg/day	1 weeks
Hydrosulfurized Kerosine (Petroleum)	Dermal	heart gastrointestinal tract muscles respiratory system	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years
Hydrosulfurized Kerosine (Petroleum)	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL not available	1 years
Hydrosulfurized Kerosine (Petroleum)	Inhalation	liver	Not classified	Rat	NOAEL 0.231 mg/l	14 weeks
Hydrosulfurized Kerosine (Petroleum)	Inhalation	heart	Not classified	Guinea pig	LOAEL 20.4 mg/l	not available
Hydrosulfurized Kerosine (Petroleum)	Inhalation	gastrointestinal tract hematopoietic system muscles respiratory system	Not classified	Multiple animal species	NOAEL 0.1 mg/l	13 weeks
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	gastrointestinal tract liver hematopoietic system	Not classified	Rat	NOAEL 12,500 mg/kg/day	2 years
Glycerin	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks

Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Oleic Acid	Ingestion	liver immune system	Not classified	Rat	NOAEL 2,250 mg/kg/day	108 weeks
Oleic Acid	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,550 mg/kg/day	108 weeks
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Naphthalene	Dermal	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Dermal	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.01 mg/l	13 weeks
Naphthalene	Inhalation	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Inhalation	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 500 mg/kg/day	15 days

Aspiration Hazard

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Distillates (Petroleum), Acid Treated, Light	Aspiration hazard
Hydrosulfurized Kerosine (Petroleum)	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	20-3304-1	Version number:	8.00
Issue Date:	2025/07/10	Supersedes Date:	2025/07/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca