



## Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	44-8455-6	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	28/10/2025	<b>Supersedes Date:</b>	09/12/2024

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Machine Polish PN05996 Plus

#### Product Identification Numbers

XP-0038-5376-7

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Paint Polish

#### 1.3. Supplier's details

<b>ADDRESS:</b>	3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
<b>Telephone:</b>	03-7884 2888
<b>E Mail:</b>	3mmyehsr@mmm.com
<b>Website:</b>	www.3M.com.my

#### 1.4. Emergency telephone number

+60 03-7884 2888

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms

**Hazard Statements:**

H317 May cause an allergic skin reaction.

**Precautionary statements****Prevention:**

P280E Wear protective gloves.

**Response:**

P333 + P313 If skin irritation or rash occurs: Get medical attention.

**2.3. Other hazards**

None known

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	70 - 80
Aluminum Oxide	1344-28-1	7 - 13
Alkanes, C12-14-iso-	68551-19-9	1 - 5
White mineral oil (petroleum)	8042-47-5	1 - 3
Kaolin, calcined	92704-41-1	1 - 3
GLYCERIN	56-81-5	<= 1
2-Methyl-4-isothiazoline-3-one	2682-20-4	< 0.03

## SECTION 4: First aid measures

**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Aluminum metal and insoluble compounds, respirable fraction	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m <sup>3</sup>	A4: Not class. as human carcin
Aluminum Oxide	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m <sup>3</sup>	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m <sup>3</sup>	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m <sup>3</sup>	
GLYCERIN	56-81-5	Malaysia OELs	TWA(as mist)(8 hours):10 mg/m <sup>3</sup>	
Particulates not Otherwise Classified (PNOC), Inhalable particulate	56-81-5	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m <sup>3</sup> ;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m <sup>3</sup>	
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m <sup>3</sup>	A4: Not class. as human carcin
Oil mist, mineral	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

None required.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

#### Respiratory protection

None required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Emulsion
Color	Gray
Odor	Odorless
Odor threshold	<i>Not Applicable</i>
pH	7 - 9
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	Flash point > 93 °C (200 °F) [ <i>Test Method: Closed Cup</i> ]
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Relative Vapor Density	<i>Not Applicable</i>
Density	1 - 1.2 g/ml
Relative Density	<i>Not Applicable</i>
Water solubility	<i>Not Applicable</i>
Solubility- non-water	<i>Not Applicable</i>
Partition coefficient: n-octanol/ water	<i>Not Applicable</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>Not Applicable</i>
Kinematic Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
--------------------------	-----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Direct sunlight  
Heat

**10.5. Incompatible materials**

Strong acids  
Strong bases

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

No known health effects.

**Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Inhalation-Dust/Mist	Rat	LC50 > 2.07 mg/l

	(4 hours)		
Kaolin, calcined	Dermal	similar compounds	LD50 > 5,000 mg/kg
Kaolin, calcined	Ingestion	similar compounds	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
GLYCERIN	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
GLYCERIN	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Methyl-4-isothiazoline-3-one	Dermal	Rat	LD50 242 mg/kg
2-Methyl-4-isothiazoline-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.11 mg/l
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	LD50 120 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Aluminum Oxide	Rabbit	No significant irritation
Kaolin, calcined	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
GLYCERIN	Rabbit	No significant irritation
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Aluminum Oxide	Rabbit	No significant irritation
Kaolin, calcined	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
GLYCERIN	Rabbit	No significant irritation
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

**Sensitization:**

**Skin Sensitization**

Name	Species	Value
White mineral oil (petroleum)	Guinea pig	Not classified
GLYCERIN	Guinea pig	Not classified
2-Methyl-4-isothiazoline-3-one	Human and animal	Sensitizing

**Photosensitization**

Name	Species	Value
2-Methyl-4-isothiazoline-3-one	Human and animal	Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value

Aluminum Oxide	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
2-Methyl-4-isothiazoline-3-one	In vivo	Not mutagenic
2-Methyl-4-isothiazoline-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
GLYCERIN	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Methyl-4-isothiazoline-3-one	Dermal	Mouse	Not carcinogenic
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
GLYCERIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
GLYCERIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
GLYCERIN	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-Methyl-4-isothiazoline-3-one	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational

Kaolin, calcined	Inhalation	pneumoconiosis	Not classified	similar compounds	available NOAEL not available	exposure occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
GLYCERIN	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
GLYCERIN	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

### Aspiration Hazard

Name	Value
White mineral oil (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

#### Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Aluminum Oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Alkanes, C12-14-iso-	68551-19-9	Green algae	Analogous Compound	72 hours	EL50	>100 mg/l
Alkanes, C12-14-iso-	68551-19-9	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
Alkanes, C12-14-iso-	68551-19-9	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
Alkanes, C12-14-iso-	68551-19-9	Water flea	Analogous Compound	21 days	NOEL	100 mg/l
Kaolin, calcined	92704-41-1	Bacteria	Estimated	16 hours	EC10	1,400 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l

**3M™ Machine Polish PN05996 Plus**

Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC10	41 mg/l
Kaolin, calcined	92704-41-1	Rainbow Trout	Estimated	30 days	NOEC	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
GLYCERIN	56-81-5	Rainbow Trout	Experimental	96 hours	LC50	54,000 mg/l
GLYCERIN	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
GLYCERIN	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Diatom	Experimental	72 hours	ErC50	0.099 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Green algae	Experimental	96 hours	ErC50	0.23 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Mysid Shrimp	Experimental	96 hours	LC50	1.81 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Sheepshead Minnow	Experimental	96 hours	LC50	25.1 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Water flea	Experimental	48 hours	LC50	0.934 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Blackworm	Experimental	28 days	NOEC	25 mg/kg (Dry Weight)
2-Methyl-4-isothiazoline-3-one	2682-20-4	Diatom	Experimental	72 hours	ErC10	0.04 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Fathead Minnow	Experimental	33 days	NOEC	2.1 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Green algae	Experimental	96 hours	NOEC	0.12 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Water flea	Experimental	21 days	NOEC	0.044 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Activated sludge	Experimental	3 hours	EC50	41 mg/l

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide	1344-28-1	Data not available - insufficient	N/A	N/A	N/A	N/A
Alkanes, C12-14-iso-	68551-19-9	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	31.3 %BOD/ThOD	OECD 301F - Manometric Respiro
Kaolin, calcined	92704-41-1	Data not available - insufficient	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
GLYCERIN	56-81-5	Experimental Biodegradation	14 days	Biological Oxygen Demand	63 %BOD/ThOD	OECD 301C - MITI (I)
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Biodegradation	29 days	Carbon dioxide evolution	50 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

**12.3. Bioaccumulative potential**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide	1344-28-1	Data not available	N/A	N/A	N/A	N/A

		or insufficient for classification				
Alkanes, C12-14-iso-	68551-19-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
GLYCERIN	56-81-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-1.75	similar to OECD 107
2-Methyl-4-isothiazoline-3-one	2682-20-4	Analogous Compound BCF - Fish	56 days	Bioaccumulation Factor	5.75	
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-0.486	OECD 107 log Kow shke flsk mtd

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

**SECTION 14: Transport Information**

Not hazardous for transportation.

**Marine Transport (IMDG)**

**UN Number:**None assigned.

**Proper Shipping Name:**None assigned.

**Technical Name:**None assigned.

**Hazard Class/Division:**None assigned.

**Subsidiary Risk:**None assigned.

**Packing Group:**None assigned.

**Limited Quantity:**None assigned.

**Marine Pollutant:** None assigned.

**Marine Pollutant Technical Name:** None assigned.

**Other Dangerous Goods Descriptions:**

None assigned.

**Air Transport (IATA)**

**UN Number:**None assigned.

**Proper Shipping Name:**None assigned.

**Technical Name:**None assigned.

**Hazard Class/Division:**None assigned.

**Subsidiary Risk:**None assigned.

**Packing Group:**None assigned.

**Limited Quantity:**None assigned.

**Marine Pollutant:** None assigned.

**Marine Pollutant Technical Name:** None assigned.

**Other Dangerous Goods Descriptions:**

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

## SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at [www.3M.com.my](http://www.3M.com.my)