



Safety Data Sheet

Copyright, 2025, Solventum. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Solventum products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Solventum, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-2096-9	Version Number:	2.00
Issue Date:	06/11/25	Supersedes Date:	02/13/18

Product identifier

Filtek™ P60 Posterior Syringe Intro Kit With Universal Etchant (4720E, 8100L)

ID Number	UPC	ID Number	UPC
70-2010-9407-8		70-2014-0123-2	
70-2014-1098-5		70-2014-1218-9	
70-2014-1220-5		70-2014-1231-2	
UU-0131-5996-5		UU-0134-9495-8	

7100017566, 7100044553, 7100141217, 7100156396, 7100156408, 7100156407, 7100364550, 7100339200

Recommended use

Dental Product, Dental restorative system

Restrictions on use

For use by dental professionals only.

Supplier's details

MANUFACTURER:	Solventum
DIVISION:	Dental Solutions
ADDRESS:	Solventum US LLC, 12930 IH 10 West, San Antonio, TX 78249
Telephone:	1-855-423-6725

Emergency telephone number

+1 703-741-5970; (24/7)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

29-8286-6, 08-7419-8, 18-9027-6

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Solventum MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Solventum product is fit for a particular purpose and suitable for user's

method of use or application. Given the variety of factors that can affect the use and application of a Solventum product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Solventum product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Solventum provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Solventum makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Solventum.

Solventum USA SDSs are available at Solventum.com



Safety Data Sheet

Copyright, 2026, Solventum. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Solventum products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Solventum, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	08-7419-8	Version Number:	14.01
Issue Date:	05/08/26	Supersedes Date:	06/10/25

SECTION 1: Identification

1.1. Product identifier

Filtek™ P60 Posterior Restorative Paste

Product Identification Numbers

70-2010-2550-2, 70-2010-2551-0, 70-2010-2552-8, 70-2010-2580-9, 70-2010-2581-7, 70-2010-2582-5, 70-2010-2605-4, 70-2010-2606-2, 70-2010-2607-0, 70-2010-5197-9, 70-2010-5198-7, 70-2010-5199-5, 70-2010-8787-4, 70-2010-8788-2, 70-2010-8789-0, 70-2014-1110-8, 70-2014-1111-6, 70-2014-1112-4, 70-2014-2046-3, 70-2014-2047-1, 70-2014-2048-9, 70-2014-2049-7, 70-2014-2050-5, 70-2014-2051-3, UU-0134-9488-3, UU-0134-9489-1, UU-0134-9490-9, UU-0137-5666-1, UU-0137-5668-7, UU-0137-5669-5, UU-0137-5670-3, UU-0137-5683-6, UU-0137-5684-4, UU-0137-5722-2, UU-0137-5723-0, UU-0137-5724-8, UU-0137-5766-9, UU-0137-5784-2, UU-0137-5796-6, UU-0137-5883-2, UU-0137-5884-0, 7000054233, 7000054234, 7000054235, 7000030430, 7000030431, 7000030432, 7000030448, 7100006639, 7000030449, 7100027797, 7000003193, 7100084423, 7100237887, 7100237889, 7100237881, 7100141053, 7100141039, 7100141052, 7100295493, 7100364545, 7100364543, 7100364544, 7100378950, 7100378951, 7100378952, 7100378896, 7100378897, 7100378898, 7100378911, 7100378994, 7100378912, 7100379012, 7100378894, 7100379024, 7100379112, 7100379111, 7100295485, 7100295498, 7100295494, 7100295299, 7100295496

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Restorative

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER:	Solventum
DIVISION:	Dental Solutions
ADDRESS:	Solventum US LLC, 12930 IH 10 West, San Antonio, TX 78249
Telephone:	1-855-423-6725

1.4. Emergency telephone number

+1 703-741-5970; (24/7)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

2.2. Label elements**Signal word**

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Precautionary statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF exposed or concerned: Get medical attention.

If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Silane treated ceramic	444758-98-9	75 - 85
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	1565-94-2	1 - 10
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	1 - 10
Diurethane Dimethacrylate (UDMA)	Trade Secret*	3 - 7
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	< 3
Aluminum Oxide	1344-28-1	<= 1
N,N-Dimethylbenzocaine (EDMAB)	10287-53-3	<= 0.3

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with

inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum metal and insoluble compounds, respirable fraction	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Color	White
Odor	Slight Acrylate
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>Not Applicable</i>
Relative Vapor Density	<i>Not Applicable</i>
Density	2.1 g/cm ³
Relative Density	2.1 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>Not Applicable</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	142,857 mm ² /sec
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H ₂ O & Exempt Solvents	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
--------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed. May cause additional health effects (see below).

Additional Health Effects:**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Silane treated ceramic	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane treated ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Diurethane Dimethacrylate (UDMA)	Dermal	Rat	LD50 > 2,000 mg/kg
Diurethane Dimethacrylate (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Ingestion	Rat	LD50 > 35,000 mg/kg
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	Rat	LD50 > 11,700 mg/kg
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Mouse	LD50 > 2,000
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Rat	LD50 10,837 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
N,N-Dimethylbenzocaine (EDMAB)	Dermal	Rat	LD50 > 2,000 mg/kg
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silane treated ceramic	similar compounds	No significant irritation
Diurethane Dimethacrylate (UDMA)	Rabbit	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	Minimal irritation
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Rabbit	No significant irritation
Triethylene Glycol Dimethacrylate (TEGDMA)	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
N,N-Dimethylbenzocaine (EDMAB)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Silane treated ceramic	similar compounds	Mild irritant
Diurethane Dimethacrylate (UDMA)	Rabbit	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	No significant irritation
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	In vitro data	No significant irritation
Triethylene Glycol Dimethacrylate (TEGDMA)	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
N,N-Dimethylbenzocaine (EDMAB)	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Silane treated ceramic	similar compounds	Not classified
Diurethane Dimethacrylate (UDMA)	Multiple animal species	Sensitizing

Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Guinea pig	Not classified
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Mouse	Not classified
Triethylene Glycol Dimethacrylate (TEGDMA)	Mouse	Sensitizing
N,N-Dimethylbenzocaine (EDMAB)		Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diurethane Dimethacrylate (UDMA)	In Vitro	Not mutagenic
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	In Vitro	Not mutagenic
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	In Vitro	Not mutagenic
Triethylene Glycol Dimethacrylate (TEGDMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	In Vitro	Not mutagenic
N,N-Dimethylbenzocaine (EDMAB)	In vivo	Not mutagenic
N,N-Dimethylbenzocaine (EDMAB)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Silane treated ceramic	Inhalation	similar compounds	Some positive data exist, but the data are not sufficient for classification
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Mouse	Not carcinogenic
Aluminum Oxide	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Diurethane Dimethacrylate (UDMA)	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Diurethane Dimethacrylate (UDMA)	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	5 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	premating into lactation
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	Toxic to male reproduction	Rat	NOAEL 50 mg/kg/day	53 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Silane treated ceramic	Inhalation	pulmonary fibrosis	Not classified	similar compounds	NOAEL Not available	
Diurethane Dimethacrylate (UDMA)	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	skin	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane Dimethacrylate (UDMA)	Ingestion	vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	skin	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000	90 days

(BISGMA)					mg/kg/day	
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Bisphenol A Diglycidyl Ether Dimethacrylate (BISGMA)	Ingestion	vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	liver	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	skin	Not classified	Mouse	NOAEL 100 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	gastrointestinal tract	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	hematopoietic system	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	nervous system	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	kidney and/or bladder	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	respiratory system	Not classified	Mouse	NOAEL 2,000 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	liver	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	nervous system	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	eyes	Not classified	Rat	NOAEL 3,849 mg/kg/day	13 weeks
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 74 mg/kg/day	28 days
N,N-Dimethylbenzocaine	Ingestion	liver	Not classified	Rat	NOAEL 900	28 days

(EDMAB)					mg/kg/day	
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	heart	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	endocrine system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	immune system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	muscles	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	nervous system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	eyes	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	respiratory system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days
N,N-Dimethylbenzocaine (EDMAB)	Ingestion	vascular system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not Applicable.

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Aluminum Oxide	1344-28-1	<= 1

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	08-7419-8	Version Number:	14.01
Issue Date:	05/08/26	Supersedes Date:	06/10/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Solventum MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Solventum product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Solventum product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Solventum product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Solventum provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Solventum makes

no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Solventum.

Solventum USA SDSs are available at Solventum.com



Safety Data Sheet

Copyright, 2025, Solventum. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Solventum products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Solventum, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	18-9027-6	Version Number:	14.00
Issue Date:	03/25/25	Supersedes Date:	04/23/24

SECTION 1: Identification

1.1. Product identifier

Adper™ Single Bond 2

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LE-F100-0350-7		70-2010-3677-2	
70-2010-8731-2		70-2014-1113-2	
70-2014-1813-7		70-2014-2097-6	
70-2014-2304-6		UU-0131-6347-0	
UU-0131-6643-2		UU-0133-0152-6	
UU-0134-9491-7			

7000030482, 7100141132, 7100263785, 7100307628, 7100339276, 7100364546, 7100339572, 7100335422, 7100350238

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER:	Solventum
DIVISION:	Dental Solutions
ADDRESS:	Solventum US LLC, 12930 IH 10 West, San Antonio, TX 78249
Telephone:	1-855-423-6725

1.4. Emergency telephone number

+1 703-741-5970; (24/7)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

Keep container tightly closed.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

15% of the mixture consists of ingredients of unknown acute oral toxicity.

100% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Ethyl Alcohol	64-17-5	25 - 35
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	1565-94-2	10 - 20
Silane treated silica	Mixture	10 - 20
HEMA	868-77-9	5 - 15
Copolymer of acrylic and itaconic acids	25948-33-8	< 10
Glycerol 1,3 dimethacrylate	1830-78-0	5 - 10
Water	7732-18-5	< 10
Diurethane dimethacrylate (UDMA)	72869-86-4	< 5
Diphenyliodonium hexafluorophosphate	58109-40-3	< 1
N,N-DIMETHYLBENZOCAINE	10287-53-3	< 0.3

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide

Condition

During Combustion

Carbon dioxide

During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethyl Alcohol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
Ethyl Alcohol	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. See Section 7.1 for additional information on skin protection.

Gloves made from the following material(s) are recommended: Chemical Protective glove of any material type

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Light White-Yellow

Specific Physical Form:

Liquid

Odor

Slight Acrylate

Odor threshold

No Data Available

pH

No Data Available

Melting point

Not Applicable

Boiling Point

78 °C

Flash Point

18.5 °C [Test Method:Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density	1.075 g/ml
Specific Gravity	1.075 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	410 °C
Decomposition temperature	No Data Available
Viscosity	No Data Available
Molecular weight	No Data Available
Percent volatile	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Overall product	Dermal	Rabbit	LD50 > 2,000 mg/kg
Ethyl Alcohol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
Ethyl Alcohol	Ingestion	Rat	LD50 17,800 mg/kg
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Ingestion	Rat	LD50 > 11,700 mg/kg
HEMA	Dermal	Rabbit	LD50 > 5,000 mg/kg
HEMA	Ingestion	Rat	LD50 5,564 mg/kg
Glycerol 1,3 dimethacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Copolymer of acrylic and itaconic acids	Ingestion	Rat	LD50 > 5,000 mg/kg
Copolymer of acrylic and itaconic acids	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Diurethane dimethacrylate (UDMA)	Dermal	Rat	LD50 > 2,000 mg/kg
Diurethane dimethacrylate (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
Diphenyliodonium hexafluorophosphate	Ingestion	Rat	LD50 32 mg/kg
N,N-DIMETHYLBENZOCAINE	Dermal	Rat	LD50 > 2,000 mg/kg
N,N-DIMETHYLBENZOCAINE	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value

Ethyl Alcohol	Rabbit	No significant irritation
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Rabbit	No significant irritation
HEMA	Rabbit	Minimal irritation
Glycerol 1,3 dimethacrylate	Rabbit	No significant irritation
Diurethane dimethacrylate (UDMA)	Rabbit	No significant irritation
Diphenyliodonium hexafluorophosphate	Rabbit	No significant irritation
N,N-DIMETHYLBENZOCAINE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Ethyl Alcohol	Rabbit	Severe irritant
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	In vitro data	No significant irritation
HEMA	Rabbit	Moderate irritant
Glycerol 1,3 dimethacrylate	In vitro data	Severe irritant
Diurethane dimethacrylate (UDMA)	Rabbit	No significant irritation
Diphenyliodonium hexafluorophosphate	Rabbit	Mild irritant
N,N-DIMETHYLBENZOCAINE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Ethyl Alcohol	Human	Not classified
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Mouse	Not classified
HEMA	Human and animal	Sensitizing
Glycerol 1,3 dimethacrylate	Mouse	Not classified
Diurethane dimethacrylate (UDMA)	Multiple animal species	Sensitizing
N,N-DIMETHYLBENZOCAINE		Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Ethyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	In Vitro	Not mutagenic
HEMA	In vivo	Not mutagenic
HEMA	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diurethane dimethacrylate (UDMA)	In Vitro	Not mutagenic
Diphenyliodonium hexafluorophosphate	In Vitro	Some positive data exist, but the data are not sufficient for classification
N,N-DIMETHYLBENZOCAINE	In vivo	Not mutagenic
N,N-DIMETHYLBENZOCAINE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Ethyl Alcohol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Ethyl Alcohol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
HEMA	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
HEMA	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
HEMA	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Diurethane dimethacrylate (UDMA)	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Diurethane dimethacrylate (UDMA)	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	56 days
Diurethane dimethacrylate (UDMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
N,N-DIMETHYLBENZOCAINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
N,N-DIMETHYLBENZOCAINE	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
N,N-DIMETHYLBENZOCAINE	Ingestion	Toxic to male reproduction	Rat	NOAEL 50 mg/kg/day	53 days

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethyl Alcohol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
Ethyl Alcohol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
Ethyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Copolymer of acrylic and itaconic acids	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	
Diphenyliodonium hexafluorophosphate	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Ethyl Alcohol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethyl Alcohol	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
Ethyl Alcohol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months

Ethyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
Bisphenol A diglycidyl ether dimethacrylate (BISGMA)	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Copolymer of acrylic and itaconic acids	Ingestion	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
Copolymer of acrylic and itaconic acids	Ingestion	heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Diurethane dimethacrylate (UDMA)	Ingestion	liver kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	56 days
N,N-DIMETHYLBENZOCAINE	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 74 mg/kg/day	28 days
N,N-DIMETHYLBENZOCAINE	Ingestion	liver heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 900 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification****Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	18-9027-6	Version Number:	14.00
Issue Date:	03/25/25	Supersedes Date:	04/23/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Solventum MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Solventum product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Solventum product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Solventum product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Solventum provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Solventum makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Solventum.

Solventum USA SDSs are available at Solventum.com



Safety Data Sheet

Copyright, 2025, Solventum. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Solventum products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Solventum, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	29-8286-6	Version Number:	6.00
Issue Date:	06/11/25	Supersedes Date:	09/02/21

SECTION 1: Identification

1.1. Product identifier

Scotchbond™ Universal Etchant (41263)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LE-F100-1014-5		LE-F100-1040-4	
70-2011-3906-3		70-2011-4006-1	
70-2011-4007-9			

7000055181, 7000055191, 7100007505

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Etching gel

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER:	Solventum
DIVISION:	Dental Solutions
ADDRESS:	Solventum US LLC, 12930 IH 10 West, San Antonio, TX 78249
Telephone:	1-855-423-6725

1.4. Emergency telephone number

+1 703-741-5970; (24/7)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Corrosive to metal: Category 1.
 Serious Eye Damage/Irritation: Category 1.
 Skin Corrosion/Irritation: Category 1C.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion |

Pictograms



Hazard Statements

May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary Statements

Prevention:

- Keep only in original container.
- Do not breathe vapors.
- Wear protective gloves, protective clothing, and eye/face protection.
- Wash thoroughly after handling.

Response:

- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.
- Wash contaminated clothing before reuse.
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	50 - 65 Trade Secret *
PHOSPHORIC ACID	7664-38-2	30 - 40 Trade Secret *

SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	112945-52-5	1 - 10 Trade Secret *
POLYETHYLENE GLYCOL	25322-68-3	1 - 5 Trade Secret *
ALUMINUM OXIDE	1344-28-1	< 2 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
SILICA, AMORPHOUS	112945-52-5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
ALUMINUM OXIDE	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
POLYETHYLENE GLYCOL	25322-68-3	AIHA	TWA:10 mg/m3	
PHOSPHORIC ACID	7664-38-2	ACGIH	TWA:1 mg/m3;STEL:3 mg/m3	
PHOSPHORIC ACID	7664-38-2	OSHA	TWA:1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state

Liquid

Color

Blue

Specific Physical Form:

Gel

Odor

Moderate Honey, Slight Solvent

Odor threshold

No Data Available

pH

< 1

Melting point

Not Applicable

Boiling Point

No Data Available

Flash Point

> 100 °C [Test Method: Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

1.1 - 1.2 g/ml

Specific Gravity

1.1 - 1.2 [Ref Std: WATER=1]

Solubility in Water

Complete

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Molecular weight

No Data Available

Volatile Organic Compounds

No Data Available

Percent volatile

No Data Available

VOC Less H2O & Exempt Solvents

No Data Available

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong bases

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
------	-------	---------	-------

Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
PHOSPHORIC ACID	Dermal	Rabbit	LD50 2,740 mg/kg
PHOSPHORIC ACID	Ingestion	Rat	LD50 1,530 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Dermal	Rabbit	LD50 > 5,000 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE GLYCOL	Dermal	Rabbit	LD50 > 20,000 mg/kg
POLYETHYLENE GLYCOL	Ingestion	Rat	LD50 32,770 mg/kg
ALUMINUM OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PHOSPHORIC ACID	Rabbit	Corrosive
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
POLYETHYLENE GLYCOL	Rabbit	Minimal irritation
ALUMINUM OXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
PHOSPHORIC ACID	official classification	Corrosive
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
POLYETHYLENE GLYCOL	Rabbit	Mild irritant
ALUMINUM OXIDE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
PHOSPHORIC ACID	Human	Not classified
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Human and animal	Not classified
POLYETHYLENE GLYCOL	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
PHOSPHORIC ACID	In Vitro	Not mutagenic
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL	In Vitro	Not mutagenic
POLYETHYLENE GLYCOL	In vivo	Not mutagenic
ALUMINUM OXIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
POLYETHYLENE GLYCOL	Ingestion	Rat	Not carcinogenic
ALUMINUM OXIDE	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
PHOSPHORIC ACID	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
PHOSPHORIC ACID	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
PHOSPHORIC ACID	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
POLYETHYLENE GLYCOL	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
POLYETHYLENE GLYCOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
POLYETHYLENE GLYCOL	Not Specified	Not classified for reproduction and/or development		NOEL N/A	
POLYETHYLENE GLYCOL	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
PHOSPHORIC ACID	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
POLYETHYLENE GLYCOL	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
POLYETHYLENE GLYCOL	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
POLYETHYLENE GLYCOL	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 5,640 mg/kg/day	13 weeks
ALUMINUM OXIDE	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

ALUMINUM OXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
----------------	------------	--------------------	----------------	-------	---------------------	-----------------------

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

Please contact the emergency numbers listed on the first page of the SDS for Transportation Information for this material.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Corrosive to metal

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ALUMINUM OXIDE	1344-28-1	Trade Secret < 2
ALUMINUM OXIDE (ALUMINUM OXIDE)	1344-28-1	Trade Secret < 2

(FIBROUS FORMS ONLY)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None
Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 29-8286-6 **Version Number:** 6.00
Issue Date: 06/11/25 **Supersedes Date:** 09/02/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Solventum MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Solventum product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Solventum product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Solventum product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Solventum provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Solventum makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Solventum.

Solventum USA SDSs are available at Solventum.com