

# Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 09-3827-4
 Version number:
 9.00

 Issue Date:
 2025/06/20
 Supercedes Date:
 2021/08/18

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Novec<sup>TM</sup> 8200 Engineered Fluid

**Product Identification Numbers** 

80-0014-3059-6 98-0212-2776-8 H0-0020-1447-2 H0-0020-1465-4

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

For Industrial Use Only. Not Intended for Use As A Medical Device Or Drug.

#### **Specific Use**

Cleaning Movie Film

#### Restrictions on use

Novec<sup>TM</sup> Engineered Fluids are used in a wide variety of applications, including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

#### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Electronics Materials Solutions Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Physical Hazards Not Otherwise Classified - Category 1

#### 2.2. Label elements

#### Signal word

Danger

#### **Symbols**

Exclamation mark

#### **Pictograms**



#### **Hazard Statements**

In use, may form flammable/explosive vapour-air mixture.

#### **Precautionary statements**

#### **Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Ethyl nonafluoroisobutyl ether	163702-06-5	55 - 90	Propane, 2-(ethoxydifluoromethyl)-
			1,1,1,2,3,3,3,-heptafluoro -
Ethyl nonafluorobutyl ether	163702-05-4	10 - 45	Butane, 1-ethoxy-1,1,2,2,3,3,4,4,4-
			nonafluoro-

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Wash with soap and water. If you feel unwell, get medical attention.

# **Eye Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### 3M<sup>TM</sup> Novec<sup>TM</sup> 8200 Engineered Fluid

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Unsuitable extinguishing media

None Determined

#### 5.3. Special hazards arising from the substance or mixture

No closed-cup flash point but flam/expl. vapor air mixture Material displays no closed-cup flash point but may form flammable/explosive vapor air mixture.

#### 5.4. Special protection actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sparks/flames/extreme heat Keep away from sparks, flames, and extreme heat. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. Observe precautions from other sections.

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Eliminate ignition sources when cleaning spill Eliminate all potential ignition sources when cleaning up spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. No smoking: Smoking while using this product can result in contamination of the tobacco

and/or smoke and lead to the formation of hazardous decomposition products. Keep away from sparks/flames/extreme heat Keep away from sparks, flames, and extreme heat.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from strong bases.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Ethyl nonafluorobutyl ether	163702-05-	Manufacturer	TWA(as total isomers):200	
	4	determined	ppm(2160 mg/m3)	
Ethyl nonafluoroisobutyl ether	163702-06-	Manufacturer	TWA(as total isomers):200	
	5	determined	ppm(2160 mg/m3)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide ventilation adequate to maintain vapour concentration below lower explosive concentration.

#### 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene

#### Respiratory protection

None required.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Dhysical state	т ' '1
Physical state	II and
1 Hysical state	Biquid

Page: 4 of 10

Specific Physical Form:	Liquid
Colour	Colourless
Odour	Faint Solvent
Odour threshold	No Data Available
pH	
•	Not Applicable -138 °C
Melting point/Freezing point	
Boiling point	76 °C
Flash Point	No flash point
Evaporation rate	33 [Ref Std:BUOAC=1]
Flammability	Not Applicable
Flammable Limits(LEL)	210 g/m3 [Details: ASTM E681-94 Method]
Flammable Limits(UEL)	1,070 g/m3 [Details: ASTM E681-94 Method]
Vapour Pressure	14,532.1 Pa [@ 25 °C ]
Relative Vapour Density	9.1 [ <i>Ref Std</i> :AIR=1]
Density	1.43 g/ml
Relative density	1.43 [ <i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	4.2 [Details:at 30 °C]
Autoignition temperature	375 °C [Details: ASTM E659-78 Method]
Decomposition temperature	Not Applicable
Kinematic Viscosity	0.43 mm2/sec
Volatile Organic Compounds	No Data Available
Percent volatile	100 %
VOC Less H2O & Exempt Solvents	No Data Available
Molecular weight	No Data Available

Particle Characteristics	Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

# 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Sparks and/or flames

# 10.5. Incompatible materials

Strong bases

# 10.6. Hazardous decomposition products

Substance **Condition** Carbon monoxide At Elevated Temperatures Carbon dioxide At Elevated Temperatures

Hydrogen Fluoride At Elevated Temperatures - extreme conditions of

Page: 5 of 10

Perfluoroisobutylene (PFIB)

heat At Elevated Temperatures - extreme conditions of heat

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No health effects are expected.

#### **Skin Contact:**

May be harmful in contact with skin. Contact with the skin during product use is not expected to result in significant irritation.

#### **Eve Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

May be harmful if swallowed.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Ethyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Ethyl nonafluoroisobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 989 mg/l
Ethyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 2,000 mg/kg
Ethyl nonafluorobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Ethyl nonafluorobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 989 mg/l
Ethyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Name	Species	Value
Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
Ethyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Ethyl nonafluorobutyl ether	Guinea	Not classified
	pig	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Ethyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Ethyl nonafluorobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluorobutyl ether	In vivo	Not mutagenic

#### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Ethyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluoroisobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
Ethyl nonafluorobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluorobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl nonafluoroisobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks

		gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system				
Ethyl nonafluoroisobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethyl nonafluorobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Ethyl nonafluorobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

# **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification**

Health: 1 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	09-3827-4	Version number:	9.00
Issue Date:	2025/06/20	Supercedes Date:	2021/08/18

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE. COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

$3M^{TM}$	Novec <sup>TM</sup>	8200	<b>Engineered</b>	Fluid
-----------	---------------------	------	-------------------	-------

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 10 of 10