



## Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 27-5082-6  
**Revision date:** 20/11/2025

**Version number:** 10.01  
**Supersedes date:** 20/11/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M 08080 Auto Adhesive Aerosol

#### Product Identification Numbers

UU-0090-3795-1

7100139848

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Adhesive aerosol.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2  
**Telephone:** +353 1 280 3555  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

Aspiration hazard classification does not apply due to the spray pattern of the product.

#### CLASSIFICATION:

Aerosol, Category 1 - Aerosol 1; H222, H229

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS09 (Environment) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
methyl acetate	79-20-9	201-185-2	10 - 30

#### HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261E	Avoid breathing vapour or spray.
P273	Avoid release to the environment.

##### Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

Contains 2% of components with unknown hazards to the aquatic environment.

## 2.3. Other hazards

May displace oxygen and cause rapid suffocation.

This material does not contain any substances that are assessed to be a PBT or vPvB

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (REACH-No.) 01-2119472128-37	30 - 60	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
methyl acetate	(CAS-No.) 79-20-9 (EC-No.) 201-185-2 (REACH-No.) 01-2119459211-47	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2 (REACH-No.) 01-2119463273-41	5 - 15	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	(CAS-No.) 31393-98-3	3 - 7	Aquatic Chronic 4, H413
SBR stabilized	Trade Secret	1 - 5	Substance not classified as hazardous
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL)BENZENE	(CAS-No.) 100199-62-0	< 2.5	Substance not classified as hazardous
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	(CAS-No.) 9017-27-0	< 2.5	Substance not classified as hazardous
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	(EC-No.) 920-901-0	0.5 - 1.5	Asp. Tox. 1, H304 EUH066
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	(EC-No.) 927-676-8	0.5 - 1.5	Asp. Tox. 1, H304 EUH066

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### **If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

#### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

## **SECTION 5: Fire-fighting measures**

### **5.1. Extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

### **5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

#### **Substance**

Hydrocarbons.  
formaldehyde  
Carbon monoxide  
Carbon dioxide.

#### **Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.

### **5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

### **6.2. Environmental precautions**

Avoid release to the environment.

### **6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
cyclohexane	110-82-7	Ireland OELs	TWA(8 hours):700 mg/m3(200 ppm);TWA(8 hours):200 ppm(700 mg/m3)	
dimethyl ether	115-10-6	Ireland OELs	TWA(8 hours):1920 mg/m3(1000 ppm);TWA(8 hours):1000 ppm(1920 mg/m3)	
methyl acetate	79-20-9	Ireland OELs	TWA(8 hours):610 mg/m3(200 ppm);STEL(15 minutes):760 mg/m3(250 ppm)	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
cyclohexane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	2,016 mg/kg bw/d
cyclohexane		Worker	Inhalation, Long-term exposure (8 hours), Local effects	700 mg/m <sup>3</sup>
cyclohexane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	700 mg/m <sup>3</sup>
cyclohexane		Worker	Inhalation, Short-term exposure, Local effects	700 mg/m <sup>3</sup>
cyclohexane		Worker	Inhalation, Short-term exposure, Systemic effects	700 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
cyclohexane		Freshwater	0.207 mg/l
cyclohexane		Freshwater sediments	3.627 mg/kg d.w.
cyclohexane		Intermittent releases to water	0.207 mg/l
cyclohexane		Marine water	0.207 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

**8.2. Exposure controls**

In addition, refer to the annex for more information.

**8.2.1. Engineering controls**

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Indirect vented goggles.

*Applicable Norms/Standards*

Use eye protection conforming to EN 166

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Colourless
Odor	Sweet Odour
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	No data available.
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	-42 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	Not applicable.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	Not applicable.
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	0.7 g/ml
Relative density	0.7 [Ref Std:WATER=1] [Details:G/cm3]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

### 9.2. Other information

**9.2.2 Other safety characteristics****EU Volatile Organic Compounds***No data available.***Evaporation rate***No data available.***Percent volatile**

85 - 95 %

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Direct sunlight

Heat.

Sparks and/or flames.

Temperatures above 45 °C (113 °F)

**10.5 Incompatible materials**

Strong acids.

Strong oxidising agents.

**10.6 Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.



**Eye contact**

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
dimethyl ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg
methyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 49 mg/l
methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Ingestion	Rat	LD50 > 2,000 mg/kg
SBR stabilized	Dermal	Rabbit	LD50 > 2,000 mg/kg
SBR stabilized	Ingestion	Rat	LD50 > 5,000 mg/kg
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL)BENZENE	Dermal		LD50 estimated to be > 5,000 mg/kg
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL)BENZENE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	Ingestion	Rat	LD50 > 10,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.4 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	similar compounds	LD50 > 2,200 mg/kg

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	similar compounds	LD50 > 15,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Dermal	similar compounds	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Ingestion	similar compounds	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
methyl acetate	Rabbit	No significant irritation
cyclohexane	Rabbit	Mild irritant
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In vitro data	No significant irritation
SBR stabilized	Professional judgement	No significant irritation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	similar compounds	Mild irritant
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	similar compounds	Mild irritant

### Serious Eye Damage/Irritation

Name	Species	Value
methyl acetate	Rabbit	Moderate irritant
cyclohexane	Rabbit	Mild irritant
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In vitro data	No significant irritation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	similar compounds	No significant irritation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	similar compounds	No significant irritation

### Skin Sensitisation

Name	Species	Value
methyl acetate	Human	Not classified
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Multiple animal species	Not classified
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	similar compounds	Not classified
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	similar compounds	Not classified

### Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

dimethyl ether	In Vitro	Not mutagenic
dimethyl ether	In vivo	Not mutagenic
methyl acetate	In Vitro	Not mutagenic
methyl acetate	In vivo	Not mutagenic
cyclohexane	In Vitro	Not mutagenic
cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
dimethyl ether	Inhalation	Rat	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
dimethyl ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
dimethyl ether	Inhalation	cardiac sensitisation	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
methyl acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Ingestion	heart   gastrointestinal tract   hematopoietic system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
cyclohexane	Aspiration hazard
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
dimethyl ether	115-10-6	Bacteria	Experimental	N/A	EC10	>1,600 mg/l

**3M 08080 Auto Adhesive Aerosol**

dimethyl ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
dimethyl ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
methyl acetate	79-20-9	Green algae	Experimental	72 hours	ErC50	>120 mg/l
methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
methyl acetate	79-20-9	Zebra Fish	Experimental	96 hours	LC50	250 mg/l
methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
methyl acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
SBR stabilized	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	9017-27-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL) BENZENE	100199-62-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Rainbow trout	Estimated	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green algae	Analogous Compound	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes,	927-676-8	Water flea	Analogous Compound	48 hours	EL50	>1,000 mg/l

cyclics, <2% aromatics						
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Rainbow trout	Experimental	96 hours	LL50	>788,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Scud	Experimental	96 hours	LL50	>10,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green algae	Analogous Compound	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Water flea	Analogous Compound	21 days	NOEL	>1 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
dimethyl ether	115-10-6	Experimental Biodegradation	28 days	BOD	5 %BOD/ThO D	OECD 301D - Closed bottle test
dimethyl ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	
methyl acetate	79-20-9	Experimental Biodegradation	28 days	BOD	70 %BOD/ThO D	OECD 301D - Closed bottle test
methyl acetate	79-20-9	Experimental Aquatic Inherent Biodegrad.	6 days	Dissolv. Organic Carbon Deplet	>95 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
methyl acetate	79-20-9	Experimental Photolysis		Photolytic half-life (in air)	94 days (t 1/2)	
methyl acetate	79-20-9	Experimental Hydrolysis		Hydrolytic half-life	44 days (t 1/2)	
cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThO D	OECD 301F - Manometric respirometry
cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Experimental Biodegradation	28 days	BOD	4 %BOD/ThO D	OECD 301D - Closed bottle test
SBR stabilized	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	9017-27-0	Modeled Biodegradation	28 days	BOD	1 %BOD/ThO D	Catalogic™
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL)BENZENE	100199-62-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Estimated Biodegradation	28 days	BOD	31.3 %BOD/ThOD	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Experimental Biodegradation	28 days	BOD	22 %BOD/ThO D	OECD 301F - Manometric respirometry

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
dimethyl ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
methyl acetate	79-20-9	Experimental Bioconcentration		Log Kow	0.18	

cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
cyclohexane	110-82-7	Experimental Bioconcentration		Log Kow	3.44	
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Experimental Bioconcentration		Log Kow	7.41	
SBR stabilized	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ALPHA-METHYLSTYRENE-VINYLTOLUENE COPOLYMER	9017-27-0	Modeled Bioconcentration		Bioaccumulation factor	<=79	Catalogic™
BENZENE, 1-ETHENYL-4-METHYL-, POLYMER WITH (1-METHYLETHENYL)BENZENE	100199-62-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

#### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
dimethyl ether	115-10-6	Modeled Mobility in Soil	Koc	3 l/kg	Episuite™
methyl acetate	79-20-9	Experimental Mobility in Soil	Koc	1.5 l/kg	OECD 121 Estim. of Koc by HPLC
cyclohexane	110-82-7	Modeled Mobility in Soil	Koc	970 l/kg	Episuite™

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

#### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

- 08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
 16 05 04\* Gases in pressure containers (including halons) containing dangerous substances

**EU waste code (product container after use)**

- 15 01 04 Metallic packaging

**SECTION 14: Transportation information**

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 UN number or ID number</b>	UN1950	UN1950	UN1950
<b>14.2 UN proper shipping name</b>	AEROSOLS	AEROSOLS, FLAMMABLE	AEROSOLS
<b>14.3 Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4 Packing group</b>	Not applicable.	Not applicable.	Not applicable.
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	5F	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the



transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

##### Ingredient

SBR stabilized

##### CAS Nbr

Trade Secret

##### Classification

Gr. 3: Not classifiable

##### Regulation

International Agency  
for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

##### Ingredient

cyclohexane

##### CAS Nbr

110-82-7

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

#### Global inventory status

Contact 3M for more information.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P3a FLAMMABLE AEROSOLS	150 (net)	500 (net)

Seveso named dangerous substances, Annex 1, Part 2

None

#### Regulation (EU) No 649/2012

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

#### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: may burst if heated.

H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Revision information:**

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

**Annex**

<b>1. Title</b>	
<b>Substance identification</b>	cyclohexane; EC No. 203-806-2; CAS Nbr 110-82-7;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives and Sealants
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 07 -Industrial spraying ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
<b>Processes, tasks and activities covered</b>	Application of product.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 100 days per year; Indoor use; Outdoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); Provide extract ventilation to points where emissions occur; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Avoid release to the environment. Refer to special instructions / safety data sheet.; Do not apply industrial sludge to natural soils; Do not release to waterways or sewers; Prevent discharge of undissolved substance to or recover from wastewater;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and

PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	cyclohexane; EC No. 203-806-2; CAS Nbr 110-82-7;
<b>Exposure Scenario Name</b>	Professional Use of Adhesives
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	PROC 11 -Non industrial spraying ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
<b>Processes, tasks and activities covered</b>	Application of product.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of exposure per day at workplace [for one worker]: 8 hours/day; Emission days per year: 365 days per year; Indoor use; Outdoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Ventilated Process Enclosures; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Avoid release to the environment. Refer to special instructions / safety data sheet.;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)