Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	06-6435-9	**Version Number:**	20.05
Issue Date:	08/24/26	**Supersedes Date:**	07/28/25

SECTION 1: Identification

1.1. Product identifier
3M™ Scotch-Weld™ PUR Adhesive TS115 HGS

Product Identification Numbers

ID Number	UPC	ID Number	UPC
62-3892-5235-4		62-3892-5236-2	
62-3892-5238-8	0 00 51115 25163 4	62-3892-6839-2	0-00-48011-53274-5
62-3892-8530-5	00-21200-89451-0	62-3892-9530-4	00-21200-89452-7
62-3892-9531-2			

7010299377, 7100019439, 7010329745, 7000000904, 7100152611, 7010367606

1.2. Recommended use and restrictions on use

Recommended use
Adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification


2.1. Hazard classification
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word
Danger

Symbols
Health Hazard |

Pictograms



Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: respiratory system.

Precautionary statements

Prevention:
Do not breathe vapors.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves.
In case of inadequate ventilation wear respiratory protection.

Response:
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Get medical attention if you feel unwell.
If experiencing respiratory symptoms or if skin irritation or rash occurs: Call a POISON CENTER or doctor.
Take off contaminated clothing and wash it before reuse.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Supplemental Information:
May cause thermal burns. Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyurethane Resin (NJTS Reg. No. 04499600-6411P)	Trade Secret*	>= 97
p,p'-Diphenylmethane Diisocyanate (MDI)	101-68-8	<= 3

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:
Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Amine Compounds	During Combustion
Isocyanates	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant

dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Methylene bisphenyl isocyanate (MDI)	101-68-8	ACGIH	TWA:0.005 ppm	
p,p'-Diphenylmethane Diisocyanate (MDI)	101-68-8	OSHA	CEIL:0.2 mg/m3(0.02 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Butyl Rubber, Neoprene, Nitrile Rubber

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards
Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Waxy Solid
Color	Off-White
Odor	Mild Isocyanate
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	302 ºF [@ 5 mmHg] [*Details:*MDI5]
Flash Point	>=390 ºF
Evaporation rate	*No Data Available*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	*No Data Available*
Relative Vapor Density	8.6 [*Ref Std:*AIR=1] [*Details:*MDI]
Density	1.14 g/cm3 [@ 20 ºC]
Relative Density	1.14 [*Ref Std:*WATER=1]
Solubility in Water	Nil

Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	12,281 mm2/sec
Hazardous Air Pollutants	<=3 % weight [*Test Method:*Calculated]
Molecular weight	*No Data Available*
VOC Less H2O & Exempt Solvents	0 g/l [*Test Method:*calculated SCAQMD rule 443.1]
VOC Less H2O & Exempt Solvents	0 % [*Test Method:*calculated SCAQMD rule 443.1]

Particle Characteristics *Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Amines
Alcohols
Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and

tightness of chest. May cause additional health effects (see below).

Skin Contact:
During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction. Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
p,p'-Diphenylmethane Diisocyanate (MDI)	Dermal	Rabbit	LD50 > 5,000 mg/kg
p,p'-Diphenylmethane Diisocyanate (MDI)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
p,p'-Diphenylmethane Diisocyanate (MDI)	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	official classification	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	official classification	Severe irritant

Skin Sensitization

Name	Species	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	Mouse	Sensitizing

Respiratory Sensitization

Name	Species	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
p,p'-Diphenylmethane Diisocyanate (MDI)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
p,p'-Diphenylmethane Diisocyanate (MDI)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
p,p'-Diphenylmethane Diisocyanate (MDI)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
p,p'-Diphenylmethane Diisocyanate (MDI)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not Applicable.

Health Hazards
Respiratory or Skin Sensitization
Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
p,p'-Diphenylmethane Diisocyanate (MDI)	101-68-8	<= 3

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	06-6435-9	**Version Number:**	20.05
Issue Date:	08/24/26	**Supersedes Date:**	07/28/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com