



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-6601-2	Version number:	8.00
Issue Date:	2025/08/07	Supersedes Date:	2023/08/14

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer, P.N. 08306, 08308

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Two-part Epoxy Seam Sealer

1.3. Supplier's details

Company: 3M Canada Company

Division: Automotive Aftermarket

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577

E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

08-6599-8, 08-6600-4

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 08-6599-8 **Version number:** 13.00
Issue Date: 2025/08/07 **Supersedes Date:** 2023/08/14

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08308

1.2. Recommended use and restrictions on use

Intended Use

Automotive

Specific Use

Seam Sealer Accelerator to be mixed at a 1:1 ratio with Sealer Base

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Automotive Aftermarket
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

May cause an allergic skin reaction.

Precautionary statements**General:**

Keep out of reach of children.

Prevention:

Avoid breathing fumes. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	80 - 100 Trade Secret *	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	3 - 7	Siloxanes and Silicones, di-Me, reaction products with silica
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	0.5 - 2 Trade Secret *	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-, polymer with methyloxirane
Triethylenetetramine	112-24-3	0.094 - 0.5 Trade Secret *	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get

medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m ³ (1 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	Off-White
Odour	Mild Mercaptan
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point	Not Applicable
Flash Point	> 93.3 °C [Test Method:Closed Cup]
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	Not Applicable
Relative Vapour Density	Not Applicable
Density	1.18 g/cm ³
Relative density	1.18 [Ref Std:WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	No Data Available
Volatile Organic Compounds	1.7 % weight [Test Method:calculated per CARB title 2]
Volatile Organic Compounds	20 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	1.7 % weight
VOC Less H ₂ O & Exempt Solvents	20 g/l [Test Method:calculated SCAQMD rule 443.1]

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong acids

10.6. Hazardous decomposition products

Substance	Condition
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Nitrogen	Not Specified
Oxides of Sulfur	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Dermal	Rabbit	LD50 > 10,200 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	Rat	LD50 2,600 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Propylene Oxide, Polymer With Triethylenetetramine	Dermal	Rat	LD50 2,150 mg/kg

Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Rat	LD50 4,500 mg/kg
Triethylenetetramine	Dermal	Rat	LD50 1,465 mg/kg
Triethylenetetramine	Ingestion	Rat	LD50 1,591 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Propylene Oxide, Polymer With Triethylenetetramine	Rabbit	Irritant
Triethylenetetramine	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Propylene Oxide, Polymer With Triethylenetetramine	Rabbit	Severe irritant
Triethylenetetramine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Mouse	Sensitizing
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Propylene Oxide, Polymer With Triethylenetetramine	Mouse	Sensitizing
Triethylenetetramine	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Mercaptan-Terminated Epoxy Curing Agent	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Propylene Oxide, Polymer With Triethylenetetramine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Triethylenetetramine	In vivo	Not mutagenic
Triethylenetetramine	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Triethylenetetramine	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction	Ingestion	Not classified for development	Rat	NOAEL 1,350	during

products with silica				mg/kg/day	organogenesis
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	prematuring into lactation
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	43 days
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	prematuring into lactation
Triethylenetetramine	Dermal	Not classified for development	Rabbit	NOAEL 125 mg/kg/day	during organogenesis
Triethylenetetramine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propylene Oxide, Polymer With Triethylenetetramine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Triethylenetetramine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	endocrine system heart skin immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	43 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	08-6599-8	Version number:	13.00
Issue Date:	2025/08/07	Supersedes Date:	2023/08/14

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 08-6600-4 **Version number:** 7.00
Issue Date: 2025/08/07 **Supersedes Date:** 2023/08/14

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08308, 08306

1.2. Recommended use and restrictions on use

Intended Use

Automotive

Specific Use

Two-part Epoxy Seam Sealer - Base

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Automotive Aftermarket
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing fumes. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and respiratory protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
4,4'-isopropylidenediphenol-epichlorohydrin polymer	25068-38-6	60 - 80 Trade Secret *	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Epoxy Resin 2	30583-72-3	10 - 30 Trade Secret *	Cyclohexanol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	3 - 7	Siloxanes and Silicones, di-Me, reaction products with silica
Carbon Black	1333-86-4	0.5 - 1.5 Trade Secret *	Carbon black

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable

local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents. Store away from amines. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron

material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	Black
Odour	Mild Epoxy
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point	Not Applicable
Flash Point	> 115 °C [Test Method:Closed Cup]
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	Not Applicable
Relative Vapour Density	Not Applicable
Density	1.16 g/cm ³
Relative density	1.16 [Ref Std:WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	No Data Available
Volatile Organic Compounds	6 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0.5 % weight [Test Method:calculated per CARB title 2]
Percent volatile	0.5 % weight
VOC Less H ₂ O & Exempt Solvents	6 g/l [Test Method:calculated SCAQMD rule 443.1]

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Amines

Strong acids

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes	Not Specified
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Epoxy Resin 2	Dermal	Rat	LD50 > 2,000 mg/kg
Epoxy Resin 2	Ingestion	Rat	LD50 > 2,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Mild irritant
Epoxy Resin 2	Rabbit	Minimal irritation
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Moderate irritant
Epoxy Resin 2	Rabbit	Mild irritant
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human and animal	Sensitizing
Epoxy Resin 2	Mouse	Sensitizing
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In vivo	Not mutagenic
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin 2	In vivo	Not mutagenic
Epoxy Resin 2	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic

Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin 2	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	during gestation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 2	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days
Epoxy Resin 2	Ingestion	heart endocrine system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days

		gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system vascular system skin muscles eyes respiratory system				
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification

requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	08-6600-4	Version number:	7.00
Issue Date:	2025/08/07	Supersedes Date:	2023/08/14

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca