

Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-2796-0
 Version number:
 15.01

 Issue Date:
 2025/06/23
 Supercedes Date:
 2023/06/21

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Neoprene Rubber and Gasket Adhesive 2141

Product Identification Numbers

62-2141-2630-2 62-2141-5530-1 62-2141-6530-0 62-2141-6535-9 62-2141-7530-9 62-2141-8530-8 62-2141-9530-7 JS-3000-4967-8 JS-3000-5092-4 RE-0009-6552-5

UU-0125-1342-8 XS-0414-1079-5

1.2. Recommended use and restrictions on use

Intended Use

Rubber and gasket adhesive.

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2. Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1A. Carcinogenicity: Category 2.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |





Hazard Statements

Highly flammable liquid and vapour.

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility or the unborn child. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure: cardiovascular system | kidney/urinary tract | liver | nervous system | respiratory system | sensory organs.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapours, dust, or spray. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and respiratory protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or doctor if you feel unwell. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Toluene	108-88-3	15 - 40 Trade Secret *	No Data Available
Acetone	67-64-1	10 - 30 Trade Secret *	2-Propanone
Petroleum Distillates	64741-84-0	10 - 30 Trade Secret *	Naphtha, petroleum, solvent-refined light a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approximately 35.degree.C to 190.degree.C
Magnesium Resinate	68037-42-3	10 - 20	Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol, magnesium oxide complex
Polychloroprene	9010-98-4	10 - 20	1,3-Butadiene, 2-chloro-, homopolymer
p-tert-Butylphenol- Formaldehyde Resin	25085-50-1	10 - 15	Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol
Hexane	110-54-3	5 - 13 Trade Secret *	Hexane
2-Methylpentane	107-83-5	1 - 5 Trade Secret *	Pentane, 2-methyl-
3-Methylpentane	96-14-0	1 - 5 Trade Secret *	Pentane, 3-methyl-
Glycerol Esters of Rosin Acids	8050-31-5	1 - 5	Resin acids and Rosin acids, esters with glycerol
Heptane	142-82-5	1 - 5 Trade Secret *	Heptane
Methylcyclopentane	96-37-7	1 - 5 Trade Secret *	Cyclopentane, methyl-
Cyclohexane	110-82-7	< 2.1	Cyclohexane
Rosin	8050-09-7	< 1	Rosin
Styrenated Phenol	61788-44-1	0.1 - 1 Trade Secret *	Phenol, styrenated
Zinc Oxide	1314-13-2	< 1	Zinc oxide (ZnO)
Ethylbenzene	100-41-4	< 0.4	Benzene, ethyl-
Methyl Alcohol	67-56-1	< 0.2	Methanol

^{*}The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	Condition
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

5.4. Special protection actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable

local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
2-Methylpentane	107-83-5	ACGIH	TWA: 200 ppm	
Toluene	108-88-3	ACGIH	TWA:20 ppm	
Hexane	110-54-3	ACGIH	H TWA:50 ppm Danger of cutane absorption	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m3;STEL(respirable fraction):10 mg/m3	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm Danger of cutaneou absorption	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	
Rosin	8050-09-7	ACGIH	TWA(as Resin, inhalable fraction):0.001 mg/m3 Dermal/Respiratory Sensitizer	
3-Methylpentane	96-14-0	ACGIH	TWA: 200 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

coe general analysis ventuation and or local estimates ventuation to control ancome especiates to obtain the estimate estimates

Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Colour	Tan	
Odour	Mild Solvent	
Odour threshold	No Data Available	
pH	Not Applicable	
Melting point/Freezing point	Not Applicable	
Boiling point	>=56 °C [Details: Acetone]	
Flash Point	-26 °C [Test Method:Closed Cup] [Details:Petroleum Distillate]	
Evaporation rate	>=2.5 [<i>Ref Std</i> :ETHER=1]	
Flammability	Flammable Liquid: Category 2.	
Flammable Limits(LEL)	1 % volume	
Flammable Limits(UEL)	12.8 % volume	
Vapour Pressure	<=24,664.6 Pa [@ 20 °C]	
Relative Vapour Density	2 [Ref Std:AIR=1]	
Density	0.86 g/ml	

Relative density	0.86 [Ref Std:WATER=1]			
Water solubility	Slight (less than 10%)			
Solubility- non-water	No Data Available			
Partition coefficient: n-octanol/ water	No Data Available			
Autoignition temperature	465 °C			
Decomposition temperature	No Data Available			
Kinematic Viscosity	1,395 mm2/sec			
Volatile Organic Compounds	No Data Available			
Percent volatile	No Data Available			
VOC Less H2O & Exempt Solvents	<=600 g/l [Test Method:calculated SCAQMD rule 443.1]			
Molecular weight	No Data Available			
Solids Content	20 - 45 %			

Particle Characteristics	Not Applicable
Particle Characteristics	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance
None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy. Olfactory Effects: Signs/symptoms may include decreased ability to detect odours and/or complete loss of smell. Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

The Hazardous Substance Assessment for toluene published by Health Canada concludes that toluene also causes target organ toxicity through prolonged or repeated exposure to the cardiovascular system (heart), respiratory system (lung), kidney, and liver. Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure. Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination. Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l

Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
T. 1	hours)	D 4	LD50 5 550 //
Toluene Petroleum Distillates	Ingestion Dermal	Rat Rat	LD50 5,550 mg/kg LD50 > 2,800 mg/kg
Petroleum Distillates	Inhalation-	Rat	LC50 > 25.2 mg/l
Tetroleum Distinutes	Vapor (4	Rut	EC30 > 23.2 mg/1
	hours)		
Petroleum Distillates	Ingestion	Rat	LD50 > 5,840 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation- Vapor (4	Rat	LC50 76 mg/l
	hours)		
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-	Rat	LC50 170 mg/l
	Vapor (4		
**	hours)	70.	X D 50 . 20 500
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Dermal		, e e
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
p-tert-Butylphenol-Formaldehyde Resin	Dermal		LD50 estimated to be > 5,000 mg/kg
p-tert-Butylphenol-Formaldehyde Resin	Ingestion	Rat	LD50 5,660 mg/kg
Magnesium Resinate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Resinate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Heptane	Dermal	similar	LD50 > 2,000 mg/kg
		compoun	
Heptane	Inhalation-	ds similar	LC50 > 33.5 mg/l
rieptane	Vapor (4	compoun	LC30 > 33.3 High
	hours)	ds	
Heptane	Ingestion	similar	LD50 > 5,000 mg/kg
		compoun	
	× 1 1 2	ds	X G50 - 252 - 4
Methylcyclopentane	Inhalation- Vapor (4	Rat	LC50 > 25.3 mg/l
	hours)		
Methylcyclopentane	Ingestion	Rat	LD50 > 5,000 mg/kg
Methylcyclopentane	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
		health	, , ,
		hazards	
2-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Inhalation-		LC50 estimated to be > 50 mg/l
2 Matheda antona	Vapor		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Ingestion		, , ,
3-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Inhalation-		LC50 estimated to be > 50 mg/l
2 Mathylpantana	Vapor	1	LD50 astimated to be > 5.000 mg/l
3-Methylpentane	Ingestion	D-11'	LD50 estimated to be > 5,000 mg/kg
Glycerol Esters of Rosin Acids Glycerol Esters of Rosin Acids	Dermal Ingestion	Rabbit	LD50 > 5,000 mg/kg
Cyclohexane	Dermal	Rat Rat	LD50 > 2,000 mg/kg LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-	Rat	LC50 > 32.9 mg/l
C _J C.O. Committee	Vapor (4	1 cut	2009 - 52.7 mg i
	hours)		
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-	Rat	LC50 > 5.7 mg/l
	Dust/Mist		
7. 0.1	(4 hours)	D 4	LD50 > 5 000 //
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg

Page: 9 of 19

Rosin	Ingestion	Rat	LD50 7,600 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapor (4		
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Styrenated Phenol	Dermal	Rat	LD50 > 2,000 mg/kg
Styrenated Phenol	Ingestion	Rat	LD50 > 2,000 mg/kg
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-		LC50 estimated to be 10 - 20 mg/l
	Vapor		
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Toluene	Rabbit	Irritant
Petroleum Distillates	Rabbit	Irritant
Acetone	Mouse	Minimal irritation
Hexane	Human	Mild irritant
	and	
	animal	
Polychloroprene	Human	No significant irritation
Heptane	Professio	Mild irritant
	nal	
	judgeme	
	nt	
Methylcyclopentane	Rabbit	No significant irritation
2-Methylpentane	Professio	Mild irritant
	nal	
	judgeme	
	nt	
3-Methylpentane	Professio	Mild irritant
	nal	
	judgeme	
Cl. IF (CD ' A 'I	nt	NC : 1: 2: 2:
Glycerol Esters of Rosin Acids	Rabbit	Minimal irritation
Cyclohexane	Rabbit	Mild irritant
Zinc Oxide	Human	No significant irritation
	and	
n ·	animal	N
Rosin	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
Styrenated Phenol	Rabbit	No significant irritation
Methyl Alcohol	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Toluene	Rabbit	Moderate irritant
Petroleum Distillates	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Hexane	Rabbit	Mild irritant
Polychloroprene	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Heptane	similar	Mild irritant
	compoun	
	ds	
Methylcyclopentane	Rabbit	Mild irritant
2-Methylpentane	Professio	Moderate irritant
	nal	

Page: 10 of 19

	judgeme nt	
3-Methylpentane	Professio	Moderate irritant
	nal	
	judgeme	
	nt	
Glycerol Esters of Rosin Acids	Rabbit	Mild irritant
Cyclohexane	Rabbit	Mild irritant
Zinc Oxide	Rabbit	Mild irritant
Rosin	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Styrenated Phenol	Rabbit	Mild irritant
Methyl Alcohol	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Toluene	Guinea	Not classified
	pig	
Petroleum Distillates	Guinea	Not classified
	pig	
Hexane	Human	Not classified
p-tert-Butylphenol-Formaldehyde Resin	Human	Some positive data exist, but the data are not
		sufficient for classification
Heptane	similar	Not classified
	compoun	
	ds	
Methylcyclopentane	similar	Not classified
	compoun	
	ds	
Glycerol Esters of Rosin Acids	Guinea	Not classified
	pig	
Zinc Oxide	Guinea	Not classified
	pig	
Rosin	Guinea	Sensitizing
	pig	
Ethylbenzene	Human	Not classified
Styrenated Phenol	Mouse	Sensitizing
Methyl Alcohol	Guinea	Not classified
	pig	

Respiratory Sensitization

Name	Species	Value
Rosin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value		
Toluene	In Vitro	Not mutagenic		
Toluene	In vivo	Not mutagenic		
Acetone	In vivo	Not mutagenic		
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Hexane	In Vitro	Not mutagenic		
Hexane	In vivo	Not mutagenic		
Heptane	In Vitro	Not mutagenic		
Methylcyclopentane	In vivo	Not mutagenic		
Methylcyclopentane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Glycerol Esters of Rosin Acids	In Vitro	Not mutagenic		
Cyclohexane	In Vitro	Not mutagenic		
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification		
Zinc Oxide	In Vitro	Some positive data exist, but the data are not		

Page: 11 of 19

		sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not
		sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Petroleum Distillates	Ingestion	Toxic to male reproduction	similar compoun ds	NOAEL not available	not available
Petroleum Distillates	Inhalation	Toxic to male reproduction	similar compoun ds	NOAEL not available	not available
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesi s
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesi s
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24	2 generation

				mg/l	
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
Methyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesi s
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	not available
Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	not available
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Methylcyclopentane	Inhalation	central nervous	May cause drowsiness or	Rat	NOAEL Not	

		system depression	dizziness		available	
Methylcyclopentane	Ingestion	central nervous	May cause drowsiness or	Rat	NOAEL Not	
Wiethyleyelopentane	Ingestion	system depression	dizziness	Kat	available	
2-Methylpentane	Inhalation	central nervous	May cause drowsiness or	Professio	NOAEL Not	
2-iviciny ipentane	Illiaiation	system depression	dizziness	nal	available	
		system depression	dizziness	judgeme	avanaoie	
				nt		
2-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
J 1			data are not sufficient for		available	
			classification			
2-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not	
• •					available	
2-Methylpentane	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	
- 1		system depression	dizziness	nal	available	
				judgeme		
				nt		
3-Methylpentane	Inhalation	central nervous	May cause drowsiness or	Professio	NOAEL Not	
		system depression	dizziness	nal	available	
				judgeme		
				nt		
3-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
			data are not sufficient for		available	
			classification			
3-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not	
					available	
3-Methylpentane	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	
		system depression	dizziness	nal	available	
				judgeme		
				nt		
Cyclohexane	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness	and	available	
				animal		
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for	and	available	
			classification	animal		
Cyclohexane	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	
		system depression	dizziness	nal	available	
				judgeme		
				nt		
Ethylbenzene	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness		available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for	and	available	
T-4 II	T .:	. 1	classification	animal	NOAFLN	ļ
Ethylbenzene	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	1
		system depression	dizziness	nal	available	1
				judgeme		
Mathyl Alach-1	Ind -1-4:-	hlindnaga	Causas damaga to our	nt	NOAEL NE	a a a um a ti 1
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not	occupational
Methyl Alcohol	Inhalatian	central nervous	May cause drowsiness or	Цител	available NOAEL Not	exposure not available
wiculyi Alcollol	Inhalation	system depression	dizziness	Human	available	not available
Mathyl Alachal	Inhalatian		Some positive data exist, but the	Dot	NOAEL Not	6 hours
Methyl Alcohol	Inhalation	respiratory irritation	data are not sufficient for	Rat	available	6 hours
			classification		avanable	
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not	poisoning
iviculyi Alcollol	mgestion	omiuness	Causes damage to organs	Tiuman	available	and/or abuse
Methyl Alcohol	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
Mentyl Alcohol	mgestion	system depression	dizziness	Tiuman	available	and/or abuse
		system depression	UIZZIIICSS	1	avanable	anu/or abuse

specific Target Organ Toxicity - repeated exposure								
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration		
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse		

Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Petroleum Distillates	Inhalation	peripheral nervous system	May cause damage to organs though prolonged or repeated exposure	similar compoun ds	NOAEL not available	not available
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Hexane	Inhalation	peripheral nervous	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Page: 15 of 19

Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Heptane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
Heptane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
Heptane	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Methylcyclopentane	Inhalation	liver kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system vascular system system	Not classified	Rat	NOAEL 20.2 mg/l	13 weeks
Methylcyclopentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL 800 mg/kg/day	8 weeks
Methylcyclopentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	4 weeks
2-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg/day	28 days
3-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
3-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
3-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg/day	28 days
Glycerol Esters of Rosin Acids	Ingestion	liver heart skin endocrine system bone, teeth, nails, and/or hair blood bone marrow hematopoietic system immune	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days

	1	T	1	1	1	1
		system muscles				
		nervous system				
		eyes kidney and/or				
		bladder respiratory				
Caralahanana	T114i	system liver	N-4 -1:£1	D-4	NOAEL 24	00 4
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7	90 days
0.11	X 1 1 .:	1:1 1/	N 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	D 113	mg/l NOAEL 2.7	10 1
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic	Not classified	Mouse	NOAEL 24	14 weeks
•		system			mg/l	
Cyclohexane	Inhalation	peripheral nervous	Not classified	Rat	NOAEL 8.6	30 weeks
-		system			mg/l	
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600	10 days
					mg/kg/day	
Zinc Oxide	Ingestion	endocrine system	Not classified	Other	NOAEL 500	6 months
		hematopoietic			mg/kg/day	
		system kidney				
		and/or bladder				
Ethylbenzene	Inhalation	kidney and/or	Some positive data exist, but the	Rat	NOAEL 1.1	2 years
-		bladder	data are not sufficient for		mg/l	
			classification			
Ethylbenzene	Inhalation	liver	Some positive data exist, but the	Mouse	NOAEL 1.1	103 weeks
			data are not sufficient for		mg/l	
			classification			
Ethylbenzene	Inhalation	hematopoietic	Not classified	Rat	NOAEL 3.4	28 days
		system			mg/l	
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4	5 days
					mg/l	
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3	103 weeks
					mg/l	
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3	2 years
					mg/l	
Ethylbenzene	Inhalation	bone, teeth, nails,	Not classified	Multiple	NOAEL 4.2	90 days
		and/or hair		animal	mg/l	
		muscles		species		
Ethylbenzene	Inhalation	heart immune	Not classified	Multiple	NOAEL 3.3	2 years
		system respiratory		animal	mg/l	
		system		species	_	
Ethylbenzene	Ingestion	liver kidney and/or	Not classified	Rat	NOAEL 680	6 months
		bladder			mg/kg/day	
Methyl Alcohol	Inhalation	liver	Not classified	Rat	NOAEL 6.55	4 weeks
					mg/l	
Methyl Alcohol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1	6 weeks
					mg/l	
Methyl Alcohol	Ingestion	liver nervous	Not classified	Rat	NOAEL	90 days
	_	system		1	2,500	
				1	mg/kg/day	1

The Hazardous Substance Assessment for toluene published by Health Canada concludes that toluene also causes adverse effects to the cardiovascular system (heart), respiratory system (lung), kidney, and liver following repeated chronic inhalation exposure to humans.

Asniration Hazard

Aspiration Hazard				
Name	Value			
Toluene	Aspiration hazard			
Petroleum Distillates	Aspiration hazard			
Hexane	Aspiration hazard			
Heptane	Aspiration hazard			
Methylcyclopentane	Aspiration hazard			
2-Methylpentane	Aspiration hazard			
3-Methylpentane	Aspiration hazard			
Cyclohexane	Aspiration hazard			
Ethylbenzene	Aspiration hazard			

Page: 17 of 19

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

Page: 18 of 19

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	10-2796-0	Version number:	15.01
Issue Date:	2025/06/23	Supercedes Date:	2023/06/21

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 19 of 19