Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	11-3307-3	**Version number:**	37.00
Issue Date:	2026/10/08	**Supersedes Date:**	2025/08/07

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Structural Adhesive Film AF 191

Product Identification Numbers

LA-T100-2677-4	62-0199-5305-8	62-0199-5306-6	62-0199-5309-0	62-2608-5301-5
62-2608-5305-6	62-2608-5309-8	62-2638-5301-2	62-2638-5309-5	62-2707-5306-4
62-2707-5309-8	62-3053-2005-3	62-3053-5305-4	62-3053-5306-2	62-3053-5309-6
62-3068-3905-1	62-3068-4105-7	62-3068-4905-0	62-3068-6005-7	62-3068-6006-5
62-3068-6008-1	62-3072-2500-3	62-3072-3905-3	62-3072-4505-0	62-3072-5305-4
62-3072-5306-2	62-3072-5307-0	62-3072-5309-6	62-3072-5338-5	62-3142-3505-2
62-3142-3705-8	62-3142-3906-2	62-3142-5304-8	62-3142-5305-5	62-3142-5306-3
62-3142-5307-1	62-3142-5308-9	62-3142-5309-7	62-3142-6005-0	62-3142-6038-1
62-3151-3903-0	62-3151-5305-6	62-3151-5306-4	62-3151-5309-8	62-3167-3905-1
62-3172-3906-9	62-3172-5305-2	62-3172-5309-4	62-3329-5305-8	62-3329-5306-6
62-3329-5307-4	62-3329-5308-2	62-3329-5309-0	62-3384-5305-3	62-3384-5308-7
62-3384-5309-5	70-0718-0658-5	87-2500-0180-4	87-2500-0216-6	87-2500-0218-2
87-3300-0016-4	87-3300-0118-8	87-3300-0159-2	87-3300-0160-0	87-3300-0517-1
87-3300-0518-9	87-3300-0519-7	87-3300-0534-6	87-3300-0535-3	87-3300-0536-1
87-3300-0537-9	87-3300-0538-7	87-3300-0539-5	87-3300-0540-3	87-3300-0541-1
87-3300-0542-9	87-3300-0553-6	87-3300-0554-4	87-3300-0555-1	87-3300-0556-9
87-3300-0557-7	87-3300-0558-5	87-3300-0559-3	87-3300-0560-1	87-3300-0561-9
98-0404-0482-8	HB-0040-7180-7	HB-0044-7305-2	XT-0615-5013-0	

1.2. Recommended use and restrictions on use

Intended Use

Structural Adhesive Film

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Automotive and Aerospace Solutions Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Acute Toxicity (oral): Category 4.
Germ Cell Mutagenicity: Category 2.
Reproductive Toxicity: Category 1B.
Reproductive Toxicity: Lactation.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark |Health Hazard |

Pictograms



Hazard Statements

Harmful if swallowed. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause harm to breast-fed children.
Causes damage to organs: blood or blood-forming organs | liver.

Causes damage to organs through prolonged or repeated exposure: blood or blood-forming organs | liver.
May cause damage to organs through prolonged or repeated exposure: nervous system.

Precautionary statements

Prevention:
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours or dust. Avoid contact during pregnancy and while nursing. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Response:
IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. Specific treatment (see Notes to Physician on this label). Rinse mouth.

Storage:
Store locked up.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Notes to Physician:

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be consider as part of the medical management

2.3. Other hazards
None known.

50% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Alkyl/ Diamine/ Phenolic Epoxy reaction product	Trade Secret	40 - 60	Not Applicable
Epoxy Resin B	28768-32-3	20 - 40 Trade Secret *	Oxiranemethanamine, N,N'-(methylenedi-4,1-phenylene)bis[N-(oxiranylmethyl)-
Epoxy Resin A	63738-22-7	10 - 20 Trade Secret *	1,3-Benzenedimethanamine, N,N,N',N'-tetrakis(oxiranylmethyl)-
p,p'-Diaminodiphenyl Sulfone	80-08-0	3 - 7 Trade Secret *	Benzenamine, 4,4'-sulfonylbis-

Alkyl/ Diamine/ Phenolic Epoxy reaction product is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

5.4. Special protection actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
p,p'-Diaminodiphenyl Sulfone	80-08-0	Manufacturer determined	TWA:0.1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Chemical Protective glove of any material type

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Film
Colour	White
Odour	Odourless
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*No Data Available*
Boiling point	*Not Applicable*
Flash Point	No flash point
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapour Pressure	*No Data Available*
Relative Vapour Density	*No Data Available*
Density	1.26 g/cm3
Relative density	*No Data Available*
Water solubility	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*Not Applicable*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*Not Applicable*
Volatile Organic Compounds	*No Data Available*
Percent volatile	<= 1.3 % weight [*Test Method:*Estimated]
VOC Less H2O & Exempt Solvents	*No Data Available*
Molecular weight	*No Data Available*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	**Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
Harmful if swallowed. Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalized weakness. Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Prolonged or repeated exposure may cause target organ effects:
Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia. Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Contains a chemical or chemicals which may interfere with lactation or be harmful to breastfed children.

Genotoxicity:
Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Epoxy Resin B	Dermal	Rabbit	LD50 > 3,000 mg/kg
Epoxy Resin B	Ingestion	Rat	LD50 > 5,000 mg/kg
Epoxy Resin A	Ingestion	Rat	LD50 630 mg/kg
p,p'-Diaminodiphenyl Sulfone	Ingestion	Professional judgement	LD50 250 mg/kg
p,p'-Diaminodiphenyl Sulfone	Dermal	Rabbit	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Multiple animal species	No significant irritation
Epoxy Resin B	Rabbit	No significant irritation
Epoxy Resin A	Rabbit	Irritant
p,p'-Diaminodiphenyl Sulfone	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin B	Rabbit	Mild irritant
Epoxy Resin A	In vitro data	No significant irritation
p,p'-Diaminodiphenyl Sulfone	In vitro data	No significant irritation

Skin Sensitization

Name	Species	Value
Overall product	Guinea pig	Not classified
Epoxy Resin B	Human and animal	Sensitizing
Epoxy Resin A	Professional judgement	Sensitizing
p,p'-Diaminodiphenyl Sulfone	Mouse	Not classified

Respiratory Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Epoxy Resin B	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin B	In vivo	Mutagenic
Epoxy Resin A	In Vitro	Some positive data exist, but the data are not sufficient for classification

p,p'-Diaminodiphenyl Sulfone	In vivo	Not mutagenic
p,p'-Diaminodiphenyl Sulfone	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
p,p'-Diaminodiphenyl Sulfone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Epoxy Resin B	Ingestion	Not classified for development	Rat	NOAEL 90 mg/kg/day	during gestation
p,p'-Diaminodiphenyl Sulfone	Ingestion	Not classified for female reproduction	Rat	NOAEL 30 mg/kg/day	2 generation
p,p'-Diaminodiphenyl Sulfone	Ingestion	Not classified for development	Mouse	NOAEL 100 mg/kg/day	during organogenesis
p,p'-Diaminodiphenyl Sulfone	Ingestion	Toxic to male reproduction	Rat	LOAEL 7.5 mg/kg/day	2 generation

Lactation

Name	Route	Species	Value
p,p'-Diaminodiphenyl Sulfone	Ingestion	Human	Causes effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin A	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
p,p'-Diaminodiphenyl Sulfone	Ingestion	blood | methemoglobinemia | liver	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
p,p'-Diaminodiphenyl Sulfone	Ingestion	central nervous system depression	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin B	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	liver	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	immune system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	nervous system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	eyes	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Epoxy Resin B	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
p,p'-Diaminodiphenyl Sulfone	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	not available

p,p'-Diaminodiphenyl Sulfone	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	not available
p,p'-Diaminodiphenyl Sulfone	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
p,p'-Diaminodiphenyl Sulfone	Ingestion	immune system	Not classified	Mouse	NOAEL 54 mg/kg/day	30 days
p,p'-Diaminodiphenyl Sulfone	Ingestion	heart	Not classified	Human	NOAEL Not available	not available
p,p'-Diaminodiphenyl Sulfone	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
p,p'-Diaminodiphenyl Sulfone	Ingestion	vascular system	Not classified	Human	NOAEL Not available	not available
p,p'-Diaminodiphenyl Sulfone	Ingestion	endocrine system	Not classified	Rat	NOAEL 100 mg/kg/day	90 days
p,p'-Diaminodiphenyl Sulfone	Ingestion	eyes	Not classified	Rat	NOAEL 100 mg/kg/day	90 days

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain

restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	11-3307-3	**Version number:**	37.00
Issue Date:	2026/10/08	**Supersedes Date:**	2025/08/07

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca