Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	36-8937-9	**Version number:**	15.00
Revision date:	29/05/2026	**Supersedes date:**	23/02/2026

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M 51815, 51816, 51818, 51815G Fast Cut Plus Extreme

Product Identification Numbers

UU-0089-7239-8	UU-0089-7240-6	UU-0089-7282-8	UU-0095-4165-5	UU-0110-6066-0
7100136343	7100136486	7100136485	7100169681	7100231952

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Automotive.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.
Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	Identifier(s)	EC No.	% by Wt
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		919-446-0	3 - 7
1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	< 0.05

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260G	Do not breathe vapours or dust.
P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066	Repeated exposure may cause skin dryness or cracking.

4% of the mixture consists of components of unknown acute oral toxicity.

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	25 - 30	Substance not classified as hazardous
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6 (REACH-No.) 01-2119529248-35	20 - 25	Substance with a national occupational exposure limit
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01-2119456620-43	< 12	Asp. Tox. 1, H304 EUH066
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8 (REACH-No.) 01-2119487078-27	< 10	Asp. Tox. 1, H304
Glycerol	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	3 - 7	Substance with a national occupational exposure limit
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC-No.) 919-446-0 (REACH-No.) 01-2119458049-33	3 - 7	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 STOT RE 1, H372
Sorbitan monooleate, ethoxylated	(CAS-No.) 9005-65-6	< 5	Substance not classified as hazardous
CASTOR OIL BASED PRODUCT AND WATER	Trade Secret	< 3	Substance not classified as hazardous
Synthetic amorphous silica, fumed, crystalline-free	(CAS-No.) 112945-52-5	< 3	Substance with a national occupational exposure limit
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	(EC-No.) 920-114-2 (REACH-No.) 01-2119459347-30	< 3	Asp. Tox. 1, H304 EUH066
Hydrocarbons, C10 aromatics, <1% naphthalene	(EC-No.) 918-811-1 (REACH-No.) 01-2119463583-34	< 3	Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 Aquatic Chronic 2, H411

Alcohols, C16-18 and C18-unsatd.	(CAS-No.) 68002-94-8 (EC-No.) 268-106-1	< 2	Substance not classified as hazardous
TERPINEOL	(CAS-No.) 8000-41-7 (EC-No.) 232-268-1	< 0.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361f
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.05	Acute Tox. 2, H330(LC50 = 0.21 mg/l ATE values per Annex VI) Acute Tox. 4, H302(LD50 = 450 mg/kg ATE values per Annex VI) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.036%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching). Dermal defatting (localized redness, itching, drying and cracking of skin). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial/occupational use only. Not for consumer sale or use. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat,

drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators…) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from oxidising agents.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
Silica, amorphous	112945-52-5	Ireland OELs	TWA(Total inhalable dust)(8 hours):6 mg/m3;TWA(as respirable dust)(8 hours):2.4 mg/m3	
Aluminium oxide	1344-28-1	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4 mg/m3	
Dusts non-specific	56-81-5	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4 mg/m3	
Mineral oil Pure, Highly & Severely Refined	8042-47-5	Ireland OELs	TWA(inhalable fraction)(8 hours):5 mg/m3	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards
Use eye protection conforming to EN 16321

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Nitrile rubber.	0.4	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls
Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Emulsion
Colour	White
Odor	Oily, Pine
Odour threshold	*No data available.*
Melting point/freezing point	*Not applicable.*
Boiling point/boiling range	*No data available.*
Flammability	Not applicable.

Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Flash point	>=100 ºC [*Test Method:*Closed Cup]
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	7.5 - 9 Units not available or not applicable. [*Details:*@20 C (+/-1 C)]
Kinematic Viscosity	17,319 - 60,870 mm²/sec
Water solubility	*No data available.*
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*No data available.*
Density	1.15 g/cm3 [@ 20 ºC]
Relative density	1.15 [*Ref Std:*WATER=1]
Relative Vapour Density	*No data available.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*Not applicable.*
Percent volatile	20 %

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
High shear and high temperature conditions
Sparks and/or flames.

10.5 Incompatible materials
Alkali and alkaline earth metals.
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain. May cause additional health effects (see below).

Skin contact
Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%	Dermal	similar	LD50 > 5,000 mg/kg

aromatics		compounds	
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation-Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
Glycerol	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerol	Ingestion	Rat	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Dermal	Not available	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
Sorbitan monooleate, ethoxylated	Ingestion	Rat	LD50 20,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C10 aromatics, <1% naphthalene	Ingestion	Rat	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
TERPINEOL	Dermal	Rat	LD50 > 2,000 mg/kg
TERPINEOL	Ingestion	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.21 mg/l
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 450 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminium oxide	Rabbit	No significant irritation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	Minimal irritation
Glycerol	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Minimal irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	No significant irritation
TERPINEOL	Rabbit	Irritant
1,2-benzisothiazol-3(2H)-one	Human	Irritant

Serious Eye Damage/Irritation

Name	Species	Value

Aluminium oxide	Rabbit	No significant irritation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
Sorbitan monooleate, ethoxylated	Rabbit	No significant irritation
Hydrocarbons, C10 aromatics, <1% naphthalene	Rabbit	Mild irritant
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
TERPINEOL	Rabbit	Moderate irritant
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	similar compounds	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Guinea pig	Not classified
Glycerol	Guinea pig	Not classified
Sorbitan monooleate, ethoxylated	Guinea pig	Not classified
Hydrocarbons, C10 aromatics, <1% naphthalene	Guinea pig	Not classified
Synthetic amorphous silica, fumed, crystalline-free	Human and animal	Not classified
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
TERPINEOL	Guinea pig	Not classified
1,2-benzisothiazol-3(2H)-one	Human	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminium oxide	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Sorbitan monooleate, ethoxylated	In Vitro	Not mutagenic
Hydrocarbons, C10 aromatics, <1% naphthalene	In Vitro	Not mutagenic
Hydrocarbons, C10 aromatics, <1% naphthalene	In vivo	Not mutagenic
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
TERPINEOL	In Vitro	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic

White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Glycerol	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Sorbitan monooleate, ethoxylated	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Glycerol	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Sorbitan monooleate, ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C10 aromatics, <1% naphthalene	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	gestation into lactation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
TERPINEOL	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	premating into lactation
TERPINEOL	Ingestion	Not classified for development	Rat	NOAEL 250 mg/kg	premating into lactation
TERPINEOL	Ingestion	Toxic to male reproduction	Rat	NOAEL 250 mg/kg/day	5 weeks

1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
Hydrocarbons, C10 aromatics, <1% naphthalene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
TERPINEOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available.	
1,2-benzisothiazol-3(2H)-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	hematopoietic system | eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver | immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure

Glycerol	Inhalation	respiratory system | heart | liver | kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerol	Ingestion	endocrine system | hematopoietic system | liver | kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Sorbitan monooleate, ethoxylated	Ingestion	heart | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | hematopoietic system | liver | immune system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 4,132 mg/kg/day	90 days
Synthetic amorphous silica, fumed, crystalline-free	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
TERPINEOL	Ingestion	liver | kidney and/or bladder | hematopoietic system | nervous system	Not classified	Rat	NOAEL 750 mg/kg/day	5 weeks
1,2-benzisothiazol-3(2H)-one	Ingestion	liver | hematopoietic system | eyes | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)-one	Ingestion	heart | endocrine system | nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Aspiration hazard
Hydrocarbons, C10 aromatics, <1% naphthalene	Aspiration hazard
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Glycerol	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerol	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Glycerol	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Green algae	Experimental	72 hours	EL50	4.1 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Rainbow trout	Experimental	96 hours	LL50	30 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Water flea	Experimental	48 hours	EL50	22 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Green algae	Experimental	72 hours	NOEL	0.76 mg/l
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Water flea	Experimental	21 days	EL10	0.316 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green algae	Analogous Compound	72 hours	EL50	58.84 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Zebra Fish	Analogous Compound	96 hours	LL50	>100 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green algae	Analogous Compound	72 hours	EL10	19.05 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Water flea	Analogous Compound	21 days	NOEL	10 mg/l

Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Green algae	Estimated	72 hours	EL50	3 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Rainbow trout	Estimated	96 hours	LL50	5 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Water flea	Estimated	48 hours	EL50	10 mg/l
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Green algae	Estimated	72 hours	NOEL	1 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Fish	Estimated	96 hours	LL50	>1,028 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Water flea	Estimated	21 days	NOEL	5 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Green algae	Analogous Compound	72 hours	ErC50	>173.1 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Sediment organism	Analogous Compound	96 hours	EC50	8,500 mg/kg (Dry Weight)
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Water flea	Analogous Compound	24 hours	EL50	>10,000 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Zebra Fish	Analogous Compound	96 hours	LL50	>10,000 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Green algae	Analogous Compound	72 hours	NOEC	173.1 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Water flea	Analogous Compound	21 days	NOEC	68 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Algae or other aquatic plants	Experimental	N/A	No tox obs at lmt of water sol	>100 mg/l
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Bacteria	Experimental	30 minutes	EC10	>10,000 mg/l
TERPINEOL	8000-41-7	Green algae	Experimental	72 hours	ErC50	68 mg/l
TERPINEOL	8000-41-7	Water flea	Experimental	48 hours	LC50	73 mg/l
TERPINEOL	8000-41-7	Zebra Fish	Experimental	96 hours	LC50	62 mg/l
TERPINEOL	8000-41-7	Green algae	Experimental	72 hours	NOEC	3.9 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	ErC50	0.11 mg/l

1,2-benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Sheepshead Minnow	Experimental	96 hours	LC50	16.7 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Activated sludge	Experimental	3 hours	EC50	12.8 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight
1,2-benzisothiazol-3(2H)-one	2634-33-5	Cabbage	Experimental	14 days	EC50	200 mg/kg (Dry Weight)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Redworm	Experimental	14 days	LC50	>410.6 mg/kg (Dry Weight)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Soil microbes	Experimental	28 days	EC50	>811.5 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
Aluminium oxide	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 %BOD/ThOD	OECD 301F - Manometric respirometry
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Glycerol	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Analogous Compound Biodegradation	28 days	BOD	74.7 %BOD/ThOD	OECD 301F - Manometric respirometry
Sorbitan monooleate, ethoxylated	9005-65-6	Experimental Biodegradation	28 days	CO2 evolution	61 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Experimental Biodegradation	28 days	BOD	49.6 %BOD/COD	OECD 301F - Manometric respirometry
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Estimated Biodegradation	28 days	BOD	82 %BOD/ThOD	OECD 301F - Manometric respirometry
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Experimental Biodegradation	28 days	BOD	87 %BOD/ThOD	EC C.4.E Closed Bottle Test
TERPINEOL	8000-41-7	Experimental Biodegradation	28 days	CO2 evolution	80 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Aquatic Inherent Biodegrad.	34 days	Dissolv. Organic Carbon Deplet	17 %removal of DOC	OECD 302A - Modified SCAS Test
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	80 %removal of DOC	OECD 303A - Simulated Aerobic
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation		Half-life (t 1/2)	4 hours (t 1/2)	
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Hydrolysis		Hydrolytic half-life	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol

Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol	56-81-5	Experimental Bioconcentration		Log Kow	-1.75	similar to OECD 107
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sorbitan monooleate, ethoxylated	9005-65-6	Modeled Bioconcentration		Bioaccumulation factor	5	Catalogic™
Sorbitan monooleate, ethoxylated	9005-65-6	Modeled Bioconcentration		Log Kow	5.61	Episuite™
Hydrocarbons, C10 aromatics, <1% naphthalene	918-811-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
TERPINEOL	8000-41-7	Experimental Bioconcentration		Log Kow	2.6	OECD 117 log Kow HPLC method
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental BCF - Fish	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
Glycerol	56-81-5	Modeled Mobility in Soil	Koc	<1 l/kg	Episuite™
Sorbitan monooleate, ethoxylated	9005-65-6	Modeled Mobility in Soil	Koc	810 l/kg	Episuite™
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Mobility in Soil	Koc	9.33 l/kg	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.

IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information.

DIRECTIVE 2012/18/EU
Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:
EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.
Professional Use of Coatings: Section 16: Annex information was modified.
Label: Graphic information was modified.
Section 8: glove data value information was added.
Section 8: glove data value information was modified.
Section 9: Vapour pressure value information was added.
Section 9: Vapour pressure value information was deleted.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.
Section 14 UN Number Column data information was deleted.
Section 14 UN Number information was deleted.

Annex

1. Title	
Substance identification	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; EC No. 926-141-6;
Exposure Scenario Name	Professional Use of Coatings
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Processes, tasks and activities covered	Application of product. (PROC 7,10,11,13)
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of exposure per day at workplace: 8 hours/day; Emission days (in days per year): 300 days per year; Frequency of exposure at workplace: Daily; Indoor use; Outdoor use;

Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** None needed; **Environmental:** None needed;
Waste management measures	Avoid release to the environment. Refer to special instructions / safety data sheet.;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com