

# Safety Data Sheet

Copyright, 2025, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 16-2711-6 **Version number:** 1.00

**Issue Date:** 27/10/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scuff-It<sup>TM</sup> Paint Prep Gel, PN 06013

### **Product Identification Numbers**

60-9800-4294-3

#### 1.2. Recommended use and restrictions on use

## Recommended use

Automotive., Preparation of automotive substrates prior to painting

## 1.3. Supplier's details

Address: 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100

**Telephone:** 080-45543000, contact Product EHS team

E Mail: productehs.in@mmm.com
Website: http://solutions.3mindia.co.in

# 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

## **SECTION 2: Hazard identification**

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

### 2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1B.

Acute Aquatic Toxicity: Category 2.

### 2.2. Label elements

### Signal Word

Warning

### **Symbols**

Exclamation mark |

### **Pictograms**



## **HAZARD STATEMENTS:**

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

### PRECAUTIONARY STATEMENTS

**Prevention:** 

P280E Wear protective gloves.

**Response:** 

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Wt	
Feldspars	68476-25-5	30 - 60	
Water	7732-18-5	15 - 40	
Quartz	14808-60-7	10 - 30	
Polyethylene Glycol	25322-68-3	3 - 7	
Glycerin	56-81-5	1 - 5	
(R)-p-mentha-1,8-diene	5989-27-5	1 - 5	
Ethoxylated C12-C15 Alcohols	68131-39-5	0.5 - 1.5	

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

Substance
Hydrocarbons.
Carbon monoxide.
Carbon dioxide.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Condition

During combustion.

During combustion.

During combustion.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use PPE - Exposure Assessment Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silica, crystalline, respirable	14808-60-7	ACGIH	TWA(respirable	A2: Suspected human
fraction			fraction):0.025 mg/m3	carcin.
Polyethylene Glycol	25322-68-3	AIHA	TWA:10 mg/m <sup>3</sup>	
(R)-p-mentha-1,8-diene	5989-27-5	AIHA	TWA:165.5 mg/m3(30 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile rubber., Polymer laminate, Polyvinyl alcohol (PVA).

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Specific Physical Form:	Paste	
Color	White	
Odor	Light Citrus	
Odour threshold	No data available.	
рН	8 Units not available or not applicable.	
Melting point/Freezing point: NA	No data available.	
Boiling point/Initial boiling point/Boiling range	>=100 °C	
Flash point	>=93.9 °C [Test Method:Closed Cup]	
Evaporation rate	No data available.	
Flammability	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	No data available.	
Relative Vapor Density	No data available.	
Density	1.55 g/ml	
Relative density	1.55 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Moderate	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Kinematic Viscosity	96,774 mm <sup>2</sup> /sec	
Volatile organic compounds (VOC)	2.1 % weight [Test Method:calculated per CARB title 2]	
Volatile organic compounds (VOC)	41 g/l [Test Method:calculated SCAQMD rule 443.1]	
Percent volatile	31.3 % weight	
VOC less H2O & exempt solvents	74 g/l [Test Method:calculated SCAQMD rule 443.1]	
Molecular weight	No data available.	
Solids content	60.73 % weight	
	-	

Particle Characteristics	Not applicable.
--------------------------	-----------------

# **SECTION 10: Stability and reactivity**

## **10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.4 Conditions to avoid

None known.

# 10.5 Incompatible materials

None known.

## 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Feldspars	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Feldspars	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg

D. . . . C . C . 1

## 3M<sup>TM</sup> Scuff-It<sup>TM</sup> Paint Prep Gel, PN 06013

(R)-p-mentha-1,8-diene	Inhalation-	Mouse	LC50 > 3.14  mg/l
	Vapor (4		
	hours)		
(R)-p-mentha-1,8-diene	Dermal	Rabbit	LD50 > 5,000 mg/kg
(R)-p-mentha-1,8-diene	Ingestion	Rat	LD50 4,400 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethoxylated C12-C15 Alcohols	Ingestion	similar	LD50 > 2,000 mg/kg
		compoun	
		ds	
Ethoxylated C12-C15 Alcohols	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
		health	
		hazards	

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
Feldspars	Professio nal judgemen t	No significant irritation
Quartz	Professio nal judgemen t	No significant irritation
Polyethylene Glycol	Rabbit	Minimal irritation
(R)-p-mentha-1,8-diene	Rabbit	Irritant
Glycerin	Rabbit	No significant irritation
Ethoxylated C12-C15 Alcohols	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Polyethylene Glycol	Rabbit	Mild irritant
(R)-p-mentha-1,8-diene	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
Ethoxylated C12-C15 Alcohols	similar	No significant irritation
	compoun	
	ds	

## **Sensitization:**

## **Skin Sensitisation**

Name	Species	Value
Polyethylene Glycol	Guinea pig	Not classified
(R)-p-mentha-1,8-diene	Mouse	Sensitising
Glycerin	Guinea pig	Not classified
Ethoxylated C12-C15 Alcohols	similar compoun ds	Not classified

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification

Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
(R)-p-mentha-1,8-diene	In Vitro	Not mutagenic
(R)-p-mentha-1,8-diene	In vivo	Not mutagenic
Ethoxylated C12-C15 Alcohols	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Quartz	Inhalation	Human	Carcinogenic.
		and	
		animal	
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
(R)-p-mentha-1,8-diene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration	
Polyethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation	
Polyethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days	
Polyethylene Glycol	Not specified.	Not classified for reproduction and/or development		NOEL N/A		
Polyethylene Glycol			Mouse	NOAEL 562 mg/animal/da y	during gestation	
(R)-p-mentha-1,8-diene	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	premating & during gestation	
(R)-p-mentha-1,8-diene	Ingestion	Not classified for development	Multiple animal species	NOAEL 591 mg/kg/day	during organogenesis	
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation	
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation	
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation	
Ethoxylated C12-C15 Alcohols	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation	
Ethoxylated C12-C15 Alcohols	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days	
Ethoxylated C12-C15 Alcohols	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation	

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polyethylene Glycol	Inhalation	respiratory irritation	Not classified	Rat	NOAEL	2 weeks

					1.008 mg/l	
(R)-p-mentha-1,8-diene	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
			data are not sufficient for		available	
			classification	hazards		
(R)-p-mentha-1,8-diene	Ingestion	nervous system	Not classified		NOAEL Not	
					available	
Ethoxylated C12-C15	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
Alcohols			data are not sufficient for	health	available.	
			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	Ingestion kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   nervous system		Rat	NOAEL 5,640 mg/kg/day	13 weeks
(R)-p-mentha-1,8-diene	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 75 mg/kg/day	103 weeks
(R)-p-mentha-1,8-diene	Ingestion	liver	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
(R)-p-mentha-1,8-diene	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	103 weeks
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Ethoxylated C12-C15 Alcohols	Ingestion	endocrine system   gastrointestinal tract   liver   kidney and/or bladder   hematopoietic system   nervous system   eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

**Aspiration Hazard** 

	Name	Value
П	(R)-p-mentha-1,8-diene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be

reflected in this section because an ingredient—is present below the threshold for labelling, an ingredient—is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

# 12.1. Toxicity

## Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

## **Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Feldspars	68476-25-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Quartz	14808-60-7	Green algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green algae	Estimated	72 hours	NOEC	60 mg/l
Polyethylene Glycol	25322-68-3	Activated sludge	Experimental	N/A	EC50	>1,000 mg/l
Polyethylene Glycol	25322-68-3	Atlantic Salmon	Experimental	96 hours	LC50	>1,000 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Fathead minnow	Experimental	96 hours	LC50	0.702 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Green algae	Experimental	72 hours	ErC50	0.32 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Water flea	Experimental	48 hours	EC50	0.307 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Fathead minnow	Experimental	8 days	EC10	0.32 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Green algae	Experimental	72 hours	ErC10	0.174 mg/l
(R)-p-mentha-1,8- diene	5989-27-5	Water flea	Experimental	21 days	NOEC	0.153 mg/l
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Glycerin	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Ethoxylated C12- C15 Alcohols	68131-39-5	Fish	Analogous Compound	96 hours	LC50	1 mg/l
Ethoxylated C12- C15 Alcohols	68131-39-5	Green algae	Analogous Compound	72 hours	ErC50	0.57 mg/l
Ethoxylated C12- C15 Alcohols	68131-39-5	Water flea	Analogous Compound	48 hours	LC50	0.1 mg/l
Ethoxylated C12- C15 Alcohols	68131-39-5	Green algae	Analogous Compound	72 hours	NOEC	0.035 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
F 11	60456.05.5		27/4	27/4	27/4	27/4
Feldspars	68476-25-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available- insufficient	N/A	N/A	N/A	N/A
Polyethylene	25322-68-3	Experimental	28 days	BOD	53 %BOD/ThOD	OECD 301C - MITI test (I)

Glycol		Biodegradation				
(R)-p-mentha-1,8-	5989-27-5	Experimental	14 days	BOD	98 %BOD/ThOD	OECD 301C - MITI test (I)
diene		Biodegradation				
(R)-p-mentha-1,8-	5989-27-5	Experimental	14 days	Dissolv. Organic	>93.8 %removal of	OECD 303A - Simulated
diene		Biodegradation		Carbon Deplet	DOC	Aerobic
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Ethoxylated C12- C15 Alcohols	68131-39-5	Analogous Compound Biodegradation	28 days		/	OECD 301B - Modified sturm or CO2

## 12.3: Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Feldspars	68476-25-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethylene Glycol	25322-68-3	Estimated Bioconcentration		Bioaccumulation factor	2.3	
(R)-p-mentha-1,8- diene	5989-27-5	Modeled Bioconcentration		Bioaccumulation factor	2100	Catalogic™
(R)-p-mentha-1,8- diene	5989-27-5	Experimental Bioconcentration		Log Kow	4.57	
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.75	similar to OECD 107
Ethoxylated C12- C15 Alcohols	68131-39-5	Modeled BCF - Fish		Bioaccumulation factor	470	Catalogic™
Ethoxylated C12- C15 Alcohols	68131-39-5	Experimental Bioconcentration		Log Kow	5.79	OECD 123 log Kow slow stir

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other Adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

Not hazardous for transportation.

Air Transport (IATA)Regulations

UN No Not applicable

Proper Shipping Name Not applicable

Hazard Classs/Division Not applicable

**Subsidiary Risk** Not applicable **Packing Group:** Not applicable

**Marine Transport (IMDG)** 

UN No Not applicable

Proper Shipping Name Not applicable Hazard Classs/Division Not applicable Subsidiary Risk Not applicable

Packing Group: Not applicable

Environmental Hazards: Not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

### Applicable Environmental, Health and Safety Regulations

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules None.

The following ingredients are classified as hazardous based on the criteria listed under Part I of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules:

The product is classified as Non-hazardous as per MSIHC Rules, 1989.

## **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **Revision information:**

No revision information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in

combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M India SDSs are available at http://solutions.3mindia.co.in