

# Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 10-2603-8
 Version Number:
 26.02

 Issue Date:
 12/19/25
 Supersedes Date:
 04/14/25

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Electrical Resin 265

### **Product Identification Numbers**

80-0002-4116-8, 80-6116-1173-4, 80-7002-6502-0, XA-0039-0018-1 7000006256, 7010319929, 7100269589, 7100378714

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Coating, Coating and Insulation for Electrical Components.

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Electrical Markets Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

## 2.1. Hazard classification

Skin Sensitizer: Category 1. Combustible Dust.

### 2.2. Label elements

### Signal word

Warning

### **Symbols**

Exclamation mark |

## **Pictograms**



#### **Hazard Statements**

May form combustible dust concentrations in air.

May cause an allergic skin reaction.

### **Precautionary statements**

### **Prevention:**

Avoid breathing vapors, dust, or spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves.

### **Response:**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

### Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL	25036-25-3	70 - 80
A COPOLYMER (MW>1200)		
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL	28064-14-4	10 - 30 Trade Secret *
ETHER		
DICYANDIAMIDE	461-58-5	1 - 5

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Powdered material may form explosive dust-air mixture. Avoid fire fighting methods that would cause powders to become airborne.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

### **5.3.** Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Eliminate all ignition sources if safe to do so. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Vacuum to avoid dusting. WARNING! A motor could be an ignition source and cause combustible dust in the spill area to burn or explode. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Dust clouds of this material in sufficient concentration in combination with an ignition source may be explosive. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions. Routine housekeeping should be instituted to ensure that combustible dusts do not accumulate on surfaces. Solids can generate static electricity charges when transferred and in mixing operations sufficient to be an ignition source. Evaluate the need for precautions, such as grounding and bonding, low energy transfer of material (e.g. low speed, short distance), or inert atmospheres.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. It is recommended that all dust control equipment (such as local exhaust ventilation), process equipment, and material transport systems involved in handling of this product be evaluated for the need for explosion-protection safeguards. Recognized safeguards include explosion relief vents, explosion suppression systems, and oxygen deficient process environments. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Evaluate the need for electrically classified equipment.

### 8.2.2. Personal protective equipment (PPE)

#### **Eve/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

**Indirect Vented Goggles** 

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

## **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical propert	ies
Physical state	Solid
Specific Physical Form:	Powder
Color	Off-White
Odor	Minimal Epoxy
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	Not Applicable
Flash Point	No flash point [Test Method: Estimated]
Evaporation rate	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	Not Applicable
Relative Vapor Density	Not Applicable
Density	1.16 g/ml
Relative Density	1.16 [ <i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	Not Applicable
Volatile Organic Compounds	0 %
Percent volatile	0 %
VOC Less H2O & Exempt Solvents	0 %
Molecular weight	No Data Available
*Dust deflagration index (Kst)	70 - 250 bar.m/s [Details: Typical Range]
*Min. explosible conc.(MEC)	35 - 55 g/m3 [Details:Typical Range]
*Min. ignition energy (MIE)	3 - 100 mJ [Details: Typical Range]
*Min. ign temp(MIT)-dust cloud	450 - 550 °C [Details: Typical Range]

<sup>\*</sup> The values noted with an asterisk (\*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further

Page 5 of 11 changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterization testing based on the use factors at the specific facility.

Particle Characteristics

Not Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Sparks and/or flames

### 10.5. Incompatible materials

Not determined

### 10.6. Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

#### **Ingestion:**

\_\_\_\_\_

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	Dermal	Rat	LD50 > 1,600 mg/kg
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	Ingestion	Rat	LD50 > 1,000 mg/kg
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Dermal	Rabbit	LD50 > 6,000  mg/kg
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.7 mg/l
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Ingestion	Rat	LD50 > 4,000  mg/kg
DICYANDIAMIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Ingestion	Rat	LD50 > 30,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER	Rabbit	No significant irritation
(MW>1200)		
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Rabbit	Minimal irritation
DICYANDIAMIDE	Human	Minimal irritation
	and	
	animal	

Serious Eve Damage/Irritation

Name S		Value
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	Rabbit	Mild irritant
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Rabbit	Mild irritant
DICYANDIAMIDE	Professio	Mild irritant
	nal	
	judgeme	
	nt	

### **Skin Sensitization**

Name	Species	Value
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER	Guinea	Not classified
(MW>1200)	pig	
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Human	Sensitizing
	and	
	animal	
DICYANDIAMIDE	Guinea	Not classified
	pig	

**Respiratory Sensitization** 

respiratory sensitization		
Name	Species	Value
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	Human	Not classified

**Germ Cell Mutagenicity** 

Name Route Value
------------------

**Page** 7 **of** 11

BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	In vivo	Not mutagenic
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER (MW>1200)	In Vitro	Some positive data exist, but the data are not sufficient for classification
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	In Vitro	Some positive data exist, but the data are not sufficient for classification
DICYANDIAMIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A	Dermal	Mouse	Some positive data exist, but the data are not
COPOLYMER (MW>1200)			sufficient for classification
DICYANDIAMIDE	Ingestion	Rat	Not carcinogenic

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
DICYANDIAMIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
DICYANDIAMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
DICYANDIAMIDE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	auditory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Page** 8 **of** 11

BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
BISPHENOL A DIGLYCIDYL ETHER- BISPHENOL A COPOLYMER (MW>1200)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
DICYANDIAMIDE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the

\_\_\_\_

available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

Physical Hazards

Combustible Dust

#### Health Hazards

Respiratory or Skin Sensitization

## 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification**

**Health:** 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 10-2603-8
 Version Number:
 26.02

 Issue Date:
 12/19/25
 Supersedes Date:
 04/14/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com