



Safety Data Sheet

Copyright,2025, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 45-5233-7 **Version number:** 1.00
Issue Date: 12/08/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

IDENTIFICATION:

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Adhesive DP8507NS, Gray, Kit

Product Identification Numbers

7100376951 7100377468 62-2882-1445-5 62-2882-3630-0

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Structural adhesive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mms.com
Website: www.3m.com.au

1.4. Emergency telephone number

Company Emergency Hotline:EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

45-5230-3, 45-5232-9

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 45-5230-3 **Version number:** 1.00
Issue Date: 12/08/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Adhesive DP8507NS, Gray, Part A

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Structural adhesive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard statements

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280E Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.
Causes mild skin irritation.
Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Dibenzoate Propanol	27138-31-4	40 - 60
Epoxy Resin	25068-38-6	15 - 35
Catalyst.	Trade Secret	10 - 15
Fillers	Trade Secret	1 - 10
Non-hazardous ingredients	Trade Secret	1 - 10
Organic Peroxide	13122-18-4	1 - 10

Carbon black	1333-86-4	< 0.1
--------------	-----------	-------

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Carbon monoxide.
Carbon dioxide.
Hydrogen Chloride

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: •3Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of

PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	A3: Confirmed animal carcinogen.
Carbon black	1333-86-4	Australia OELs	TWA(8 hours): 3 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Gray
Odour	Mild Ester
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	$\geq 65.6\text{ }^{\circ}\text{C}$
Flash point	$> 93.3\text{ }^{\circ}\text{C}$ [Test Method: Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>

Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative Vapor Density	<i>No data available.</i>
Density	1.08 g/ml
Relative density	1.08 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Kinematic Viscosity	18,519 mm ² /sec
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H₂O & exempt solvents	20.2 g/l [Details:when used as intended with Part B]
Molecular weight	<i>No data available.</i>

Particle Characteristics	<i>Not applicable.</i>
---------------------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Dibzoate Propanol	Dermal	Rat	LD50 > 2,000 mg/kg
Dibzoate Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Dibzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Catalyst.	Ingestion	Rat	LD50 >300, <2000 mg/kg
Organic Peroxide	Dermal	Rat	LD50 > 2,000 mg/kg
Organic Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
Organic Peroxide	Ingestion	Rat	LD50 12,905 mg/kg
Fillers	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fillers	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fillers	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dibzoate Propanol	Rabbit	No significant irritation
Epoxy Resin	Rabbit	Mild irritant
Catalyst.	In vitro data	No significant irritation
Organic Peroxide	Rabbit	No significant irritation
Fillers	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Dibenoate Propanol	Rabbit	No significant irritation
Epoxy Resin	Rabbit	Moderate irritant
Catalyst.	In vitro data	Severe irritant
Organic Peroxide	Rabbit	No significant irritation
Fillers	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Dibenoate Propanol	Guinea pig	Not classified
Epoxy Resin	Human and animal	Sensitising
Catalyst.	Guinea pig	Not classified
Organic Peroxide	Guinea pig	Sensitising
Fillers	Human and animal	Not classified

Respiratory Sensitisation

Name	Species	Value
Epoxy Resin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Dibenoate Propanol	In Vitro	Not mutagenic
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Catalyst.	In Vitro	Not mutagenic
Fillers	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Fillers	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Dibenoate Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Dibenoate Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Dibenoate Propanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Fillers	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fillers	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fillers	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Catalyst.	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dibenoate Propanol	Ingestion	hematopoietic system liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Fillers	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not Determined

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Dibenzoate Propanol	27138-31-4	Fathead minnow	Experimental	96 hours	LC50	3.7 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Dibenzoate Propanol	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Epoxy Resin	25068-38-6	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
Epoxy Resin	25068-38-6	Green algae	Estimated	72 hours	EC50	>11 mg/l
Epoxy Resin	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
Epoxy Resin	25068-38-6	Water flea	Estimated	48 hours	EC50	1.8 mg/l
Epoxy Resin	25068-38-6	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
Epoxy Resin	25068-38-6	Water flea	Estimated	21 days	NOEC	0.3 mg/l
Catalyst.	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Fillers	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Organic Peroxide	13122-18-4	Green algae	Experimental	72 hours	ErC50	0.51 mg/l
Organic Peroxide	13122-18-4	Rainbow trout	Experimental	96 hours	LC50	7.03 mg/l
Organic Peroxide	13122-18-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Organic Peroxide	13122-18-4	Green algae	Experimental	72 hours	NOEC	0.125 mg/l
Organic Peroxide	13122-18-4	Water flea	Experimental	21 days	NOEC	0.22 mg/l
Organic Peroxide	13122-18-4	Activated sludge	Experimental	3 hours	EC50	327.02 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate Propanol	27138-31-4	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THCO2	OECD 301B - Modified sturm or CO2

					evolution	
Epoxy Resin	25068-38-6	Estimated Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
Epoxy Resin	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Catalyst.	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	29.1 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2 evolution
Catalyst.	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	
Fillers	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Organic Peroxide	13122-18-4	Experimental Biodegradation	28 days	BOD	72 %BOD/ThOD	OECD 301D - Closed bottle test
Organic Peroxide	13122-18-4	Experimental Aquatic Inherent Biodegrad.	56 days	BOD	58 %BOD/ThOD	OECD 302A - Modified SCAS Test
Organic Peroxide	13122-18-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	51 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Carbon black	1333-86-4	Data not available-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate Propanol	27138-31-4	Modeled Bioconcentration		Bioaccumulation factor	8	Catalogic™
Epoxy Resin	25068-38-6	Estimated Bioconcentration		Log Kow	3.242	
Catalyst.	Trade Secret	Experimental Bioconcentration		Log Kow	2.57	
Fillers	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Peroxide	13122-18-4	Modeled Bioconcentration		Bioaccumulation factor	380	Catalogic™
Organic Peroxide	13122-18-4	Experimental Bioconcentration		Log Kow	5.16	OECD 117 log Kow HPLC method
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (Epoxy Resin; Organic Peroxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Hazchem Code: •3Z

IERG: 47

International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (Epoxy Resin; Organic Peroxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN3082

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , (Epoxy Resin; Organic Peroxide)

Class/Division: 9

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

Conditions may apply prior to introduction for direct importers of this product. Please contact 3M Australia on 136 136 for further details.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 45-5232-9 **Version number:** 1.00
Issue Date: 12/08/2025 **Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Adhesive DP8507NS, Gray, Part B

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Flame |Exclamation mark |Health Hazard |

Pictograms



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure: sensory organs.

Precautionary statements

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280E	Wear protective gloves.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235

P405

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if inhaled.

Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Methyl Methacrylate	80-62-6	38 - 80
Proprietary polymer#2	Trade Secret	6 - 15
Proprietary polymer#1	Trade Secret	< 13
Hydroxyethyl Methacrylate	868-77-9	2 - 9
Silane, trimethoxyoctyl-, hydrolysis products with silica	67762-90-7	< 5
filler	Trade Secret	< 5
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	27697-00-3	< 4
Calcium Stearate	1592-23-0	< 2
Phosphate Esters of PPG Methacrylate	95175-93-2	<= 1.6
Methacrylic Acid	79-41-4	<= 1.3
Copper Naphthenates	1338-02-9	< 0.2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
 Carbon dioxide.
 Hydrogen gas.
 Oxides of nitrogen.

Condition

During combustion.
 During combustion.
 During combustion.
 During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: •3YE**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
CAS NO M~CU~C	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m3;TWA(as Cu dust or mist):1 mg/m3	
Stearates	1592-23-0	ACGIH	TWA(respirable fraction):3 mg/m3;TWA(inhalable fraction):10 mg/m3	A4: Not class. as human carcin
Stearates	1592-23-0	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Methacrylic Acid	79-41-4	ACGIH	TWA:20 ppm	
Methacrylic Acid	79-41-4	Australia OELs	TWA(8 hours):70 mg/m3(20 ppm)	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human carcin, Dermal Sensitizer
Methyl Methacrylate	80-62-6	Australia OELs	TWA(8 hours):208 mg/m3(50 ppm);STEL(15 minutes):416 mg/m3(100 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure

Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Grey
Odour	Methacrylate
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	>=37.8 °C
Flash point	>=10 °C [Test Method:Closed Cup]

Evaporation rate	<i>No data available.</i>
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative Vapor Density	<i>No data available.</i>
Density	1.01 g/ml
Relative density	1.01 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Kinematic Viscosity	14,852 mm ² /sec
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H₂O & exempt solvents	20.2 g/l [Details:when used as intended with Part A]
VOC less H₂O & exempt solvents	2 % [Details:when used as intended with Part A]
Molecular weight	<i>No data available.</i>

Particle Characteristics	<i>Not applicable.</i>
---------------------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29.8 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Proprietary polymer#2	Dermal	Rabbit	LD50 > 15,000 mg/kg
Proprietary polymer#2	Ingestion	Rat	LD50 > 30,000 mg/kg
Proprietary polymer#1	Dermal		LD50 estimated to be > 5,000 mg/kg
Proprietary polymer#1	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silane, trimethoxyoctyl-, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg

Phosphate Esters of PPG Methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Phosphate Esters of PPG Methacrylate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Methacrylic Acid	Dermal	Rabbit	LD50 > 500 mg/kg
Methacrylic Acid	Inhalation-Dust/Mist (4 hours)	Rat	LC50 7.1 mg/l
Methacrylic Acid	Ingestion	Rat	LD50 1,320 mg/kg
Calcium Stearate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Stearate	Ingestion	Rat	LD50 > 2,000 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Methacrylate	Rabbit	Irritant
Proprietary polymer#2	Professional judgement	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Silane, trimethoxyoctyl-, hydrolysis products with silica	Rabbit	No significant irritation
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	Professional judgement	Irritant
Phosphate Esters of PPG Methacrylate	Not available	Irritant
Methacrylic Acid	Rabbit	Corrosive
Calcium Stearate	In vitro data	No significant irritation
Copper Naphthenates	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Methacrylate	Rabbit	Mild irritant
Proprietary polymer#2	Professional judgement	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Silane, trimethoxyoctyl-, hydrolysis products with silica	Rabbit	No significant irritation
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	Professional judgement	Severe irritant
Phosphate Esters of PPG Methacrylate	Not available	Corrosive
Methacrylic Acid	Rabbit	Corrosive
Calcium Stearate	In vitro data	No significant irritation
Copper Naphthenates	In vitro data	No significant irritation

Skin Sensitisation

Name	Species	Value
Methyl Methacrylate	Human and animal	Sensitising
Hydroxyethyl Methacrylate	Human and animal	Sensitising
Silane, trimethoxyoctyl-, hydrolysis products with silica	Human and animal	Not classified
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	Professional judgement	Sensitising
Methacrylic Acid	Guinea pig	Not classified
Calcium Stearate	similar compounds	Not classified
Copper Naphthenates	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
Methyl Methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silane, trimethoxyoctyl-, hydrolysis products with silica	In Vitro	Not mutagenic
Methacrylic Acid	In Vitro	Not mutagenic
Methacrylic Acid	In vivo	Not mutagenic
Calcium Stearate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
Silane, trimethoxyoctyl-, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Silane, trimethoxyoctyl-, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silane, trimethoxyoctyl-, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silane, trimethoxyoctyl-,	Ingestion	Not classified for development	Rat	NOAEL 1,350	during organogenesis

hydrolysis products with silica				mg/kg/day	
Methacrylic Acid	Inhalation	Not classified for development	Rat	NOAEL 1,076 mg/l	during gestation
Calcium Stearate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating into lactation
Calcium Stearate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Calcium Stearate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	pre mating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	Inhalation	respiratory irritation	May cause respiratory irritation	Professional judgement	NOAEL Not available	
Phosphate Esters of PPG Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methacrylic Acid	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Ingestion	kidney and/or bladder heart skin endocrine system gastrointestinal tract	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years

		hematopoietic system liver muscles nervous system respiratory system				
Silane, trimethoxyoctyl-, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Methacrylic Acid	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.352 mg/l	90 days
Methacrylic Acid	Inhalation	blood nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 1.232 mg/l	90 days
Calcium Stearate	Ingestion	hematopoietic system nervous system kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair liver immune system eyes respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not Determined

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Methyl Methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
Methyl Methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
Methyl Methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
Methyl Methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
Methyl Methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
Proprietary polymer#2	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Proprietary polymer#1	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
Hydroxyethyl Methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Silane, trimethoxyoctyl-, hydrolysis products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl]ester	27697-00-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Calcium Stearate	1592-23-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium Stearate	1592-23-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Calcium Stearate	1592-23-0	Green algae	Experimental	72 hours	NOEC	100 mg/l
Phosphate Esters of PPG Methacrylate	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Methacrylic Acid	79-41-4	Bacteria	Experimental	17 hours	EC50	270 mg/l
Methacrylic Acid	79-41-4	Green algae	Experimental	72 hours	EC50	45 mg/l
Methacrylic Acid	79-41-4	Water flea	Experimental	48 hours	EC50	>130 mg/l
Methacrylic Acid	79-41-4	Green algae	Experimental	72 hours	NOEC	8.2 mg/l
Methacrylic Acid	79-41-4	Water flea	Experimental	21 days	NOEC	53 mg/l
Copper Naphthenates	1338-02-9	Green algae	Estimated	72 hours	EC50	0.629 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
Copper Naphthenates	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.07 mg/l

Copper Naphthenates	1338-02-9	Fathead minnow	Estimated	32 days	EC10	0.0354 mg/l
Copper Naphthenates	1338-02-9	Green algae	Estimated	N/A	NOEC	0.132 mg/l
Copper Naphthenates	1338-02-9	Sediment Worm	Estimated	28 days	NOEC	110 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Copper Naphthenates	1338-02-9	Activated sludge	Estimated	N/A	EC50	42 mg/l
Copper Naphthenates	1338-02-9	Barley	Estimated	4 days	NOEC	96 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Redworm	Estimated	56 days	NOEC	60 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Soil microbes	Estimated	4 days	NOEC	72 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Springtail	Estimated	28 days	NOEC	167 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl Methacrylate	80-62-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThOD	OECD 301C - MITI test (I)
Proprietary polymer#2	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Proprietary polymer#1	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/COD	OECD 301D - Closed bottle test
Hydroxyethyl Methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
Silane, trimethoxyoctyl-, hydrolysis products with silica	67762-90-7	Data not available-insufficient	N/A	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	27697-00-3	Modeled Biodegradation	28 days	BOD	85 %BOD/ThOD	Catalogic™
Calcium Stearate	1592-23-0	Experimental Biodegradation	24 days	CO2 evolution	91 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Phosphate Esters of PPG Methacrylate	95175-93-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Methacrylic Acid	79-41-4	Experimental Biodegradation	28 days	BOD	86 %BOD/ThOD	OECD 301D - Closed bottle test
Copper Naphthenates	1338-02-9	Data not available-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl Methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flsk mtd

3M™ Scotch-Weld™ Acrylic Adhesive DP8507NS, Gray, Part B

Proprietary polymer#2	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Proprietary polymer#1	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
Silane, trimethoxyoctyl-, hydrolysis products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, mono[2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl] ester	27697-00-3	Modeled Bioconcentration		Log Kow	2.64	Episuite™
Calcium Stearate	1592-23-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Phosphate Esters of PPG Methacrylate	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methacrylic Acid	79-41-4	Experimental Bioconcentration		Log Kow	0.93	
Copper Naphthenates	1338-02-9	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	≤27	OECD305-Bioconcentration

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Hazchem Code: •3YE

IERG: 14

International Air Transport Association (IATA) - Air Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product. Please contact 3M Australia on 136 136 for further details.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Initial issue.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au