Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	41-6414-1	**Version number:**	3.00
Revision date:	14/11/2024	**Supersedes date:**	25/09/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
Scotchgard™ Heavy Duty Water Shield

Product Identification Numbers
UU-0110-0916-2

7100228883

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Water repellent

1.3. Details of the supplier of the safety data sheet
Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:
Aerosol, Category 1 - Aerosol 1; H222, H229
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Aspiration Hazard, Category 1 - Asp. Tox. 1; H304

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
DANGER.

Symbols
GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		919-857-5	60 - 90

HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS
General:

P102	Keep out of reach of children.

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331	Do NOT induce vomiting.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

3% of the mixture consists of components of unknown acute oral toxicity.

Contains 70% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

May displace oxygen and cause rapid suffocation.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(EC-No.) 919-857-5 (REACH-No.) 01-2119463258-33	60 - 90	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (REACH-No.) 01-2119486944-21	5 - 15	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (REACH-No.) 01-2119474691-32	7 - 13	Flam. Gas 1A, H220 Liquified gas, H280 Nota C,U
Poly(dimethylsiloxane)	(CAS-No.) 63148-62-9	1 - 10	Substance not classified as hazardous
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc.	(CAS-No.) 68988-56-7	< 5	Substance not classified as hazardous

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. Get medical attention.

Skin contact
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed
Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the CLP classification include:
Dermal defatting (localized redness, itching, drying and cracking of skin). Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50ºC/122ºF. Store away from heat. Store away from oxidising agents.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
butane	106-97-8	Ireland OELs	STEL(15 minutes):1000 ppm	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls
Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 166

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136
Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Colourless
Odor	Petroleum
Odour threshold	*No data available.*
Melting point/freezing point	*No data available.*
Boiling point/boiling range	150 ºC
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	1.5 %
Flammable Limits(UEL)	10 %
Flash point	*Not applicable.*
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	*No data available.*
Water solubility	Insoluble
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	>=300 kPa [@ 50 ºC]
Density	805 g/l [@ 20 ºC]
Relative density	*No data available.*

Relative Vapour Density	*No data available.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds *No data available.*
Evaporation rate *No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Heat.
Sparks and/or flames.
Temperatures above 45 ºC (113 ºF)

10.5 Incompatible materials
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact
Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion
Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Single exposure may cause target organ effects:
Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Dermal	similar compounds	LD50 > 5,000 mg/kg
propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
Poly(dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar compounds	Mild irritant
propane	Rabbit	Minimal irritation
butane	Professional judgement	No significant irritation
Poly(dimethylsiloxane)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar	No significant irritation

	compoun ds	
propane	Rabbit	Mild irritant
butane	Rabbit	No significant irritation
Poly(dimethylsiloxane)	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	similar compoun ds	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	In Vitro	Not mutagenic
propane	In Vitro	Not mutagenic
butane	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

For the component/components, either no data is currently available or the data is not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL Not available	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
butane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Inhalation	liver | kidney and/or bladder | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | hematopoietic system | muscles | nervous system | respiratory system | vascular system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
butane	Inhalation	kidney and/or bladder | blood	Not classified	Rat	NOAEL 4,489 ppm	90 days

Aspiration Hazard

Name	Value
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
propane	74-98-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
butane	106-97-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Poly(dimethylsiloxane)	63148-62-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc.	68988-56-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A

propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	
butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	
Poly(dimethylsiloxane)	63148-62-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc.	68988-56-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	919-857-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	
butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	
Poly(dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc.	68988-56-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil
No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
16 05 04* Gases in pressure containers (including halons) containing dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

EU waste code (product container after use)

15 01 04 Metallic packaging

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS, FLAMMABLE	AEROSOLS
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	5F	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information.

DIRECTIVE 2012/18/EU
Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P3a FLAMMABLE AEROSOLS	150 (net)	500 (net)

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

Revision information:
Section 7: Conditions safe storage information was modified.
Section 11: Health Effects - Ingestion information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com