



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 11-0058-5
Revision Date: 03/03/2025
Transportation version number:

Version Number: 1.00
Supersedes Date: Initial Issue

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B

Product Identification Numbers

62-3764-9132-0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

ADDRESS: 3M Israel, 91 Medinat Ha'Yehudim Street, Herzeliya 46120
Telephone: 09-961 5000
E Mail: innovation.il@mmm.com
Website: www.3M.com/il

1.4. Emergency telephone number

09-961 5000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH210 Safety data sheet available on request.

EUH208 Contains MALEIC ANHYDRIDE. May produce an allergic reaction.

Supplemental Precautionary Statements:

Avoid contact with hot extruded molten material or applicator tip. Avoid direct eye exposure to vapors. In case of eye/skin contact with molten material, immediately flush with cold water and cover with a clean dressing. Do not attempt to remove molten material. Have burn treated by a physician.

2.3. Other hazards

May cause thermal burns.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ETHYLENE-VINYL ACETATE POLYMER	(CAS-No.) 24937-78-8	< 65	Substance not classified as hazardous
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	(CAS-No.) 68132-00-3	< 40	Substance not classified as hazardous
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Mixture	< 35	Substance not classified as hazardous
ETHYLENE-MALEIC ANHYDRIDE POLYMER	(CAS-No.) 9006-26-2	1 - 10	Substance not classified as hazardous
Paraffin Wax	(CAS-No.) 8002-74-2 (EC-No.) 232-315-6	1 - 10	Substance with a national occupational exposure limit
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	(CAS-No.) 6683-19-8 (EC-No.) 229-722-6	< 2	Substance not classified as hazardous
VINYL ACETATE	(CAS-No.) 108-05-4 (EC-No.) 203-545-4	< 0.5	Flam. Liq. 2, H225 Acute Tox. 4, H332 Carc. 2, H351 STOT SE 3, H335 Nota D Aquatic Chronic 3, H412
MALEIC ANHYDRIDE	(CAS-No.) 108-31-6	< 0.001	EUH071 Acute Tox. 4, H302

	(EC-No.) 203-571-6		Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372
--	--------------------	--	--

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
MALEIC ANHYDRIDE	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	(C >= 0.001%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:

Rinse mouth. If you are concerned, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
VINYL ACETATE	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	A3: Confirmed animal carcin.
MALEIC ANHYDRIDE	108-31-6	ACGIH	TWA(inhalable fraction and	A4: Not class. as human

			vapor):0.01 mg/m3	carcin, Dermal/Respiratory Sensitizer
Paraffin Wax	8002-74-2	ACGIH	TWA(as fume):2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Waxy Solid
Color	White
Odor	Odorless
Odor threshold	No Data Available
Melting point/freezing point	No Data Available
Boiling point/boiling range	Not Applicable
Flammability	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Flash Point	267.8 °C [Test Method:Cleveland Open Cup] [Details:CONDITIONS: ASTM D-92-72]
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available

pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>Not Applicable</i>
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Density	0.95 g/cm3
Relative Density	0.95 [Ref Std: WATER=1]
Relative Vapor Density	<i>No Data Available</i>
Particle Characteristics	<i>Not Applicable</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No Data Available</i>
Evaporation rate	<i>Not Applicable</i>
Molecular weight	<i>No Data Available</i>
Percent volatile	0 % weight
Solids Content	100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Eye Contact:

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Ingestion:

May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ETHYLENE-VINYL ACETATE POLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg
ETHYLENE-VINYL ACETATE POLYMER	Ingestion	Rat	LD50 > 1,000 mg/kg
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Dermal		LD50 estimated to be > 5,000 mg/kg
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Ingestion		LD50 estimated to be > 5,000 mg/kg
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Ingestion	Professional judgement	LD50 7,000 mg/kg
ETHYLENE-MALEIC ANHYDRIDE POLYMER	Dermal	Rabbit	LD50 > 7,940 mg/kg
ETHYLENE-MALEIC ANHYDRIDE POLYMER	Ingestion	Rat	LD50 > 10,000 mg/kg
Paraffin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Paraffin Wax	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Dermal	Rabbit	LD50 > 3,160 mg/kg
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.95 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	Rat	LD50 > 10,250 mg/kg
VINYL ACETATE	Dermal	Rabbit	LD50 2,320 mg/kg
VINYL ACETATE	Inhalation-Vapor (4 hours)	Rat	LC50 11.3 mg/l
VINYL ACETATE	Ingestion	Rat	LD50 2,920 mg/kg

MALEIC ANHYDRIDE	Dermal	Rabbit	LD50 2,620 mg/kg
MALEIC ANHYDRIDE	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ETHYLENE-VINYL ACETATE POLYMER	Professional judgement	No significant irritation
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Professional judgement	No significant irritation
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Professional judgement	No significant irritation
ETHYLENE-MALEIC ANHYDRIDE POLYMER	Rabbit	No significant irritation
Paraffin Wax	Rabbit	No significant irritation
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Rabbit	No significant irritation
VINYL ACETATE	Rabbit	Minimal irritation
MALEIC ANHYDRIDE	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
ETHYLENE-VINYL ACETATE POLYMER	Professional judgement	No significant irritation
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Professional judgement	No significant irritation
ETHYLENE-MALEIC ANHYDRIDE POLYMER	Rabbit	Mild irritant
Paraffin Wax	Rabbit	No significant irritation
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Rabbit	Mild irritant
VINYL ACETATE	Rabbit	Mild irritant
MALEIC ANHYDRIDE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Paraffin Wax	Guinea pig	Not classified
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Human and animal	Not classified
VINYL ACETATE	Guinea pig	Not classified
MALEIC ANHYDRIDE	Multiple animal species	Sensitizing

Respiratory Sensitization

Name	Species	Value
------	---------	-------

MALEIC ANHYDRIDE	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	In Vitro	Not mutagenic
Paraffin Wax	In Vitro	Not mutagenic
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	In Vitro	Not mutagenic
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	In vivo	Not mutagenic
VINYL ACETATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
VINYL ACETATE	In vivo	Some positive data exist, but the data are not sufficient for classification
MALEIC ANHYDRIDE	In vivo	Not mutagenic
MALEIC ANHYDRIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Paraffin Wax	Ingestion	Rat	Not carcinogenic
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	Multiple animal species	Not carcinogenic
VINYL ACETATE	Ingestion	Multiple animal species	Carcinogenic
VINYL ACETATE	Inhalation	Rat	Carcinogenic

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	Not classified for female reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during organogenesis
VINYL ACETATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
VINYL ACETATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
VINYL ACETATE	Ingestion	Not classified for development	Rat	NOAEL 700 mg/kg/day	2 generation
VINYL ACETATE	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during organogenesis
MALEIC ANHYDRIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYL ACETATE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
VINYL ACETATE	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
MALEIC ANHYDRIDE	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYLENE-VINYL ACETATE POLYMER	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
Paraffin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Paraffin Wax	Ingestion	hematopoietic system liver immune system skin endocrine system bone, teeth, nails, and/or hair muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	endocrine system	Not classified	Rat	NOAEL 450 mg/kg/day	2 years
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	liver	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	Ingestion	auditory system eyes	Not classified	Dog	NOAEL 302 mg/kg/day	90 days

propanediyl ester						
VINYL ACETATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.2 mg/l	104 weeks
VINYL ACETATE	Inhalation	heart hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 2.1 mg/l	104 weeks
VINYL ACETATE	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
VINYL ACETATE	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	3 months
VINYL ACETATE	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
VINYL ACETATE	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months
VINYL ACETATE	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
VINYL ACETATE	Ingestion	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
VINYL ACETATE	Ingestion	immune system respiratory system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
VINYL ACETATE	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
MALEIC ANHYDRIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
MALEIC ANHYDRIDE	Inhalation	endocrine system hematopoietic system nervous system kidney and/or bladder heart liver eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
MALEIC ANHYDRIDE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	heart nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
MALEIC ANHYDRIDE	Ingestion	skin endocrine system immune system eyes respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Material	CAS #	Organism	Type	Exposure	Test Endpoint	Test Result
ETHYLENE-VINYL ACETATE POLYMER	24937-78-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	68132-00-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Mixture	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ETHYLENE-MALEIC ANHYDRIDE POLYMER	9006-26-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Green algae	Analogous Compound	96 hours	EC50	>1,000 mg/l
Paraffin Wax	8002-74-2	Rainbow Trout	Analogous Compound	96 hours	LC50	>1,000 mg/l
Paraffin Wax	8002-74-2	Water flea	Analogous Compound	48 hours	EC50	>10,000 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Water flea	Endpoint not reached	24 hours	EC50	>100 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l

hydroxyphenyl]-1-oxopropoxy)methyl]-1,3-propanediyl ester						
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy)methyl]-1,3-propanediyl ester	6683-19-8	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy)methyl]-1,3-propanediyl ester	6683-19-8	Redworm	Experimental	56 days	NOEC	>=1,000 mg/kg (Dry Weight)
VINYL ACETATE	108-05-4	Green algae	Experimental	72 hours	EC50	8.9 mg/l
VINYL ACETATE	108-05-4	Medaka	Experimental	96 hours	LC50	2.4 mg/l
VINYL ACETATE	108-05-4	Water flea	Experimental	48 hours	EC50	9.2 mg/l
VINYL ACETATE	108-05-4	Fathead Minnow	Experimental	34 days	NOEC	0.551 mg/l
VINYL ACETATE	108-05-4	Green algae	Experimental	72 hours	NOEC	0.2 mg/l
VINYL ACETATE	108-05-4	Water flea	Experimental	21 days	NOEC	0.32 mg/l
MALEIC ANHYDRIDE	108-31-6	Bacteria	Experimental	18 hours	EC10	44.6 mg/l
MALEIC ANHYDRIDE	108-31-6	Rainbow Trout	Experimental	96 hours	LC50	75 mg/l
MALEIC ANHYDRIDE	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC50	74.4 mg/l
MALEIC ANHYDRIDE	108-31-6	Water flea	Hydrolysis Product	48 hours	EC50	93.8 mg/l
MALEIC ANHYDRIDE	108-31-6	Water flea	Experimental	21 days	NOEC	10 mg/l
MALEIC ANHYDRIDE	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC10	11.8 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
ETHYLENE-VINYL ACETATE POLYMER	24937-78-8	Data not availbl-insufficient	N/A	N/A	N/A	N/A
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	68132-00-3	Modeled Biodegradation	28 days	Biological Oxygen Demand	0 %BOD/ThO D	Catalogic™
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Mixture	Data not availbl-insufficient	N/A	N/A	N/A	N/A
ETHYLENE-MALEIC ANHYDRIDE POLYMER	9006-26-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	40 %BOD/ThO D	OECD 301F - Manometric Respiro
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-	6683-19-8	Experimental Biodegradation	28 days	Carbon dioxide evolution	5 %CO2 evolution/THC	OECD 301B - Mod. Sturm or CO2

hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester					O2 evolution	
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Experimental Biodegradation	26 days	Percent degraded	45.2 %removal of DOC	OECD 303A - Simulated Aerobic
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Modeled Hydrolysis		Hydrolytic half-life (pH 7)	2.06 years (t 1/2)	Episuite™
VINYL ACETATE	108-05-4	Experimental Biodegradation	14 days	Biological Oxygen Demand	90 %BOD/ThO D	OECD 301C - MITI (I)
MALEIC ANHYDRIDE	108-31-6	Hydrolysis product Biodegradation	25 days	Carbon dioxide evolution	>90 %CO2 evolution/THC O2 evolution	OECD 301B - Mod. Sturm or CO2
MALEIC ANHYDRIDE	108-31-6	Experimental Hydrolysis		Hydrolytic half-life	0.37 minutes (t 1/2)	

12.3. Bioaccumulative potential

Material	Cas No.	Test Type	Duration	Study Type	Test Result	Protocol
ETHYLENE-VINYL ACETATE POLYMER	24937-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	68132-00-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROCARBONS, C6-20, POLYMERS, HYDROGENATED	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ETHYLENE-MALEIC ANHYDRIDE POLYMER	9006-26-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	10.2	Episuite™
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Experimental BCF - Fish	42 days	Bioaccumulation Factor	<2.3	OECD305-Bioconcentration
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	22.7	
VINYL ACETATE	108-05-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.73	
MALEIC ANHYDRIDE	108-31-6	Experimental Bioconcentration		Log of Octanol/H2O part.	-2.61	OECD 107 log Kow shke flask mtd

				coeff		
--	--	--	--	-------	--	--

12.4. Mobility in soil

Material	Cas No.	Test Type	Study Type	Test Result	Protocol
Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester	6683-19-8	Modeled Mobility in Soil	Koc	10,000,000,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

200127* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No Data Available	No Data Available	No Data Available

14.2 UN proper shipping name	No Data Available	No Data Available	No Data Available
14.3 Transport hazard class(es)	No Data Available	No Data Available	No Data Available
14.4 Packing group	No Data Available	No Data Available	No Data Available
14.5 Environmental hazards	No Data Available	No Data Available	No Data Available
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No Data Available	No Data Available	No Data Available
Control Temperature	No Data Available	No Data Available	No Data Available
Emergency Temperature	No Data Available	No Data Available	No Data Available
ADR Classification Code	No Data Available	No Data Available	No Data Available
IMDG Segregation Code	No Data Available	No Data Available	No Data Available

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>	<u>Regulation</u>
VINYL ACETATE	108-05-4	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
VINYL ACETATE	108-05-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012

No chemicals listed

SECTION 16: Other information**List of relevant H statements**

EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Israel SDSs are available at www.3M.com/il