



Safety Data Sheet

Copyright, 2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 10-3197-0 **Version number:** 15.03
Issue Date: 2026/02/02 **Supersedes Date:** 2025/06/23

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Seal™ Tamper Proof Sealant White

Product Identification Numbers

62-1926-0304-1	62-1926-0604-4	62-1926-2604-2	62-1926-2605-9	62-1926-8530-3
62-1926-9530-2				

1.2. Recommended use and restrictions on use

Intended Use

Industrial use

Specific Use

Sealant

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Industrial Adhesives and Tapes Division
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.
 Serious Eye Damage/Irritation: Category 2A.
 Skin Sensitizer: Category 1A.
 Carcinogenicity: Category 2.
 Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Highly flammable liquid and vapour.

Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility or the unborn child. May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure: skin.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapours, dust, or spray. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and if needed, respiratory protection (see SDS Section 8).

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or doctor if you feel unwell. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Methyl Ethyl Ketone	78-93-3	15 - 40 Trade Secret *	2-Butanone
Limestone	1317-65-3	10 - 30	Limestonests primarily of calcium carbonate.
Mica-Group Minerals	12001-26-2	10 - 30 Trade Secret *	Mica-group Minerals
Titanium Dioxide	13463-67-7	5 - 10 Trade Secret *	Titanium oxide (TiO2)
Acrylonitrile-Butadiene Polymer	9003-18-3	3 - 7	2-Propenenitrile, polymer with 1,3-butadiene
Alkanes, C20-28, chloro	2097144-43-7	1 - 5	No Data Available
Ammonia, o-Cresol, Formaldehyde, Phenol Polymer	55185-45-0	1 - 5	Formaldehyde, polymer with ammonia, 2-methylphenol and phenol
Antimony Trioxide	1309-64-4	1 - 5 Trade Secret *	Antimony oxide (Sb2O3)
Feldspars	68476-25-5	< 5	Feldspar-group minerals
Isopropyl Alcohol	67-63-0	1 - 5 Trade Secret *	2-Propanol
p-tert-Butylphenol-Formaldehyde Resin	25085-50-1	1 - 5	Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol
Quartz Silica	14808-60-7	0.1 - 2.6	Quartz (SiO2)
Kaolin	1332-58-7	< 2.5	Kaolin
Heptane	142-82-5	< 1	Heptane
Salicylic Acid	69-72-7	0.1 - 1	Benzoic acid, 2-hydroxy-
Toluene	108-88-3	< 1	No Data Available
Zinc Oxide	1314-13-2	< 0.4	Zinc oxide (ZnO)
Formaldehyde	50-00-0	< 0.1	Formaldehyde
Ocithilinone	26530-20-1	0.05 - 0.06	No Data Available
Lead	7439-92-1	< 0.04	Lead

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Antimony	During Combustion

5.4. Special protection actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	
Mica-Group Minerals	12001-26-2	ACGIH	TWA(respirable fraction):0.1 mg/m ³	
Antimony Trioxide	1309-64-4	ACGIH	TWA(inhalable fraction):0.02 mg/m ³	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ; STEL(respirable fraction):10 mg/m ³	
Kaolin	1332-58-7	ACGIH	TWA(respirable fraction):2 mg/m ³	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m ³ ; TWA(Respirable finescale particles):2.5 mg/m ³	
Heptane, straight and branched isomers	142-82-5	ACGIH	TWA:200 ppm; STEL:400 ppm	
Silica, crystalline, respirable fraction	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m ³	
Formaldehyde	50-00-0	ACGIH	TWA:0.1 ppm; STEL:0.3 ppm	Dermal/Respiratory Sensitizer
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm; STEL:400 ppm	
Lead and inorganic compounds, as Pb	7439-92-1	ACGIH	TWA(as Pb):0.05 mg/m ³	
Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:75 ppm; STEL:150 ppm	Danger of cutaneous absorption

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Colour	White
Odour	Strong Solvent
Odour threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point	80 °C [<i>Details:MEK</i>]
Flash Point	-8.9 °C [<i>Test Method:Closed Cup</i>]
Evaporation rate	2.7 [<i>Ref Std:ETHER=1</i>]
Flammability	Flammable Liquid: Category 2.

Flammable Limits(LEL)	1.8 % volume
Flammable Limits(UEL)	10 % volume
Vapour Pressure	91 mmHg [@ 77 °F]
Relative Vapour Density	2.41 [Ref Std: AIR=1]
Density	1.5 g/ml
Relative density	1.5 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	404 °C
Decomposition temperature	No Data Available
Kinematic Viscosity	166,667 mm ² /sec
Volatile Organic Compounds	510 g/l [Details: EU VOC content]
Percent volatile	33.9 % weight
VOC Less H₂O & Exempt Solvents	511 g/l [Test Method: calculated SCAQMD rule 443.1]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
---------------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Silica, Crystalline (Respirable Size)	14808-60-7	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Antimony trioxide	1309-64-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Antimony Trioxide	1309-64-4	Anticipated human carcinogen	National Toxicology Program Carcinogens
Formaldehyde	50-00-0	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Formaldehyde	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
FORMALDEHYDE	50-00-0	Cancer hazard	OSHA Carcinogens
Lead	7439-92-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Lead	7439-92-1	Anticipated human carcinogen	National Toxicology Program Carcinogens
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000

			mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Mica-Group Minerals	Dermal		LD50 estimated to be > 5,000 mg/kg
Mica-Group Minerals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Antimony Trioxide	Dermal	Rabbit	LD50 > 6,685 mg/kg
Antimony Trioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.76 mg/l
Antimony Trioxide	Ingestion	Rat	LD50 > 34,600 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Feldspars	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Feldspars	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Ammonia, o-Cresol, Formaldehyde, Phenol Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ammonia, o-Cresol, Formaldehyde, Phenol Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
p-tert-Butylphenol-Formaldehyde Resin	Dermal		LD50 estimated to be > 5,000 mg/kg
p-tert-Butylphenol-Formaldehyde Resin	Ingestion	Rat	LD50 5,660 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Heptane	Dermal	similar compounds	LD50 > 2,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	similar compounds	LC50 > 33.5 mg/l
Heptane	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Salicylic Acid	Dermal	Rat	LD50 > 2,000 mg/kg
Salicylic Acid	Ingestion	Rat	LD50 891 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Ocithilinone	Dermal	Rabbit	LD50 311 mg/kg
Ocithilinone	Inhalation-Dust/Mist	Rat	LC50 0.27 mg/l

	(4 hours)		
Ocithilinone	Ingestion	Rat	LD50 125 mg/kg
Formaldehyde	Dermal	Rabbit	LD50 270 mg/kg
Formaldehyde	Inhalation-Gas (4 hours)	Rat	LC50 470 ppm
Formaldehyde	Ingestion	Rat	LD50 800 mg/kg
Lead	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Minimal irritation
Limestone	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Antimony Trioxide	Human and animal	Minimal irritation
Quartz Silica	Professional judgement	No significant irritation
Feldspars	Professional judgement	No significant irritation
Kaolin	Professional judgement	No significant irritation
Isopropyl Alcohol	Multiple animal species	No significant irritation
Heptane	Professional judgement	Mild irritant
Toluene	Rabbit	Irritant
Salicylic Acid	Rabbit	No significant irritation
Zinc Oxide	Human and animal	No significant irritation
Ocithilinone	Rabbit	Corrosive
Formaldehyde	Official classification	Corrosive
Lead	similar compounds	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Severe irritant
Limestone	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation

Antimony Trioxide	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Isopropyl Alcohol	Rabbit	Severe irritant
Heptane	similar compounds	Mild irritant
Toluene	Rabbit	Moderate irritant
Salicylic Acid	Rabbit	Corrosive
Zinc Oxide	Rabbit	Mild irritant
Ocithilinone	similar health hazards	Corrosive
Formaldehyde	official classification	Corrosive
Lead	similar compounds	Mild irritant

Skin Sensitization

Name	Species	Value
Titanium Dioxide	Human and animal	Not classified
Antimony Trioxide	Human	Not classified
p-tert-Butylphenol-Formaldehyde Resin	Human	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	Guinea pig	Not classified
Heptane	similar compounds	Not classified
Toluene	Guinea pig	Not classified
Salicylic Acid	Mouse	Not classified
Zinc Oxide	Guinea pig	Not classified
Ocithilinone	Human and animal	Sensitizing
Formaldehyde	Guinea pig	Sensitizing

Photosensitization

Name	Species	Value
Salicylic Acid	Mouse	Not sensitizing

Respiratory Sensitization

Name	Species	Value
Formaldehyde	Human	Some positive data exist, but the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Antimony Trioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification

		sufficient for classification
Antimony Trioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
Heptane	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Salicylic Acid	In Vitro	Not mutagenic
Salicylic Acid	In vivo	Not mutagenic
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Ocithilinone	In Vitro	Not mutagenic
Ocithilinone	In vivo	Not mutagenic
Formaldehyde	In Vitro	Some positive data exist, but the data are not sufficient for classification
Formaldehyde	In vivo	Mutagenic
Lead	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Antimony Trioxide	Inhalation	Multiple animal species	Carcinogenic
Quartz Silica	Inhalation	Human and animal	Carcinogenic
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Formaldehyde	Not Specified	Human and animal	Carcinogenic
Lead	Not Specified	official classification	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625	pre mating &

				mg/kg/day	during gestation
Antimony Trioxide	Inhalation	Not classified for female reproduction	Rat	LOAEL 0.25 mg/l	pre mating & during gestation
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Salicylic Acid	Ingestion	Toxic to development	Rat	NOAEL 75 mg/kg/day	during organogenesis
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	pre mating & during gestation
Octhilinone	Ingestion	Not classified for development	Rabbit	NOEL 20 mg/kg/day	during organogenesis
Formaldehyde	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg	not applicable
Formaldehyde	Inhalation	Not classified for development	Rat	NOAEL 10 ppm	during gestation
Lead	Not Specified	Toxic to female reproduction	Human	LOAEL 10 ug/dl blood	
Lead	Not Specified	Toxic to male reproduction	Human	LOAEL 37 ug/dl blood	
Lead	Not Specified	Toxic to development	Human	NOAEL Not available	

Lactation

Name	Route	Species	Value
Lead	Not Specified	Human	Causes effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or	Not classified	Rat	LOAEL	not applicable

		bladder			1,080 mg/kg	
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Antimony Trioxide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Octhilinone	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL Not available	
Formaldehyde	Inhalation	respiratory system	Causes damage to organs	Rat	LOAEL 128 ppm	6 hours
Formaldehyde	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Lead	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90 ug/dl blood	poisoning and/or abuse
Lead	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	heart	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	endocrine system	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	immune system	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Inhalation	muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days

					available	
Methyl Ethyl Ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Mica-Group Minerals	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Antimony Trioxide	Dermal	skin	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Antimony Trioxide	Inhalation	pulmonary fibrosis	May cause damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.002 mg/l	1 years
Antimony Trioxide	Inhalation	liver	Not classified	Rat	NOAEL 0.043 mg/l	1 years
Antimony Trioxide	Inhalation	blood	Not classified	Rat	NOAEL 0.004 mg/l	not available
Antimony Trioxide	Inhalation	pneumoconiosis	Not classified	Human	LOAEL 0.01 mg/l	occupational exposure
Antimony Trioxide	Inhalation	heart	Not classified	Rat	NOAEL 0.02 mg/l	1 years
Antimony Trioxide	Ingestion	blood	Not classified	Rat	NOAEL 418 mg/kg/day	not available
Antimony Trioxide	Ingestion	liver	Not classified	Rat	NOAEL 418 mg/kg/day	not available
Antimony Trioxide	Ingestion	heart	Not classified	Rat	NOAEL Not available	not available
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Heptane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
Heptane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
Heptane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Heptane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Toluene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	liver	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	kidney and/or	Not classified	Rat	NOAEL 11.3	15 weeks

					mg/l	
Toluene	Inhalation	bladder endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Salicylic Acid	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	3 days
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Zinc Oxide	Ingestion	hematopoietic system	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Zinc Oxide	Ingestion	kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Formaldehyde	Dermal	respiratory system	Not classified	Mouse	NOAEL 80 mg/kg/day	60 weeks
Formaldehyde	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 ppm	28 months
Formaldehyde	Inhalation	liver	Not classified	Rat	NOAEL 20 ppm	13 weeks
Formaldehyde	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 15 ppm	3 weeks
Formaldehyde	Inhalation	nervous system	Not classified	Mouse	NOAEL 10 ppm	13 weeks
Formaldehyde	Inhalation	endocrine system	Not classified	Rat	NOAEL 15 ppm	28 months
Formaldehyde	Inhalation	immune system	Not classified	Rat	NOAEL 15 ppm	28 months
Formaldehyde	Inhalation	muscles	Not classified	Rat	NOAEL 15 ppm	28 months
Formaldehyde	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 15 ppm	28 months
Formaldehyde	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 15 ppm	2 years
Formaldehyde	Inhalation	eyes	Not classified	Rat	NOAEL 14.3 ppm	2 years
Formaldehyde	Inhalation	vascular system	Not classified	Rat	NOAEL 14.3 ppm	2 years
Formaldehyde	Inhalation	heart	Not classified	Mouse	NOAEL 14.3	2 years

					ppm	
Formaldehyde	Ingestion	liver	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	immune system	Not classified	Rat	NOAEL 20 mg/kg/day	4 weeks
Formaldehyde	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 15 mg/kg/day	24 months
Formaldehyde	Ingestion	nervous system	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
Formaldehyde	Ingestion	heart	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	endocrine system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	vascular system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
Formaldehyde	Ingestion	skin	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
Formaldehyde	Ingestion	muscles	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
Formaldehyde	Ingestion	eyes	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
Lead	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
Lead	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
Lead	Inhalation	gastrointestinal tract	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
Lead	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
Lead	Inhalation	heart	Not classified	Human	NOAEL Not available	occupational exposure
Lead	Inhalation	endocrine system	Not classified	Human	NOAEL Not available	occupational exposure
Lead	Inhalation	immune system	Not classified	Human	NOAEL Not available	occupational exposure
Lead	Inhalation	vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Lead	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
Lead	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.5 mg/kg/day	20 days
Lead	Ingestion	gastrointestinal tract	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	environmental exposure
Lead	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
Lead	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
Lead	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 11 ug/dl blood	environmental exposure
Lead	Ingestion	auditory system	Not classified	Human	NOAEL Not available	environmental exposure
Lead	Ingestion	heart	Not classified	Human	NOAEL Not available	environmental exposure

Lead	Ingestion	endocrine system	Not classified	Human	NOAEL Not available	environmental exposure
Lead	Ingestion	vascular system	Not classified	Human	NOAEL Not available	environmental exposure

Aspiration Hazard

Name	Value
Heptane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	10-3197-0	Version number:	15.03
Issue Date:	2026/02/02	Supersedes Date:	2025/06/23

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca