Safety Data Sheet

© 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-0278-1	**Version number:**	3.00
Issue Date:	19/05/2025	**Supersedes date:**	20/01/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

IDENTIFICATION:

1.1. Product identifier
3M™ Scotchcast™ Easy Dispenser 250

Product Identification Numbers
7100231726 (UU-0110-2916-0)

1.2. Recommended use and restrictions on use

Recommended use
Electrical

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number
24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

29-0077-7, 29-0076-9

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

TRANSPORT INFORMATION

The Components of this KIT have various Dangerous Goods Transportation Classifications. Please refer to the attached component Safety Data Sheets for individual Transportation Classifications.

Revision information:
Complete document review.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz

Safety Data Sheet

© 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-0076-9	**Version number:**	3.00
Issue Date:	19/05/2025	**Supersedes date:**	24/01/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier
3M™ Scotchcast™ Easy Dispenser 250 Part A

1.2. Recommended use and restrictions on use

Recommended use
Electrical

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number
24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.
Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture
Respiratory sensitisation: Category 1
Skin sensitisation: Category 1
Reproductive Toxicity: Category 1

2.2. Label elements
SIGNAL WORD
Danger

Symbols:
Health Hazard |

Pictograms

HAZARD STATEMENTS:

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.

PRECAUTIONARY STATEMENTS

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280E	Wear protective gloves.
P284	Wear respiratory protection.

Response

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage

P405	Store locked up.

Disposal

P501	Dispose of contents/container via an approved hazardous waste disposal contractor.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Soybean oil	8001-22-7	64 - 67
Butadiene-maleic anhydride copolymer	25655-35-0	24 - 28
Soybean oil, epoxidised	8013-07-8	6 - 8
2,6-Di-tert-butyl-p-cresol	128-37-0	< 0.8
Maleic anhydride	108-31-6	< 0.3
Toluene	108-88-3	< 0.3

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling
Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators…) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Certified handler
Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Maleic anhydride	108-31-6	ACGIH	TWA(inhalable fraction and vapor):0.01 mg/m3	A4: Not class. as human carcin, Dermal/Respiratory Sensitizer
Maleic anhydride	108-31-6	New Zealand WES	TWA(inhalable fraction and vapor)(8 hours):0.01 mg/m3(0.0025 ppm)	Capable of csng resp/skin sens
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	108-88-3	New Zealand WES	TWA(8 hours):75 mg/m3(20 ppm);STEL(15 minutes):377 mg/m3(100 ppm)	Ototoxicant, SKIN
2,6-Di-tert-butyl-p-cresol	128-37-0	ACGIH	TWA(inhalable fraction and vapor):2 mg/m3	A4: Not class. as human carcinogin
2,6-Di-tert-butyl-p-cresol	128-37-0	New Zealand WES	TWA(8 hours):10 mg/m3	
Vegetable oil mist, total dust.	8001-22-7	New Zealand WES	TWA(as mist)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines
New Zealand WES : New Zealand Workplace Exposure Standards.
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
ppm: parts per million
mg/m^3: milligrams per cubic metre
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Clear Amber
Odour	Mild Hydrocarbon
Odour threshold	*No data available.*
pH	*Not applicable.*
Melting point/Freezing point	*Not applicable.*
Boiling point/Initial boiling point/Boiling range	246.1 ºC

Flash point	>=148.9 ºC [*Test Method:*Closed Cup]
Evaporation rate	*No data available.*
Flammability	Not applicable.
Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Vapour pressure	<=186,158.4 Pa [@ 55 ºC]
Relative Vapour Density	*No data available.*
Density	0.89 g/ml
Relative density	0.89 [*Ref Std:*WATER=1]
Water solubility	Negligible
Solubility- non-water	Nil
Partition coefficient: n-octanol/water	*No data available.*
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
Kinematic Viscosity	140,449 mm²/sec
Volatile organic compounds (VOC)	*No data available.*
Percent volatile	*No data available.*
VOC less H2O & exempt solvents	*No data available.*
Molecular weight	*No data available.*

Particle Characteristics	*Not applicable.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
None known.

10.5 Incompatible materials
Strong acids.
Strong bases.
Strong oxidising agents.
Reducing agents.

10.6 Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact
Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Soybean oil	Dermal		LD50 estimated to be > 5,000 mg/kg
Soybean oil	Ingestion		LD50 estimated to be > 5,000 mg/kg
Soybean oil, epoxidised	Dermal	Rabbit	LD50 > 20,000 mg/kg
Soybean oil, epoxidised	Ingestion	Rat	LD50 > 5,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Maleic anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
Maleic anhydride	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Soybean oil	Professional	Minimal irritation

	judgement	
Soybean oil, epoxidised	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation
Toluene	Rabbit	Irritant
Maleic anhydride	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Soybean oil	Professional judgement	Mild irritant
Soybean oil, epoxidised	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Maleic anhydride	Rabbit	Corrosive

Sensitisation:

Skin Sensitisation

Name	Species	Value
Soybean oil, epoxidised	Guinea pig	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified
Toluene	Guinea pig	Not classified
Maleic anhydride	Multiple animal species	Sensitising

Respiratory Sensitisation

Name	Species	Value
Maleic anhydride	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Soybean oil, epoxidised	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Maleic anhydride	In vivo	Not mutagenic
Maleic anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Soybean oil, epoxidised	Ingestion	Rat	Not carcinogenic
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Soybean oil, epoxidised	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Soybean oil, epoxidised	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Soybean oil, epoxidised	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Maleic anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
Maleic anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
Maleic anhydride	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Maleic anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Soybean oil, epoxidised	Ingestion	liver | kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	2 years
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 250 mg/kg/day	28 days

			classification			
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
Toluene	Inhalation	auditory system | nervous system | eyes | olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart | liver | kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system | vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver | kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Maleic anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
Maleic anhydride	Inhalation	endocrine system | hematopoietic system | nervous system | kidney and/or bladder | heart | liver | eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
Maleic anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
Maleic anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
Maleic anhydride	Ingestion	heart | nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
Maleic anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
Maleic anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
Maleic anhydride	Ingestion	skin | endocrine system | immune	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

		system | eyes | respiratory system				

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity
Ecotoxic to the aquatic environment.
Acute Aquatic Toxicity: Category 3

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Soybean oil	8001-22-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Butadiene-maleic anhydride copolymer	25655-35-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Green algae	Endpoint not reached	72 hours	EbC50	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Water flea	Experimental	24 hours	No tox obs at lmt of water sol	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Green algae	Endpoint not reached	72 hours	NOEC	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Rape	Experimental	21 days	EC50	909 mg/kg (Dry Weight)
Soybean oil, epoxidised	8013-07-8	Redworm	Experimental	56 days	NOEC	1,000 mg/kg (Dry Weight)
Soybean oil, epoxidised	8013-07-8	Soil microbes	Experimental	28 days	EC50	402 mg/kg (Dry Weight)
2,6-Di-tert-butyl-p-cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
Maleic anhydride	108-31-6	Bacteria	Experimental	18 hours	EC10	44.6 mg/l
Maleic anhydride	108-31-6	Rainbow trout	Experimental	96 hours	LC50	75 mg/l
Maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC50	74.4 mg/l
Maleic anhydride	108-31-6	Water flea	Hydrolysis Product	48 hours	EC50	93.8 mg/l
Maleic anhydride	108-31-6	Water flea	Experimental	21 days	NOEC	10 mg/l
Maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC10	11.8 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Soybean oil	8001-22-7	Experimental Biodegradation	28 days	CO2 evolution	76 %CO2 evolution/THCO2 evolution	
Butadiene-maleic anhydride copolymer	25655-35-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Experimental Biodegradation	28 days	CO2 evolution	92 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Soybean oil, epoxidised	8013-07-8	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not availbl-	N/A	N/A	N/A	N/A

		insufficient				
Maleic anhydride	108-31-6	Hydrolysis product Biodegradation	25 days	CO2 evolution	>90 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Maleic anhydride	108-31-6	Experimental Hydrolysis		Hydrolytic half-life	0.37 minutes (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Soybean oil	8001-22-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Butadiene-maleic anhydride copolymer	25655-35-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Experimental Bioconcentration		Log Kow	>6.2	OECD 117 log Kow HPLC method
2,6-Di-tert-butyl-p-cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
Maleic anhydride	108-31-6	Experimental Bioconcentration		Log Kow	-2.61	OECD 107 log Kow shke flsk mtd
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil
Please contact manufacturer for more details

12.5 Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods
In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport
UN No.: Not applicable.
Proper Shipping Name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.

Hazchem Code: Not applicable.
IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport
UN No.: Not applicable.
Proper Shipping Name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport
UN No.: Not applicable.
Proper Shipping Name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number	HSR002670
Group standard name	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020
HSNO Hazard classification	Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status
All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1

	substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information

Revision information:
Complete document review.

Document group:	29-0076-9	**Version number:**	3.00
Issue Date:	19/05/2025	**Supersedes date:**	24/01/2021

Key to abbreviations and acronyms
GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017
HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz

Safety Data Sheet

© 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	29-0077-7	**Version number:**	3.00
Issue Date:	19/05/2025	**Supersedes date:**	20/01/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier
3M™ Scotchcast™ Easy Dispenser 250 Part B

1.2. Recommended use and restrictions on use

Recommended use
Electrical

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number
24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.
Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture
Reproductive Toxicity: Category 2
Hazardous to the aquatic environment acute: Category 1
Hazardous to the aquatic environment chronic: Category 1

2.2. Label elements
SIGNAL WORD
Warning

Symbols:
Health Hazard |Environment |

Pictograms

HAZARD STATEMENTS:

H361	Suspected of damaging fertility or the unborn child.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response

P308 + P313	IF exposed or concerned: Get medical advice/attention.
P391	Collect spillage.

Storage

P405	Store locked up.

Disposal

P501	Dispose of contents/container via an approved hazardous waste disposal contractor.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Hydrotreated heavy naphthenic petroleum distillates	64742-52-5	60 - 90
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	10 - 30
N-Methyldidecylamine	7396-58-9	3 - 7
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	< 0.25
Methyldioctylamine	4455-26-9	< 0.25

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: 3Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators…) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Certified handler
Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Paraffin oil	64742-52-5	New Zealand WES	TWA(as mist)(8 hours):5 mg/m3;STEL(as mist)(15 minutes):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
New Zealand WES : New Zealand Workplace Exposure Standards.
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
ppm: parts per million
mg/m^3: milligrams per cubic metre
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection
None required.

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Clear Amber
Odour	Mild Aliphatic hydrocarbon
Odour threshold	*No data available.*
pH	*Not applicable.*
Melting point/Freezing point	*Not applicable.*
Boiling point/Initial boiling point/Boiling range	>=260 ºC
Flash point	>=232.2 ºC [*Test Method:*Closed Cup]
Evaporation rate	*No data available.*
Flammability	Not applicable.
Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Vapour pressure	<=133.3 Pa [@ 55 ºC]
Relative Vapour Density	*No data available.*
Density	0.94 g/ml
Relative density	0.94 [*Ref Std:*WATER=1]
Water solubility	<=1 % [@ 77 ºF]
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Autoignition temperature	>=260 ºC
Decomposition temperature	*No data available.*
Kinematic Viscosity	665 mm²/sec
Volatile organic compounds (VOC)	*No data available.*
Percent volatile	*No data available.*
VOC less H2O & exempt solvents	*No data available.*
Molecular weight	*No data available.*

Particle Characteristics	*Not applicable.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials
Strong acids.
Strong bases.
Strong oxidising agents.
Reducing agents.

10.6 Hazardous decomposition products

Substance	Condition
Aldehydes.	Oxidation, heat or reaction
Hydrocarbons.	Oxidation, heat or reaction
Carbon monoxide.	Oxidation, heat or reaction
Carbon dioxide.	Oxidation, heat or reaction
Irritant vapours or gases.	Oxidation, heat or reaction
Oxides of nitrogen.	Oxidation, heat or reaction
Toxic vapour, gas, particulate.	Oxidation, heat or reaction

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
No health effects are expected.

Skin contact
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated heavy naphthenic petroleum distillates	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrotreated heavy naphthenic petroleum distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Dermal		LD50 estimated to be > 5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
N-Methyldidecylamine	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-Methyldidecylamine	Ingestion	Rat	LD50 990 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Hydrotreated heavy naphthenic petroleum distillates	Rabbit	Minimal irritation
N-Methyldidecylamine	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Hydrotreated heavy naphthenic petroleum distillates	Rabbit	Mild irritant
N-Methyldidecylamine	Rabbit	Mild irritant

Sensitisation:

Skin Sensitisation

Name	Species	Value
Overall product	Guinea pig	Not classified
Hydrotreated heavy naphthenic petroleum distillates	Guinea pig	Not classified
N-Methyldidecylamine	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
N-Methyldidecylamine	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydrotreated heavy naphthenic petroleum distillates	Ingestion	Rat	Not carcinogenic
Hydrotreated heavy naphthenic petroleum distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
N-Methyldidecylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 50 mg/kg/day	29 days
N-Methyldidecylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 30 mg/kg/day	premating into lactation

N-Methyldidecylamine	Ingestion	Toxic to development	Rat	NOAEL 30 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated heavy naphthenic petroleum distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
N-Methyldidecylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
N-Methyldidecylamine	Ingestion	gastrointestinal tract | respiratory system	Not classified	Rat	NOAEL 30 mg/kg/day	29 days
N-Methyldidecylamine	Ingestion	heart | endocrine system | hematopoietic system | liver | immune system | nervous system | kidney and/or bladder	Not classified	Rat	NOAEL 50 mg/kg/day	29 days

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity
Ecotoxic to the aquatic environment.
Acute Aquatic Toxicity: Category 1
Chronic Aquatic Toxicity: Category 1

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Hydrotreated heavy naphthenic petroleum distillates	64742-52-5	Green algae	Estimated	96 hours	EC50	>100 mg/l
Hydrotreated heavy naphthenic	64742-52-5	Water flea	Estimated	48 hours	EC50	>100 mg/l

petroleum distillates						
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Activated sludge	Experimental	3 hours	EC50	948 mg/l
N-Methyldidecylamine	7396-58-9	Green algae	Experimental	72 hours	ErC50	0.004 mg/l
N-Methyldidecylamine	7396-58-9	Rainbow trout	Experimental	96 hours	LC50	0.41 mg/l
N-Methyldidecylamine	7396-58-9	Water flea	Experimental	48 hours	EC50	0.024 mg/l
N-Methyldidecylamine	7396-58-9	Green algae	Experimental	72 hours	NOEC	0.002 mg/l
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Green algae	Analogous Compound	72 hours	ErC50	0.004 mg/l
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Rainbow trout	Analogous Compound	96 hours	LC50	0.41 mg/l
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Water flea	Analogous Compound	48 hours	EC50	0.024 mg/l
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Green algae	Analogous Compound	72 hours	NOEC	0.002 mg/l
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Activated sludge	Analogous Compound	3 hours	EC50	948 mg/l
Methyldioctylamine	4455-26-9	Green algae	Analogous Compound	72 hours	ErC50	0.004 mg/l
Methyldioctylamine	4455-26-9	Rainbow trout	Analogous Compound	96 hours	LC50	0.41 mg/l
Methyldioctylamine	4455-26-9	Water flea	Analogous Compound	48 hours	EC50	0.024 mg/l
Methyldioctylamine	4455-26-9	Green algae	Analogous Compound	72 hours	NOEC	0.002 mg/l
Methyldioctylamine	4455-26-9	Activated sludge	Analogous Compound	3 hours	EC50	948 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol

Hydrotreated heavy naphthenic petroleum distillates	64742-52-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Experimental Biodegradation	28 days	CO2 evolution	74 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Analogous Compound Biodegradation	28 days	CO2 evolution	74 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Methyldioctylamine	4455-26-9	Analogous Compound Biodegradation	28 days	CO2 evolution	74 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hydrotreated heavy naphthenic petroleum distillates	64742-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Modeled Bioconcentration		Bioaccumulation factor	405	Episuite™
N-Methyldidecylamine	7396-58-9	Modeled Bioconcentration		Log Kow	8.8	Episuite™
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Modeled Bioconcentration		Bioaccumulation factor	7	Catalogic™
1-Dodecanamine, N-dodecyl-N-methyl-	2915-90-4	Modeled Bioconcentration		Log Kow	10.84	Episuite™
Methyldioctyla	4455-26-9	Modeled		Bioaccumulatio	6	Catalogic™

mine		Bioconcentration		n factor		
Methyldioctylamine	4455-26-9	Modeled Bioconcentration		Log Kow	6.91	Episuite™

12.4. Mobility in soil
Please contact manufacturer for more details

12.5 Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods
In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport
UN No.: UN3082
Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ,
(N-methyldidecylamine)
Class/Division: 9
Sub Risk: Not applicable.
Packing Group: III

Hazchem Code: 3Z
IERG: 47

International Air Transport Association (IATA) - Air Transport
UN No.: UN3082
Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ,
(N-methyldidecylamine)
Class/Division: 9
Sub Risk: Not applicable.
Packing Group: III
Special Instructions: Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport
UN No.: UN3082
Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ,
(N-methyldidecylamine)
Class/Division: 9
Sub Risk: Not applicable.

Packing Group: III
Marine Pollutant: Not applicable.
Special Instructions: Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

SECTION 15: Regulatory information

HSNO Approval number	HSR002670
Group standard name	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020
HSNO Hazard classification	Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status
All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information

Revision information:
Complete document review.

Document group:	29-0077-7	**Version number:**	3.00
Issue Date:	19/05/2025	**Supersedes date:**	20/01/2021

Key to abbreviations and acronyms
GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz