Safety Data Sheet

Copyright,2025, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	21-7498-5	**Version Number:**	3.00
Issue Date:	27/05/2025	**Supercedes Date:**	28/11/2023

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier
3M™ Finesse-it™ Polish Professional Finish

Product Identification Numbers
JC-3100-3292-8

1.2. Recommended use and restrictions on use

Recommended use
Polish for Automotive Paints.

1.3. Supplier's details
ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number
+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Not classified as hazardous according to Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

2.2. Label elements
Signal word
Not applicable

Symbols
Not applicable

Pictograms
Not applicable

2.3. Other hazards
None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 90
Aluminum Oxide	1344-28-1	1 - 10
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	1 - 10
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	1 - 10
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	1 - 10
WHITE MINERAL OIL	8042-47-5	1 - 5
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	34398-01-1	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion

Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Particles (insoluble or poorly	1344-28-1	ACGIH	TWA(inhalable	

soluble) not otherwise specified, inhalable particles			particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-14-9	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
MINERAL OILS, HIGHLY-REFINED OILS	64742-47-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
OIL MIST, MINERAL	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
CMRG : Chemical Manufacturer's Recommended Guidelines
Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Slurry
Color	Light Purple
Odor	Solvent
Odor threshold	*No Data Available*
pH	7.5 - 8
Melting point/Freezing point	*Not Applicable*
Boiling point/Initial boiling point/Boiling range	100 ºC
Flash Point	No flash point [*Test Method:*Closed Cup] [*Details:*Seta Closed Cup Flash Point Tester]
Evaporation rate	*No Data Available*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	2,399.8 Pa [@ 20 ºC]
Relative Vapor Density	*No Data Available*
Density	0.96 - 0.98 g/ml
Relative Density	0.96 - 0.98 [*Ref Std:*WATER=1]
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*No Data Available*
Volatile Organic Compounds	20.7 % weight [*Details:*Calculated]
Percent volatile	90.4 % [*Details:*Calculated including water]
VOC Less H2O & Exempt Solvents	623.1 g/l [*Details:*Calculated]

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
No health effects are expected.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Ingestion	Rat	LD50 > 15,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.4 mg/l
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Dermal	similar compounds	LD50 > 5,000 mg/kg

HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	similar compounds	LD50 > 5,000 mg/kg
WHITE MINERAL OIL	Dermal	Rabbit	LD50 > 2,000 mg/kg
WHITE MINERAL OIL	Ingestion	Rat	LD50 > 5,000 mg/kg
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	Dermal	Rabbit	LD50 > 2,000 mg/kg
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	Ingestion	Rat	LD50 > 700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED PETROLEUM DISTILLATES	similar compounds	Mild irritant
Aluminum Oxide	Rabbit	No significant irritation
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	similar compounds	Mild irritant
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Mild irritant
WHITE MINERAL OIL	Rabbit	No significant irritation
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	similar health hazards	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED PETROLEUM DISTILLATES	similar compounds	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	similar compounds	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	No significant irritation
WHITE MINERAL OIL	Rabbit	Mild irritant
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	Professional judgement	Corrosive

Sensitization:

Skin Sensitization

Name	Species	Value
HYDROTREATED PETROLEUM DISTILLATES	similar compounds	Not classified
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	similar compounds	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compoun	Not classified

	ds	
WHITE MINERAL OIL	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED PETROLEUM DISTILLATES	In Vitro	Not mutagenic
Aluminum Oxide	In Vitro	Not mutagenic
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
WHITE MINERAL OIL	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
WHITE MINERAL OIL	Dermal	Mouse	Not carcinogenic
WHITE MINERAL OIL	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
WHITE MINERAL OIL	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL Not available	
HYDROTREATED PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED PETROLEUM	Inhalation	liver | kidney and/or bladder | endocrine	Not classified	Rat	NOAEL 6 mg/l	13 weeks

DISTILLATES		system | gastrointestinal tract | bone, teeth, nails, and/or hair | hematopoietic system | muscles | nervous system | respiratory system | vascular system				
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Ingestion	hematopoietic system | eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
WHITE MINERAL OIL	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
WHITE MINERAL OIL	Ingestion	liver | immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
HYDROTREATED PETROLEUM DISTILLATES	Aspiration hazard
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	Aspiration hazard
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
WHITE MINERAL OIL	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:
GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Aluminum Oxide	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Rainbow Trout	Estimated	96 hours	LL50	>1,000 mg/l
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Green algae	Estimated	72 hours	NOEL	>1,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green algae	Analogous Compound	72 hours	EL50	>1,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Analogous Compound	48 hours	EL50	>1,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Rainbow Trout	Experimental	96 hours	LL50	>788,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Scud	Experimental	96 hours	LL50	>10,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green algae	Analogous Compound	72 hours	NOEL	1,000 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Analogous Compound	21 days	NOEL	>1 mg/l
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Rainbow Trout	Experimental	96 hours	LL50	>1,000 mg/l
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Green algae	Experimental	72 hours	NOEL	100 mg/l
WHITE MINERAL OIL	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
WHITE MINERAL OIL	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
WHITE MINERAL OIL	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l

WHITE MINERAL OIL	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	34398-01-1	Green algae	Analogous Compound	72 hours	ErC50	0.43 mg/l
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	34398-01-1	Green algae	Analogous Compound	72 hours	NOEC	0.09 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Estimated Biodegradation	28 days	Biological Oxygen Demand	69 %BOD/ThOD	OECD 301F - Manometric Respiro
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Experimental Biodegradation	28 days	Biological Oxygen Demand	22 %BOD/ThOD	OECD 301F - Manometric Respiro
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	80% %BOD/ThOD	OECD 301F - Manometric Respiro
WHITE MINERAL OIL	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	34398-01-1	Modeled Biodegradation	28 days	Carbon dioxide evolution	95 %CO2 evolution/THCO2 evolution	Catalogic™

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
DISTILLATES (PETROLEUM) ACID TREATED, LIGHT	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREATED PETROLEUM DISTILLATES	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
WHITE MINERAL OIL	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OME	34398-01-1	Modeled Bioconcentration		Bioaccumulation Factor	50	Catalogic™

GA.-HYDROXY-						

12.4. Mobility in soil
Please contact manufacturer for more details

12.5 Other adverse effects
No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number: None assigned.
Proper Shipping Name: None assigned.
Technical Name: None assigned.
Hazard Class/Division: None assigned.
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number: None assigned.
Proper Shipping Name: None assigned.
Technical Name: None assigned.
Hazard Class/Division: None assigned.
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my