



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document Group: | 21-7498-5 | Version Number: | 3.00 |
| Issue Date: | 27/05/2025 | Supersedes Date: | 28/11/2023 |

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Finesse-it™ Polish Professional Finish

Product Identification Numbers

JC-3100-3292-8

1.2. Recommended use and restrictions on use

Recommended use

Polish for Automotive Paints.

1.3. Supplier's details

| | |
|-------------------|--|
| ADDRESS: | 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor |
| Telephone: | 03-7884 2888 |
| E Mail: | 3mmyehsr@mmm.com |
| Website: | www.3M.com.my |

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified as hazardous according to Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

2.2. Label elements

Signal word

Not applicable

Symbols

Not applicable

Pictograms

Not applicable

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt |
|---|-------------------|----------------|
| Water | 7732-18-5 | 60 - 90 |
| Aluminum Oxide | 1344-28-1 | 1 - 10 |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | 1 - 10 |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | 1 - 10 |
| HYDROTREATED PETROLEUM DISTILLATES | 64742-48-9 | 1 - 10 |
| WHITE MINERAL OIL | 8042-47-5 | 1 - 5 |
| POLY(OXY-1,2-ETHANEDIYL), ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | 34398-01-1 | < 1 |

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide

Condition

During Combustion

Carbon dioxide
Irritant Vapors or Gases

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------------------|------------|---------------|----------------------------------|--------------------------------|
| Aluminum Oxide | 1344-28-1 | Malaysia OELs | TWA (proposed)(8 hours):10 mg/m3 | |
| Aluminum, insoluble compounds | 1344-28-1 | ACGIH | TWA(respirable fraction):1 mg/m3 | A4: Not class. as human carcin |
| Particles (insoluble or poorly | 1344-28-1 | ACGIH | TWA(inhalable | |

| | | | | |
|---|------------|---------------|--|------------------------------------|
| soluble) not otherwise specified, inhalable particles | | | particulates):10 mg/m3 | |
| Particles (insoluble or poorly soluble) not otherwise specified, respirable particles | 1344-28-1 | ACGIH | TWA(respirable particles):3 mg/m3 | |
| JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR | 64742-14-9 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., SKIN |
| JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., SKIN |
| Kerosine (petroleum) | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | A3: Confirmed animal carcin., SKIN |
| MINERAL OILS, HIGHLY-REFINED OILS | 64742-47-8 | ACGIH | TWA(inhalable fraction):5 mg/m3 | A4: Not class. as human carcin |
| MINERAL OILS, HIGHLY-REFINED OILS | 8042-47-5 | ACGIH | TWA(inhalable fraction):5 mg/m3 | A4: Not class. as human carcin |
| OIL MIST, MINERAL | 8042-47-5 | Malaysia OELs | TWA(as mist)(8 hours):5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | Liquid |
| Specific Physical Form: | Slurry |
| Color | Light Purple |
| Odor | Solvent |
| Odor threshold | No Data Available |
| pH | 7.5 - 8 |
| Melting point/Freezing point | Not Applicable |
| Boiling point/Initial boiling point/Boiling range | 100 °C |
| Flash Point | No flash point [Test Method:Closed Cup] [Details:Seta Closed Cup Flash Point Tester] |
| Evaporation rate | No Data Available |
| Flammability | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | 2,399.8 Pa [@ 20 °C] |
| Relative Vapor Density | No Data Available |
| Density | 0.96 - 0.98 g/ml |
| Relative Density | 0.96 - 0.98 [Ref Std:WATER=1] |
| Water solubility | No Data Available |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | No Data Available |
| Kinematic Viscosity | No Data Available |
| Volatile Organic Compounds | 20.7 % weight [Details:Calculated] |
| Percent volatile | 90.4 % [Details:Calculated including water] |
| VOC Less H2O & Exempt Solvents | 623.1 g/l [Details:Calculated] |

| | |
|--------------------------|----------------|
| Particle Characteristics | Not Applicable |
|--------------------------|----------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products**Substance**

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|--------------------------------|-------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| HYDROTREATED PETROLEUM DISTILLATES | Ingestion | Rat | LD50 > 5,000 mg/kg |
| HYDROTREATED PETROLEUM DISTILLATES | Dermal | similar compounds | LD50 > 5,000 mg/kg |
| Aluminum Oxide | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum Oxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 2.3 mg/l |
| Aluminum Oxide | Ingestion | Rat | LD50 > 5,000 mg/kg |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Ingestion | Rat | LD50 > 15,000 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.4 mg/l |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Dermal | similar compounds | LD50 > 5,000 mg/kg |

| | | | |
|---|-----------|-------------------|--------------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Dermal | similar compounds | LD50 > 5,000 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | similar compounds | LD50 > 5,000 mg/kg |
| WHITE MINERAL OIL | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| WHITE MINERAL OIL | Ingestion | Rat | LD50 > 5,000 mg/kg |
| POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | Ingestion | Rat | LD50 > 700 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| HYDROTREATED PETROLEUM DISTILLATES | similar compounds | Mild irritant |
| Aluminum Oxide | Rabbit | No significant irritation |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | similar compounds | Mild irritant |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | Mild irritant |
| WHITE MINERAL OIL | Rabbit | No significant irritation |
| POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | similar health hazards | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| HYDROTREATED PETROLEUM DISTILLATES | similar compounds | No significant irritation |
| Aluminum Oxide | Rabbit | No significant irritation |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | similar compounds | No significant irritation |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | No significant irritation |
| WHITE MINERAL OIL | Rabbit | Mild irritant |
| POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | Professional judgement | Corrosive |

Sensitization:

Skin Sensitization

| Name | Species | Value |
|---|-------------------|----------------|
| HYDROTREATED PETROLEUM DISTILLATES | similar compounds | Not classified |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | similar compounds | Not classified |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | Not classified |

| | | |
|-------------------|------------|----------------|
| | ds | |
| WHITE MINERAL OIL | Guinea pig | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| HYDROTREATED PETROLEUM DISTILLATES | In Vitro | Not mutagenic |
| Aluminum Oxide | In Vitro | Not mutagenic |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | In Vitro | Not mutagenic |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | In Vitro | Not mutagenic |
| WHITE MINERAL OIL | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|-------------------|------------|-------------------------|------------------|
| Aluminum Oxide | Inhalation | Rat | Not carcinogenic |
| WHITE MINERAL OIL | Dermal | Mouse | Not carcinogenic |
| WHITE MINERAL OIL | Inhalation | Multiple animal species | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-------------------|-----------|--|---------|-----------------------|-------------------|
| WHITE MINERAL OIL | Ingestion | Not classified for female reproduction | Rat | NOAEL 4,350 mg/kg/day | 13 weeks |
| WHITE MINERAL OIL | Ingestion | Not classified for male reproduction | Rat | NOAEL 4,350 mg/kg/day | 13 weeks |
| WHITE MINERAL OIL | Ingestion | Not classified for development | Rat | NOAEL 4,350 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|-----------------------------------|--|------------------------|---------------------|-------------------|
| HYDROTREATED PETROLEUM DISTILLATES | Inhalation | central nervous system depression | May cause drowsiness or dizziness | similar compounds | NOAEL Not available | |
| HYDROTREATED PETROLEUM DISTILLATES | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| POLY(OXY-1,2-ETHANEDIYL),.ALPHA.-UNDECYL-.OMEGA.-HYDROXY- | Inhalation | respiratory irritation | May cause respiratory irritation | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------|------------|---|----------------|---------|--------------|-------------------|
| HYDROTREATED PETROLEUM | Inhalation | liver kidney and/or bladder endocrine | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |

| | | | | | | |
|---|------------|--|--|-------|-----------------------|-----------------------|
| DISTILLATES | | system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system muscles nervous system respiratory system vascular system | | | | |
| Aluminum Oxide | Inhalation | pneumoconiosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Aluminum Oxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Inhalation | liver | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.5 mg/l | 13 weeks |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Ingestion | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 100 mg/kg/day | 13 weeks |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Ingestion | hematopoietic system eyes | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| WHITE MINERAL OIL | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 1,381 mg/kg/day | 90 days |
| WHITE MINERAL OIL | Ingestion | liver immune system | Not classified | Rat | NOAEL 1,336 mg/kg/day | 90 days |

Aspiration Hazard

| Name | Value |
|---|-------------------|
| HYDROTREATED PETROLEUM DISTILLATES | Aspiration hazard |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | Aspiration hazard |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Aspiration hazard |
| WHITE MINERAL OIL | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

| Material | Cas # | Organism | Type | Exposure | Test Endpoint | Test Result |
|---|------------|---------------|--------------------|----------|---------------|---------------|
| Aluminum Oxide | 1344-28-1 | N/A | Experimental | 96 hours | LC50 | >100 mg/l |
| Aluminum Oxide | 1344-28-1 | Green algae | Experimental | 72 hours | EC50 | >100 mg/l |
| Aluminum Oxide | 1344-28-1 | Water flea | Experimental | 48 hours | LC50 | >100 mg/l |
| Aluminum Oxide | 1344-28-1 | Green algae | Experimental | 72 hours | NOEC | >100 mg/l |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Green algae | Estimated | 72 hours | EL50 | >1,000 mg/l |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Rainbow Trout | Estimated | 96 hours | LL50 | >1,000 mg/l |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Water flea | Estimated | 48 hours | EL50 | >1,000 mg/l |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Green algae | Estimated | 72 hours | NOEL | >1,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Green algae | Analogous Compound | 72 hours | EL50 | >1,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Water flea | Analogous Compound | 48 hours | EL50 | >1,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Rainbow Trout | Experimental | 96 hours | LL50 | >788,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Scud | Experimental | 96 hours | LL50 | >10,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Green algae | Analogous Compound | 72 hours | NOEL | 1,000 mg/l |
| HYDROTREATE D LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Water flea | Analogous Compound | 21 days | NOEL | >1 mg/l |
| HYDROTREATE D PETROLEUM DISTILLATES | 64742-48-9 | Green algae | Experimental | 72 hours | EL50 | >1,000 mg/l |
| HYDROTREATE D PETROLEUM DISTILLATES | 64742-48-9 | Rainbow Trout | Experimental | 96 hours | LL50 | >1,000 mg/l |
| HYDROTREATE D PETROLEUM DISTILLATES | 64742-48-9 | Water flea | Experimental | 48 hours | EL50 | >1,000 mg/l |
| HYDROTREATE D PETROLEUM DISTILLATES | 64742-48-9 | Green algae | Experimental | 72 hours | NOEL | 100 mg/l |
| WHITE MINERAL OIL | 8042-47-5 | Water flea | Analogous Compound | 48 hours | EL50 | >100 mg/l |
| WHITE MINERAL OIL | 8042-47-5 | Bluegill | Experimental | 96 hours | LL50 | >100 mg/l |
| WHITE MINERAL OIL | 8042-47-5 | Green algae | Analogous Compound | 72 hours | NOEL | 100 mg/l |

| | | | | | | |
|--|------------|-------------|--------------------|----------|-------|-----------|
| WHITE MINERAL OIL | 8042-47-5 | Water flea | Analogous Compound | 21 days | NOEL | >100 mg/l |
| POLY(OXY-1,2-ETHANEDIYL),,A LPHA.-UNDECYL-OME GA.-HYDROXY- | 34398-01-1 | Green algae | Analogous Compound | 72 hours | ErC50 | 0.43 mg/l |
| POLY(OXY-1,2-ETHANEDIYL),,A LPHA.-UNDECYL-OME GA.-HYDROXY- | 34398-01-1 | Green algae | Analogous Compound | 72 hours | NOEC | 0.09 mg/l |

12.2. Persistence and degradability

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|--|------------|------------------------------------|----------|--------------------------|-----------------------------------|--------------------------------|
| Aluminum Oxide | 1344-28-1 | Data not available or insufficient | N/A | N/A | N/A | N/A |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Estimated Biodegradation | 28 days | Biological Oxygen Demand | 69 %BOD/ThOD | OECD 301F - Manometric Respiro |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 22 %BOD/ThOD | OECD 301F - Manometric Respiro |
| HYDROTREATED PETROLEUM DISTILLATES | 64742-48-9 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 80% %BOD/ThOD | OECD 301F - Manometric Respiro |
| WHITE MINERAL OIL | 8042-47-5 | Experimental Biodegradation | 28 days | Carbon dioxide evolution | 0 %CO2 evolution/THCO2 evolution | OECD 301B - Mod. Sturm or CO2 |
| POLY(OXY-1,2-ETHANEDIYL),,A LPHA.-UNDECYL-OME GA.-HYDROXY- | 34398-01-1 | Modeled Biodegradation | 28 days | Carbon dioxide evolution | 95 %CO2 evolution/THCO2 evolution | Catalogic™ |

12.3. Bioaccumulative potential

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|---|------------|---|----------|------------------------|-------------|------------|
| Aluminum Oxide | 1344-28-1 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| DISTILLATES (PETROLEUM) ACID TREATED, LIGHT | 64742-14-9 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| HYDROTREATED PETROLEUM DISTILLATES | 64742-48-9 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| WHITE MINERAL OIL | 8042-47-5 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| POLY(OXY-1,2-ETHANEDIYL),,A LPHA.-UNDECYL-OME | 34398-01-1 | Modeled Bioconcentration | | Bioaccumulation Factor | 50 | Catalogic™ |

GA.-HYDROXY-

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)**UN Number:**None assigned.**Proper Shipping Name:**None assigned.**Technical Name:**None assigned.**Hazard Class/Division:**None assigned.**Subsidiary Risk:**None assigned.**Packing Group:**None assigned.**Limited Quantity:**None assigned.**Marine Pollutant:** None assigned.**Marine Pollutant Technical Name:** None assigned.**Other Dangerous Goods Descriptions:**

None assigned.

Air Transport (IATA)**UN Number:**None assigned.**Proper Shipping Name:**None assigned.**Technical Name:**None assigned.**Hazard Class/Division:**None assigned.**Subsidiary Risk:**None assigned.**Packing Group:**None assigned.**Limited Quantity:**None assigned.**Marine Pollutant:** None assigned.**Marine Pollutant Technical Name:** None assigned.**Other Dangerous Goods Descriptions:**

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my