

Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	40-1401-5	Version number:	6.00
Revision date:	04/03/2025	Supersedes date:	20/12/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M[™] Scotch-Weld[™] Composite Surfacing and Lightning Strike Protection Film AF 536

Product Identification	1 Numbers			
UU-0110-1508-6	UU-0110-1813-0	UU-0110-1814-8	UU-0110-1815-5	UU-0110-1816-3
UU-0110-1817-1	UU-0111-1151-3	UU-0112-0928-3	UU-0112-0929-1	UU-0112-0930-9
UU-0112-0941-6				
7100231631	7100230081	7100230123	7100230192	7100230191
7100230122	7100238767	7100244135	7100244136	7100244137
7100244138				

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial use.

1.3. Details of the su	pplier of the safety data sheet
Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	tox.uk@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases

where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The eye damage/irritation classification is not applied due to the nature of this product (adhesive film).

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Germ Cell Mutagenicity, Category 2 - Muta. 2; H341 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	10 - 35
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bis-, polymer with 1,1'- methylenebis[isocyanatobenzene]	60684-77-7		5 - 20
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9		2 - 10
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	28390-91-2	500-062-3	0.1 - 5
Adipohydrazide	1071-93-8	213-999-5	< 1

HAZARD STATEMENTS:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

H411 Tox	ic to aquatic life	e with long lasting	geffects.
----------	--------------------	---------------------	-----------

PRECAUTIONARY STATEMENTS

Prevention:P273Avoid release to the environment.P280EWear protective gloves.Response:P333 + P313If skin irritation or rash occurs: Get medical advice/attention.P391Collect spillage.

Contains 27% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Copper screen	None	30 - 55	Substance not classified as hazardous
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	10 - 35	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Oxirane, 2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]bis-, polymer with 1,1'- methylenebis[isocyanatobenzene]	(CAS-No.) 60684-77-7	5 - 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
FIBERGLASS	None	1 - 15	Substance not classified as hazardous
Bisphenol A - epichlorhydrin - formaldehyde copolymer	(CAS-No.) 28906-96-9	2 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Flexiblizer	Trade Secret	0.1 - 10	Substance not classified as hazardous
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	1 - 10	Substance with a national occupational exposure limit
CURATIVE 1	Trade Secret	0.1 - 5	Substance not classified as hazardous
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	(CAS-No.) 28390-91-2 (EC-No.) 500-062-3	0.1 - 5	Aquatic Chronic 2, H411 Skin Sens. 1, H317 Muta. 2, H341
Filler	Trade Secret	0.1 - 5	Substance with a national occupational exposure limit
Adipohydrazide	(CAS-No.) 1071-93-8 (EC-No.) 213-999-5	< 1	Aquatic Chronic 2, H411 Skin Sens. 1B, H317
4-methylpentan-2-one	(CAS-No.) 108-10-1 (EC-No.) 203-550-1	< 0.5	Flam. Liq. 2, H225 Acute Tox. 4, H332(LC50 = 11 mg/l **ATE values per GB MCL**) Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen gas.	During combustion.
Hydrogen Chloride	During combustion.
Hydrogen cyanide.	During combustion.

Ammonia Oxides of nitrogen. Phosgene During combustion. During combustion. During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing

dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4-methylpentan-2-one	108-10-1	UK HSE	TWA:208 mg/m3(50	SKIN

Oxide glass chemicals	65997-17-3	Manufacturer determined	ppm);STEL:416 mg/m3(100 ppm) TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10
Filler	Trade Secret	UK HSE	mg/m3 TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable dust):6 mg/m3
UK HSE : UK Health and Safety Commiss TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling	ion		

Biological limit values

Ingredient	CAS	Agency	Determinant	Biological	Sampling	Value	Additional
	Nbr			Specimen	Time		comments
4-methylpentan-2-	108-10-	UK EH40	4-Methyl	Urine	EOS	20 umol/L	
one	1	BMGVs	pentan-2-one				
UK EH40 BMGVs : UK.	EH40 Biolo	gical Monitoring G	uidance Values (BM	1GVs)			
EOS: End of shift.							

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Film
Colour	Beige
Odor	Low Epoxy
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	Not applicable.
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	No flash point
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	Not applicable.
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Density	Not applicable.
Relative density	No data available.
Relative Vapour Density	Nil
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rate Molecular weight Percent volatile No data available. Not applicable. Not applicable. 0 - 2 % weight [Details:Max 2% in the AF 536 film, % reduced due to copper content]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid Heat.

10.5 Incompatible materials Amines.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-	Dermal	Professio	LD50 estimated to be $> 5,000 \text{ mg/kg}$
phenyleneoxymethylene)]bis-, polymer with 1,1'-		nal	
methylenebis[isocyanatobenzene]		judgeme	
		nt	
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-	Inhalation-	Professio	LC50 estimated to be > 12.5 mg/l
phenyleneoxymethylene)]bis-, polymer with 1,1'-	Dust/Mist	nal	
methylenebis[isocyanatobenzene]		judgeme	
O_{1}	To a set i so	nt Professio	
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1- phenyleneoxymethylene)]bis-, polymer with 1,1'-	Ingestion	nal	LD50 estimated to be $>$ 5,000 mg/kg
methylenebis[isocyanatobenzene]		judgeme	
neuryieneois[isoeyunutobenzene]		nt	
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Ingestion	Rat	LD50 > 2,000 mg/kg
Flexiblizer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Flexiblizer	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzenamine, 4,4'-methylenebis-, polymer with	Dermal	Rabbit	LD50 > 3,000 mg/kg
(chloromethyl)oxirane			
Benzenamine, 4,4'-methylenebis-, polymer with	Ingestion	Rat	LD50 > 5,000 mg/kg
(chloromethyl)oxirane			
CURATIVE 1	Dermal	Rabbit	LD50 > 10,000 mg/kg
CURATIVE 1	Ingestion	Rat	LD50 > 30,000 mg/kg
Filler	Dermal	Rabbit	LD50 > 5,000 mg/kg
Filler	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Filler	Ingestion	Rat	LD50 > 5,110 mg/kg
Adipohydrazide	Ingestion	Mouse	LD50 > 5,000 mg/kg
4-methylpentan-2-one	Dermal	Rabbit	LD50 > 16,000 mg/kg
4-methylpentan-2-one	Inhalation-	Rat	LC50 11 mg/l
	Vapour (4		
4 4 1 4 2	hours)	D (
4-methylpentan-2-one	Ingestion	Rat	LD50 3,038 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, polymer with 1,1'-methylenebis[isocyanatobenzene]	Professio nal judgemen t	Irritant
Oxide glass chemicals	Professio nal judgemen t	No significant irritation

Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professio	Irritant
	nal	
	judgemen	
	t	
Flexiblizer	Professio	Minimal irritation
	nal	
	judgemen	
	t	
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Rabbit	No significant irritation
CURATIVE 1	Human	Minimal irritation
	and	
	animal	
Filler	Rabbit	No significant irritation
Adipohydrazide	Rabbit	No significant irritation
4-methylpentan-2-one	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
	D 11.4	M 1 4 5 7 4
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-,	Professio	Severe irritant
polymer with 1,1'-methylenebis[isocyanatobenzene]	nal	
	judgemen	
	t	
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professio	Severe irritant
	nal	
	judgemen	
	t	
Flexiblizer	Professio	Mild irritant
	nal	
	judgemen	
	t	
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Rabbit	Mild irritant
CURATIVE 1	Professio	Mild irritant
	nal	
	judgemen	
	t	
Filler	Rabbit	No significant irritation
4-methylpentan-2-one	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, polymer with 1,1'-methylenebis[isocyanatobenzene]	Professio nal judgemen t	Sensitising
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professio nal judgemen t	Sensitising
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Human and animal	Sensitising
CURATIVE 1	Guinea pig	Not classified
Filler	Human and animal	Not classified

Adipohydrazide	Guinea	Sensitising
	pig	
4-methylpentan-2-one	Guinea	Not classified
	pig	

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	In vivo	Mutagenic		
CURATIVE 1	In Vitro	Not mutagenic		
Filler	In Vitro	Not mutagenic		
Adipohydrazide	In vivo	Not mutagenic		
4-methylpentan-2-one	In Vitro	Not mutagenic		

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Oxide glass chemicals	Inhalation	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
CURATIVE 1	Ingestion	Rat	Not carcinogenic
Filler	Not	Mouse	Some positive data exist, but the data are not
	specified.		sufficient for classification
4-methylpentan-2-one	Inhalation	Multiple	Carcinogenic.
		animal	
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Benzenamine, 4,4'-methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	Not classified for development	Rat	NOAEL 90 mg/kg/day	during gestation
CURATIVE 1	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
CURATIVE 1	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
CURATIVE 1	Ingestion	Not classified for development	Rat	NOAEL 1,000	premating & during

				mg/kg/day	gestation
Filler	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Filler	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Filler	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
4-methylpentan-2-one	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professio nal judgeme nt	NOAEL not available	
4-methylpentan-2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
4-methylpentan-2-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
4-methylpentan-2-one	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
4-methylpentan-2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	13 weeks
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxirane	Ingestion	gastrointestinal tract liver immune system nervous system eyes kidney and/or	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks

		bladder				
CURATIVE 1	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
Filler	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
4-methylpentan-2-one	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
4-methylpentan-2-one	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
4-methylpentan-2-one	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
4-methylpentan-2-one	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
4-methylpentan-2-one	Inhalation	endocrine system hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
4-methylpentan-2-one	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
4-methylpentan-2-one	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Ingestion	heart immune system muscles nervous system respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days

Aspiration Hazard

Name	Value
4-methylpentan-2-one	Some positive data exist, but the data are not sufficient for
	classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Туре	Exposure	Test endpoint	Test result
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l

bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Oxirane, 2,2'-[(1- methylethylidene)b is(4,1- phenyleneoxymeth ylene)]bis-, polymer with 1,1'- methylenebis[isocy anatobenzene]	60684-77-7	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Flexiblizer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Bacteria	Experimental	24 hours	IC50	>10,000 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Common Carp	Experimental	96 hours	LC50	7 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Green algae	Experimental	72 hours	EC50	>11 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Water flea	Experimental	48 hours	EC50	4.7 mg/l
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Green algae	Experimental	72 hours	EC10	2.4 mg/l
CURATIVE 1	Trade Secret	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
CURATIVE 1	Trade Secret	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
		1	1	40.1	5050	2 177 /1
CURATIVE 1	Trade Secret	Water flea	Experimental	48 hours	EC50	3,177 mg/l

CURATIVE 1	Trade Secret	Water flea	Experimental	21 days	NOEC	25 mg/l
CURATIVE 1	Trade Secret	Redworm	Experimental	14 days	LC50	>3,200 mg/kg (Dry Weight)
Filler	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Adipohydrazide	1071-93-8	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Adipohydrazide	1071-93-8	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	ErC50	8.7 mg/l
Adipohydrazide	1071-93-8	Water flea	Experimental	48 hours	EC50	>=106 mg/l
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
4-methylpentan-2- one	108-10-1	Green algae	Experimental	96 hours	EC50	400 mg/l
4-methylpentan-2- one	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
4-methylpentan-2- one	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
4-methylpentan-2- one	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
4-methylpentan-2- one	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
4-methylpentan-2- one	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Oxirane, 2,2'-[(1- methylethylidene)b is(4,1- phenyleneoxymeth ylene)]bis-, polymer with 1,1'- methylenebis[isocy anatobenzene]	60684-77-7	Estimated Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Flexiblizer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Experimental Biodegradation	28 days	CO2 evolution	10 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
CURATIVE 1	Trade Secret	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 301E - Modif. OECD Screen
CURATIVE 1	Trade Secret	Experimental Aquatic Inherent Biodegrad.	14 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 302B Zahn- Wellens/EVPA
CURATIVE 1	Trade Secret	Experimental Biodegradation	61 days	CO2 evolution	1.1 %CO2 evolution/THCO2	OECD 309 Aero Sim Biod Water

					evolution	
Filler	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Adipohydrazide	1071-93-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	62.1 %removal of DOC	OECD 301E - Modif. OECD Screen
Adipohydrazide	1071-93-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)		OECD 111 Hydrolysis func of pH
4-methylpentan-2- one	108-10-1	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301F - Manometric respirometry
4-methylpentan-2- one	108-10-1	Experimental Photolysis		Photolytic half-life (in air)	2.3 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Oxirane, 2,2'-[(1- methylethylidene)b is(4,1- phenyleneoxymeth ylene)]bis-, polymer with 1,1'- methylenebis[isocy anatobenzene]	60684-77-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Modeled Bioconcentration		Bioaccumulation factor	5.7	Catalogic™
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Modeled Bioconcentration		Log Kow	≥5.7	Episuite™
Flexiblizer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Benzenamine, 4,4'- methylenebis-, polymer with (chloromethyl)oxir ane	28390-91-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
CURATIVE 1	Trade Secret	Experimental BCF - Fish	42 days	Bioaccumulation factor	<=3.1	OECD305-Bioconcentration
CURATIVE 1	Trade Secret	Experimental Bioconcentration		Log Kow	-0.52	OECD 107 log Kow shke flsk mtd
Filler	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Adipohydrazide	1071-93-8	Experimental Bioconcentration		Log Kow	-2.7	OECD 107 log Kow shke flsk mtd
4-methylpentan-2- one	108-10-1	Experimental Bioconcentration		Log Kow	1.9	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane		Modeled Mobility in Soil	Кос	450 l/kg	Episuite™
Bisphenol A - epichlorhydrin - formaldehyde		Modeled Mobility in Soil	Koc	≥3.5E+07 l/kg	Episuite™

copolymer					
CURATIVE 1	Trade Secret	Modeled Mobility in Soil	Koc	9 l/kg	Episuite TM
Adipohydrazide	1071-93-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite TM
4-methylpentan-2- one	108-10-1	Modeled Mobility in Soil	Koc	150 l/kg	Episuite TM

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN1845	UN1845	UN1845
14.2 UN proper shipping name	CARBON DIOXIDE, SOLID, AS COOLANT	CARBON DIOXIDE, SOLID	CARBON DIOXIDE, SOLID, AS COOLANT
14.3 Transport hazard class(es)	Not applicable.	Not applicable.	Not applicable.
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Not applicable.	Not applicable	Not applicable.
14.6 Special precautions for user	Please refer to the other sections of the SDS for	Please refer to the other sections of the SDS for further	Please refer to the other sections of the SDS for further information.

SECTION 14: Transportation information

	further information.	information.	
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	Not applicable.	Not applicable.	Not applicable.
Emergency Temperature	Not applicable.	Not applicable.	Not applicable.
ADR Classification Code	Not applicable.	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	Not applicable.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity <u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
4-methylpentan-2-one	108-10-1	Carc. 2	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain, UK Mandatory Classification and Labelling list
4-methylpentan-2-one	108-10-1	Grp. 2B: Possible human care.	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

Restriction status: listed in UK REACH Annex XVII Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Global inventory status

Contact 3M for more information.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic	200	500
environment		

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
		requirements	
4-methylpentan-2-one	108-10-1	10	50

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 15: Carcinogenicity information information was modified.

Section 1: Product name information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.