



## Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 27-0721-4      **Version number:** 10.00  
**Revision date:** 18/12/2025      **Supersedes date:** 14/12/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

3M™ Acryl-Green Spot Putty PN 05096

#### Product Identification Numbers

60-4550-4709-6

7000028276

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Automotive.

### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2  
**Telephone:** +353 1 280 3555  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com

### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

#### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318  
 Reproductive Toxicity, Category 2 - Repr. 2; H361d  
 Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) | GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
toluene	108-88-3	203-625-9	10 - 30
butan-1-ol	71-36-3	200-751-6	1 - 5

#### HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361d	Suspected of damaging the unborn child.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure: sensory organs.
H412	Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### General:

P102	Keep out of reach of children.
------	--------------------------------

##### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260G	Do not breathe vapours or dust.
P280I	Wear protective gloves, eye protection, face protection, and respiratory protection.

##### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

P370 + P378

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

18% of the mixture consists of components of unknown acute oral toxicity.

Contains 18% of components with unknown hazards to the aquatic environment.

**EU VOC Directive (2004/42/EC) labelling:** 2004/42/EC IIB(c)(540)

420g/l

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

### SECTION 3: Composition/information on ingredients

**3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	15 - 40	Substance with a national occupational exposure limit
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (REACH-No.) 01-2119471310-51	10 - 30	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Acrylic Polymers	None	7 - 13	Substance not classified as hazardous
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17	7 - 13	Substance with a national occupational exposure limit
Magnesium carbonate	(CAS-No.) 546-93-0 (EC-No.) 208-915-9	3 - 8	Substance with a national occupational exposure limit
Oxydipropyl dibenzoate	(CAS-No.) 27138-31-4 (EC-No.) 248-258-5 (REACH-No.) 01-2119529241-49	< 5.5	Aquatic Chronic 3, H412
Oxydiethylene dibenzoate	(CAS-No.) 120-55-8 (EC-No.) 204-407-6	< 5.5	Substance not classified as hazardous
Rheological Additive	Trade Secret	1 - 5	Substance not classified as hazardous

butan-1-ol	(CAS-No.) 71-36-3 (EC-No.) 200-751-6	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
Chlorite-group minerals	(CAS-No.) 1318-59-8 (EC-No.) 215-285-9	< 2	Substance not classified as hazardous
copper flakes (coated with aliphatic acid)	(CAS-No.) 7440-50-8 (EC-No.) 231-159-6	< 0.015	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and

personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m <sup>3</sup> (50 ppm);TWA(8 hours):50 ppm(192 mg/m <sup>3</sup> );STEL(15 minutes):384 mg/m <sup>3</sup> (100 ppm);STEL(15 minutes):100 ppm(384 mg/m <sup>3</sup> )	SKIN
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):4 mg/m <sup>3</sup>	
Talc	14807-96-6	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):0.8 mg/m <sup>3</sup>	
Dusts non-specific	546-93-0	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):4 mg/m <sup>3</sup>	
butan-1-ol	71-36-3	Ireland OELs	TWA(8 hours):20 ppm	
copper flakes (coated with aliphatic acid)	7440-50-8	Ireland OELs	TWA(as fume)(8 hours):0.2 mg/m <sup>3</sup> ;TWA(as dust or mist)(8 hours):1 mg/m <sup>3</sup> ;TWA(as Cu, fume)(8 hours):0.2 mg/m <sup>3</sup> ;TWA(as Cu dust or mist)(8 hours):1 mg/m <sup>3</sup>	as Cu dust

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
toluene		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	384 mg/kg bw/d
toluene		Worker	Inhalation, Long-term exposure (8 hours), Local effects	192 mg/m <sup>3</sup>
toluene		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	192 mg/m <sup>3</sup>

toluene		Worker	Inhalation, Short-term exposure, Local effects	384 mg/m <sup>3</sup>
toluene		Worker	Inhalation, Short-term exposure, Systemic effects	384 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
toluene		Agricultural soil	2.89 mg/kg d.w.
toluene		Freshwater	0.68 mg/l
toluene		Sewage Treatment Plant	13.61 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

## 8.2. Exposure controls

In addition, refer to the annex for more information.

### 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

#### Applicable Norms/Standards

Use eye protection conforming to EN 16321

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polyethylene	>0.30	=>8 hours
Polyvinyl alcohol (PVA).	>0.30	=>8 hours
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

#### Applicable Norms/Standards

Use gloves tested to EN 374

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Green
Odor	Solvent
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	>=93.3 °C
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	1 %
Flammable Limits(UEL)	13 %
Flash point	17.2 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	196,078 mm <sup>2</sup> /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=186,158.4 Pa [@ 55 °C ] [Details: MITS data]
Density	1.46 - 1.6 g/ml
Relative density	1.46 - 1.6 [Ref Std:WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

### 9.2. Other information

#### 9.2.2 Other safety characteristics

EU Volatile Organic Compounds

*No data available.*

Evaporation rate

*No data available.*

Percent volatile

27.6 % weight

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Sparks and/or flames.

Heat.

### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not specified.
Carbon dioxide.	Not specified.
Toxic vapour, gas, particulate.	Not specified.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests. Ocular effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects:

Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Magnesium carbonate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium carbonate	Ingestion	Rat	LD50 > 2,000 mg/kg
Oxydipropyl dibenzoate	Dermal	Rat	LD50 > 2,000 mg/kg
Oxydipropyl dibenzoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Oxydipropyl dibenzoate	Ingestion	Rat	LD50 3,295 mg/kg
Oxydiethylene dibenzoate	Dermal	Rat	LD50 > 2,000 mg/kg
Oxydiethylene dibenzoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Oxydiethylene dibenzoate	Ingestion	Rat	LD50 3,535 mg/kg
butan-1-ol	Dermal	Rabbit	LD50 3,402 mg/kg
butan-1-ol	Inhalation-Vapour (4	Rat	LC50 24 mg/l

	hours)		
butan-1-ol	Ingestion	Rat	LD50 2,290 mg/kg
Chlorite-group minerals	Dermal		LD50 estimated to be > 5,000 mg/kg
Chlorite-group minerals	Ingestion		LD50 estimated to be > 5,000 mg/kg
copper flakes (coated with aliphatic acid)	Dermal	Rat	LD50 > 2,000 mg/kg
copper flakes (coated with aliphatic acid)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.11 mg/l
copper flakes (coated with aliphatic acid)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
toluene	Rabbit	Irritant
Titanium dioxide	Rabbit	No significant irritation
Magnesium carbonate	In vitro data	No significant irritation
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Oxydiethylene dibenzoate	Rabbit	No significant irritation
butan-1-ol	Rabbit	Mild irritant
Chlorite-group minerals	Professional judgement	No significant irritation
copper flakes (coated with aliphatic acid)	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant
Titanium dioxide	Rabbit	No significant irritation
Magnesium carbonate	Rabbit	Mild irritant
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Oxydiethylene dibenzoate	Rabbit	No significant irritation
butan-1-ol	Rabbit	Severe irritant
Chlorite-group minerals	Professional judgement	No significant irritation
copper flakes (coated with aliphatic acid)	Rabbit	Mild irritant

#### Skin Sensitisation

Name	Species	Value
toluene	Guinea pig	Not classified
Titanium dioxide	Human and animal	Not classified
Oxydipropyl dibenzoate	Guinea pig	Not classified
Oxydiethylene dibenzoate	Guinea pig	Not classified
butan-1-ol	Human	Not classified

#### Respiratory Sensitisation

Name	Species	Value

Talc	Human	Not classified
------	-------	----------------

**Germ Cell Mutagenicity**

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Oxydipropyl dibenzoate	In Vitro	Not mutagenic
Oxydiethylene dibenzoate	In Vitro	Not mutagenic
butan-1-ol	In vivo	Not mutagenic
butan-1-ol	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Oxydipropyl dibenzoate	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Oxydiethylene dibenzoate	Ingestion	Not classified for female reproduction	Rat	NOAEL 10000 ppm in the diet	2 generation
Oxydiethylene dibenzoate	Ingestion	Not classified for male reproduction	Rat	NOAEL 10000 ppm in the diet	2 generation
Oxydiethylene dibenzoate	Ingestion	Not classified for development	Rabbit	NOAEL 75 mg/kg/day	during gestation
butan-1-ol	Ingestion	Not classified for female reproduction	Rat	NOAEL	premating &

				5,000 mg/kg/day	during gestation
butan-1-ol	Inhalation	Not classified for male reproduction	Rat	NOAEL 18 mg/l	6 weeks
butan-1-ol	Inhalation	Not classified for development	Rat	NOAEL 10.6 mg/l	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
butan-1-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
butan-1-ol	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
butan-1-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal	NOAEL 2,500	13 weeks

				species	mg/kg/day	
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Oxydipropyl dibenzoate	Ingestion	hematopoietic system   liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Oxydiethylene dibenzoate	Ingestion	hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
butan-1-ol	Inhalation	blood	Not classified	Rat	NOAEL 0.3 mg/l	3 months
butan-1-ol	Inhalation	auditory system	Not classified	Human	NOAEL Not available	occupational exposure
butan-1-ol	Inhalation	liver   kidney and/or bladder   respiratory system	Not classified	Guinea pig	NOAEL Not available	3 months
butan-1-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 9.09 mg/l	13 weeks
butan-1-ol	Ingestion	blood	Not classified	Rat	NOAEL 500 mg/kg/day	13 weeks

### Aspiration Hazard

Name	Value
toluene	Aspiration hazard
butan-1-ol	Some positive data exist, but the data are not sufficient for classification

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l

toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Magnesium carbonate	546-93-0	Activated sludge	Estimated	3 hours	EC50	>900 mg/l
Magnesium carbonate	546-93-0	Fathead minnow	Estimated	96 hours	LC50	1,880 mg/l
Magnesium carbonate	546-93-0	Green algae	Estimated	72 hours	EC50	>100 mg/l
Magnesium carbonate	546-93-0	Water flea	Estimated	48 hours	LC50	486 mg/l
Magnesium carbonate	546-93-0	Green algae	Estimated	72 hours	NOEC	100 mg/l
Magnesium carbonate	546-93-0	Water flea	Estimated	21 days	EC10	284 mg/l
Oxydipropyl dibenzoate	27138-31-4	Fathead minnow	Experimental	96 hours	LC50	3.7 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Oxydipropyl dibenzoate	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Oxydiethylene dibenzoate	120-55-8	Green algae	Experimental	72 hours	EL50	11 mg/l
Oxydiethylene dibenzoate	120-55-8	Rainbow trout	Experimental	96 hours	LL50	2.9 mg/l
Oxydiethylene dibenzoate	120-55-8	Water flea	Experimental	48 hours	EL50	6.7 mg/l
Oxydiethylene dibenzoate	120-55-8	Green algae	Experimental	72 hours	NOEL	2.2 mg/l
Oxydiethylene dibenzoate	120-55-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l

Oxydiethylene dibenzoate	120-55-8	Redworm	Experimental	14 days	LC50	>1,000 mg/kg (Dry Weight)
butan-1-ol	71-36-3	Copepod	Experimental	96 hours	LC50	1,900 mg/l
butan-1-ol	71-36-3	Fathead minnow	Experimental	96 hours	LC50	1,376 mg/l
butan-1-ol	71-36-3	Green algae	Experimental	96 hours	ErC50	225 mg/l
butan-1-ol	71-36-3	Water flea	Experimental	48 hours	EC50	1,328 mg/l
butan-1-ol	71-36-3	Green algae	Experimental	96 hours	ErC10	134 mg/l
butan-1-ol	71-36-3	Water flea	Experimental	21 days	NOEC	4.1 mg/l
butan-1-ol	71-36-3	Bacteria	Experimental	17 hours	EC50	4,390 mg/l
Rheological Additive	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Chlorite-group minerals	1318-59-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
copper flakes (coated with aliphatic acid)	7440-50-8	Green algae	Analogous Compound	72 hours	ErC50	0.1049 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Water flea	Analogous Compound	48 hours	EC50	0.0126 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Zebra Fish	Analogous Compound	96 hours	LC50	0.0117 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Fathead minnow	Analogous Compound	32 days	EC10	0.0059 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Green algae	Analogous Compound	N/A	NOEC	0.022 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Water flea	Analogous Compound	7 days	NOEC	0.004 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Activated sludge	Analogous Compound	N/A	EC50	7 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not available-insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Titanium dioxide	13463-67-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Magnesium carbonate	546-93-0	Data not available-insufficient	N/A	N/A	N/A	N/A
Oxydipropyl dibenzoate	27138-31-4	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Oxydiethylene dibenzoate	120-55-8	Experimental Biodegradation	28 days	CO2 evolution	93 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
butan-1-ol	71-36-3	Experimental Biodegradation	19 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 301E - Modif. OECD Screen
butan-1-ol	71-36-3	Experimental Aquatic Inherent Biodegrad.	5 days	Dissolv. Organic Carbon Deplet	93 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
butan-1-ol	71-36-3	Experimental Photolysis		Photolytic half-life (in air)	3.4 days (t 1/2)	
Rheological Additive	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Chlorite-group minerals	1318-59-8	Data not available	N/A	N/A	N/A	N/A

copper flakes (coated with aliphatic acid)	7440-50-8	insufficient Data not availbl- insufficient	N/A	N/A	N/A	N/A
--	-----------	---	-----	-----	-----	-----

### 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Magnesium carbonate	546-93-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxydipropyl dibenzoate	27138-31-4	Modeled Bioconcentration		Bioaccumulation factor	8	Catalogic™
Oxydiethylene dibenzoate	120-55-8	Experimental Bioconcentration		Log Kow	3.2	
butan-1-ol	71-36-3	Experimental Bioconcentration		Log Kow	1	OECD 117 log Kow HPLC method
Rheological Additive	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chlorite-group minerals	1318-59-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
copper flakes (coated with aliphatic acid)	7440-50-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
Oxydiethylene dibenzoate	120-55-8	Experimental Mobility in Soil	Koc	1,500 l/kg	OECD 121 Estim. of Koc by HPLC
butan-1-ol	71-36-3	Experimental Mobility in Soil	Koc	3 l/kg	

### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

### 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 04 09*	Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27*	Paint, inks, adhesives and resins containing dangerous substances

## SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
<b>14.1 UN number or ID number</b>	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
<b>14.3 Transport hazard class(es)</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Talc	14807-96-6	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

None

#### Regulation (EU) No 649/2012

No chemicals listed

## 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: sensory organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Revision information:

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Supplemental Hazard Statements information was deleted.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Particle Characteristics N/A information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 15: Carcinogenicity information information was modified.

Section 15: Seveso Substance Text information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

## Annex

<b>1. Title</b>	
<b>Substance identification</b>	toluene; EC No. 203-625-9; CAS Nbr 108-88-3;
<b>Exposure Scenario Name</b>	Professional Use of Fillers and Putties
<b>Lifecycle Stage</b>	<b>Widespread use by professional workers</b>
<b>Contributing activities</b>	PROC 10 -Roller application or brushing ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 08d -Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
<b>Processes, tasks and activities covered</b>	Application of product.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Assumes use at not more than 20°C above ambient temperature; Duration of use: 8 hours/day; Emission days per year: 365 days/year; Indoors with good general ventilation; Outdoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Air-purifying Full-Face (with gas/vapour cartridge, that can be combined with a particulate filter); Air-purifying Half-Mask (with gas/vapour-cartridge, that can be combined with a particulate filter) (APF 10); Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> Municipal Sewage Treatment Plant;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**