Safety Data Sheet

Copyright,2021, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	37-0146-3	**Version Number:**	1.02
Issue Date:	06/11/21	**Supercedes Date:**	06/03/21

Product identifier
3M™ Perfect-It™ Headlight Lens Restoration Kit (Professional Use), 02516

ID Number(s):

60-4550-8980-9

7100123189

Recommended use
Automotive

Supplier's details

MANUFACTURER:	3M
DIVISION:	Construction and Home Improvement Markets
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

34-5178-8, 40-6556-1

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2025, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-5178-8	**Version Number:**	2.05
Issue Date:	05/29/25	**Supercedes Date:**	06/08/21

SECTION 1: Identification

1.1. Product identifier
3M™ Perfect-It™ EX Machine Polish, 06093, 06094, 06095, 06096, 36093

Product Identification Numbers
LB-K100-1803-8, 60-4550-8470-1, 60-4550-8471-9, 60-4550-8472-7, 60-4550-8473-5, 60-4551-1035-7
7100068200, 7100075861, 7100075860, 7100075862, 7100225393

1.2. Recommended use and restrictions on use

Recommended use
Automotive, Rubbing Compound

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Skin Sensitizer: Category 1B.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms



Hazard Statements
May cause an allergic skin reaction.

Precautionary Statements
General:
Keep out of reach of children.

Prevention:
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	45 - 70 Trade Secret *
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	10 - 30 Trade Secret *
Aluminum Oxide (non-fibrous)	1344-28-1	7 - 13 Trade Secret *
Dodecamethylcyclohexasiloxane	540-97-6	1 - 5 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	1 - 5 Trade Secret *
Ethylene oxide, polymer with ethylenediamine and propylene oxide	26316-40-5	0.5 - 1.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide (non-fibrous)	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
MINERAL OILS, HIGHLY-REFINED OILS	64742-47-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Gray
Odor	Mild Solvent
Odor threshold	*No Data Available*
pH	7.5 - 9
Melting point	*No Data Available*
Boiling Point	*No Data Available*
Flash Point	No flash point
Evaporation rate	*No Data Available*
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Vapor Density	*No Data Available*
Density	1.0 - 1.02 g/ml
Specific Gravity	1.0 - 1.02 [*Ref Std:*WATER=1]
Solubility In Water	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	22,000 - 28,000 centipoise
Hazardous Air Pollutants	0 lb HAPS/lb solids [*Test Method:*Calculated]
Molecular weight	*Not Applicable*
Volatile Organic Compounds	167 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Volatile Organic Compounds	16.0 % weight [*Test Method:*calculated per CARB title 2]
Percent volatile	81.5 % weight
VOC Less H2O & Exempt Solvents	487 g/l [*Test Method:*calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
No health effects are expected.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Information:
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 15,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Mild irritant
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	No significant irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Not classified
Dodecamethylcyclohexasiloxane	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Mouse	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Dodecamethylcyclohexasiloxane	In Vitro	Not mutagenic
Dodecamethylcyclohexasiloxane	In vivo	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Ethylene oxide, polymer with ethylenediamine and propylene oxide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	40 days
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Dodecamethylcyclohexasiloxane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks

HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	hematopoietic system | eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Dodecamethylcyclohexasiloxane	Inhalation	liver	Not classified	Rat	NOAEL 0.546 mg/l	90 days
Dodecamethylcyclohexasiloxane	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.018 mg/l	90 days
Dodecamethylcyclohexasiloxane	Inhalation	hematopoietic system | eyes	Not classified	Rat	NOAEL 0.546 mg/l	90 days
Dodecamethylcyclohexasiloxane	Ingestion	endocrine system | liver | hematopoietic system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver | immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	gastrointestinal tract | hematopoietic system | respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Ethylene oxide, polymer with ethylenediamine and propylene oxide	Ingestion	heart | skin | bone, teeth, nails, and/or hair | liver | immune system | muscles | nervous system | vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Respiratory or Skin Sensitization

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
Aluminum Oxide (non-fibrous)	1344-28-1	Trade Secret 7 - 13

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	34-5178-8	**Version Number:**	2.05
Issue Date:	05/29/25	**Supercedes Date:**	06/08/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2022, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	40-6556-1	**Version Number:**	1.03
Issue Date:	08/30/22	**Supercedes Date:**	06/08/21

SECTION 1: Identification

1.1. Product identifier
3M™ Perfect-It™ EX AC Rubbing Compound, 36057, 36058, 36060, 36061, 36062, 36063

Product Identification Numbers

ID Number	UPC	ID Number	UPC
60-4551-0940-9		60-4551-0941-7	
60-4551-0942-5		60-4551-0943-3	
60-4551-0944-1		60-4551-1032-4	

7100208109, 7100210661, 7100210683, 7100210709, 7100210684, 7100226749

1.2. Recommended use and restrictions on use

Recommended use
Automotive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Skin Sensitizer: Category 1A.

2.2. Label elements
Signal word
Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements
May cause an allergic skin reaction.

Precautionary Statements
General:
Keep out of reach of children.

Prevention:
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70 Trade Secret *
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	10 - 30 Trade Secret *
Aluminum Oxide (non-fibrous)	1344-28-1	10 - 20 Trade Secret *
Glycerin	56-81-5	1 - 5 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	1 - 5 Trade Secret *
Alcohols, C10-16	67762-41-8	<= 1 Trade Secret *
Fatty Organic Compound	Trade Secret*	<= 1 Trade Secret *
2-METHYL-4-ISOTHIAZOLINE-3-ONE	2682-20-4	< 0.01 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide (non-fibrous)	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Glycerin	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	White
Odor	Slight Pine
Odor threshold	*No Data Available*
pH	7.5 - 9
Melting point	*No Data Available*
Boiling Point	*No Data Available*
Flash Point	No flash point
Evaporation rate	*No Data Available*
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Vapor Density	*No Data Available*
Density	8.8 - 9 lb/gal
Specific Gravity	1.05 - 1.1 [*Ref Std:*WATER=1]
Solubility In Water	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	20,000 - 70,000 centipoise
Hazardous Air Pollutants	0 lb HAPS/lb solids [*Test Method:*Calculated]
Molecular weight	*Not Applicable*
Volatile Organic Compounds	16.2 % weight [*Test Method:*calculated per CARB title 2]
Percent volatile	77.5 % weight
VOC Less H2O & Exempt Solvents	498 g/l [*Test Method:*calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value

Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Fatty Organic Compound	Ingestion	Rat	LD50 > 2,000 mg/kg
Fatty Organic Compound	Dermal	similar compounds	LD50 > 5,000 mg/kg
Fatty Organic Compound	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 17.5 mg/l
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Dermal	Rabbit	LD50 87 mg/kg
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Fatty Organic Compound	Human	No significant irritation
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Fatty Organic Compound	Rabbit	Severe irritant
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Fatty Organic Compound	Guinea pig	Not classified
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Human and animal	Sensitizing

Photosensitization

Name	Species	Value
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Human and animal	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In vivo	Not mutagenic
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Fatty Organic Compound	In Vitro	Not mutagenic
Fatty Organic Compound	In vivo	Not mutagenic
2-METHYL-4-ISOTHIAZOLINE-3-ONE	In vivo	Not mutagenic
2-METHYL-4-ISOTHIAZOLINE-3-ONE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not available	Not carcinogenic
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Dermal	Mouse	Not carcinogenic
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Not Specified	Not classified for development	Rat	NOAEL Not available	1 generation
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Fatty Organic Compound	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	premating into lactation

Fatty Organic Compound	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	41 days
Fatty Organic Compound	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	premating into lactation
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Fatty Organic Compound	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-METHYL-4-ISOTHIAZOLINE-3-ONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Glycerin	Inhalation	respiratory system | heart | liver | kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system | hematopoietic system | liver | kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver | immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Respiratory or Skin Sensitization

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations
Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address

the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	40-6556-1	**Version Number:**	1.03
Issue Date:	08/30/22	**Supercedes Date:**	06/08/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com