



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	23-2991-0	Version number:	5.03
Revision date:	16/04/2025	Supersedes date:	13/02/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

Product Identification Numbers

62-4979-8032-6

7100138125

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The aspiration hazard classification is not required due to the product's physical form.

CLASSIFICATION:

Flammable Liquid, Category 1 - Flam. Liq. 1; H224

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Hexane, mix	601-007-00-7		15 - 40
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		915-687-0	< 0.2

HAZARD STATEMENTS:

H224	Extremely flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261E	Avoid breathing vapour or spray.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

Storage:

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Contains 8% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

May displace oxygen and cause rapid suffocation.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hexane, mix	(CAS-No.) 601-007-00-7	15 - 40	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 Nota 4,C
Non-Volatile Components	Trade Secret	10 - 30	Substance not classified as hazardous
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (REACH-No.) 01-2119472128-37	10 - 30	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2 (REACH-No.) 01-2119463273-41	10 - 24	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
Terpene Phenolic	Trade Secret	< 10	Substance not classified as hazardous
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	(CAS-No.) 31393-98-3	< 10	Aquatic Chronic 4, H413
isobutane	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (REACH-No.) 01-2119485395-27	3 - 7	Flam. Gas 1A, H220 Liquified gas, H280 Nota C,U
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (REACH-No.) 01-2119486944-21	3 - 7	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
pentane	(CAS-No.) 109-66-0 (EC-No.) 203-692-4	< 5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 Aquatic Chronic 2, H411 Nota C
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6	< 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6	< 0.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336

			STOT RE 2, H373 Aquatic Chronic 2, H411
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(EC-No.) 915-687-0	< 0.2	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1 Skin Sens. 1A, H317 Repr. 2, H361f

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6	(C >= 50%) Eye Irrit. 2, H319
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6	(C >= 5%) STOT RE 2, H373

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Hydrocarbons.
formaldehyde
Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m3(50 ppm);TWA(8 hours):50 ppm(192 mg/m3);STEL(15 minutes):384 mg/m3(100 ppm);STEL(15 minutes):100 ppm(384 mg/m3)	SKIN
pentane	109-66-0	Ireland OELs	TWA(8 hours):3000 mg/m3(1000 ppm);TWA(8 hours):1000 ppm(3000 mg/m3)	
n-hexane	110-54-3	Ireland OELs	TWA(8 hours):72 mg/m3(20 ppm);TWA(8 hours):20 ppm(72 mg/m3)	SKIN
cyclohexane	110-82-7	Ireland OELs	TWA(8 hours):700 mg/m3(200 ppm);TWA(8 hours):200 ppm(700 mg/m3)	
dimethyl ether	115-10-6	Ireland OELs	TWA(8 hours):1920 mg/m3(1000 ppm);TWA(8 hours):1000 ppm(1920 mg/m3)	
ethanol	64-17-5	Ireland OELs	STEL(15 minutes):1000 ppm	
isobutane	75-28-5	Ireland OELs	STEL(15 minutes):1000 ppm	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Nitrile rubber.	No data available	No data available
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Multicolor
Odor	Mild Solvent
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	<=20 °C
Flammability	Flammable Liquid: Category 1.
Flammable Limits(LEL)	1.2 % volume
Flammable Limits(UEL)	27 % volume
Flash point	-45.6 °C [Test Method:Closed Cup] [Details:Flammable Gas]
Autoignition temperature	No data available.
Decomposition temperature	Not applicable.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	Not applicable.
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	583985.9 Pa [@ 20 °C]
Density	0.735 g/ml
Relative density	0.735 [Ref Std: WATER=1]
Relative Vapour Density	>=1 [Ref Std: AIR=1]
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Molecular weight	No data available.
Solids content	20 - 30 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the

foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hexane, mix	Dermal		LD50 estimated to be > 5,000 mg/kg
Hexane, mix	Inhalation-Vapour		LC50 estimated to be > 50 mg/l
Hexane, mix	Ingestion		LD50 estimated to be > 5,000 mg/kg
dimethyl ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Non-Volatile Components	Dermal		LD50 estimated to be > 5,000 mg/kg
Non-Volatile Components	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Ingestion	Rat	LD50 > 2,000 mg/kg
Terpene Phenolic	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Terpene Phenolic	Ingestion	Rat	LD50 > 7,000 mg/kg
pentane	Dermal	Rabbit	LD50 3,000 mg/kg
pentane	Inhalation-Vapour (4 hours)	Rat	LC50 > 18 mg/l
pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
ethanol	Inhalation-Vapour (4 hours)	Rat	LC50 124.7 mg/l
ethanol	Ingestion	Rat	LD50 17,800 mg/kg
n-hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
n-hexane	Inhalation-Vapour (4 hours)	Rat	LC50 170 mg/l
n-hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

toluene	Ingestion	Rat	LD50 5,550 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Rat	LD50 3,125 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hexane, mix	Professional judgement	Mild irritant
cyclohexane	Rabbit	Mild irritant
Non-Volatile Components	Professional judgement	Minimal irritation
isobutane	Professional judgement	No significant irritation
propane	Rabbit	Minimal irritation
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In vitro data	No significant irritation
pentane	Rabbit	Minimal irritation
ethanol	Rabbit	No significant irritation
n-hexane	Human and animal	Mild irritant
toluene	Rabbit	Irritant
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hexane, mix	Professional judgement	Moderate irritant
cyclohexane	Rabbit	Mild irritant
isobutane	Professional judgement	No significant irritation
propane	Rabbit	Mild irritant
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In vitro data	No significant irritation
pentane	Rabbit	Mild irritant
ethanol	Rabbit	Severe irritant
n-hexane	Rabbit	Mild irritant
toluene	Rabbit	Moderate irritant
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Multiple animal	Not classified

	species	
Terpene Phenolic	Human	Some positive data exist, but the data are not sufficient for classification
pentane	Guinea pig	Not classified
ethanol	Human	Not classified
n-hexane	Human	Not classified
toluene	Guinea pig	Not classified
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
dimethyl ether	In Vitro	Not mutagenic
dimethyl ether	In vivo	Not mutagenic
cyclohexane	In Vitro	Not mutagenic
cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
isobutane	In Vitro	Not mutagenic
propane	In Vitro	Not mutagenic
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	In Vitro	Not mutagenic
pentane	In vivo	Not mutagenic
pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
n-hexane	In Vitro	Not mutagenic
n-hexane	In vivo	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In vivo	Not mutagenic
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
dimethyl ether	Inhalation	Rat	Not carcinogenic
ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
n-hexane	Dermal	Mouse	Not carcinogenic
n-hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure
------	-------	-------	---------	-------------	----------

					Duration
dimethyl ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
pentane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
pentane	Inhalation	Not classified for development	Rat	NOAEL 30 mg/l	during organogenesis
ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ethanol	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
n-hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
n-hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
n-hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
n-hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexane, mix	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Hexane, mix	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hexane, mix	Inhalation	cardiac sensitisation	Not classified	Dog	NOAEL Not available	
Hexane, mix	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

				nt		
dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
dimethyl ether	Inhalation	cardiac sensitisation	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
isobutane	Inhalation	cardiac sensitisation	Causes damage to organs	Multiple animal species	NOAEL Not available	
isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
pentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
pentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
pentane	Inhalation	cardiac sensitisation	Not classified	Dog	NOAEL Not available	not available
pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	not available
ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ethanol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
ethanol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
n-hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning

		system depression	dizziness		available	and/or abuse
--	--	-------------------	-----------	--	-----------	--------------

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexane, mix	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
Hexane, mix	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
Hexane, mix	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	Ingestion	heart gastrointestinal tract hematopoietic system liver nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days
pentane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
pentane	Inhalation	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 20 mg/l	13 weeks
pentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ethanol	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
n-hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	respiratory system	Some positive data exist, but the	Mouse	LOAEL 1.76	13 weeks

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

			data are not sufficient for classification		mg/l	
n-hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
n-hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
n-hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
n-hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
n-hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
n-hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-	Ingestion	gastrointestinal tract liver immune system heart endocrine system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

pentamethyl-4-piperidyl sebacate		hematopoietic system nervous system kidney and/or bladder				
----------------------------------	--	---	--	--	--	--

Aspiration Hazard

Name	Value
Hexane, mix	Aspiration hazard
cyclohexane	Aspiration hazard
pentane	Aspiration hazard
n-hexane	Aspiration hazard
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hexane, mix	601-007-00-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
dimethyl ether	115-10-6	Bacteria	Experimental	N/A	EC10	>1,600 mg/l
dimethyl ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
dimethyl ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
Non-Volatile Components	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
Terpene Phenolic	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
isobutane	75-28-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
propane	74-98-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ethanol	64-17-5	Fathead minnow	Experimental	96 hours	LC50	14,200 mg/l
ethanol	64-17-5	Fish	Experimental	96 hours	LC50	11,000 mg/l
ethanol	64-17-5	Green algae	Experimental	72 hours	EC50	275 mg/l
ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
ethanol	64-17-5	Green algae	Experimental	72 hours	ErC10	11.5 mg/l
ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
pentane	109-66-0	Green algae	Experimental	72 hours	EC50	10.7 mg/l
pentane	109-66-0	Rainbow trout	Experimental	96 hours	LC50	4.26 mg/l
pentane	109-66-0	Water flea	Experimental	48 hours	EC50	2.7 mg/l
pentane	109-66-0	Green algae	Experimental	72 hours	NOEC	2.04 mg/l
n-hexane	110-54-3	Fathead minnow	Experimental	96 hours	LC50	2.5 mg/l
n-hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Activated sludge	Experimental	3 hours	IC50	>=100 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	ErC50	1.68 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Zebra Fish	Experimental	96 hours	LC50	0.9 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Water flea	Experimental	21 days	NOEC	1 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hexane, mix	601-007-00-7	Data not available - insufficient	N/A	N/A	N/A	N/A
dimethyl ether	115-10-6	Experimental Biodegradation	28 days	BOD	5 %BOD/ThO D	OECD 301D - Closed bottle test
dimethyl ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	
Non-Volatile Components	Trade Secret	Data not available - insufficient	N/A	N/A	N/A	N/A
cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThO D	OECD 301F - Manometric respirometry
cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Experimental Biodegradation	28 days	BOD	4 %BOD/ThO D	OECD 301D - Closed bottle test
Terpene Phenolic	Trade Secret	Estimated Biodegradation	28 days	BOD	27.5 %BOD/ThO D	
isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.4 days (t 1/2)	
propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	
ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 %BOD/ThO D	OECD 301C - MITI test (I)
pentane	109-66-0	Experimental Biodegradation	28 days	BOD	87 %BOD/ThO D	OECD 301F - Manometric respirometry

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

pentane	109-66-0	Experimental Photolysis		Photolytic half-life (in air)	8.07 days (t 1/2)	
n-hexane	110-54-3	Experimental Bioconcentration	28 days	BOD	100 %BOD/Th OD	OECD 301C - MITI test (I)
n-hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThO D	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	38 %removal of DOC	OECD 301E - Modif. OECD Screen

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hexane, mix	601-007-00-7	Estimated Bioconcentration		Bioaccumulation factor	150	
dimethyl ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Volatile Components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
cyclohexane	110-82-7	Experimental Bioconcentration		Log Kow	3.44	
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene, polymer with 6,6-dimethyl-2-methylenebicyclo[3.1.1]heptane	31393-98-3	Experimental Bioconcentration		Log Kow	7.41	
Terpene Phenolic	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	18.9	
isobutane	75-28-5	Experimental Bioconcentration		Log Kow	2.76	
propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	
ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.35	
pentane	109-66-0	Estimated Bioconcentration		Bioaccumulation factor	26	
n-hexane	110-54-3	Modeled Bioconcentration		Bioaccumulation factor	50	Catalogic™
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Analogous Compound BCF - Fish	56 days	Bioaccumulation factor	31.4	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
dimethyl ether	115-10-6	Modeled Mobility in Soil	Koc	3 l/kg	Episuite™

3M™ Super 77™ Cylinder Spray Adhesive (clear or red)

cyclohexane	110-82-7	Modeled Mobility in Soil	Koc	970 l/kg	Episuite™
pentane	109-66-0	Estimated Mobility in Soil	Koc	72 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Modeled Mobility in Soil	Koc	200,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 16 05 04* Gases in pressure containers (including halons) containing dangerous substances

EU waste code (product container after use)

- 15 01 04 Metallic packaging

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3501	UN3501	UN3501

14.2 UN proper shipping name	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(DIMETHYL ETHER; CYCLOHEXANE)	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(DIMETHYL ETHER; CYCLOHEXANE)	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.(DIMETHYL ETHER; CYCLOHEXANE; 2-METHYLPENTANE)
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	8F	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

toluene

CAS Nbr

108-88-3

Classification

Gr. 3: Not classifiable

Regulation

International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient

cyclohexane

toluene

CAS Nbr

110-82-7

108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P5a FLAMMABLE LIQUIDS	10	50

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:

Section 1: E-mail address information was modified.

Section 7: Conditions safe storage information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com