# Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document Group:** | 42-6523-7 | **Version Number:** | 1.07 |
| **Issue Date:** | 09/27/26 | **Supersedes Date:** | 09/01/26 |

## SECTION 1: Identification

**1.1. Product identifier**
3M™ Scotch-Weld™ Composite Urethane Adhesive 6301NS, Part B

**Product Identification Numbers**

| ID Number | UPC | ID Number | UPC |
|---|---|---|---|
| LA-D100-3113-6 | | 62-3591-8530-3 | |
| 62-3591-9530-2 | | | |

7100255362, 7100277119

**1.2. Recommended use and restrictions on use**

**Recommended use**
Adhesive

**1.3. Supplier's details**

| | |
|---|---|
| **MANUFACTURER:** | 3M |
| **DIVISION:** | Industrial Adhesives and Tapes Division |
| **ADDRESS:** | 3M Center, St. Paul, MN 55144-1000, USA |
| **Telephone:** | 1-888-3M HELPS (1-888-364-3577) |

**1.4. Emergency telephone number**
1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

**2.1. Hazard classification**
Reproductive Toxicity: Category 2.

**2.2. Label elements**
**Signal word**
Warning

**Symbols**
Health Hazard |

**Pictograms**



**Hazard Statements**

Suspected of damaging fertility or the unborn child.

**Precautionary statements**

**Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves.

**Response:**
IF exposed or concerned: Get medical attention.

**Storage:**
Store locked up.

**Disposal:**
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

## SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---|---|
| Polyol (NJTS Reg. No. 04466600-7463) | Trade Secret* | 30 - 50 |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | Trade Secret* | 10 - 30 |
| Talc | 14807-96-6 | 10 - 30 Trade Secret * |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Trade Secret* | 1 - 10 |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Trade Secret* | 0.1 - 5 |
| Treated Silica | 68611-44-9 | < 1 |
| Piperazine | 110-85-0 | 0.1 - 1 Trade Secret * |
| Triethylenediamine | 280-57-9 | < 0.5 |
| Quartz Silica | 14808-60-7 | <= 0.3 |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Wash with soap and water. If you are concerned, get medical advice.

**Eye Contact:**
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**
Rinse mouth. If you are concerned, get medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**
None inherent in this product.

**Hazardous Decomposition or By-Products**

| Substance | Condition |
|---|---|
| Aldehydes | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Chloride | During Combustion |
| Oxides of Nitrogen | During Combustion |

**5.3. Special protective actions for fire-fighters**
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**
Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label

and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**
Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| Piperazine and salts, inhalable fraction and vapor, as piperazine | 110-85-0 | ACGIH | TWA(as piperazine, inhalable fraction & vapor):0.03 ppm | A4: Not class. as human carcin, Dermal/Respiratory Sensitizer |
| Silicates (less than 1% crystalline silica) talc (containing asbestos) | 14807-96-6 | OSHA | TWA - Use asbestos limits: | |
| Talc | 14807-96-6 | ACGIH | TWA(respirable fraction):2 mg/m3 | A4: Not class. as human carcin |
| Talc | 14807-96-6 | OSHA | TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft. | |
| Quartz Silica | 14808-60-7 | OSHA | TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.) | |
| Silica, crystalline, respirable fraction | 14808-60-7 | ACGIH | TWA(respirable fraction):0.025 mg/m3 | A2: Suspected human carcin. |
| Silica: Amorphous, including natural diatomaceous earth | 68611-44-9 | OSHA | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Natural Rubber, Neoprene, Nitrile Rubber

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Liquid |
| **Specific Physical Form:** | Paste |
| **Color** | Dark Green |
| **Odor** | Slight Ammoniacal |
| **Odor threshold** | *No Data Available* |
| **pH** | *Not Applicable* |
| **Melting point** | *Not Applicable* |
| **Boiling Point** | *No Data Available* |
| **Flash Point** | >=340 ºF [*Test Method:*Closed Cup] |
| **Evaporation rate** | *Not Applicable* |
| **Flammability** | Not Applicable |
| **Flammable Limits(LEL)** | *Not Applicable* |
| **Flammable Limits(UEL)** | *Not Applicable* |
| **Vapor Pressure** | <= 0.000004 mmHg [@ 68 ºF] |

| | |
|---|---|
| **Relative Vapor Density** | *Not Applicable* |
| **Density** | 1.2 g/ml |
| **Relative Density** | 1.2 [*Ref Std:*WATER=1] |
| **Solubility in Water** | Negligible |
| **Solubility- non-water** | *No Data Available* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *No Data Available* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | 1,910 mm2/sec |
| **Hazardous Air Pollutants** | 0 % weight [*Test Method:*Calculated] |
| **Molecular weight** | *No Data Available* |
| **VOC Less H2O & Exempt Solvents** | < 1 g/l [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*when used as intended with Part A] |
| **VOC Less H2O & Exempt Solvents** | <=0.1 % [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*when used as intended with Part A] |
| **VOC Less H2O & Exempt Solvents** | < 2 g/l [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*as supplied] |
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**
Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
None known.

**10.5. Incompatible materials**
Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**
Contact with the skin during product use is not expected to result in significant irritation.

**Eye Contact:**
Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**
May cause additional health effects (see below).

**Additional Health Effects:**

**Reproductive/Developmental Toxicity:**
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

| Ingredient | CAS No. | Class Description | Regulation |
|---|---|---|---|
| Silica, Crystalline (Respirable Size) | 14808-60-7 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| Silica dust, crystalline, in the form of quartz or cristobalite | 14808-60-7 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Talc | 14807-96-6 | Grp. 2A: Probable human carc. | International Agency for Research on Cancer |

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Polyol (NJTS Reg. No. 04466600-7463) | Dermal | Rat | LD50 > 2,000 mg/kg |
| Polyol (NJTS Reg. No. 04466600-7463) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 50 mg/l |
| Polyol (NJTS Reg. No. 04466600-7463) | Ingestion | Rat | LD50 4,600 mg/kg |
| Talc | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Talc | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | Dermal | similar compounds | LD50 > 2,000 mg/kg |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | Inhalation-Dust/Mist (4 hours) | similar compounds | LC50 > 3.2 mg/l |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | Ingestion | similar compounds | LD50 > 5,000 mg/kg |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Dermal | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Ingestion | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Inhalation- | Rat | LC50 > 5.2 mg/l |

| | | | |
|---|---|---|---|
| | Dust/Mist (4 hours) | | |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Ingestion | similar compounds | LD50 > 5,000 mg/kg |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Dermal | similar health hazards | LD50 estimated to be > 5,000 mg/kg |
| Treated Silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Treated Silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Treated Silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Piperazine | Ingestion | Rat | LD50 2,300 mg/kg |
| Quartz Silica | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Quartz Silica | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Triethylenediamine | Dermal | Rabbit | LD50 > 3,200 mg/kg |
| Triethylenediamine | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.05 mg/l |
| Triethylenediamine | Ingestion | Rat | LD50 1,870 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| Polyol (NJTS Reg. No. 04466600-7463) | Rabbit | No significant irritation |
| Talc | Rabbit | No significant irritation |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | similar compounds | Minimal irritation |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Professional judgement | No significant irritation |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | similar compounds | No significant irritation |
| Treated Silica | Rabbit | No significant irritation |
| Piperazine | Rabbit | Corrosive |
| Quartz Silica | Professional judgement | No significant irritation |
| Triethylenediamine | Rabbit | Mild irritant |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| Polyol (NJTS Reg. No. 04466600-7463) | Rabbit | Mild irritant |
| Talc | Rabbit | No significant irritation |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | similar compounds | Mild irritant |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Professional judgement | No significant irritation |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | similar compounds | Mild irritant |
| Treated Silica | Rabbit | No significant irritation |
| Piperazine | similar health | Corrosive |

| | | |
|---|---|---|
| | hazards | |
| Triethylenediamine | Rabbit | Corrosive |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | similar compounds | Not classified |
| Urethane Prepolymer (NJTS Reg. No. 04499600-7462) | Professional judgement | Not classified |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Guinea pig | Not classified |
| Treated Silica | Human and animal | Not classified |
| Piperazine | Human and animal | Sensitizing |

**Respiratory Sensitization**

| Name | Species | Value |
|---|---|---|
| Talc | Human | Not classified |
| Piperazine | Human | Sensitizing |

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| Talc | In Vitro | Not mutagenic |
| Talc | In vivo | Not mutagenic |
| Polyether Polyol (NJTS Reg. No. 04466600-7417) | In Vitro | Not mutagenic |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | In Vitro | Not mutagenic |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | In vivo | Not mutagenic |
| Treated Silica | In Vitro | Not mutagenic |
| Piperazine | In vivo | Not mutagenic |
| Piperazine | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In vivo | Some positive data exist, but the data are not sufficient for classification |

**Carcinogenicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Talc | Dermal | Human | Some positive data exist, but the data are not sufficient for classification |
| Talc | Inhalation | Rat | Carcinogenic |
| Treated Silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | Inhalation | Human and animal | Carcinogenic |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|
| Talc | Ingestion | Not classified for development | Rat | NOAEL 1,600 mg/kg | during organogenesis |

| | | | | | |
|---|---|---|---|---|---|
| Treated Silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Treated Silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Treated Silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Piperazine | Ingestion | Toxic to female reproduction | Rat | NOAEL 125 mg/kg/day | 2 generation |
| Piperazine | Ingestion | Toxic to male reproduction | Rat | NOAEL 125 mg/kg/day | 2 generation |
| Piperazine | Ingestion | Toxic to development | Rabbit | NOAEL 94 mg/kg/day | during organogenesis |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| Piperazine | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL not available | |
| Piperazine | Ingestion | nervous system | Causes damage to organs | Human and animal | NOAEL not available | therapeutic use |

**Specific Target Organ Toxicity - repeated exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| Talc | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Talc | Inhalation | pulmonary fibrosis | Not classified | Rat | NOAEL 18 mg/m3 | 113 weeks |
| Talc | Inhalation | respiratory system | Not classified | Rat | NOAEL 18 mg/m3 | 113 weeks |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Ingestion | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Thickening Agent (NJTS Reg. No. 04466600-7416) | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Treated Silica | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Treated Silica | Inhalation | silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Piperazine | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 1,250 mg/kg/day | 90 days |
| Piperazine | Ingestion | eyes | Not classified | Rat | NOAEL 1,250 mg/kg/day | 90 days |
| Piperazine | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,250 mg/kg/day | 90 days |
| Quartz Silica | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |

**Aspiration Hazard**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

# SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# SECTION 13: Disposal considerations

**13.1. Disposal methods**
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

# SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# SECTION 15: Regulatory information

## 15.1. US Federal Regulations
Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

| Physical Hazards |
|---|
| Not Applicable. |

| Health Hazards |
|---|
| Reproductive toxicity |

## 15.2. State Regulations
Contact 3M for more information.

## 15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

**NFPA Hazard Classification**
**Health:** 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|---|---|---|---|
| **Document Group:** | 42-6523-7 | **Version Number:** | 1.07 |
| **Issue Date:** | 09/27/26 | **Supersedes Date:** | 09/01/26 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at www.3M.com**