



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the Minister of Industry Decree No. 23/M-IND/PER/4/2013 and GHS Classification 4th Edition.

Document Group:	31-9640-9	Version Number:	1.00
Issue Date:	21/02/2025	Supersedes Date:	Initial Issue

SECTION 1: Identification

1.1. Product identifier

3M™ Finesse-it™ Polish Purple [120]

Product Identification Numbers

LB-K100-1523-1	LB-K100-1363-7	LB-K100-1363-8	LB-K100-1363-9	60-4402-4031-9
60-4402-4032-7	60-4402-4042-6	60-4402-4174-7	60-4403-6210-5	60-4403-6211-3
H0-0021-1765-5	HC-0005-4130-6	J1-4402-4031-2		

1.2. Recommended use and restrictions on use

Recommended use

Industrial use

1.3. Supplier's details

ADDRESS: PT 3M Indonesia, Perkantoran Hijau Arkadia, Menara F, Lt. 8. Jl. TB. Simatupang Kav. 88, Jakarta Selatan, 12520, Indonesia

Telephone: +6221-29974000

Website: https://www.3m.co.id/3M/en_ID/company-id/

1.4. Emergency telephone number

(021)29974000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified as hazardous according to UN GHS criteria.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 80
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	5 - 10
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	5 - 10
Hydrotreated Light Petroleum Distillates	64742-47-8	4 - 6
Distillates (Petroleum), Acid Treated, Light	64742-14-9	4 - 6
Mineral Oil	8042-47-5	< 2
Light aromatic solvent naphtha (petroleum)	64742-95-6	< 0.5
1,2,4-Trimethylbenzene	95-63-6	< 0.2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Keep from freezing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Indonesia OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(8 hours):10 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human

			mg/m ³	carcin
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m ³	A4: Not class. as human carcin
OIL MIST, MINERAL	8042-47-5	Indonesia OELs	TWA(as mist)(8 hours):5 mg/m ³ ;STEL(as mist)(15 minutes):10 mg/m ³	
1,2,4-Trimethylbenzene	95-63-6	ACGIH	TWA:10 ppm	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Indonesia OELs : Indonesia. Minister of Manpower and Transmigration Decree No. 13/MEN/X/2011 concerning Threshold Values, Chemical and Physical Factors in the Workplace.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Purple
Odor	Mild Solvent
Odor threshold	No Data Available
pH	7.5 - 8
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	100 °C
Flash Point	≥93.3 °C [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available

Vapor Pressure	2,399.8 Pa [@ 20 °C]
Relative Vapor Density	No Data Available
Density	0.96 - 0.98 g/ml
Relative Density	0.96 - 0.98 [Ref Std: WATER=1]
Water solubility	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	14,433 mm ² /sec
Volatile Organic Compounds	20.7 % weight [Details: Calculated]
Percent volatile	90.4 % weight [Details: Calculated including water]
VOC Less H ₂ O & Exempt Solvents	623.1 g/l [Details: Calculated]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	similar compounds	LD50 > 5,000 mg/kg
Aluminum Oxide Mineral (nonfibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (nonfibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (nonfibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.4 mg/l
Distillates (Petroleum), Acid Treated, Light	Dermal	similar compounds	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	similar compounds	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2,4-Trimethylbenzene	Dermal	Rabbit	LD50 > 3,160 mg/kg
1,2,4-Trimethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 18 mg/l
1,2,4-Trimethylbenzene	Ingestion	Rat	LD50 3,400 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Hydrotreated Heavy Naphtha (Petroleum)	similar compounds	Mild irritant
Aluminum Oxide Mineral (nonfibrous)	Rabbit	No significant irritation
Distillates (Petroleum), Acid Treated, Light	similar compounds	Mild irritant
Hydrotreated Light Petroleum Distillates	similar compounds	Mild irritant
Mineral Oil	Rabbit	No significant irritation
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
1,2,4-Trimethylbenzene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	similar compounds	No significant irritation
Aluminum Oxide Mineral (nonfibrous)	Rabbit	No significant irritation
Distillates (Petroleum), Acid Treated, Light	similar compounds	No significant irritation
Hydrotreated Light Petroleum Distillates	similar compounds	No significant irritation
Mineral Oil	Rabbit	Mild irritant
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
1,2,4-Trimethylbenzene	Rabbit	Mild irritant

Sensitization:

Skin Sensitization

Name	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	similar compounds	Not classified
Distillates (Petroleum), Acid Treated, Light	similar compounds	Not classified
Hydrotreated Light Petroleum Distillates	similar compounds	Not classified
Mineral Oil	Guinea pig	Not classified
Light aromatic solvent naphtha (petroleum)	Guinea pig	Not classified
1,2,4-Trimethylbenzene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrotreated Heavy Naphtha (Petroleum)	In Vitro	Not mutagenic
Aluminum Oxide Mineral (nonfibrous)	In Vitro	Not mutagenic
Distillates (Petroleum), Acid Treated, Light	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic

Mineral Oil	In Vitro	Not mutagenic
1,2,4-Trimethylbenzene	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral (nonfibrous)	Inhalation	Rat	Not carcinogenic
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for development	Rat	NOAEL 500 ppm	2 generation
1,2,4-Trimethylbenzene	Inhalation	Not classified for female reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for male reproduction	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 1.5 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL Not available	
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Distillates (Petroleum), Acid Treated, Light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

				nt		
1,2,4-Trimethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
1,2,4-Trimethylbenzene	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,2,4-Trimethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	liver kidney and/or bladder endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system muscles nervous system respiratory system vascular system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Aluminum Oxide Mineral (nonfibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (nonfibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Distillates (Petroleum), Acid Treated, Light	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	hematopoietic system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
1,2,4-Trimethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.1 mg/l	3 months
1,2,4-Trimethylbenzene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2,4-Trimethylbenzene	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract immune system	Not classified	Rat	NOAEL 1.2 mg/l	3 months
1,2,4-Trimethylbenzene	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 600 mg/kg/day	14 days

1,2,4-Trimethylbenzene	Ingestion	liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
------------------------	-----------	---	----------------	-----	-----------------------------	---------

Aspiration Hazard

Name	Value
Hydrotreated Heavy Naphtha (Petroleum)	Aspiration hazard
Distillates (Petroleum), Acid Treated, Light	Aspiration hazard
Hydrotreated Light Petroleum Distillates	Aspiration hazard
Mineral Oil	Aspiration hazard
Light aromatic solvent naphtha (petroleum)	Aspiration hazard
1,2,4-Trimethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Rainbow Trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Green algae	Experimental	72 hours	NOEL	100 mg/l
Distillates (Petroleum), Acid	64742-14-9	Green algae	Estimated	72 hours	EL50	>1,000 mg/l

Treated, Light						
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Rainbow Trout	Estimated	96 hours	LL50	>1,000 mg/l
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Green algae	Estimated	72 hours	NOEL	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Analogous Compound	72 hours	EL50	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Analogous Compound	48 hours	EL50	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Rainbow Trout	Experimental	96 hours	LL50	>788,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Scud	Experimental	96 hours	LL50	>10,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Analogous Compound	72 hours	NOEL	1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Analogous Compound	21 days	NOEL	>1 mg/l
Mineral Oil	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
Mineral Oil	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
Mineral Oil	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
Mineral Oil	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Fathead Minnow	Estimated	96 hours	LL50	8.2 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Green algae	Estimated	72 hours	EL50	7.9 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Water flea	Estimated	48 hours	EL50	3.2 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Green algae	Estimated	72 hours	NOEL	0.22 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Water flea	Experimental	21 days	NOEL	2.6 mg/l
1,2,4-Trimethylbenzene	95-63-6	Fathead Minnow	Experimental	96 hours	LC50	7.72 mg/l
1,2,4-Trimethylbenzene	95-63-6	Mysid Shrimp	Experimental	96 hours	LC50	2 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Experimental	48 hours	LC50	3.6 mg/l
1,2,4-Trimethylbenzene	95-63-6	Water flea	Analogous Compound	21 days	NOEC	0.4 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide	1344-28-1	Data not availbl-	N/A	N/A	N/A	N/A

Mineral (nonfibrous)		insufficient				
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	80% %BOD/ThOD	OECD 301F - Manometric Respiro
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Estimated Biodegradation	28 days	Biological Oxygen Demand	69 %BOD/ThOD	OECD 301F - Manometric Respiro
Hydrotreated Light Petroleum Distillates	64742-47-8	Experimental Biodegradation	28 days	Biological Oxygen Demand	22 %BOD/ThOD	OECD 301F - Manometric Respiro
Mineral Oil	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Light aromatic solvent naphtha (petroleum)	64742-95-6	Estimated Biodegradation	28 days	Biological Oxygen Demand	78 %BOD/COD	OECD 301F - Manometric Respiro
1,2,4-Trimethylbenzene	95-63-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	>60 %BOD/ThOD	OECD 301F - Manometric Respiro
1,2,4-Trimethylbenzene	95-63-6	Experimental Photolysis		Photolytic half-life (in air)	11.8 hours (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide Mineral (nonfibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mineral Oil	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Light aromatic solvent naphtha (petroleum)	64742-95-6	Estimated BCF - Fish	42 days	Bioaccumulation Factor	598	OECD305-Bioconcentration
1,2,4-Trimethylbenzene	95-63-6	Experimental BCF - Fish	56 days	Bioaccumulation Factor	≤275	OECD305-Bioconcentration
1,2,4-Trimethylbenzene	95-63-6	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.63	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be

disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

Local Regulations

Land Transport: In accordance with Director General of Land Transportation Decree No. SK.725/AJ.302/DRJD/2004 which refer to UN Standard.

Sea Transport: In accordance with Minister of Transportation Decree No. KM 2/2010 which refer to IMDG Code Standard.

International Regulations

UN No.: Not applicable

UN Proper Shipping Name: Not applicable

Transportation Class (IMO): Not applicable

Transportation Class (IATA): Not applicable

Packing Group: Not applicable

Marine Pollutant: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Local Inventory Status

Addendum I Government Regulation No. 74/2001:

List of Hazardous Substances Approved for Use :

Benzene is listed as a Hazardous Substance Approved for Use.

Diethanolamine is listed as a Hazardous Substance Approved for Use.

Ethanolamine is listed as a Hazardous Substance Approved for Use.

ETHYL ACRYLATE is listed as a Hazardous Substance Approved for Use.

ETHYLENE OXIDE is listed as a Hazardous Substance Approved for Use.

Glycerin is listed as a Hazardous Substance Approved for Use.

PROPYLENE OXIDE is listed as a Hazardous Substance Approved for Use.

Toluene is listed as a Hazardous Substance Approved for Use.

Addendum II Government Regulation No. 74/2001:

Tab.1 List of Prohibited Substances for Use:

None of the substances are listed as a Prohibited Substance for Use.

Addendum II Government Regulation No. 74/2001:

Tab.2 List of Restricted Substances for Use:

ETHYLENE OXIDE is listed as a Restricted Substance for Use.

Addendum I Ministry of Health Regulation No. 472/1996:

List and Classification of Hazardous Substances for Health:

1,4-DIOXANE is listed and classified as a Hazardous Substance for Health.

Benzene is listed and classified as a Hazardous Substance for Health.

ETHYLENE OXIDE is listed and classified as a Hazardous Substance for Health.

PROPYLENE OXIDE is listed and classified as a Hazardous Substance for Health.

Addendum I Act of Minister of Industry and Trade No. 254/MPP/KEP/2000

List of Hazardous Substances that are Regulated to Import Trade System:

Triethanolamine is listed as a Hazardous Substance that is Regulated to Import Trade System

SECTION 16: Other information

Document Group:	31-9640-9	Version Number:	1.00
Issue Date:	21/02/2025	Supersedes Date:	Initial Issue

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Indonesia SDSs are available at https://www.3m.co.id/3M/en_ID/company-id/