Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-0664-3	**Version number:**	1.01
Issue Date:	2025/08/07	**Supersedes Date:**	2024/04/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Abrasive Products, 461F P220-P600

Product Identification Numbers

60-0001-0437-6	60-0001-0448-3	60-0001-0884-9	60-0001-0885-6	60-0001-0886-4
60-0001-0887-2	60-0001-0888-0	60-0001-0889-8	60-0001-0890-6	60-0001-1738-6
60-0001-1739-4	60-0001-1740-2	60-0001-1741-0	60-0001-1743-6	60-0003-0855-5
60-0003-0856-3	60-0003-0870-4	60-0003-0899-3	60-0003-0900-9	60-0003-2773-8
60-0003-2774-6	60-0003-6667-8	60-0004-0644-1	60-0004-0645-8	60-0004-0646-6
60-0004-0647-4	60-0004-0648-2	60-0004-0883-5	60-0004-0884-3	60-0004-0885-0
60-0004-0886-8	60-0004-0887-6	60-0004-0913-0	60-0004-0914-8	60-0004-0915-5
60-0004-0916-3	60-0004-0917-1	60-0004-0949-4	60-0004-0950-2	60-0004-0951-0
60-0004-0952-8	60-0004-0953-6	60-0004-1115-1	60-0004-1116-9	60-0004-1117-7
60-0004-1118-5	60-0004-1119-3	60-4100-1416-5	60-4100-1417-3	60-4100-1426-4
60-4100-1433-0	60-4100-1435-5	60-4100-1437-1	60-4100-1444-7	60-4100-1447-0
60-4100-1451-2	60-4100-1452-0	60-4100-1453-8	60-4100-1458-7	60-4100-1460-3
60-4100-1464-5	60-4100-1465-2	60-4100-1468-6	60-4100-1469-4	60-4100-1470-2
60-4100-1472-8	60-4100-1474-4	60-4100-1479-3	60-4100-1486-8	60-4100-1500-6
60-4100-1501-4	60-4100-1502-2	60-4100-1503-0	60-4100-1504-8	60-4100-1505-5
60-4100-1506-3	60-4100-1507-1	60-4100-1508-9	60-4100-1510-5	60-4200-1269-6
60-4200-1276-1	60-4200-1285-2	60-4200-1286-0	60-4200-1288-6	60-4300-4829-2
60-4300-4833-4	60-4300-4835-9	60-4401-2075-0	60-4401-2086-7	60-4401-2373-9
60-4401-4506-2	60-4401-4535-1	60-4401-4550-0	60-4401-4635-9	60-4401-4741-5
60-4401-4788-6	60-4401-4836-3	60-4401-5279-5	60-4401-5317-3	60-4401-5410-6
60-4401-5414-8	60-4401-5603-6	60-4401-5837-0	60-4401-5912-1	60-4401-5990-7
60-4401-5998-0	60-4401-6145-7	60-4401-6172-1	60-4401-6235-6	60-4401-6241-4
60-4401-6627-4	60-4401-7001-1	60-4401-7120-9	60-4401-7133-2	60-4401-7265-2
60-4401-7337-9	60-4401-8634-8	60-4401-8669-4	60-4401-8723-9	60-4402-1295-3
60-4402-1303-5	60-4402-1306-8	60-4402-1307-6	60-4402-1316-7	60-4402-1323-3
60-4402-1325-8	60-4402-1327-4	60-4402-1334-0	60-4402-1337-3	60-4402-1341-5
60-4402-1342-3	60-4402-1343-1	60-4402-1349-8	60-4402-1351-4	60-4402-1355-5
60-4402-1356-3	60-4402-1359-7	60-4402-1360-5	60-4402-1361-3	60-4402-1363-9
60-4402-1365-4	60-4402-1370-4	60-4402-1377-9	60-4402-1391-0	60-4402-1392-8
60-4402-1393-6	60-4402-1394-4	60-4402-1395-1	60-4402-1396-9	60-4402-1397-7
60-4402-1398-5	60-4402-1399-3	60-4402-1401-7	60-4402-2823-1	60-4402-3280-3
60-4403-2108-5	60-4403-2141-6	60-4403-2204-2	60-4403-2245-5	60-4403-2247-1
60-4403-5285-8	60-4403-5286-6	60-4403-5561-2	60-4403-5562-0	60-4403-5566-1
60-4403-5567-9	60-4403-5569-5	60-4403-5570-3	60-4403-5571-1	60-4403-5574-5

60-4403-5576-0	60-4403-5577-8	60-4404-0244-8	60-4404-0249-7	60-4404-0325-5
60-4404-0406-3	60-4404-0585-4	60-4404-0586-2	60-4404-0680-3	60-4404-0708-2
60-4404-0971-6	60-4404-0972-4	60-4404-1008-6	60-4404-1051-6	60-4404-1052-4
60-4406-1700-3	60-4406-1737-5	60-4406-1738-3	60-6001-2679-5	60-6001-2683-7
60-6001-2684-5	60-6001-2686-0	60-6001-2699-3	60-6001-2700-9	60-6001-2707-4
60-6001-2708-2	60-6001-2712-4	60-6001-2713-2	60-6001-2714-0	60-6001-4446-7
60-6001-4447-5	60-6001-4671-0	60-6001-4897-1	60-6001-4901-1	60-6001-4902-9
60-6500-3826-2	60-6500-3827-0	60-6500-3829-6	60-6500-3830-4	60-9901-7808-3
CY-9987-6780-0	CY-9988-6416-9	CY-9988-7465-5	UU-0130-1539-9	UU-0130-2003-5
XX-1000-1431-3	XX-1000-1432-1	XX-1000-1433-9		

1.2. Recommended use and restrictions on use

Intended Use
Abrasive Product

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Abrasive Systems Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements
Signal word
Not applicable.

Symbols
Not applicable

Pictograms
Not applicable

2.3. Other hazards
None known.

13% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name

Paper Backing	Mixture	65 - 75	Not Applicable
Cured Resin	Mixture	10 - 20	Not Applicable
Silicon Carbide Mineral	409-21-2	10 - 20	Silicon carbide (SiC)
Attachment Button	Mixture	0 - 10	Not Applicable

Paper Backing is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.
Cured Resin is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.
Attachment Button is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.4. Special protection actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Not applicable.

6.3. Methods and material for containment and cleaning up
Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Not for consumer sale or use. Avoid breathing of dust created by sanding, grinding or machining. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls
Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

8.2.2. Personal protective equipment (PPE)

Eye/face protection

To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

Respiratory protection

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.
An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Colour	Black
Odour	Slight Polymeric
Odour threshold	*Not Applicable*
pH	*Not Applicable*
Melting point/Freezing point	*Not Applicable*
Boiling point	*Not Applicable*
Flash Point	*Not Applicable*
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapour Pressure	*Not Applicable*
Relative Vapour Density	*Not Applicable*
Density	*Not Applicable*
Relative density	*Not Applicable*
Water solubility	*Not Applicable*
Solubility- non-water	*Not Applicable*
Partition coefficient: n-octanol/ water	*Not Applicable*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*Not Applicable*
Kinematic Viscosity	*Not Applicable*
Volatile Organic Compounds	*No Data Available*
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	*No Data Available*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:
Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion. Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
No known health effects.

Additional Information:
This document covers only the 3M product. For completeassessment, when determining the degree of hazard, the material being abraded must also be considered.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Silicon Carbide Mineral	Dermal	Rat	LD50 > 2,000 mg/kg
Silicon Carbide Mineral	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silicon Carbide Mineral	Rat	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Silicon Carbide Mineral	Professional judgement	No significant irritation

Skin Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Respiratory Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Silicon Carbide Mineral	In Vitro	Not mutagenic

Carcinogenicity
For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects
For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure
For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure
For the component/components, either no data are currently available or the data are not sufficient for classification.

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	24-0664-3	**Version number:**	1.01
Issue Date:	2025/08/07	**Supersedes Date:**	2024/04/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca