Safety Data Sheet

Copyright,2025, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	06-3395-8	**Version Number:**	41.04
Issue Date:	10/09/25	**Supersedes Date:**	07/14/23

SECTION 1: Identification

1.1. Product identifier
3M™ Scotchkote™ Fusion Bonded Epoxy Coating 226N Slow 8G and 11G

Product Identification Numbers
80-0002-1609-5, 80-0002-1612-9, 80-6107-8232-0, 80-6108-6728-7, 80-6109-1726-4, 80-6109-1993-0, 80-6116-1642-8, 80-6300-0138-8, 80-6300-0139-6, CE-1006-9318-9, CE-1006-9343-7, CE-1006-9344-5, CE-1006-9345-2, CE-1006-9346-0, CE-1007-3874-5
7000058333, 7100007609, 7010348990, 7000058490, 7000058896, 7010293967, 7000134459, 7000148904, 7000134453, 7100031369, 7000134458, 7100198865, 7100198629

1.2. Recommended use and restrictions on use

Recommended use
Coating, Corrosion Protection Coating for Metal Pipes.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Skin Sensitizer: Category 1.
Carcinogenicity: Category 1A.
Reproductive Toxicity: Category 2.
Combustible Dust.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark |Health Hazard |

Pictograms



Hazard Statements
May form combustible dust concentrations in air.

May cause an allergic skin reaction.
May cause cancer.
Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention:
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing vapors, dust, or spray.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves and if needed, respiratory protection (see SDS Section 8).

Response:
IF ON SKIN: Wash with plenty of soap and water.
IF exposed or concerned: Get medical attention.
If skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

Storage:
Store locked up.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	25036-25-3	40 - 70
Calcium Silicate	13983-17-0	20 - 40
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	25036-25-3	1 - 5 Trade Secret *
Dicyandiamide	461-58-5	1 - 5
Titanium Dioxide	13463-67-7	0.5 - 1.5 Trade Secret *
4,4'-isopropylidenediphenol	80-05-7	0.1 - 1 Trade Secret *
Epoxy Resin - Amine Condensate	68002-42-6	< 1
Quartz Silica	14808-60-7	< 0.9

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
Powdered material may form explosive dust-air mixture. Avoid fire fighting methods that would cause powders to become airborne.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Eliminate all ignition sources if safe to do so. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2

and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Vacuum to avoid dusting. WARNING! A motor could be an ignition source and cause combustible dust in the spill area to burn or explode. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required. Dust clouds of this material in sufficient concentration in combination with an ignition source may be explosive. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions. Routine housekeeping should be instituted to ensure that combustible dusts do not accumulate on surfaces. Solids can generate static electricity charges when transferred and in mixing operations sufficient to be an ignition source. Evaluate the need for precautions, such as grounding and bonding, low energy transfer of material (e.g. low speed, short distance), or inert atmospheres.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Calcium Silicate	13983-17-0	ACGIH	TWA(inhalable fraction):1 mg/m3	A4: Not class. as human carcin
Quartz Silica	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. It is recommended that all dust control equipment (such as local exhaust ventilation), process equipment, and material transport systems involved in handling of this product be evaluated for the need for explosion-protection safeguards. Recognized safeguards include explosion relief vents, explosion suppression systems, and oxygen deficient process environments. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Evaluate the need for electrically classified equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid

Specific Physical Form:	Powder
Color	Green
Odor	Minimal Epoxy
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*No Data Available*
Boiling point/Initial boiling point/Boiling range	*Not Applicable*
Flash Point	No flash point
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*Not Applicable*
Relative Vapor Density	*Not Applicable*
Density	1.44 g/cm3
Relative Density	1.44 [*Ref Std:*WATER=1]
Water solubility	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*Not Applicable*
Volatile Organic Compounds	0 %
Percent volatile	0 %
VOC Less H2O & Exempt Solvents	0 %
Molecular weight	*No Data Available*
***Dust deflagration index (Kst)**	70 - 250 bar.m/s [*Details:*Typical Range]
***Min. explosible conc.(MEC)**	35 - 55 g/m3 [*Details:*Typical Range]
***Min. ignition energy (MIE)**	3 - 100 mJ [*Details:*Typical Range]
***Min. ign temp(MIT)-dust cloud**	450 - 550 ºC [*Details:*Typical Range]

***** The values noted with an asterisk (*****) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterization testing based on the use factors at the specific facility.

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid
Sparks and/or flames

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:
Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Photosensitization: Signs/symptoms may include a sunburn-like reaction such as blistering, redness, swelling, and itching from minor exposure to sunlight.

Eye Contact:
Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Silica, Crystalline (Respirable Size)	14808-60-7	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Ingestion	Rat	LD50 > 1,000 mg/kg
Calcium Silicate	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Silicate	Dermal	similar compounds	LD50 > 5,000 mg/kg
Calcium Silicate	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 2.08 mg/l
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Ingestion	Rat	LD50 > 1,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Epoxy Resin - Amine Condensate	Dermal	Rat	LD50 > 2,000 mg/kg
Epoxy Resin - Amine Condensate	Ingestion	Rat	LD50 > 2,000 mg/kg
4,4'-isopropylidenediphenol	Dermal	Rabbit	LD50 > 2,000 mg/kg
4,4'-isopropylidenediphenol	Ingestion	Rat	LD50 3,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Rabbit	No significant irritation
Calcium Silicate	similar compounds	No significant irritation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Rabbit	Mild irritant
Dicyandiamide	Human and animal	Minimal irritation
Titanium Dioxide	Rabbit	No significant irritation
Quartz Silica	Professional judgement	No significant irritation

Epoxy Resin - Amine Condensate	Rabbit	No significant irritation
4,4'-isopropylidenediphenol	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Rabbit	Mild irritant
Calcium Silicate	similar compounds	Mild irritant
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Rabbit	Moderate irritant
Dicyandiamide	Professional judgement	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Epoxy Resin - Amine Condensate	Rabbit	No significant irritation
4,4'-isopropylidenediphenol	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Guinea pig	Not classified
Calcium Silicate	Human	Not classified
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Human and animal	Sensitizing
Dicyandiamide	Guinea pig	Not classified
Titanium Dioxide	Human and animal	Not classified
Epoxy Resin - Amine Condensate	Guinea pig	Sensitizing
4,4'-isopropylidenediphenol	official classification	Sensitizing

Photosensitization

Name	Species	Value
4,4'-isopropylidenediphenol	Human and animal	Sensitizing

Respiratory Sensitization

Name	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Human	Not classified
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	In vivo	Not mutagenic
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	In Vitro	Some positive data exist, but the data are not sufficient for classification
Calcium Silicate	In Vitro	Not mutagenic
Calcium Silicate	In vivo	Not mutagenic
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	In vivo	Not mutagenic
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	In Vitro	Not mutagenic

Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin - Amine Condensate	In Vitro	Not mutagenic
4,4'-isopropylidenediphenol	In vivo	Not mutagenic
4,4'-isopropylidenediphenol	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Quartz Silica	Inhalation	Human and animal	Carcinogenic
4,4'-isopropylidenediphenol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Calcium Silicate	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,600 mg/kg/day	during organogenesis
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
4,4'-isopropylidenediphenol	Ingestion	Not classified for female reproduction	Multiple animal	NOAEL 50 mg/kg/day	

			species		
4,4'-isopropylidenediphenol	Ingestion	Not classified for male reproduction	Multiple animal species	NOAEL 50 mg/kg/day	
4,4'-isopropylidenediphenol	Ingestion	Toxic to development	Multiple animal species	NOAEL 50 mg/kg/day	

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-isopropylidenediphenol	Inhalation	respiratory irritation	May cause respiratory irritation	Multiple animal species	LOAEL 0.152 mg/l	15 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>1200	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Calcium Silicate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Calcium Silicate	Inhalation	pulmonary fibrosis	Not classified	Human and animal	NOAEL Not available	
Calcium Silicate	Ingestion	liver | kidney and/or bladder | hematopoietic system	Not classified	Rat	NOAEL 2,500 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A Diglycidyl Ether-Bisphenol A Copolymer, MW>700, <=1200	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz Silica	Inhalation	silicosis	Causes damage to organs through	Human	NOAEL Not	occupational

			prolonged or repeated exposure		available	exposure
4,4'-isopropylidenediphenol	Inhalation	liver | kidney and/or bladder | hematopoietic system	Not classified	Rat	NOAEL 0.15 mg/l	13 weeks
4,4'-isopropylidenediphenol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	3 generation
4,4'-isopropylidenediphenol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 370 mg/kg/day	13 weeks
4,4'-isopropylidenediphenol	Ingestion	endocrine system | hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	3 generation
4,4'-isopropylidenediphenol	Ingestion	nervous system	Not classified	Rat	NOAEL 185 mg/kg/day	90 days
4,4'-isopropylidenediphenol	Ingestion	heart | bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 2,400 mg/kg/day	13 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Combustible Dust

Health Hazards
Carcinogenicity
Reproductive toxicity
Respiratory or Skin Sensitization

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations
Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: *2 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	06-3395-8	**Version Number:**	41.04
Issue Date:	10/09/25	**Supersedes Date:**	07/14/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES

NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com