Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	31-7396-0	**Version number:**	3.00
Issue Date:	2025/06/12	**Supercedes Date:**	2020/10/22

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M(TM) AEROSPACE SEALANT AC-380 B-1/2 PMF

Product Identification Numbers

70-0052-0639-9	70-0052-0640-7	70-0052-0753-8	70-0052-0754-6	70-0052-0755-3
70-0052-0763-7	70-0052-0764-5	70-0052-0943-5	70-0052-0945-0	70-0052-0946-8
70-0052-0947-6	UU-0097-5644-4	UU-0097-5645-1	UU-0097-5662-6	

1.2. Recommended use and restrictions on use

Intended Use
For industrial or professional use only., Sealant

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Automotive and Aerospace Solutions Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark |Health Hazard |

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: nervous system | respiratory system.

Precautionary statements

Prevention:
Do not breathe vapours, dust, or spray. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and respiratory protection.

Response:
IF ON SKIN: Wash with plenty of soap and water. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards
None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Polysulfide Rubber	68611-50-7	60 - 70	Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na2(Sx)), reduced
Calcium Carbonate	471-34-1	10 - 20	Carbonic acid calcium salt (1:1)
Hydrogenated terphenyl	61788-32-7	1 - 5	Terphenyl, hydrogenated
Manganese Dioxide	1313-13-9	1 - 5 Trade Secret *	Manganese oxide (MnO2)
Titanium Dioxide	13463-67-7	1 - 2 Trade Secret *	Titanium oxide (TiO2)
Epoxy Resin	25085-99-8	0.1 - 1 Trade Secret *	Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer
Quartz Silica	14808-60-7	< 0.1	Quartz (SiO2)

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

5.4. Special protection actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
MANGANESE, INORGANIC COMPOUNDS	1313-13-9	ACGIH	TWA(as Mn, respirable fraction):0.02 mg/m3;TWA(as Mn, inhalable fraction):0.1 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	
Hydrogenated terphenyl	61788-32-7	ACGIH	TWA:0.5 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Dark Gray
Odour	Pungent Sulfuric
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*Not Applicable*
Boiling point	*Not Applicable*
Flash Point	>=93.3 ºC [*Test Method:*Closed Cup]
Evaporation rate	*No Data Available*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapour Pressure	*No Data Available*
Relative Vapour Density	*No Data Available*
Density	1.1 g/ml
Relative density	1.1 [*Ref Std:*WATER=1]
Water solubility	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*No Data Available*

Volatile Organic Compounds	2.4 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	2.4 g/l [*Test Method:*calculated SCAQMD rule 443.1]

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
Reducing agents
Strong bases
Strong acids

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
May cause additional health effects (see below).

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE (RESPIRABLE SIZE)	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
SILICA DUST, CRYSTALLINE, IN THE FORM OF QUARTZ OR CRISTOBALITE	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polysulfide Rubber	Dermal	Rat	LD50 > 7,800 mg/kg
Polysulfide Rubber	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Manganese Dioxide	Dermal	Rat	LD50 2,000 mg/kg
Manganese Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
Manganese Dioxide	Ingestion	Rat	LD50 > 2,197 mg/kg
Hydrogenated terphenyl	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrogenated terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.7 mg/l
Hydrogenated terphenyl	Ingestion	Rat	LD50 > 10,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polysulfide Rubber	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Manganese Dioxide	Rabbit	No significant irritation

Hydrogenated terphenyl	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Epoxy Resin	Rabbit	Mild irritant
Quartz Silica	Professional judgement	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Polysulfide Rubber	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Manganese Dioxide	Rabbit	Mild irritant
Hydrogenated terphenyl	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Epoxy Resin	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Polysulfide Rubber		Not classified
Manganese Dioxide	Mouse	Not classified
Hydrogenated terphenyl	Human	Not classified
Titanium Dioxide	Human and animal	Not classified
Epoxy Resin	Human and animal	Sensitizing

Respiratory Sensitization

Name	Species	Value
Epoxy Resin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Manganese Dioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Manganese Dioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Hydrogenated terphenyl	In Vitro	Not mutagenic
Hydrogenated terphenyl	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	Inhalation	Human	Carcinogenic

		and animal	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Manganese Dioxide	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m3	2 generation
Manganese Dioxide	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
Manganese Dioxide	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	premating into lactation
Manganese Dioxide	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m3	gestation into lactation
Hydrogenated terphenyl	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Manganese Dioxide	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m3	10 months
Manganese Dioxide	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hydrogenated terphenyl	Dermal	skin	Not classified	Rabbit	NOAEL 500 mg/kg/day	3 weeks
Hydrogenated terphenyl	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 2,000 mg/kg/day	3 weeks
Hydrogenated terphenyl	Inhalation	liver | hematopoietic system | eyes	Not classified	Rat	NOAEL 0.5 mg/l	13 weeks
Hydrogenated terphenyl	Ingestion	hematopoietic system | kidney and/or bladder | liver | eyes | respiratory system	Not classified	Rat	NOAEL 120 mg/kg/day	14 weeks

Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	31-7396-0	**Version number:**	3.00
Issue Date:	2025/06/12	**Supercedes Date:**	2020/10/22

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca