



## Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	19-2499-2	<b>Version number:</b>	9.07
<b>Issue Date:</b>	2025/09/11	<b>Supersedes Date:</b>	2025/06/19

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT

##### Product Identification Numbers

98-0400-5503-4	98-0400-5503-4	98-0400-5504-2	98-0400-5504-2	98-0400-5553-9
98-0400-5553-9	98-0400-5586-9	AK-2001-2921-6	JE-6000-0338-6	JS-3000-5104-7
UU-0108-7770-0	XE-1014-9500-2	XE-1014-9924-4		

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Caulk

##### Specific Use

Fire barrier caulking.

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Industrial Adhesives and Tapes Division
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

### SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place:  
XE-1014-9924-4

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.  
Carcinogenicity: Category 1B.  
Reproductive Toxicity: Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure: kidney/urinary tract.  
May cause damage to organs through prolonged or repeated exposure: blood or blood-forming organs | respiratory system.

### Precautionary statements

#### General:

Keep out of reach of children.

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and if needed, respiratory protection (see SDS Section 8).

#### Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse.

#### Storage:

Store locked up.

#### Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

## 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>% by Wt</b>	<b>Common Name</b>
Melamine	108-78-1	30 - 40 Trade Secret *	1,3,5-Triazine-2,4,6-triamine
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	70131-67-8	15 - 40	Siloxanes and Silicones, di-Me, hydroxy-terminated
Graphite	7782-42-5	10 - 25	Graphite
Poly (Dimethylsiloxane)	63148-62-9	10 - 25	Siloxanes and Silicones, di-Me
Methyl Tris(2-Butylideneaminoxy)Silane	22984-54-9	3 - 5 Trade Secret *	2-Butanone, O,O',O''-(methylsilyldiyl)trioxime
Silica	7631-86-9	<= 3	Silica
Methyl ethyl ketone oxime	96-29-7	<= 1	No Data Available
3-Iodo-2-Propynyl Butylcarbamate	55406-53-6	< 0.1	Carbamic acid, butyl-, 3-iodo-2-propynyl ester
Octamethylcyclotetrasiloxane	556-67-2	< 0.1	Octamethylcyclotetrasiloxane

\*The concentration (exact or range) of this component has been withheld as a trade secret.

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### **4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

### **5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### **5.2. Unsuitable extinguishing media**

None Determined

### **5.3. Special hazards arising from the substance or mixture**

None inherent in this product.

### **Hazardous Decomposition or By-Products**

#### **Substance**

Formaldehyde

#### **Condition**

During Combustion

Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

During Combustion  
During Combustion  
During Combustion

**5.4. Special protection actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from oxidizing agents. Store locked up.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Melamine	108-78-1	AIHA	TWA(inhalable particulates):3 mg/m3	
Octamethylcyclotetrasiloxane	556-67-2	AIHA	TWA:10 ppm	
Particles (insoluble or poorly soluble) not otherwise specified,	7631-86-9	ACGIH	TWA(inhalable particulates):10 mg/m3	

inhalable particles				
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	7631-86-9	ACGIH	TWA(respirable particles):3 mg/m3	
Graphite	7782-42-5	ACGIH	TWA(respirable fraction):2 mg/m3	
Methyl ethyl ketone oxime	96-29-7	AIHA	TWA:36 mg/m3(10 ppm)	Dermal Sensitizer

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	Black, Gray
Odour	Moderate Silicone
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	No Data Available
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Relative Vapour Density	Nil
Relative density	1.25 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Kinematic Viscosity	No Data Available
Volatile Organic Compounds	<=5.3 % weight [Test Method:tested per EPA method 24]
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	<=65 g/l [Test Method:tested per EPA method 24]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Not determined

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

##### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Hematopoietic Effects: Signs/symptoms may include generalized weakness, fatigue and alterations in numbers of circulating blood cells. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure. Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

##### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Melamine	108-78-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

**3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Melamine	Dermal	Rabbit	LD50 > 1,000 mg/kg
Melamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
Melamine	Ingestion	Rat	LD50 3,161 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Dermal	Rabbit	LD50 > 16,000 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	Ingestion	Rat	LD50 > 64,000 mg/kg
Graphite	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly (Dimethylsiloxane)	Dermal	Multiple animal species	LD50 > 2,000 mg/kg
Graphite	Ingestion	Rat	LD50 > 2,000 mg/kg
Poly (Dimethylsiloxane)	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl Tris(2-Butylideneaminoxy)Silane	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	Rat	LD50 2,260 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Methyl ethyl ketone oxime	Dermal	official classification	LD50 1,100 mg/kg
Methyl ethyl ketone oxime	Ingestion	official classification	LD50 100 mg/kg
Methyl ethyl ketone oxime	Inhalation-Vapor	Rat	LC50 estimated to be 20 - 50 mg/l
Octamethylcyclotetrasiloxane	Dermal	Rat	LD50 > 2,400 mg/kg
Octamethylcyclotetrasiloxane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 36 mg/l
Octamethylcyclotetrasiloxane	Ingestion	Rat	LD50 > 4,800 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Dermal	Rabbit	LD50 > 2,000 mg/kg
3-Iodo-2-Propynyl Butylcarbamate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.67 mg/l
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Rat	LD50 1,056 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Melamine	Rabbit	No significant irritation
Graphite	Rabbit	No significant irritation
Poly (Dimethylsiloxane)	Human and animal	No significant irritation
Methyl Tris(2-Butylideneaminoxy)Silane	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Methyl ethyl ketone oxime	Rabbit	Irritant
Octamethylcyclotetrasiloxane	Rabbit	No significant irritation
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Melamine	Rabbit	No significant irritation



**3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT**

Graphite	Rabbit	No significant irritation
Poly (Dimethylsiloxane)	Rabbit	No significant irritation
Methyl Tris(2-Butylideneaminoxy)Silane	Rabbit	Moderate irritant
Silica	Rabbit	No significant irritation
Methyl ethyl ketone oxime	Rabbit	Corrosive
Octamethylcyclotetrasiloxane	Rabbit	No significant irritation
3-Iodo-2-Propynyl Butylcarbamate	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
Melamine	Guinea pig	Not classified
Poly (Dimethylsiloxane)	Human and animal	Not classified
Methyl Tris(2-Butylideneaminoxy)Silane	Guinea pig	Sensitizing
Silica	Human and animal	Not classified
Methyl ethyl ketone oxime	Guinea pig	Sensitizing
Octamethylcyclotetrasiloxane	Human and animal	Not classified
3-Iodo-2-Propynyl Butylcarbamate	Multiple animal species	Sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Melamine	In Vitro	Not mutagenic
Melamine	In vivo	Not mutagenic
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	In Vitro	Not mutagenic
Graphite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Poly (Dimethylsiloxane)	In Vitro	Not mutagenic
Poly (Dimethylsiloxane)	In vivo	Not mutagenic
Methyl Tris(2-Butylideneaminoxy)Silane	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
Methyl ethyl ketone oxime	In Vitro	Not mutagenic
Methyl ethyl ketone oxime	In vivo	Not mutagenic
Octamethylcyclotetrasiloxane	In vivo	Not mutagenic
Octamethylcyclotetrasiloxane	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-Iodo-2-Propynyl Butylcarbamate	In Vitro	Not mutagenic
3-Iodo-2-Propynyl Butylcarbamate	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Melamine	Ingestion	Multiple animal species	Carcinogenic
Poly (Dimethylsiloxane)	Dermal	Mouse	Not carcinogenic
Poly (Dimethylsiloxane)	Ingestion	Mouse	Not carcinogenic
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl ethyl ketone oxime	Inhalation	Multiple animal species	Carcinogenic

**3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT**

Octamethylcyclotetrasiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Melamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,227 mg/kg/day	2 generation
Melamine	Ingestion	Not classified for development	Rat	NOAEL 1,060 mg/kg/day	during organogenesis
Melamine	Ingestion	Toxic to male reproduction	Rat	NOAEL 89 mg/kg/day	2 generation
Poly (Dimethylsiloxane)	Ingestion	Not classified for development	Rat	NOAEL 3,800 mg/kg/day	during organogenesis
Poly (Dimethylsiloxane)	Dermal	Not classified for development	Rabbit	NOAEL 1,000 mg/kg/day	during organogenesis
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	premating into lactation
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	28 days
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	Not classified for development	Rat	NOAEL 250 mg/kg/day	premating into lactation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Methyl ethyl ketone oxime	Ingestion	Not classified for female reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Methyl ethyl ketone oxime	Ingestion	Not classified for male reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Methyl ethyl ketone oxime	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	during organogenesis
Octamethylcyclotetrasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxane	Inhalation	Not classified for development	Rabbit	NOAEL 6 mg/l	during organogenesis
Octamethylcyclotetrasiloxane	Ingestion	Not classified for development	Rabbit	NOAEL 100 mg/kg	during organogenesis
Octamethylcyclotetrasiloxane	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for female reproduction	Rat	NOAEL 37.5 mg/kg/day	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for male reproduction	Rat	NOAEL 37.5 mg/kg/day	2 generation
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

**3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT**

Methyl Tris(2-Butylideneaminoxy)Silane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl ethyl ketone oxime	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl ethyl ketone oxime	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 100 mg/kg	
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Melamine	Ingestion	kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 44.6 mg/kg/day	90 days
Melamine	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,400 mg/kg/day	90 days
Graphite	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Poly (Dimethylsiloxane)	Ingestion	eyes	Not classified	Rat	NOAEL 10%	90 days
Poly (Dimethylsiloxane)	Ingestion	respiratory system	Not classified	Rat	NOAEL 1%	90 days
Poly (Dimethylsiloxane)	Ingestion	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 10%	90 days
Poly (Dimethylsiloxane)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10%	90 days
Poly (Dimethylsiloxane)	Ingestion	heart   liver   kidney and/or bladder   vascular system	Not classified	Rat	NOAEL 1%	90 days
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 10 mg/kg/day	28 days
Methyl Tris(2-Butylideneaminoxy)Silane	Ingestion	endocrine system   liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 250 mg/kg/day	28 days
Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Methyl ethyl ketone oxime	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.36 mg/l	28 days
Methyl ethyl ketone oxime	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Mouse	NOAEL 0.01 mg/l	90 days
Methyl ethyl ketone oxime	Inhalation	liver	Not classified	Rat	NOAEL 1.44 mg/l	28 days
Methyl ethyl ketone oxime	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 25 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	nervous system	Not classified	Rat	NOAEL 400 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	liver   kidney and/or bladder   heart	Not classified	Rat	NOAEL 335 mg/kg/day	90 days

**3M(TM) FIRE BARRIER WATERTIGHT SEALANT 3000 WT**

		endocrine system   bone, teeth, nails, and/or hair   immune system				
Octamethylcyclotetrasiloxane	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
Octamethylcyclotetrasiloxane	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxane	Inhalation	endocrine system   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxane	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks
3-Iodo-2-Propynyl Butylcarbamate	Dermal	skin   heart   hematopoietic system   liver   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.00116 mg/l	90 days
3-Iodo-2-Propynyl Butylcarbamate	Inhalation	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   vascular system	Not classified	Rat	NOAEL 0.00625 mg/l	90 days
3-Iodo-2-Propynyl Butylcarbamate	Ingestion	liver   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the

respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification**

**Health: \*3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document group:</b>	19-2499-2	<b>Version number:</b>	9.07
<b>Issue Date:</b>	2025/09/11	<b>Supersedes Date:</b>	2025/06/19

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**