

Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 07-4018-3
 Version number:
 17.00

 Revision date:
 08/01/2025
 Supersedes date:
 23/05/2023

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3MTM Scotch-WeldTM EC-9323 B/A

Product Identification Numbers

FS-9100-5467-5 FS-9100-5468-3 FS-9100-5470-9

7000080436 7000080437 7000080439

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

07-4016-7, 07-4015-9

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |





Contains:

bis-[4-(2,3-epoxipropoxi)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); 2,4,6-tris(dimethylaminomethyl)phenol

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260B Do not breathe dust.

P273 Avoid release to the environment.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260B Do not breathe dust.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit: Component document group number(s) information was modified. Section 2: <125ml Precautionary - Response information was modified. Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 07-4015-9
 Version number:
 19.03

 Revision date:
 08/01/2025
 Supersedes date:
 06/09/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |





Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	60 - 90
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	7 - 13

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P260B Do not breathe dust.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260B Do not breathe dust.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	60 - 90	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9	7 - 13	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
Synthetic amorphous silica, fumed, crystalline-free	(CAS-No.) 112945-52-5	5 - 10	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide.
Irritant vapours or gases.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Condition

During combustion.

During combustion.

During combustion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Silicon dioxide 112945-52-5 UK HSE TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eve/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.7	=>8 hours
Neoprene.	0.5	=>8 hours
Nitrile rubber.	0.4	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing.

Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Red
Odor	Light Amine
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	>=100 °C
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	>=100 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	15,094 mm ² /sec
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	Not applicable.
Density	1.04 - 1.08 g/ml
Relative density	1.04 - 1.08 [<i>Ref Std:</i> WATER=1]
Relative Vapour Density	Not applicable.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Molecular weightNot applicable.Percent volatile0 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling,

itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professio nal judgemen t	Sensitising
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified
Synthetic amorphous silica, fumed, crystalline-free	Human	Not classified

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

and	
animal	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Synthetic amorphous silica, fumed, crystalline-free	Not	Mouse	Some positive data exist, but the data are not
	specified.		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2,4,6- tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic	Not classified	Rat	NOAEL 600 mg/kg/day	59 days

		system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system				
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Ingestion	heart endocrine system hematopoietic system liver muscles nervous system kidney and/or bladder respiratory system vascular system auditory system skin gastrointestinal tract bone, teeth, nails, and/or hair immune system eyes	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
Synthetic amorphous silica, fumed, crystalline-free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
3,3'-	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Oxybis(ethyleneox			1			
y)bis(propylamine)						
3,3'-	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Oxybis(ethyleneox			1			
y)bis(propylamine)						

3,3'-	1246 51 0	C1	E	72 hours	ECEO	> 500/1
Oxybis(ethyleneox	4246-51-9	Green algae	Experimental	/2 nours	EC50	>500 mg/l
y)bis(propylamine)						
3,3'-	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
2,4,6-	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
tris(dimethylamino			1			
methyl)phenol						
2,4,6-	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
tris(dimethylamino	70-72-2	Common Carp	Experimental	70 Hours	LCSO	> 100 mg/1
methyl)phenol						
	00.72.2	C 1	F ' / 1	72.1	ECEO	46.7
2,4,6-	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
tris(dimethylamino						
methyl)phenol						
2,4,6-	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
tris(dimethylamino						
methyl)phenol						
2,4,6-	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
tris(dimethylamino						
methyl)phenol						
Synthetic	112945-52-5	Green algae	Analogous	72 hours	ErC50	>173.1 mg/l
amorphous silica,	1127 10 02 0	Green argue	Compound	72 110410	Liceo	1,311 mg.1
fumed, crystalline-			Compound			
free						
Synthetic	112945-52-5	Sediment organism	Analogous	96 hours	EC50	8,500 mg/kg (Dry Weight)
amorphous silica,	112943-32-3	Sedifficiti organism	Compound	90 Hours	ECSU	6,500 mg/kg (Dry Weight)
			Compound			
fumed, crystalline-						
free	112045 52 5	777 · G		241	EX 50	10.000 //
Synthetic	112945-52-5	Water flea	Analogous	24 hours	EL50	>10,000 mg/l
amorphous silica,			Compound			
fumed, crystalline-						
free						
Synthetic	112945-52-5	Zebra Fish	Analogous	96 hours	LL50	>10,000 mg/l
amorphous silica,			Compound			
fumed, crystalline-						
free						
Synthetic	112945-52-5	Green algae	Analogous	72 hours	NOEC	173.1 mg/l
amorphous silica,			Compound			5
fumed, crystalline-						
free						
Synthetic	112945-52-5	Water flea	Analogous	21 days	NOEC	68 mg/l
amorphous silica,	114945-34-3	water rica	Compound	21 days	NOEC	00 mg/1
			Compound			
fumed, crystalline-						
free	1110015	1	- · ·	2.1	Pos:	1,000 "
Synthetic	112945-52-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
amorphous silica,						
fumed, crystalline-						
free						
	•	•	-	•	•	•

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test
Synthetic amorphous silica,	112945-52-5	Data not availbl- insufficient	N/A	N/A	N/A	N/A

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part A)

fumed, crystalline-			
free			

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	''''	830.7550 Part.Coef Shake Flask
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
-)-			Koc	1 l/kg	ACD/Labs ChemSketch™
Oxybis(ethyleneoxy		in Soil			
)bis(propylamine)					

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Ground Transport (ADR) Air Transport (IATA)	Marine Transport (IMDG)
---	-------------------------

14.1 UN number	UN3259	UN3259	UN3259
14.2 UN proper shipping name	AMINES, SOLID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	AMINES, SOLID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	AMINES, SOLID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY)BIS(PRO PYLAMINE))
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C8	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Revision information:

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was modified.

Section 02: Label Elements: GB Percent Unknown information was deleted.

Section 7: Precautions safe handling information information was modified.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Section 8: Respiratory protection - recommended respirators information information was modified.

Section 8: Skin protection - protective clothing information information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 11: Health Effects - Skin information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Section 14: Transportation classification information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 07-4016-7
 Version number:
 22.00

 Revision date:
 08/07/2025
 Supersedes date:
 06/09/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms





Ingredient CAS Nbr EC No. % by Wt

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3 216-823-5 60 - 90

HAZARD STATEMENTS:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

16% of the mixture consists of components of unknown acute oral toxicity.

Contains 18% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	60 - 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Acrylic copolymer	Trade Secret	10 - 20	Substance not classified as hazardous
Calcium carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	5 - 10	Substance with a national occupational exposure limit
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 5	Substance with a national occupational exposure limit
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4	< 0.5	Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
	l` ′	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part B)

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionAldehydes.During combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2,6-Di-tert-butyl-p-cresol	128-37-0	UK HSE	TWA:10 mg/m ³	
DUST, INERT OR NUISANCE	471-34-1	UK HSE	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Silicon dioxide	67762-90-7	UK HSE	TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable dust):6 mg/m3	

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminate>0.30=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.	
Specific Physical Form:	Paste	
Colour	Off-White	
Odor	Light Epoxy	
Odour threshold	No data available.	
Melting point/freezing point	No data available.	
Boiling point/boiling range	No data available.	
Flammability	Not applicable.	
Flammable Limits(LEL)	Not applicable.	
Flammable Limits(UEL)	Not applicable.	
Flash point	150 °C [Test Method:Closed Cup]	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
pH	substance/mixture is non-soluble (in water)	
Kinematic Viscosity	1,271,186 mm ² /sec	
Water solubility	Nil	

Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	Not applicable.
Density	1.16 - 1.2 g/ml
Relative density	1.16 - 1.2 [<i>Ref Std</i> :WATER=1]
Relative Vapour Density	Not applicable.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Molecular weightNot applicable.Percent volatile<=1 % weight</th>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Calcium carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium carbonate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant	
Calcium carbonate	Rabbit	No significant irritation	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation	
2,6-Di-tert-butyl-p-cresol	Human	Minimal irritation	
	and		
	animal		

Serious Eve Damage/Irritation

Serious Lye Damage/Hittation			
Name	Species	Value	
	•		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant	
Calcium carbonate	Rabbit	No significant irritation	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation	

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part B)

2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
----------------------------	--------	---------------

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
2,6-Di-tert-butyl-p-cresol	Human	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Calcium carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500	2 generation

				mg/kg/day	
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500	2 generation
	_	_		mg/kg/day	
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100	2 generation
		•		mg/kg/day	

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
Calcium carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes
					0.812 mg/l	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Calcium carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and

data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2,6-Di-tert-butyl-p- cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p- cresol		Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p- cresol		Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p- cresol		Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Calcium carbonate	471-34-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me,	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part B)

reaction products with silica						
2,6-Di-tert-butyl-p-	128-37-0	Data not availbl-	N/A	N/A	N/A	N/A
cresol		insufficient				

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Calcium carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,6-Di-tert-butyl-p- cresol	128-37-0	Experimental BCF - Fish	,	Bioaccumulation factor	1277	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-	1675-54-3		Koc	450 l/kg	Episuite TM
epoxipropoxi)pheny		in Soil			
1]propane					

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(4,4'- ISOPROPYLIDENEDIPHE NOL-EPICHLOROHYDRIN POLYMER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(4,4'- ISOPROPYLIDENEDIPHEN OL-EPICHLOROHYDRIN POLYMER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(4,4'- ISOPROPYLIDENEDIPHENOL- EPICHLOROHYDRIN POLYMER)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity <u>Ingredient</u>	CAS Nbr	Classification	Regulation
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

1675-54-3

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 1: E-mail address information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 11: Health Effects - Inhalation information information was modified.

3M Scotch-Weld™ Structural Adhesive EC-9323 B/A (Part B)

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.