

# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-1562-5
 Version number:
 18.00

 Revision date:
 29/09/2025
 Supersedes date:
 20/08/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>™</sup> EDGE SEALER 4150S

#### **Product Identification Numbers**

70-0012-0729-2 75-3465-4470-5

7000005083 7100282732

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Sealant

### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

### **CLASSIFICATION:**

Flammable Liquid, Category 3 - Flam. Liq. 3; H226

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

WARNING.

#### **Symbols**

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

#### **Pictograms**







Ingredient	CAS Nbr	EC No.	% by Wt
2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	15 - 40
m-xylene	108-38-3	203-576-3	7 - 13
ethylbenzene	100-41-4	202-849-4	1 - 7
p-xylene	106-42-3	203-396-5	1 - 7
o-xylene	95-47-6	202-422-2	1 - 5
xylene	1330-20-7	215-535-7	1 - 5

#### **HAZARD STATEMENTS:**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure: nervous system | sensory

organs.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260A Do not breathe vapours.

**Response:** 

### 3M<sup>TM</sup> EDGE SEALER 4150S

P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P370 + P378In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or

carbon dioxide to extinguish.

#### SUPPLEMENTAL INFORMATION:

### **Supplemental Hazard Statements:**

**EUH208** Contains methyl methacrylate. May produce an allergic reaction.

25% of the mixture consists of components of unknown acute oral toxicity.

25% of the mixture consists of components of unknown acute dermal toxicity.

25% of the mixture consists of components of unknown acute inhalation toxicity.

Contains 25% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	0/0	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9	15 - 40	Flam. Liq. 3, H226 STOT SE 3, H336
Acrylic Polymer(s)	Trade Secret	10 - 30	Substance not classified as hazardous
Proprietary Polymer	Trade Secret	5 - 15	Substance not classified as hazardous
m-xylene	(CAS-No.) 108-38-3 (EC-No.) 203-576-3	7 - 13	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315 Nota C Asp. Tox. 1, H304 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4	1 - 7	Flam. Liq. 2, H225 Acute Tox. 4, H332 Asp. Tox. 1, H304 STOT RE 2, H373 Aquatic Chronic 3, H412
p-xylene	(CAS-No.) 106-42-3 (EC-No.) 203-396-5	1 - 7	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315 Nota C

		1	
			Asp. Tox. 1, H304
			Eye Irrit. 2, H319
			STOT SE 3, H335
			STOT RE 2, H373
			Aquatic Chronic 3, H412
o-xylene	(CAS-No.) 95-47-6	1 - 5	Flam. Liq. 3, H226
	(EC-No.) 202-422-2		Acute Tox. 4, H332
			Acute Tox. 4, H312
			Skin Irrit. 2, H315
			Nota C
			Asp. Tox. 1, H304
			Eye Irrit. 2, H319
			STOT SE 3, H335
			STOT RE 2, H373
			Aquatic Acute 1, H400,M=1
			Aquatic Chronic 3, H412
1	(CAS No.) 1220 20 7	1 - 5	
xylene	(CAS-No.) 1330-20-7	1 - 3	Flam. Liq. 3, H226
	(EC-No.) 215-535-7		Acute Tox. 4, H332
			Acute Tox. 4, H312
			Skin Irrit. 2, H315
			Nota C
			Asp. Tox. 1, H304
			Eye Irrit. 2, H319
			STOT SE 3, H335
			STOT RE 2, H373
			Aquatic Chronic 3, H412
methyl methacrylate	(CAS-No.) 80-62-6	< 0.3	Flam. Liq. 2, H225
	(EC-No.) 201-297-1		Skin Irrit. 2, H315
			Skin Sens. 1, H317
			STOT SE 3, H335
			Nota D
methacrylic acid	(CAS-No.) 79-41-4	< 0.3	Acute Tox. 3, H311
	(EC-No.) 201-204-4		Acute Tox. 4, H302
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			STOT SE 3, H335
			Nota D
			Acute Tox. 4, H332
toluene	(CAS-No.) 108-88-3	< 0.3	Flam. Liq. 2, H225
	(EC-No.) 203-625-9		Asp. Tox. 1, H304
	(20 1.0.) 200 020 9		Skin Irrit. 2, H315
			Repr. 2, H361d
			STOT SE 3, H336
			STOT SE 3, 11330 STOT RE 2, H373
			Aquatic Chronic 3, H412
			Aquade Chronic 3, 11412

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
1	(EC-No.) 201-204-4	(C >= 10%) Skin Corr. 1A, H314 (1% =< C < 10%) Skin Irrit. 2, H315 (C >= 1%) STOT SE 3, H335

Page: 4 of 26

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an

accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin: or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type **Additional comments** ethylbenzene 100-41-4 UK HSE TWA:441 mg/m3(100 SKIN

ppm);STEL:552 mg/m3(125

ppm)

2-methoxy-1-methylethyl acetate	108-65-6	UK HSE	TWA:274 mg/m3(50 ppm);STEL:548 mg/m3(100 ppm)	SKIN
toluene	108-88-3	UK HSE	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN
xylene	1330-20-7	UK HSE	TWA:220 mg/m3(50 ppm);STEL:441 mg/m3(100 ppm)	SKIN
methacrylic acid	79-41-4	UK HSE	TWA:72 mg/m³(20 ppm);STEL:143 mg/m³(40 ppm)	
methyl methacrylate	80-62-6	UK HSE	TWA:208 mg/m3(50 ppm);STEL:416 mg/m3(100 ppm)	

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
xylene	1330- 20-7	UK EH40 BMGVs	Methyl hippuric acid	Creatinine in urine	EOS	650 mmol/mol	l

UK EH40 BMGVs: UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	<b>Breakthrough Time</b>
Polymer laminate	No data available	No data available

Applicable Norms/Standards Use gloves tested to EN 374

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part

### 3MTM EDGE SEALER 4150S

of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

intormation on basic physical and chemical prop	crucs		
Physical state	Liquid.		
Colour	Colourless		
Odor	Moderate Solvent		
Odour threshold	No data available.		
Melting point/freezing point	Not applicable.		
Boiling point/boiling range	>=136.1 °C		
Flammability	Flammable liquid: Category 3.		
Flammable Limits(LEL)	approximately 1 % volume		
Flammable Limits(UEL)	approximately 7 % volume		
Flash point	27.2 °C [Test Method: Tagliabue closed cup]		
Autoignition temperature	No data available.		
Decomposition temperature	No data available.		
pH	substance/mixture is non-soluble (in water)		
Kinematic Viscosity	1,129 mm <sup>2</sup> /sec		
Water solubility	approximately 8 g/100 ml		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Vapour pressure	<=946.6 Pa [@ 20 °C ]		
Density	0.93 g/ml		
Relative density	0.93 [ <i>Ref Std</i> :WATER=1]		
Relative Vapour Density	approximately 4.2 Units not available or not applicable. [Ref		
	Std:AIR=1]		
Particle Characteristics	Not applicable.		

### 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

**Evaporation rate** <=1 [Ref Std:BUOAC=1]

Molecular weight No data available.

Percent volatile 50 - 70 %

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

#### 3M<sup>™</sup> EDGE SEALER 4150S

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat

Sparks and/or flames.

#### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

#### Substance

Carbon monoxide Carbon dioxide.

#### Condition

Not specified. Not specified.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### **Eve contact**

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

### Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

### Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

# **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### **Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Acute Toxicity Name	Route	Species	Value
Overall product	Dermal	Species	No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE >50 mg/l
Overall product	Vapour(4		No data available, calculated ATE >30 Hig/I
	hr)		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-methoxy-1-methylethyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-methoxy-1-methylethyl acetate	Inhalation-	Rat	LC50 > 28.8  mg/l
,,	Vapour (4		Jan 111 g
	hours)		
2-methoxy-1-methylethyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Proprietary Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Proprietary Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
m-xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
m-xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapour (4		
	hours)		
m-xylene	Ingestion	Rat	LD50 3,523 mg/kg
p-xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
p-xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapour (4		
	hours)	D-4	I D50 2 522/-
p-xylene ethylbenzene	Ingestion Dermal	Rat Rabbit	LD50 3,523 mg/kg LD50 15,433 mg/kg
ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
emyloenzene	Vapour (4	Kat	LC30 17.4 mg/1
	hours)		
ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
o-xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
o-xylene	Inhalation-	Rat	LC50 29 mg/l
·	Vapour (4		
	hours)		
o-xylene	Ingestion	Rat	LD50 3,523 mg/kg
xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
xylene	Inhalation-	Rat	LC50 29 mg/l
	Vapour (4		
	hours)	D :	I D 50 2 522 //
xylene	Ingestion	Rat	LD50 3,523 mg/kg
toluene toluene	Dermal Inhalation-	Rat Rat	LD50 12,000 mg/kg LC50 30 mg/l
toruene	Vapour (4	Kat	LC50 30 mg/l
	hours)		
toluene	Ingestion	Rat	LD50 5,550 mg/kg
methyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
methyl methacrylate	Inhalation-	Rat	LC50 29.8 mg/l
y	Vapour (4		
	hours)		
methyl methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
methacrylic acid	Dermal	Rabbit	LD50 > 500 mg/kg
methacrylic acid	Inhalation-	Rat	LC50 7.1 mg/l
	Dust/Mist		_

Page: 10 of 26

# 3MTM EDGE SEALER 4150S

	(4 hours)		
methacrylic acid	Ingestion	Rat	LD50 1,320 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
2-methoxy-1-methylethyl acetate	Rabbit	No significant irritation
Proprietary Polymer	Rabbit	No significant irritation
m-xylene	Rabbit	Mild irritant
p-xylene	Rabbit	Mild irritant
ethylbenzene	Rabbit	Mild irritant
o-xylene	Rabbit	Mild irritant
xylene	Rabbit	Mild irritant
toluene	Rabbit	Irritant
methyl methacrylate	Rabbit	Irritant
methacrylic acid	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
2-methoxy-1-methylethyl acetate	Rabbit	Mild irritant
Proprietary Polymer	Rabbit	Mild irritant
m-xylene	Rabbit	Mild irritant
p-xylene	Rabbit	Mild irritant
ethylbenzene	Rabbit	Moderate irritant
o-xylene	Rabbit	Mild irritant
xylene	Rabbit	Mild irritant
toluene	Rabbit	Moderate irritant
methyl methacrylate	Rabbit	Mild irritant
methacrylic acid	Rabbit	Corrosive

# **Skin Sensitisation**

Name	Species	Value
2-methoxy-1-methylethyl acetate	Guinea pig	Not classified
ethylbenzene	Human	Not classified
toluene	Guinea	Not classified
	pig	
methyl methacrylate	Human	Sensitising
	and	
	animal	
methacrylic acid	Guinea	Not classified
	pig	

**Respiratory Sensitisation** 

Name	Species	Value
methyl methacrylate	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
2-methoxy-1-methylethyl acetate	In Vitro	Not mutagenic
m-xylene	In Vitro	Not mutagenic
m-xylene	In vivo	Not mutagenic
p-xylene	In Vitro	Not mutagenic
p-xylene	In vivo	Not mutagenic
ethylbenzene	In vivo	Not mutagenic
ethylbenzene	In Vitro	Some positive data exist, but the data are not

		sufficient for classification
o-xylene	In Vitro	Not mutagenic
o-xylene	In vivo	Not mutagenic
xylene	In Vitro	Not mutagenic
xylene	In vivo	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
methyl methacrylate	In vivo	Not mutagenic
methyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
methacrylic acid	In Vitro	Not mutagenic
methacrylic acid	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
m-xylene	Dermal	Rat	Not carcinogenic
m-xylene	Ingestion	Multiple animal species	Not carcinogenic
m-xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
p-xylene	Dermal	Rat	Not carcinogenic
p-xylene	Ingestion	Multiple animal species	Not carcinogenic
p-xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
o-xylene	Dermal	Rat	Not carcinogenic
o-xylene	Ingestion	Multiple animal species	Not carcinogenic
o-xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
xylene	Dermal	Rat	Not carcinogenic
xylene	Ingestion	Multiple animal species	Not carcinogenic
xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
methyl methacrylate	Ingestion	Rat	Not carcinogenic
methyl methacrylate	Inhalation	Human and animal	Not carcinogenic

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects							
Name	Route	Value	Species	Test result	Exposure		
					Duration		
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL	premating &		
				1,000	during		
				mg/kg/day	gestation		
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL	premating &		
				1,000	during		
				mg/kg/day	gestation		
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for development	Rat	NOAEL	premating &		

				1,000	during
				mg/kg/day	gestation
2-methoxy-1-methylethyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesis
m-xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
m-xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
m-xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
p-xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
p-xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
p-xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
o-xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
o-xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
o-xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
methyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
methyl methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
methacrylic acid	Inhalation	Not classified for development	Rat	NOAEL 1.076 mg/l	during gestation

# Lactation

Name	Route	Species	Value
m-xylene	Ingestion	Mouse	Not classified for effects on or via lactation
p-xylene	Ingestion	Mouse	Not classified for effects on or via lactation
o-xylene	Ingestion	Mouse	Not classified for effects on or via lactation
xylene	Ingestion	Mouse	Not classified for effects on or via lactation

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-methoxy-1-methylethyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-methoxy-1-methylethyl acetate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
m-xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
m-xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
m-xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
m-xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
m-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
m-xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
m-xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
p-xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
p-xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
p-xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
p-xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
p-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
p-xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
p-xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
o-xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
o-xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
o-xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
o-xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
o-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
o-xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
o-xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable

Page: 14 of 26

xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
methyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
methacrylic acid	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-methoxy-1-methylethyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
2-methoxy-1-methylethyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
2-methoxy-1-methylethyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
2-methoxy-1-methylethyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
m-xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
m-xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
m-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
m-xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
m-xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
m-xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
m-xylene	Ingestion	liver	Not classified	Multiple animal	NOAEL Not available	

				species		
m-xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
p-xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
p-xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
p-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
p-xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
p-xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
p-xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
p-xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
p-xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
ethylbenzene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.9 mg/l	13 weeks
ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
o-xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks

o-xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
o-xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
o-xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
o-xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
o-xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
o-xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
o-xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse

toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
methyl methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
methyl methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
methyl methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Ingestion	kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   liver   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
methacrylic acid	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.352 mg/l	90 days
methacrylic acid	Inhalation	blood   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1.232 mg/l	90 days

**Aspiration Hazard** 

Aspiration mazaru						
Name	Value					
m-xylene	Aspiration hazard					
p-xylene	Aspiration hazard					
ethylbenzene	Aspiration hazard					
o-xylene	Aspiration hazard					
xylene	Aspiration hazard					
toluene	Aspiration hazard					

D 10 C 5

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
2-methoxy-1-	108-65-6	Activated sludge	Experimental	30 minutes	EC10	>1,000 mg/l
methylethyl acetate						
2-methoxy-1-	108-65-6	Green algae	Experimental	72 hours	ErC50	>1,000 mg/l
methylethyl acetate						
2-methoxy-1-	108-65-6	Rainbow trout	Experimental	96 hours	LC50	134 mg/l
methylethyl acetate						
2-methoxy-1-	108-65-6	Water flea	Experimental	48 hours	EC50	370 mg/l
methylethyl acetate						
2-methoxy-1- methylethyl acetate		Green algae	Experimental	72 hours	NOEC	1,000 mg/l
2-methoxy-1-	108-65-6	Water flea	Experimental	21 days	NOEC	100 mg/l
methylethyl acetate			1			
Proprietary	Trade Secret	N/A	Data not available	N/A	N/A	N/A
Polymer			or insufficient for			
			classification			
m-xylene	108-38-3	Activated sludge	Experimental	24 hours	EC50	115 mg/l
m-xylene	108-38-3	Rainbow trout	Experimental	96 hours	LC50	8.4 mg/l
m-xylene	108-38-3	Water flea	Experimental	48 hours	EC50	2.4 mg/l
m-xylene	108-38-3	Rainbow trout	Estimated	56 days	NOEC	1.3 mg/l
m-xylene	108-38-3	Green algae	Experimental	72 hours	NOEC	5.3 mg/l
m-xylene	108-38-3	Water flea	Experimental	21 days	NOEC	0.41 mg/l
ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
ethylbenzene	100-41-4	Green algae	Experimental	96 hours	EC50	3.6 mg/l
ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
p-xylene	106-42-3	Activated sludge	Experimental	N/A	EC50	>196 mg/l

Page: 19 of 26

p-xylene	106-42-3	Green algae	Experimental	73 hours	ErC50	4.36 mg/l
p-xylene	106-42-3	Rainbow trout	Experimental	96 hours	LC50	2.6 mg/l
p-xylene	106-42-3	Water flea	Experimental	24 hours	EC50	3.6 mg/l
p-xylene	106-42-3	Green algae	Experimental	73 hours	ErC10	1.9 mg/l
p-xylene	106-42-3	Water flea	Experimental	21 days	EC10	1.91 mg/l
p-xylene	106-42-3	Zebra Fish	Experimental	35 days	NOEC	0.714 mg/l
o-xylene	95-47-6	Activated sludge	Estimated	3 hours	NOEC	157 mg/l
o-xylene	95-47-6	Green algae	Experimental	73 hours	EC50	4.36 mg/l
o-xylene	95-47-6	Rainbow trout	Experimental	96 hours	LC50	2.6 mg/l
o-xylene	95-47-6	Water flea	Experimental	24 hours	IC50	1 mg/l
o-xylene	95-47-6	Green algae	Experimental	73 hours	NOEC	0.44 mg/l
o-xylene	95-47-6	Rainbow trout	Experimental	56 days	NOEC	>1.3 mg/l
o-xylene	95-47-6	Water flea	Experimental	7 days	NOEC	1.17 mg/l
xylene	1330-20-7	Green algae	Analogous Compound	73 hours	ErC50	4.36 mg/l
xylene	1330-20-7	Rainbow trout	Analogous Compound	96 hours	LC50	2.6 mg/l
xylene	1330-20-7	Water flea	Analogous Compound	48 hours	EC50	3.82 mg/l
xylene	1330-20-7	Green algae	Analogous Compound	73 hours	NOEC	0.44 mg/l
xylene	1330-20-7	Water flea	Analogous Compound	7 days	NOEC	0.96 mg/l
xylene	1330-20-7	Rainbow trout	Experimental	56 days	NOEC	1.3 mg/l
xylene	1330-20-7	Activated sludge	Analogous Compound	30 minutes	EC50	>198 mg/l
xylene	1330-20-7	Redworm	Experimental	56 days	NOEC	42.6 mg/kg (Dry Weight)
xylene	1330-20-7	Soil microbes	Experimental	28 days	EC50	>1,000 mg/kg (Dry Weight)
methacrylic acid	79-41-4	Bacteria	Experimental	17 hours	EC50	270 mg/l
methacrylic acid	79-41-4	Green algae	Experimental	72 hours	EC50	45 mg/l
methacrylic acid	79-41-4	Water flea	Experimental	48 hours	EC50	>130 mg/l
methacrylic acid	79-41-4	Green algae	Experimental	72 hours	NOEC	8.2 mg/l
methacrylic acid	79-41-4	Water flea	Experimental	21 days	NOEC	53 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
methyl methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
methyl methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
			1			1

\_\_\_\_\_

methyl methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Biodegradation	28 days	BOD	87.2 %BOD/ThOD	OECD 301C - MITI test (I)
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Aquatic Inherent Biodegrad.		Dissolv. Organic Carbon Deplet	>100 %removal of DOC	similar to OECD 302B
Proprietary Polymer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
m-xylene	108-38-3	Experimental Biodegradation	28 days	BOD	100 %BOD/ThOD	OECD 301C - MITI test (I)
ethylbenzene	100-41-4	Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	
p-xylene	106-42-3	Experimental Biodegradation	28 days	BOD	90 %BOD/ThOD	OECD 301F - Manometric respirometry
o-xylene	95-47-6	Estimated Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301F - Manometric respirometry
xylene	1330-20-7	Analogous Compound Biodegradation	28 days	BOD	94 %BOD/ThOD	OECD 301F - Manometric respirometry
xylene	1330-20-7	Experimental Photolysis		Photolytic half-life (in air)	1.4 days (t 1/2)	
methacrylic acid	79-41-4	Experimental Biodegradation	28 days	BOD	86 %BOD/ThOD	OECD 301D - Closed bottle test
methyl methacrylate	80-62-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThOD	OECD 301C - MITI test (I)
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Bioconcentration		Log Kow	0.36	OECD 107 log Kow shke flsk mtd
Proprietary Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
m-xylene	108-38-3	Estimated BCF - Fish	56 days	Bioaccumulation factor	14	
ethylbenzene	100-41-4	Experimental BCF - Fish	42 days	Bioaccumulation factor	1	
p-xylene	106-42-3	Analogous Compound BCF - Fish	56 days	Bioaccumulation factor	25.9	
p-xylene	106-42-3	Experimental Bioconcentration		Log Kow	3.15	
o-xylene	95-47-6	Experimental Bioconcentration		Log Kow	3.12	
xylene	1330-20-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	<=25.9	
xylene	1330-20-7	Analogous Compound Bioconcentration		Log Kow	3.2	
methacrylic acid	79-41-4	Experimental Bioconcentration		Log Kow	0.93	
methyl methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flsk mtd
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Mobility in Soil	Koc	4 l/kg	Episuite <sup>TM</sup>
p-xylene	106-42-3	Experimental Mobility in Soil	Koc	246 l/kg	
xylene	1330-20-7	Analogous Compound Mobility in Soil	Koc	537 l/kg	
methyl methacrylate	80-62-6	Experimental Mobility in Soil	Koc	8.7-72 l/kg	
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal

facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

# EU waste code (product as sold)

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN1866	UN1866	UN1866
14.2 UN proper shipping name	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Page: 23 of 26

	•		•	• .
( '01	cinc	MAN	11	•1 <b>1</b> **/
Cai	CHIL	ノとし	ш	JILY

•	Ingredient	CAS Nbr	Classification	Regulation
	ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
	methyl methacrylate	80-62-6	Gr. 3: Not classifiable	International Agency for Research on Cancer
	m-xylene	108-38-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
	o-xylene	95-47-6	Gr. 3: Not classifiable	International Agency for Research on Cancer
	Proprietary Polymer	Trade Secret	Gr. 3: Not classifiable	International Agency for Research on Cancer
	p-xylene	106-42-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
	toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
	xylene	1330-20-7	Gr. 3: Not classifiable	International Agency for Research on Cancer

### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr
toluene	108-88-3
xylene	1330-20-7

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

<sup>\*</sup>If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply Seveso named dangerous substances, Annex 1, Part 2

None

### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

#### List of relevant H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   sensory
	organs.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

GB Section 02: CLP Ingredient table information was modified.

GB Section 15: Carcinogenicity information information was modified.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was added.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 03: SCL table information was added.

Section 6: Accidental release clean-up information information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Occupational exposure limit table information was modified.

\_\_\_\_\_

#### 3M<sup>TM</sup> EDGE SEALER 4150S

- Section 08: Personal Protection Apron Statement information was deleted.
- Section 8: Personal Protection Respiratory Information information was modified.
- Section 8: Respiratory protection recommended respirators information information was modified.
- Section 09: Kinematic Viscosity information information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Aspiration Hazard Table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Skin information information was modified.
- Lactation Table information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.