Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	45-1119-2	**Version Number:**	1.08
Issue Date:	11/02/26	**Supersedes Date:**	06/16/25

SECTION 1: Identification

1.1. Product identifier
3M™ Scotch-Weld™ One-Part Epoxy Adhesive 6105 Black

Product Identification Numbers
LA-D100-3672-9, UU-0132-9409-3, UU-0132-9410-1
7100350802, 7100350853

1.2. Recommended use and restrictions on use

Recommended use
Adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Acute Toxicity (oral): Category 4.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2A.
Skin Sensitizer: Category 1.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms



Hazard Statements

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Precautionary statements

Prevention:
Avoid breathing vapors.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves and eye protection.

Response:
IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Rinse mouth.
If eye irritation persists or if skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

69% of the mixture consists of ingredients of unknown acute oral toxicity.
100% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
epoxy resin 1	25068-38-6	6 - 54
Epoxy resin 3	9003-36-5	<= 32
PETMP	7575-23-7	8 - 32
Silica filler #2	Trade Secret*	<= 32
TMPMP	33007-83-9	<= 25
Acrylic copolymer	Trade Secret*	1 - 20
Modified aliphatic curative #1	None	1 - 16
MBS polymer	Trade Secret*	<= 12
Modified aliphatic curative #2	None	<= 10
Epoxy resin 2	36484-54-5	<= 10
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	7539-04-0	0.7 - 6.3
Catalyst	Trade Secret*	<= 5

	3M Unique ID: 394748	
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	<= 5
Amorphous Silica	67762-90-7	<= 5
copolymer	Trade Secret*	< 4
Other esters	Trade Secret*	< 3
TRIMETHYLOLPROPANE DI(3-MPA)	None	<= 3
acid polyester	Trade Secret*	< 2
Carbon black	1333-86-4	<= 1

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Silica: Amorphous, including natural diatomaceous earth	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Silica filler #2	Trade Secret	ACGIH	TWA(inhalable particulates):10 mg/m3	
Silica filler #2	Trade Secret	ACGIH	TWA(respirable particles):3 mg/m3	

Silica filler #2	Trade Secret	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	Black
Odor	Epoxy

Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	*Not Applicable*
Flash Point	> 250 ºF [*Test Method:*Closed Cup]
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	*No Data Available*
Relative Vapor Density	*Not Applicable*
Density	1.07 g/ml
Relative Density	1.07 [*Ref Std:*WATER=1]
Solubility in Water	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	24,390 mm2/sec
Molecular weight	*Not Applicable*
Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

To prevent accelerated curing, avoid mixing cleaning solvents (such as MEK, IPA, etc.) with more than 50 grams of uncured material

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:
Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
epoxy resin 1	Dermal	Rat	LD50 > 1,600 mg/kg
epoxy resin 1	Ingestion	Rat	LD50 > 1,000 mg/kg
Epoxy resin 3	Dermal	Rat	LD50 > 2,000 mg/kg
Epoxy resin 3	Ingestion	Rat	LD50 > 5,000 mg/kg
Silica filler #2	Dermal	Rat	LD50 > 2,000 mg/kg
Silica filler #2	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Silica filler #2	Ingestion	Rat	LD50 6,450 mg/kg
PETMP	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.363 mg/l
PETMP	Ingestion	Rat	LD50 >300, <2000 mg/kg
TMPMP	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 3.363 mg/l

TMPMP	Ingestion	similar compounds	LD50 >300, <2000 mg/kg
Epoxy resin 2	Ingestion	Rat	LD50 > 2,000 mg/kg
Epoxy resin 2	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Dermal	Rat	LD50 > 2,000 mg/kg
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	Rat	LD50 908 mg/kg
3-(Trimethoxysilyl)propyl Glycidyl Ether	Dermal	Rabbit	LD50 4,000 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
3-(Trimethoxysilyl)propyl Glycidyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Rat	LD50 7,010 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Catalyst	Ingestion	Rat	LD50 >300, <2000 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
epoxy resin 1	Rabbit	Mild irritant
Epoxy resin 3	Rabbit	Irritant
Silica filler #2	Rabbit	No significant irritation
PETMP	Rabbit	No significant irritation
TMPMP	similar compounds	No significant irritation
Epoxy resin 2	In vitro data	No significant irritation
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Rabbit	No significant irritation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Rabbit	Mild irritant
Amorphous Silica	Rabbit	No significant irritation
Catalyst	In vitro data	No significant irritation
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
epoxy resin 1	Rabbit	Moderate irritant
Epoxy resin 3	Rabbit	No significant irritation
Silica filler #2	Rabbit	No significant irritation
PETMP	Rabbit	No significant irritation
TMPMP	similar compounds	No significant irritation
Epoxy resin 2	In vitro data	No significant irritation
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Rabbit	No significant irritation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
Catalyst	In vitro data	Severe irritant

Carbon black	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
epoxy resin 1	Human and animal	Sensitizing
Epoxy resin 3	Multiple animal species	Sensitizing
PETMP	Guinea pig	Sensitizing
TMPMP	similar compounds	Sensitizing
Epoxy resin 2	Mouse	Sensitizing
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Guinea pig	Sensitizing
3-(Trimethoxysilyl)propyl Glycidyl Ether	Guinea pig	Not classified
Amorphous Silica	Human and animal	Not classified
Catalyst	Guinea pig	Not classified

Respiratory Sensitization

Name	Species	Value
epoxy resin 1	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
epoxy resin 1	In vivo	Not mutagenic
epoxy resin 1	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epoxy resin 3	In vivo	Not mutagenic
Epoxy resin 3	In Vitro	Some positive data exist, but the data are not sufficient for classification
PETMP	In Vitro	Not mutagenic
TMPMP	In Vitro	Not mutagenic
Epoxy resin 2	In Vitro	Some positive data exist, but the data are not sufficient for classification
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	In Vitro	Not mutagenic
3-(Trimethoxysilyl)propyl Glycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(Trimethoxysilyl)propyl Glycidyl Ether	In vivo	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	In Vitro	Not mutagenic
Catalyst	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
epoxy resin 1	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
3-(Trimethoxysilyl)propyl Glycidyl Ether	Dermal	Mouse	Not carcinogenic
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic

Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
epoxy resin 1	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
epoxy resin 1	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
epoxy resin 1	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
epoxy resin 1	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Silica filler #2	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
PETMP	Ingestion	Not classified for development	Rat	NOAEL 120 mg/kg/day	during gestation
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	29 days
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating into lactation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
epoxy resin 1	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Epoxy resin 3	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Silica filler #2	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Catalyst	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure

						Duration
epoxy resin 1	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
epoxy resin 1	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
epoxy resin 1	Ingestion	auditory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
epoxy resin 1	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy resin 3	Ingestion	heart	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	endocrine system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	liver	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	immune system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	nervous system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	respiratory system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Epoxy resin 3	Ingestion	vascular system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Silica filler #2	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
PETMP	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
PETMP	Ingestion	immune system	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
PETMP	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
PETMP	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
PETMP	Ingestion	nervous system	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
PETMP	Ingestion	eyes	Not classified	Rat	NOAEL 200 mg/kg/day	90 days
Propanoic acid, 3-	Ingestion	endocrine system	Not classified	Rat	NOAEL 500	29 days

mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester					mg/kg/day	
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	29 days
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	29 days
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	immune system	Not classified	Rat	NOAEL 500 mg/kg/day	29 days
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	29 days
Propanoic acid, 3-mercapto-, 1,1'-[2-(hydroxymethyl)-2-[(3-mercapto-1-oxopropoxy)methyl]-1,3-propanediyl] ester	Ingestion	nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	29 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Amorphous Silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous Silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not Applicable.

Health Hazards
Acute toxicity
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	45-1119-2	**Version Number:**	1.08
Issue Date:	11/02/26	**Supersedes Date:**	06/16/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com