

Safety Data Sheet

© 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4142-7	Version number:	5.00
Issue Date:	09/04/2025	Supersedes date:	16/03/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

Scotchgard[™] Stone Floor Protector

Product Identification Numbers

7100135693 (SAP ID) 70-0716-8335-6 (Legacy ID)

1.2. Recommended use and restrictions on use

Recommended use Hard floor maintenance.

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin sensitisation: Category 1 Specific target organ toxicity – repeated exposure: Category 2

2.2. Label elements SIGNAL WORD Warning

Symbols:

Exclamation mark |Health Hazard |

Pictograms



HAZARD STATEMENTS: H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.

PRECAUTIONARY STATEMENTS

Prevention P260 P272	Do not breathe dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace.
Response	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P314	Get medical advice/attention if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal	
P501	Dispose of contents/container via an approved hazardous waste disposal contractor.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material has been tested for eye damage/irritation and the test results do not meet the criteria for classification. This material has been tested for skin corrosion/irritation and the test results do not meet the criteria for classification.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	60 - 90
Lithium Polysilicate	12627-14-4	15 - 25
Acrylic Polymer	Trade Secret	4 - 5
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	1 - 5
Potassium Methylsilanetriolate	31795-24-1	<= 3

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralise spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralising agent until reaction stops. Let cool before collecting. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No protective gloves required. Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.		
Colour	White		
Odour	Slight Ammoniacal		
Odour threshold	No data available.		
рН	11 - 12		
Melting point/Freezing point	Not applicable.		
Boiling point/Initial boiling point/Boiling range	± 100 °C		
Flash point	No flash point		
Evaporation rate	No data available.		
Flammability	Not applicable.		
Flammable Limits(LEL)	Not applicable.		
Flammable Limits(UEL)	Not applicable.		
Vapour pressure	2,333.1 Pa [@ 20 °C]		
Relative Vapour Density	No data available.		
Density	$\pm 1 \text{ g/ml}$		
Relative density	± 1 [<i>Ref Std</i> :WATER=1]		
Water solubility	Complete		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Autoignition temperature	Not applicable.		
Decomposition temperature	No data available.		
Kinematic Viscosity	No data available.		
Volatile organic compounds (VOC)	<1 % weight		
Percent volatile	No data available.		
VOC less H2O & exempt solvents	± 10 g/l [Test Method: calculated per CARB title 2]		
Molecular weight	No data available.		
L			

Particle Characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u> Carbon monoxide. Carbon dioxide. Condition Not specified. Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

ScotchgardTM Stone Floor Protector

Lithium Polysilicate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Lithium Polysilicate	Ingestion	Rat	LD50 > 2,000 mg/kg
Potassium Methylsilanetriolate	Ingestion	Rat	LD50 > 2,000 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation-	Rat	LC50 >1.49, <2.44 mg/l
	Dust/Mist		
	(4 hours)		
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Rat	LD50 1,897 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro	No significant irritation
	data	
Lithium Polysilicate	Rabbit	Minimal irritation
Potassium Methylsilanetriolate	Professio	Corrosive
	nal	
	judgemen	
	t	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro	No significant irritation
	data	-
Lithium Polysilicate	Rabbit	Corrosive
Potassium Methylsilanetriolate	similar	Corrosive
	health	
	hazards	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Corrosive

Sensitisation:

Skin Sensitisation

Name	Species	Value
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Multiple animal species	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	In Vitro	Not mutagenic
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	In vivo	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
N-(3-	Ingestion	Not classified for female reproduction	Rat	NOAEL 500	premating

(Trimethoxysilyl)propyl)ethylenediamine				mg/kg/day	into lactation
N-(3-	Ingestion	Not classified for male reproduction	Rat	NOAEL 500	28 days
(Trimethoxysilyl)propyl)ethylenediamine				mg/kg/day	
N-(3-	Ingestion	Not classified for development	Rat	NOAEL 750	during
(Trimethoxysilyl)propyl)ethylenediamine	-	*		mg/kg/day	gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
Lithium Polysilicate	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
-			data are not sufficient for	compoun	available	
			classification	ds		
N-(3-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
(Trimethoxysilyl)propyl)et			data are not sufficient for	health	available	
hylenediamine			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Lithium Polysilicate	Ingestion	nervous system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	similar compoun ds	NOAEL Not available	
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Dermal	skin endocrine system hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,545 mg/kg/day	11 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.015 mg/l	90 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 0.044 mg/l	90 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Lithium	12627-14-4	Green algae	Estimated	72 hours	EC50	>345.4 mg/l
Polysilicate						

Lithium	12627-14-4	Water flea	Experimental	48 hours	EC50	>220 mg/l
Polysilicate	12027 11 1	Water fied	Experimental	10 nouis	Less	220 mg/1
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Bacteria	Experimental	16 hours	EC50	67 mg/l
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Fathead minnow	Experimental	96 hours	LC50	168 mg/l
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Green algae	Experimental	72 hours	ErC50	8.8 mg/l
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Water flea	Experimental	48 hours	EC50	81 mg/l
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Green algae	Experimental	72 hours	NOEC	3.1 mg/l
Acrylic Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Potassium Methylsilanetri olate	31795-24-1	Green algae	Estimated	72 hours	EC50	>120 mg/l
Potassium Methylsilanetri olate	31795-24-1	Water flea	Estimated	48 hours	EC50	>500 mg/l
Potassium Methylsilanetri olate	31795-24-1	Zebra Fish	Estimated	96 hours	LC50	>500 mg/l
Potassium Methylsilanetri olate	31795-24-1	Activated sludge	Experimental	3 hours	EC10	>100 mg/l
Potassium Methylsilanetri olate	31795-24-1	Green algae	Estimated	72 hours	NOEC	>=120 mg/l
Potassium Methylsilanetri olate	31795-24-1	Water flea	Estimated	21 days	NOEC	>=100 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Lithium Polysilicate	12627-14-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	39 % removal of DOC	EC C.4.A. DOC Die- Away Test

N-(3- (Trimethoxysil yl)propyl)ethyl enediamine	1760-24-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	1.5 minutes (t 1/2)	
Acrylic Polymer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Potassium Methylsilanetri olate	31795-24-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Lithium	12627-14-4	Data not	N/A	N/A	N/A	N/A
Polysilicate		available or				
		insufficient for				
		classification				
N-(3-	1760-24-3	Data not	N/A	N/A	N/A	N/A
(Trimethoxysil		available or				
yl)propyl)ethyl		insufficient for				
enediamine		classification				
Acrylic	Trade Secret	Data not	N/A	N/A	N/A	N/A
Polymer		available or				
		insufficient for				
		classification				
Potassium	31795-24-1	Data not	N/A	N/A	N/A	N/A
Methylsilanetri		available or				
olate		insufficient for				
		classification				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable. IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval numberHSR002670Group standard nameSurface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020HSNO Hazard classificationRefer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
1	1
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1
	substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin
	sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to
	the aquatic environment Category 2 or Hazardous to the aquatic environment
	Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity
	Category 1, Reproductive toxicity Category 1, Specific target organ toxicity
	Category 1, Serious eye damage Category 1, Hazardous to the aquatic
	environment Category 4 substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1
	substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin
	sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to
	the aquatic environment Category 2 or Hazardous to the aquatic environment

Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Not required
100 L or 100 kg (for Hazardous to the aquatic environment Category 1
substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1,
Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	28-4142-7	Version number:	5.00
Issue Date:	09/04/2025	Supersedes date:	16/03/2021

Key to abbreviations and acronyms

GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017 **HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz