

Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 22-2293-3
 Version number:
 16.00

 Revision date:
 24/05/2024
 Supersedes date:
 16/06/2023

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M[™] 55045 Superfast Plastic Adhesive

Product Identification Numbers

FS-9100-4549-1 UU-0108-5079-8 UU-0108-8615-6

7000080185 7100222866 7100224759

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

22-1822-0, 22-1877-4

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Acute Toxicity, Category 3 - Acute Tox. 3; H331

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Carcinogenicity, Category 2 - Carc. 2; H351

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS06 (Skull and crossbones) |GHS08 (Health Hazard) |

Pictograms





Contains:

Triethoxy(3-isocyanatopropyl)silane; m-Xylene-.alpha.alpha'.-diamine; 4,4'-Methylenediphenyl diisocyanate, oligomers

HAZARD STATEMENTS:

H331	Toxic if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H335 May cause respiratory irritation.

777	
373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
,,,	inay taust admings to organis through protonged or repeated emposare, respiratory system.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

ERROR: Dataview MMM KIT GB SENSITIZER DV not found.ERROR: Dataview

MMM KIT GB SENSITIZER DV not found.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

Revision information:

GB Label: CLP Ingredients - kit components information was modified.

Kit Information: CLP Target Organ Hazard Statement information was deleted.

Kit: Component document group number(s) information was modified.

Kit Information: Contains statement for sensitisers information was added.

Section 2: <125ml Hazard - Environmental information was added.

Section 2: <125ml Hazard - Health information was modified.

Section 2: <125ml Precautionary - Prevention information was modified.

Section 2: <125ml Precautionary - Storage information was added.

Section 02: CLP Physical and Health Hazard Statements information was modified.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was added.

Label: CLP Precautionary - Prevention information was modified.
Label: CLP Precautionary - Response information was modified.
Label: CLP Precautionary - Storage information was added.
Label: CLP Target Organ Hazard Statement information was added.
Label: Graphic information was modified.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 22-1822-0
 Version number:
 21.01

 Revision date:
 14/11/2025
 Supersedes date:
 29/10/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3MTM 55045 Superfast Plastic Adhesive (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Acute Toxicity, Category 3 - Acute Tox. 3; H331 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Carcinogenicity, Category 2 - Carc. 2; H351

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS06 (Skull and crossbones) |GHS08 (Health Hazard) |

Pictograms





Ingredient	CAS Nbr	EC No.	% by Wt
4,4'-Methylenediphenyl diisocyanate, oligomers		500-040-3	45 - 85
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	24801-88-5	246-467-6	0.1 - 1

HAZARD STATEMENTS:

III E STATEMENTS.	
H331	Toxic if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure: respiratory system.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H331 Toxic if inhaled.

3MTM 55045 Superfast Plastic Adhesive (Part A)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

<=125 ml Precautionary statements

Prevention:

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

39% of the mixture consists of components of unknown acute oral toxicity.

Contains 39% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) 2020/1149, amendment to REACH Regualtion (1907/2006) as amended for Great Britain, as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
4,4'-Methylenediphenyl diisocyanate, oligomers	(EC-No.) 500-040-3	45 - 85	Carc. 2, H351 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 2, H373
Castor Oil, Polymer With 1,1'- Methylenebis[4-Isocyanatobenzene]	(CAS-No.) 68424-09-9	15 - 40	Substance with a national occupational exposure limit
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2	1 - 5	Eye Dam. 1, H318 Aquatic Chronic 3, H412

Isocyanic Acid, 3-(Triethoxysilyl)Propyl	(CAS-No.) 24801-88-5	0.1 -	1	Acute Tox. 1, H330
Ester	(EC-No.) 246-467-6			Acute Tox. 4, H312
				Acute Tox. 4, H302
				Skin Corr. 1B, H314
				Resp. Sens. 1, H334
				Skin Sens. 1, H317

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
4,4'-Methylenediphenyl diisocyanate, oligomers		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Toxic if inhaled. Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Isocyanates, all (as -NCO)	24801-88-5	UK HSE	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07	Respiratory Sensitizer
			mg/m3	
Isocyanates, all (as -NCO)	68424-09-9	UK HSE	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)	24801- 88-5	UK EH40 BMGVs	Isocyanate- derived diamine	Creatinine in urine	EPE	1 umol/mol	
ISOCYANATES (APPLIES TO HDI, IPDI, TDI AND MDI)	68424- 09-9	UK EH40 BMGVs	Isocyanate- derived diamine	Creatinine in urine	EPE	1 umol/mol	

UK EH40 BMGVs: UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EPE: At the end of the period of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Colour	Colourless
Odor	Mild Urethane , Odourless
Odour threshold	No data available.
Melting point/freezing point	No data available.
Boiling point/boiling range	>=204.4 °C
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	>=143.3 °C [Test Method: Tagliabue closed cup]
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	1,364 mm ² /sec
Water solubility	Negligible
Solubility- non-water	No data available.

Partition coefficient: n-octanol/water	No data available.
Vapour pressure	<=0 Pa [@ 20 °C]
Density	1.1 g/ml
Relative density	1.1 [Ref Std:WATER=1]
Relative Vapour Density	>=1 [<i>Ref Std</i> :AIR=1]
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate <=1 [Details: Gels with exposure to humidity.]

Molecular weight No data available.

Percent volatile 2 % weight [Test Method: Estimated]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Water

Strong acids.

Strong bases.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomers	Ingestion	Rat	LD50 31,600 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	Dermal	Rabbit	LD50 1,259 mg/kg
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	Inhalation- Vapour (4 hours)	Rat	LC50 0.36 mg/l
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	Ingestion	Rat	LD50 706 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Skiii Corrosion/irritation		
Name	Species	Value
4.4'-Methylenediphenyl diisocyanate, oligomers	official	Irritant

	classificat ion	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-Methylenediphenyl diisocyanate, oligomers	official classificat ion	Severe irritant
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
4,4'-Methylenediphenyl diisocyanate, oligomers	Mouse	Sensitising
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	similar compoun ds	Sensitising

Respiratory Sensitisation

Name	Species	Value
4,4'-Methylenediphenyl diisocyanate, oligomers	Human	Sensitising
Isocyanic Acid, 3-(Triethoxysilyl)Propyl Ester	similar	Sensitising
	compoun	
	ds	

Germ Cell Mutagenicity

Name	Route	Value
4,4'-Methylenediphenyl diisocyanate, oligomers	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation

[3-(2,3-	Ingestion	Not classified for development	Rat	NOAEL	during
epoxypropoxy)propyl]trimethoxysilane				3,000	organogenesis
				mg/kg/day	

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
[3-(2,3-epoxypropoxy)propyl]trim ethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
4,4'-	500-040-3	Water flea	Analogous	24 hours	EC50	>100 mg/l
Methylenediphenyl			Compound			
diisocyanate,						
oligomers						
Castor Oil,	68424-09-9	N/A	Data not available	N/A	N/A	NA
Polymer With 1,1'-			or insufficient for			
Methylenebis[4-			classification			
Isocyanatobenzene]						
[3-(2,3-	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
epoxypropoxy)prop						
yl]trimethoxysilane						

[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Green algae	Estimated	72 hours	EC50	>1,000 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Water flea	Estimated	48 hours	EC50	331 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Zebra Fish	Estimated	96 hours	LC50	>934 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Activated sludge	Experimental	3 hours	NOEC	10 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Green algae	Estimated	72 hours	NOEC	1.3 mg/l
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Water flea	Estimated	21 days	NOEC	>=100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
4,4'- Methylenediphenyl diisocyanate, oligomers	500-040-3	Analogous Compound Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
4,4'- Methylenediphenyl diisocyanate, oligomers	500-040-3	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	<2 hours (t 1/2)	
Castor Oil, Polymer With 1,1'- Methylenebis[4- Isocyanatobenzene]	68424-09-9	Data not availblinsufficient	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Estimated Hydrolysis		Hydrolytic half-life	8.5 hours (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
4,4'-	500-040-3	Analogous	28 days	Bioaccumulation	200	
Methylenediphenyl		Compound BCF -	-	factor		
diisocyanate,		Fish				
oligomers						

	68424-09-9	Data not available	N/A	N/A	N/A	N/A
Polymer With 1,1'-		or insufficient for				
Methylenebis[4-		classification				
Isocyanatobenzene]						
[3-(2,3-	2530-83-8	Experimental		Log Kow	0.5	Episuite TM
epoxypropoxy)prop		Bioconcentration				
yl]trimethoxysilane						
Isocyanic Acid, 3-	24801-88-5	Estimated BCF -	56 days	Bioaccumulation	<3.4	OECD305-Bioconcentration
(Triethoxysilyl)Pro		Fish	-	factor		
pyl Ester						

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite TM
Isocyanic Acid, 3- (Triethoxysilyl)Pro pyl Ester	24801-88-5	Estimated Mobility in Soil	Koc	0.2 l/kg	Episuite TM

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.

14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	CAS Nbr	Classification	Regulation
4,4'-Methylenediphenyl diisocyanate, oligomers	500-040-3	Carc. 2	Vendor classified according to the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingi	edient	CAS Nbr

4,4'-Methylenediphenyl diisocyanate, oligomers 500-040-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application	cation of
	Lower-tier requirements	Upper-tier requirements
H2 ACUTE TOXICITY	50	200

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

3MTM 55045 Superfast Plastic Adhesive (Part A)

H351	Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure: respiratory system.

H412 Harmful to aquatic life with long lasting effects.

Revision information:

Section 2: <125ml Precautionary - Prevention information was modified.

Label: CLP Precautionary - Prevention information was modified.

Section 02: Label Elements: GB Percent Unknown information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 22-1877-4 Version number: 16 00 **Revision date:** 14/12/2023 Supersedes date: 10/10/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M[™] Superfast Plastic Adhesive PN 55045 (Part B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 E Mail: tox.uk@mmm.com Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark)

Pictograms



Ingredient CAS Nbr EC No. % by Wt

m-Xylene-.alpha.alpha'.-diamine 1477-55-0 216-032-5 < 3

HAZARD STATEMENTS:

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

18% of the mixture consists of components of unknown acute inhalation toxicity. Contains 53% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%		Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Glycerol poly(oxyethylene, oxypropylene) ether	(CAS-No.) 9082-00-2	40 -	60	Substance not classified as hazardous
Glycerol, propoxylated	(CAS-No.) 25791-96-2 (EC-No.) 500-044-5	10 -	30	Substance not classified as hazardous
1,1',1"'-Ethylenedinitrilotetrapropan-2-ol	(CAS-No.) 102-60-3 (EC-No.) 203-041-4	10 -	30	Eye Irrit. 2, H319
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4	< 0.5		Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1
m-Xylenealpha.alpha'diamine	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5	< 3		Acute Tox. 4, H332 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide.

Oxides of nitrogen.

Condition

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising

3M[™] Superfast Plastic Adhesive PN 55045 (Part B)

agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Limit type **Additional comments** Agency

2,6-Di-tert-butyl-p-cresol 128-37-0 **UK HSC** TWA:10 mg/m³

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Natural rubber.	0.5	< 1 hour
Butyl rubber.	0.5	=>8 hours
Neoprene.	0.5	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Specific Physical Form:

Gel

Colour G

ColourColourlessOdorSlight Ammoniacal

Odour threshold

No data available.

Melting point/freezing point

Boiling point/boiling range

Flammability (solid gas)

Not applicable

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Not applicable.

Not applicable.

Not applicable.

Flash point >=143.3 °C [Test Method: Tagliabue closed cup]

Autoignition temperatureNot applicable.Decomposition temperatureNo data available.

pH substance/mixture is non-soluble (in water)

Kinematic Viscosity

1,569 mm²/sec
Water solubility
Negligible
Solubility- non-water
No data available.
Partition coefficient: n-octanol/water
No data available

Partition coefficient: n-octanol/waterNo data available.Vapour pressureNot applicable.Density1.02 g/ml

Relative density1.02 [Ref Std: WATER=1] **Relative Vapour Density**>=1 [Ref Std: AIR=1]

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

3MTM Superfast Plastic Adhesive PN 55045 (Part B)

Evaporation rate Molecular weight Percent volatile <=1 [*Ref Std*:WATER=1] *No data available.*

<=1 % weight [*Test Method*:Estimated]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Inhalation- Dust/Mist (4 hours)	similar compoun ds	LC50 > 3.2 mg/l
Glycerol poly(oxyethylene, oxypropylene) ether	Ingestion	similar compoun ds	LD50 > 5,000 mg/kg
Glycerol, propoxylated	Dermal	Rat	LD50 > 2,000 mg/kg
Glycerol, propoxylated	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Glycerol, propoxylated	Ingestion	Rat	LD50 4,600 mg/kg
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	Dermal	Rat	LD50 > 2,000 mg/kg
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	Ingestion	Rat	LD50 2,890 mg/kg
m-Xylenealpha.alpha'diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
m-Xylenealpha.alpha'diamine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
m-Xylenealpha.alpha'diamine	Ingestion	Rat	LD50 980 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Glycerol poly(oxyethylene, oxypropylene) ether	similar	Minimal irritation
	compoun	
	ds	
Glycerol, propoxylated	Rabbit	No significant irritation
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	Rabbit	No significant irritation
m-Xylenealpha.alpha'diamine	Rat	Corrosive
2,6-Di-tert-butyl-p-cresol	Human	Minimal irritation
	and	
	animal	

Serious Eve Damage/Irritation

Serious Lye Damage/II Itation		
Name	Species	Value
	1	
Glycerol poly(oxyethylene, oxypropylene) ether	similar compoun ds	Mild irritant
Glycerol, propoxylated	Rabbit	Mild irritant
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	Rabbit	Severe irritant

3MTM Superfast Plastic Adhesive PN 55045 (Part B)

m-Xylenealpha.alpha'diamine	Rabbit	Corrosive
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Glycerol poly(oxyethylene, oxypropylene) ether	similar	Not classified
	compoun	
	ds	
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	Guinea	Not classified
	pig	
m-Xylenealpha.alpha'diamine	Guinea	Sensitising
	pig	
2,6-Di-tert-butyl-p-cresol	Human	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Glycerol poly(oxyethylene, oxypropylene) ether	In Vitro	Not mutagenic
1,1',1",1"'-Ethylenedinitrilotetrapropan-2-ol	In Vitro	Not mutagenic
m-Xylenealpha.alpha'diamine	In Vitro	Not mutagenic
m-Xylenealpha.alpha'diamine	In vivo	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
1,1',1"',1"''-Ethylenedinitrilotetrapropan-2-ol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
1,1',1"',1"'-Ethylenedinitrilotetrapropan-2-ol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	30 days
1,1',1"',1"'-Ethylenedinitrilotetrapropan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg	1 generation
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	1 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,1',1",1"'- Ethylenedinitrilotetrapropa n-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Positive	
m-Xylenealpha.alpha' diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not avaliable	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,1',1",1"'- Ethylenedinitrilotetrapropa n-2-ol	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	30 days
1,1',1",1"'- Ethylenedinitrilotetrapropa n-2-ol	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	30 days
m-Xylenealpha.alpha' diamine	Ingestion	endocrine system blood bone marrow	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
1,1',1",1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Green algae	Analogous Compound	72 hours	ErC50	>100 mg/l
1,1',1",1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Water flea	Analogous Compound	48 hours	EC50	>500 mg/l
1,1',1",1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
1,1',1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Fathead minnow	Experimental	96 hours	LC50	>1,000 mg/l
1,1',1",1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Green algae	Analogous Compound	72 hours	ErC10	16.1 mg/l
Glycerol, propoxylated	25791-96-2	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Glycerol, propoxylated	25791-96-2	Green algae	Experimental	72 hours	ErC50	>100 mg/l
Glycerol, propoxylated	25791-96-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Glycerol, propoxylated	25791-96-2	Green algae	Experimental	72 hours	NOEC	>100 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Bacteria	Experimental	16 hours	EC10	24 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Green algae	Experimental	72 hours	ErC50	28 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Medaka	Experimental	96 hours	LC50	87.6 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Water flea	Experimental	48 hours	EC50	15.2 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Green algae	Experimental	72 hours	NOEC	9.8 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Water flea	Experimental	21 days	NOEC	4.7 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Modeled Biodegradation	28 days	BOD	20 %BOD/ThOD	Catalogic™
1,1',1",1"- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Experimental Biodegradation	28 days	BOD	1 %BOD/ThOD	OECD 301C - MITI test (I)
Glycerol, propoxylated	25791-96-2	Experimental Biodegradation	28 days	CO2 evolution	38 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental Biodegradation	28 days	CO2 evolution	49 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental Aquatic Inherent Biodegrad.	28 days	BOD	22 %BOD/ThOD	OECD 302C - Modified MITI (II)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Modeled Bioconcentration		Bioaccumulation factor	2	Catalogic™
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Modeled Bioconcentration		Log Kow	-2.6	Episuite TM
1,1',1",1"'- Ethylenedinitrilotet rapropan-2-ol	102-60-3	Experimental Bioconcentration		Log Kow	0.27	OECD 107 log Kow shke flsk mtd
Glycerol, propoxylated	25791-96-2	Experimental BCF - Fish	42 days	Bioaccumulation factor	≤7	
2,6-Di-tert-butyl-p- cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental BCF - Fish	42 days	Bioaccumulation factor	<2.7	OECD305-Bioconcentration
m- Xylenealpha.alph a'diamine	1477-55-0	Extrapolated Bioconcentration		Log Kow	0.18	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Glycerol	9082-00-2	Modeled Mobility	Koc	13 l/kg	Episuite TM
poly(oxyethylene,		in Soil			
oxypropylene) ether					
m-	1477-55-0	Modeled Mobility	Koc	<1 l/kg	ACD/Labs ChemSketch TM
Xylenealpha.alpha		in Soil		_	
'diamine					

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.

Page: 13 of 16

3M[™] Superfast Plastic Adhesive PN 55045 (Part B)

ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	CAS Nbr	<u>Classification</u>	Regulation
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

3M™ Superfast Plastic Adhesive PN 55045 (Part B)

Causes serious eye irritation.
Harmful if inhaled.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.
Harmful to aquatic life with long lasting effects.

Revision information:

- GB Section 02: CLP Ingredient table information was added.
- GB Section 02: Other hazards phrase information was added.
- GB Section 04: First Aid Symptoms and Effects (GB CLP) information was added.
- GB Section 04: Information on toxicological effects information was added.
- GB Section 12: Classification Warning information was added.
- GB Section 15: Carcinogenicity information information was added.
- GB Section 15: Chemical Safety Assessment information was added.
- GBSDS Section 14 Transport in bulk Main Heading information was added.
- GBSDS Section 14 UN Number information was added.
- Section 2: <125ml Hazard Environmental information was added.
- Section 2: <125ml Precautionary Response information was added.
- CLP: Ingredient table information was deleted.
- Label: CLP Classification information was modified.
- Label: CLP Environmental Hazard Statements information was added.
- Label: CLP Percent Unknown information was deleted.
- Label: CLP Precautionary Response information was added.
- Section 02: Label Elements: GB Percent Unknown information was added.
- Section 2: Other hazards phrase information was deleted.
- Section 3: Composition/Information of ingredients table information was added.
- Section 3: Composition/Information of ingredients table information was deleted.
- Section 04: Information on toxicological effects information was deleted.
- Section 6: Accidental release environmental information information was modified.
- Section 8: Eye/face protection information information was modified.
- Section 8: glove data value information was modified.
- Section 8: Occupational exposure limit table information was added.
- Section 8: Occupational exposure limit table information was modified.
- OEL Reg Agency Desc information was added.
- Section 8: Skin protection protective clothing information information was modified.
- Section 8: STEL key information was added.
- Section 8: TWA key information was added.
- Section 9: Vapour density value information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was added.
- Section 11: Carcinogenicity text information was deleted.
- Section 11: Classification disclaimer information was deleted.
- Section 11: GB Classification disclaimer information was added.
- Section 11: GB No endocrine disruptor information available warning information was added.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: No endocrine disruptor information available warning information was deleted.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 12: 12.6. Endocrine Disrupting Properties information was deleted.
- Section 12: 12.6. Other adverse effects information was added.
- Section 12: 12.7. Other adverse effects information was deleted.
- Section 12: Classification Warning information was deleted.
- Section 12: Component ecotoxicity information information was modified.

3MTM Superfast Plastic Adhesive PN 55045 (Part B)

Section 12: Mobility in soil information information was modified.

Prints No Data if Adverse effects information is not present information was deleted.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: No endocrine disruptor information available warning information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14 Marine transport in bulk according to IMO instruments - Main Heading information was deleted.

Section 14 UN Number information was deleted.

Section 14: Transportation classification information was deleted.

Section 15: Chemical Safety Assessment information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

Section 16: Web address information was added.

Section 16: Web address information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.